

Contents

1. Introduction	1-1
1.1 Document Organization	1-1
1.2 General	1-2
1.3 Background on T3POS	1-3
1.4 General Support of T3POS	1-4
1.4.1 Benefits of T3POS Protocol	1-5
1.5 T3POS PAD Support in a PPSN	1-6
1.6 Requirements Terminology	1-7
1.7 Requirement Labeling Conventions	1-8
1.7.1 Numbering of Requirement and Related Objects	1-8
1.7.2 Requirement, Conditional Requirement, and Objective Object Identification	1-8
2. Character Exchange and Service Initialization	2-1
2.1 Data Formats and Character Sets	2-1
2.1.1 7-bit, Even Parity Data Format	2-1
2.1.2 7-bit, Odd Parity Data Format	2-2
2.1.3 7-bit, Space Parity Data Format	2-3
2.1.4 7-bit, Mark Parity Data Format	2-3
2.1.5 7-bit, No parity Data Format	2-4
2.1.6 7-bit Character Set	2-5
2.1.7 8-bit, No Parity Data Format	2-6
2.1.8 8-bit, No Parity Character Set	2-7
2.2 Service Initialization	2-7
2.2.1 Required Service Parameters	2-8
2.2.1.1 Descriptions of Required T3POS Service Parameters	2-9
2.2.2 Optional Service Parameters	2-13
2.2.2.1 Descriptions of Optional T3POS Service Parameters	2-13
3. DTE Interface	3-1
3.1 Local Mode and Call Establishment	3-1
3.1.1 Data Format and Character Set	3-1
3.1.2 Frame Structures	3-1
3.1.2.1 Information Frame Structures	3-1
3.1.2.2 Supervisory Frame Structures	3-4
3.1.3 Parsing Frames from Transmission Blocks	3-5
3.1.3.1 DLE,EOT Frame Parsing Rules	3-5
3.1.3.2 Information Frame Parsing Rules	3-6
3.1.3.3 Single Character Supervisory Frame Parsing Rules	3-6
3.1.4 Half-Duplex Rules	3-6
3.2 Transparent Mode	3-7
3.2.1 Data Format and Character Set	3-7
3.2.2 Data Structures	3-7
3.2.2.1 Information Structures	3-7
3.2.2.2 Supervisory Frame Structures	3-7

- 3.2.3 Full-Duplex Rules 3-8
- 3.3 Blind Mode 3-8
 - 3.3.1 Data Format and Character Set 3-8
 - 3.3.2 Frame Structures 3-8
 - 3.3.2.1 Information Frame Structures 3-8
 - 3.3.2.2 Supervisory Frame Structures 3-8
 - 3.3.3 Full-Duplex Rules 3-9
- 3.4 "New" Binary Local Mode 3-9
 - 3.4.1 Data Format and Character Sets 3-9
 - 3.4.1.1 Control Character Set 3-9
 - 3.4.1.2 Control Character Sequence 3-10
 - 3.4.2 Frame Structures/Formats 3-10
 - 3.4.2.1 Information Frame Structure 3-10
 - 3.4.2.2 Supervisory Frame Structures 3-11
 - 3.4.3 Parsing Frames 3-12
 - 3.4.3.1 DLE, EOT Frame Parsing Rules 3-12
 - 3.4.3.2 Information Frame Parsing Rules 3-12
- 4. X.25 Host Interface 4-1
 - 4.1 Notification Events 4-1
 - 4.2 X.25 Maximum Packet Size Exceeded 4-2
 - 4.3 ENO Waiting 4-3
 - 4.4 X.3 Parameter Profile for Point-Of-Service 4-4
- 5. T3POS State Descriptions and Procedures 5-1
 - 5.1 Active Link State 5-1
 - 5.2 PAD Waiting State 5-2
 - 5.2.1 Special PAD Waiting State Procedures for Dial-in DTE 5-3
 - 5.3 Terminal-Initiated Call Establishment State 5-3
 - 5.3.1 Opening Frame Processing 5-4
 - 5.3.2 Call Clearing and Opening Frame Timing 5-6
 - 5.3.3 Control Field 5-6
 - 5.3.4 Call Request Packet Construction 5-8
 - 5.3.4.1 Called Address 5-8
 - 5.3.4.2 Called User Data (CUD) 5-8
 - 5.3.4.3 Calling Number 5-11
 - 5.3.5 Opening Frame ACK Suppression 5-11
 - 5.3.6 Opening Frame Control Field Stripping 5-12
 - 5.3.7 Terminal-initiated Call Establishment Error Conditions 5-12
 - 5.3.7.1 Frame Arrival Timer (T6) expiry 5-12
 - 5.3.7.2 Failed X-25 Virtual Call 5-13
 - 5.3.8 Call Establishment Error Recovery 5-13
 - 5.3.9 DTE Interface Flow Control 5-13
 - 5.4 Host-initiated Call Establishment State 5-13
 - 5.4.1 Host-Initiated Call Processing 5-14
 - 5.4.2 Call Clear Request Diagnosis 5-15
 - 5.4.3 Opening Frame Construction 5-16
 - 5.4.4 Host-Initiated Call Establishment Error Conditions 5-17

5.4.5	Host-Initiated Call Establishment Error Recovery	5-18
5.4.6	DTE Interface Flow Control	5-18
5.5	Local Mode Data Transfer State	5-18
5.5.1	Local Mode Data Transfer State Machine	5-19
5.5.1.1	Local Mode Counters and Variables	5-20
5.5.1.2	Idle State	5-23
5.5.1.3	Forward Data to Host State	5-25
5.5.1.4	Forward Data to DTE State	5-26
5.5.1.5	PAD Loop Back in the Local Mode	5-27
5.5.2	Local Mode Error Conditions	5-28
5.5.2.1	Received ENQ Supervisory Frame from DTE	5-28
5.5.2.2	Received NAK Supervisory Frame from DTE	5-28
5.5.2.3	DTE Framing Error	5-28
5.5.2.4	DTE Parity Error	5-28
5.5.2.5	DTE LRC Error	5-29
5.5.2.6	Response Timer (T4) Timeout	5-29
5.5.2.7	Protocol Violations	5-29
5.5.2.8	DLE,EOT Timer (T5) Expiry	5-29
5.5.2.9	Retry Counter over Limit	5-30
5.5.2.10	Max Block Size Exceeded	5-30
5.5.2.11	Error Precedence	5-30
5.5.2.12	Host Errors	5-31
5.5.3	Local Mode Error Recovery	5-31
5.5.3.1	Retransmission Error Recovery	5-31
5.5.3.2	ENO (SFR) Error Recovery	5-31
5.5.3.3	ENO (MR) Error Recovery	5-32
5.5.3.4	NAK Error Recovery	5-32
5.5.3.5	Call Clearing Error Recovery	5-32
5.5.4	DTE Interface Flow Control	5-33
5.5.5	Exiting the Local Mode Data Transfer States	5-33
5.6	"New" Binary Local Mode Data Transfer State	5-33
5.6.1	BL Mode Data Transfer State Overview	5-33
5.6.1.1	Counters and Variables	5-35
5.6.1.2	Binary Local Mode States	5-35
5.6.2	Error Conditions	5-35
5.6.3	Error Recovery	5-36
5.7	Transparent and Blind Mode Data Transfer States	5-36
5.7.1	Data Forwarding Conditions	5-36
5.7.2	PAD Loop Back in the Transparent and Blind Modes	5-37
5.7.3	Max Block Size Exceeded	5-37
5.7.4	DTE Interface Flow Control	5-38
5.7.5	Exiting the Transparent and Blind Mode Data Transfer States	5-38
5.8	Call Clearing State	5-39
5.9	Timer Summary	5-40
6.	Examples	6-1
6.1	Call Establishment Call Flows	6-1
6.1.1	Basic Call Flows	6-1

6.1.1.1 Terminal Initiated	6-1
6.1.1.2 Host Initiated	6-1
6.1.2 ENQ Handling	6-2
6.1.2.1 Recommended Behavior	6-2
6.1.2.2 Non-Recommended Behavior	6-2
6.1.2.3 ENQ Handling timer (T3) Expiry, Recommended	6-4
6.1.2.4 ENQ Handling timer (T3) Expiry, Non-Recommended	6-4
6.1.3 Opening Frame ACK Suppression	6-4
6.1.4 Overriding the Default Mode	6-5
6.1.4.1 Terminal Initiated	6-5
6.1.4.2 Host Initiated	6-7
6.1.5 SYN Character Usage	6-7
6.1.5.1 Terminal-Initiated	6-7
6.1.5.2 Host-initiated	6-9
6.2 Local Mode Data Transfer	6-9
6.2.1 Basic	6-9
6.2.2 SYN Character Usage	6-11
6.2.3 DTE Framing Error	6-13
6.2.4 DTE Timeout	6-13
6.2.5 NAK Received from DTE	6-13
6.2.6 ENQ Received from DTE	6-14
6.2.7 Maximum Retry	6-16
7. Multi-Aspect PAD Support	7-1
7.1 Overview of MAPs	7-1
7.2 PAD Aspect Default	7-3
7.3 Common Procedures	7-4
7.3.1 MAP Status Inquiry	7-4
7.3.2 Modify MAP	7-4
7.3.3 Change MAP Capability	7-5
7.3.4 Change MAP Procedures	7-6
Appendix A: References	A-1
Appendix B: Glossary	B-1

List of Figures

Figure 1-1	An Overview of the Transaction Switching and Transport Service Architecture	1-3
Figure 1-2	T3POS PAD Support in a PPSN	1-7
Figure 2-1	7-bit, Even Parity Character Format	2-1
Figure 2-2	7-bit, Odd Parity Character Format	2-2
Figure 2-3	7-bit, Space Parity Character Format	2-3
Figure 2-4	7-bit, Mark Parity Character Format	2-4
Figure 2-5	7-bit, No Parity Character Format	2-5
Figure 2-6	8-bit, No Parity Data Format	2-7
Figure 3-1	General Frame Format	3-2
Figure 3-2	Control Frame Format	3-2
Figure 3-3	Range of the LRC Calculation	3-3
Figure 3-4	General Frame	3-10
Figure 5-1	T3POS Transaction/Call State Diagram	5-1
Figure 5-2	Control Field Format	5-6
Figure 5-3	Encoding of the T3POS Protocol Identifier	5-9
Figure 5-4	Encoding of the X.29 Protocol Identifier	5-9
Figure 5-5	Local Mode Data Transfer State Machine	5-20
Figure 5-6	Last Transmission Not Retransmitted, Case 1	5-22
Figure 5-7	Last Transmission Not Retransmitted, Case 2a	5-22
Figure 5-8	Last Transmission Not Retransmitted, Case 2b	5-22
Figure 5-9	Last Transmission Not Retransmitted, Case 3	5-23
Figure 5-10A.	Host frame; DTE clear request	5-34
Figure 5-10B.	DTE frame; DTE clear request	5-34
Figure 5-10C.	Host and DTE exchange	5-34
Figure 6-1	Basic Terminal Initiated Call Establishment	6-1
Figure 6-2	Basic Host-Initiated Call Establishment	6-2
Figure 6-3	ENQ Handling, Recommended	6-3
Figure 6-4	ENQ Handling, Non-Recommended	6-3
Figure 6-5	ENQ Handling timer (T3) Expiry, Recommended	6-4
Figure 6-6	ENQ Handling timer (T3) Expiry, Non-Recommended	6-5
Figure 6-7	Opening Frame ACK Suppression ON	6-5
Figure 6-8	Terminal-Initiated Mode Switching, Method of Host Notification = 'None'	6-6
Figure 6-9	Terminal-Initiated Mode Switching, Method of Host Notification = 'Call Request Packet'	6-6
Figure 6-10	Terminal-Initiated Mode Switching, Method of Host Notification = 'Mode Switch Frame'	6-7
Figure 6-11	Host-Initiated Mode Swtiching	6-8
Figure 6-12	SYN Character Usage During Terminal-Initiated Call Establishment	6-8
Figure 6-13	SYN Character Usage During Host-Initiated Call Establishment	6-9
Figure 6-14A.	Local Mode Host Frame Exchange with DTE CALL Clear Request	6-10

Figure 6-14B.	Local Mode DTE Frame Exchange with DTE CALL Clear Request	6-10
Figure 6-14C.	Local Mode Host and DTE Frame Exchange with Host CALL Clear Notification from PAD to DTE	6-11
Figure 6-15	Exchange Sequence with DTE and PAD Transmitting SYN Characters . 6-12	
Figure 6-16	Local Mode DTE Frame Exchange Sequence	6-13
Figure 6-17	DTE Response timeout and retransmission	6-13
Figure 6-18	Host Opening Frame Exchange Sequence	6-14
Figure 6-19A.	Local Mode DTE Frame Exchange Sequence	6-14
Figure 6-19B.	Local Mode PAD Frame Exchange Sequence	6-15
Figure 6-19C.	Opening Frame Exchange Sequence with Parity Error Detected . .	6-15
Figure 6-19D.	Opening Frame Exchange Sequence with a PAD Response Timeout . . 6-16	
Figure 6-20	Maximum Retry Path with Response Timeout, and NAK and ACK Parity Errors	6-16
Figure 7-1	Functional Illustration of a MAP with Single Access Interface . . .	7-2
Figure 7-2	Functional Illustration of a Multi-Aspect PAD with Multiple Access Interfaces	7-2

List of Tables

Table 2-1	IA5 Character Set	2-6
Table 2-2	Required Service Parameters of a T3POS PAD Interface	2-8
Table 2-3	Optional Service Parameter of a T3POS PAD Interface	2-13
Table 4-1	T3POS PAD X.3 Parameters	4-6
Table 5-1	Mode Selection Signal Values	5-7
Table 5-2	Terminal-Initiated Call - Called User Data Field Format	5-10
Table 5-3	T3POS PAD Timers	5-41
Table 7-1	Multi-Aspect PAD Codes	7-3