

# Generic Requirements for CCS Nodes Supporting ATM High Speed Signaling Links (HSLs)

## Contents

Preface .....	Preface-1
1. Introduction.....	1-1
1.1 Purpose and Scope .....	1-1
1.2 Related Documents .....	1-1
1.3 Organization of This Document.....	1-2
1.4 Requirements Terminology.....	1-3
1.5 Requirement Labeling Conventions.....	1-4
1.5.1 Numbering of Requirement and Related Objects .....	1-4
1.5.2 Requirement, Conditional Requirement, and Objective Object Identification .....	1-5
1.6 Summary of Changes .....	1-5
1.6.1 Reasons for Reissue .....	1-5
1.6.2 Highlights of Principal Revisions and Additions.....	1-5
1.6.3 Change Bars .....	1-5
1.6.4 List of Revisions .....	1-6
2. HSL Signaling and Network Architecture.....	2-1
2.1 SS7 and ATM Protocol Architecture .....	2-1
2.1.1 Overview .....	2-1
2.1.2 Physical Layer.....	2-2
2.1.3 ATM Layer .....	2-3
2.1.3.1 Overview of ATM Technology .....	2-3
2.1.3.2 Application of ATM to HSLs .....	2-5
2.1.4 Signaling ATM Adaptation Layer (SAAL) .....	2-5
2.1.4.1 Common Part (CP) .....	2-6
2.1.4.2 Service Specific Connection Oriented Protocol (SSCOP) .....	2-6
2.1.4.3 Service Specific Coordination Function (SSCF).....	2-7
2.1.4.4 SAAL Layer Management.....	2-7
2.1.5 Signaling Network Layer (MTP - Level 3).....	2-7
2.2 HSLs in LEC CCS Networks - Topology Overview .....	2-8
2.2.1 HSL Deployment Drivers .....	2-8
2.2.2 HSL Implementation at CCS Network Nodes .....	2-9
2.2.3 HSL Deployment in LEC CCS Networks.....	2-9
2.2.4 Potential Use of HSLs in CCS Network Interconnection.....	2-11
2.2.5 Potential Future HSL Application to Broadband Network Interworking.....	2-11

3.	Network Element Requirements .....	3-1
3.1	ATM and Physical Layer Requirements .....	3-1
3.1.1	ATM Layer Requirements .....	3-1
3.1.2	Physical Layer Requirements.....	3-2
3.1.2.1	Synchronization Requirements.....	3-4
3.1.2.2	Connector.....	3-5
3.2	Signaling ATM Adaptation Layer (SAAL) Requirements .....	3-5
3.2.1	AAL Type 5 Common Part.....	3-5
3.2.2	SSCOP-Related Requirements.....	3-6
3.2.2.1	General.....	3-6
3.2.2.2	Credit Determination and Peer-to-Peer Flow Control .....	3-7
3.2.3	SSCF-Related Requirements.....	3-7
3.2.4	Layer Management-Related Requirements.....	3-8
3.2.4.1	Error Monitoring for In-Service Signaling Links.....	3-9
3.2.4.2	Determination of Failed Proving Attempts.....	3-9
3.2.4.3	Forced Proving Procedures to Prevent Link Oscillations...	3-9
3.2.4.4	Timer for No Receipt of Credit .....	3-11
3.2.4.5	Peer-to-Peer Layer Management Communications.....	3-12
3.2.5	Other - SAAL Related Requirements .....	3-12
3.2.5.1	Signaling Link Speed.....	3-12
3.2.5.2	PDU Lengths .....	3-12
3.2.6	SAAL Timer and Parameter Values .....	3-13
3.3	Message Transfer Part - Level 3 .....	3-15
3.3.1	Signaling Message Handling .....	3-16
3.3.1.1	Message Routing .....	3-16
3.3.1.2	Message Handling During Overload .....	3-18
3.3.2	MTP Network Management Functions.....	3-19
3.3.2.1	Congestion Control.....	3-19
3.3.2.2	Signaling Link Activation, Restoration, Deactivation, and Link Set Activation.....	3-21
3.3.2.3	Signaling Link Changeover .....	3-29
3.3.2.4	Transfer Restricted Timer.....	3-31
3.3.2.5	Signaling Link Test.....	3-31
3.3.2.6	Use of the MTP3 Link Oscillation Filter for HSLs at STPs .....	3-32
3.4	SCCP Functions .....	3-34
4.	Node Operations Requirements .....	4-1
4.1	General .....	4-1
4.1.1	Scope and Organization of the HSL Operations Requirements.....	4-1
4.1.2	General Considerations and Related Operations Requirements .....	4-2
4.2	Configuration Management (Memory Administration).....	4-3
4.2.1	Configuration of Common Link Parameters.....	4-3
4.2.2	Configurable Parameters: Physical Layer Interface (DS1).....	4-7
4.2.3	Configurable Parameters: ATM Layer .....	4-7

4.2.3.1	Configuration of the ATM Interface at the CCS Node.....	4-9
4.2.3.2	Configuration of the Signaling Link VCC/VCL .....	4-11
4.2.4	Configurable Parameters: SAAL (SSCOP/SSCF/Layer Management) .....	4-18
4.2.5	MTP3 Link Congestion Thresholds .....	4-20
4.2.6	Link Marginal Performance Thresholds .....	4-21
4.2.7	Link Parameter Administration: Data Operations .....	4-22
4.2.8	Summary of HSL Configurable Parameters .....	4-23
4.3	In-band Operations Flows .....	4-31
4.3.1	Physical Layer Operations Flows: DS1-Level.....	4-31
4.3.2	ATM-Layer Operations Flows.....	4-32
4.4	Fault Management (Maintenance) .....	4-34
4.4.1	Link Event Notification Functions.....	4-35
4.4.1.1	Link Outage-Related Event Detection and Reporting .....	4-35
4.4.1.2	Common Requirements for Link Event Reports .....	4-39
4.4.1.3	Link Outage Event Report .....	4-41
4.4.1.4	Link Available Event Report .....	4-51
4.4.1.5	Sustained Link Failure/Craft Referral Event Report .....	4-55
4.4.1.6	Unavailable-Link Minor State Change Event Report.....	4-57
4.4.1.7	Oversized Message Routing Attempt on an MTP2 Signaling Link.....	4-61
4.4.2	Link Status Logging.....	4-64
4.4.3	Lower-Layer Fault-Management Surveillance Functions .....	4-68
4.4.3.1	ATM-Layer Defect and Failure Detection and Reporting.....	4-68
4.4.3.2	Physical Layer Defect and Failure Detection and Reporting (DS1).....	4-69
4.4.4	Link Testing Functions .....	4-71
4.4.4.1	Physical-Level Testing: DS1 ESF Loopbacks.....	4-71
4.4.4.2	ATM-Layer OAM Loopback Tests .....	4-73
4.4.5	Link Control Functions (Removal From Service) .....	4-73
4.5	Performance Management (Maintenance and Network Traffic Management) .....	4-74
4.5.1	Scheduled Link Performance Measurements.....	4-75
4.5.1.1	MTP Level 3 Performance Measurements: Daily and Marginal.....	4-76
4.5.1.2	MTP Level 3 Performance Measurements: 5-Minute .....	4-78
4.5.1.3	SAAL-Level Performance Measurements: Daily and Marginal.....	4-82
4.5.1.4	SAAL-Level Performance Measurements: 5-Minute.....	4-84
4.5.1.5	ATM-Level Performance Measurements: Daily and Marginal.....	4-86
4.5.1.6	Physical-Level (DS1) Performance Measurements.....	4-87
4.5.2	Exception-Based Performance Monitoring.....	4-87
4.5.2.1	HSL Marginal Performance Reports .....	4-87

4.5.2.2	HSL Threshold Crossing Alerts (TCAs) .....	4-89
4.5.2.3	Exception-Based Facility Monitoring (DS1).....	4-90
4.5.3	Management-Initiated Performance Monitoring .....	4-90
4.5.3.1	SAAL-Level: SSCOP PDU Data Capture.....	4-91
4.5.3.2	ATM-Level: Use of F5 Performance Monitoring OAM Cells.....	4-91
4.5.3.3	DS1 Level: Scheduling of DS1 Performance Reports.....	4-92
4.6	Network Data Collection (NDC) .....	4-92
4.6.1	MTP Level 3 Link Traffic and Performance Measurements (30 Minute) .....	4-94
4.6.1.1	MTP3 Link Measurements .....	4-94
4.6.1.2	MTP3 Link Set Measurements .....	4-99
4.6.2	SAAL-Level Measurements: 30-minutes .....	4-100
4.6.2.1	SAAL-Level Link Measurements.....	4-100
4.6.2.2	SAAL-Level Link Set Measurements .....	4-101
4.6.3	ATM-Cell Traffic Measurements: 30-Minutes .....	4-102
4.6.3.1	ATM-Level Link Measurements .....	4-102
4.6.3.2	ATM-Level Link Set Measurements .....	4-102
4.6.4	Additional Measurement Requirements.....	4-103
5.	Operations Interface Support .....	5-1
5.1	General .....	5-1
5.2	Configuration Management/Memory Administration OS Interface Support ..	5-3
5.2.1	For STPs (GR-310-CORE) .....	5-3
5.2.2	For CCS End-Nodes.....	5-5
5.2.3	For All CCS Nodes (GR-981-CORE).....	5-6
5.3	Maintenance OS Interface Support .....	5-6
5.3.1	For Fault Management Functions .....	5-6
5.3.1.1	For All CCS Node Types (TA-TSY-000387) .....	5-6
5.3.1.2	For STPs (GR-310-CORE).....	5-7
5.3.1.3	For SCPs (TA-NWT-000365) .....	5-8
5.3.2	For Performance Management Functions .....	5-8
5.3.2.1	For All CCS Node Types (TA-TSY-000387) .....	5-8
5.3.2.2	For STPs (GR-310-CORE).....	5-9
5.4	Network Traffic Management (NTM) OS Interface Support .....	5-10
5.4.1	For All CCS Node Types (GR-495-CORE) .....	5-10
5.4.2	For STPs (GR-310-CORE) .....	5-10
5.4.3	Considerations For CCS SOs/SSPs.....	5-11
5.5	Network Data Collection (NDC) OS Interface Support .....	5-11
5.5.1	For All CCS Node Types (GR-376-CORE) .....	5-11
5.5.2	For STPs (GR-310-CORE) .....	5-12
5.5.3	For SCPs (TA-NWT-000365).....	5-13
5.5.4	For CCS SOs/SSPs (FSD 45-09-0100).....	5-13
5.6	User-System Interface (USI) Support (TR-TSY-000825) .....	5-14

6.	Performance .....	6-1	
6.1	Reliability .....	6-1	
6.2	Network Performance Parameters and Objectives.....	6-1	
6.2.1	Parameters Related to the Message Transfer Part.....	6-2	
6.2.2	Message Transfer Times .....	6-3	
6.2.3	SAAL Performance.....	6-5	
6.2.4	ATM Layer Performance .....	6-5	
6.3	Capacity.....	6-6	
7.	Environmental Requirements.....	7-1	
7.1	Power.....	7-1	
7.2	Equipment .....	7-1	
7.3	Electromagnetic and Electrical Environment.....	7-1	
8.	Quality.....	8-1	
8.1	Introduction .....	8-1	
8.2	Reliability and Quality Switching Systems Generic Requirements.....	8-1	
8.2.1	System Design and Architecture .....	8-2	
8.2.2	Manufacturing and Production.....	8-2	
8.2.3	In-Service Performance and Product Support.....	8-2	
9.	Transitional Considerations .....	9-1	
10.	Supplier Support .....	10-1	
10.1	General .....	10-1	
10.2	HSL NE Operations Documentation.....	10-1	
10.3	HSL NE Software Documentation.....	10-2	
Appendix A: Guidelines for Peer-to-Peer Credit Flow Control and			
	Receive Buffer Sizing .....	A-1	
A.1	SAAL Flow-Control Mechanism .....	A-1	
A.2	Credit Assignment Schemes .....	A-2	
A.3	Basic Credit Requirements.....	A-4	
A.4	Impact of Level 3 Capacity on Credit Allocation .....	A-7	
A.5	Impact of Message Size .....	A-7	
A.6	Guidelines .....	A-9	
Appendix B: Overview of SAAL Error Monitors .....			B-1
B.1	SAAL Error Monitor.....	B-1	
B.2	Proving Algorithm .....	B-2	
Appendix C: Analysis of HSL Transmit Congestion Thresholds .....			C-1
C.1	Link Transmit Congestion Control .....	C-1	
C.1.1	STP-STP HSL Transmit Congestion .....	C-2	
C.1.2	STP-SCP HSL Transmit Congestion .....	C-4	
C.2	Message Size Sensitivity of Buffer Thresholds .....	C-5	
Appendix D: HSL Measurement Summary.....			D-1

D.1	HSL and MTP2 Measurements Comparison .....	D-1
D.2	HSL Link Marginal Performance Indicators.....	D-14
Appendix E:	Considerations Regarding HSL Marginal Performance Thresholds.....	E-1
E.1	Number of Automatic Changeovers.....	E-1
E.2	SSCOP SD PDUs Transmitted Requiring Retransmission.....	E-2
E.2.1	Average Sustained BER Criteria.....	E-3
E.2.2	Error-Burst Frequency Criteria .....	E-6
E.2.3	Recommendations Regarding the PDUs-Retransmitted Thresholds .	E-8
E.3	SSCOP Connection Sum-of-Errors Counter .....	E-9
E.4	SSCOP Errored PDUs Sum-of-Errors Counter.....	E-9
Appendix F:	The Effectiveness of Congestion Controls .....	F-1
F.1	Network Model .....	F-2
F.2	Overload Scenarios .....	F-4
F.2.1	Level 3 Capacity Limitations in STP1 only.....	F-4
F.2.2	Level 3 Capacity Limitations in all STPs .....	F-5
F.3	Summary .....	F-6
Appendix G:	Notes on Protocol Standards Discrepancies .....	G-1
G.1	General .....	G-1
G.2	SSCF (T1.645) SDL Diagram vs. State Table Discrepancy .....	G-1
G.3	Table 6/Q.2140 Initial-State-Column Labeling Errors .....	G-3
References	.....	References-1
Glossary	.....	Glossary-1
Acronyms	.....	Acronyms-1
Requirement-Object Index	.....	ROI-1

## List of Figures

Figure 2-1.	High-Speed Link Protocol Model.....	2-2
Figure 2-2.	ATM Cell Structure .....	2-4
Figure 2-3.	LEC Potential HSL Deployment Plans .....	2-10
Figure 2-4.	Example Architectures for HSLs Used in CCS Network Interconnection .....	2-12
Figure 2-5.	Potential CCS Network - Broadband Network Interconnection Architecture .....	2-13
Figure 3-1.	ATM NNI Cell Structure .....	3-1
Figure C-1.	Network Architecture for HSL Simulation .....	C-1
Figure F-1.	Network Model Used in Telcordia Congestion Control Study .....	F-2





## List of Tables

Table 3-1.	SAAL Timers and Parameters .....	3-14
Table 4-1.	Summary of HSL Configurable Parameters .....	4-27
Table 6-1.	High Speed Link Output Delay .....	6-4
Table 6-2.	High Speed Link Cross-STP Transport Time.....	6-5
Table C-1.	Message Categories .....	C-2
Table C-2.	Preliminary STP-STP HSL Congestion Threshold and Buffer Size Recommendations .....	C-3
Table C-3.	Preliminary STP-SCP HSL Congestion Threshold and Buffer Size Recommendations .....	C-4
Table D-1.	HSL and MTP2-Links Measurements Summary and Comparison; Plus GR-310/TA-365 Interface Standardized Data Groupings and Register Labels.....	D-4
Table D-2.	HSL and MTP2 Link Marginal Performance Indicators .....	D-14
Table F-1.	Call Processing Capacities of the SSPs in Figure F-1 .....	F-2
Table F-2.	SMH Congestion Thresholds in Seconds <sup>a</sup> .....	F-4