

Contents

Preface	xi
1 Introduction	
1.1 General Product Description	1-1
1.2 Application of this Document	1-1
1.3 Changes From GR-2916-CORE, Issue 1, to Issue 2	1-2
1.4 Test Conditions	1-2
1.5 Sample Selection and Retest	1-3
1.6 Requirements Terminology	1-4
1.7 Requirement Labeling Conventions	1-4
1.7.1 Numbering of Requirement and Related Objects	1-5
1.7.2 Requirement, Conditional Requirement, and Objective Identification	1-5
2 General Requirements	
2.1 Network Side	2-1
2.1.1 Termination Capacity	2-1
2.1.2 Connectorized Input	2-1
2.2 Protector Module	2-1
2.2.1 Plating Finish of Pins and Terminal	2-2
2.2.2 Protector Unit Installation/Removal Orientation	2-2
2.2.3 Protector Output Conductors	2-3
2.3 Grounding Conductors	2-3
2.4 Listing	2-3
2.5 Materials	2-3
2.6 Construction Safety	2-5
2.7 Instructions	2-5
2.8 Marking	2-5
2.9 Packing and Shipping	2-5
2.10 Flammability	2-6
2.11 Stub Cable	2-6
2.11.1 Cable Construction	2-6
2.11.2 Cable Attachment	2-7
2.11.3 Flame Retardant Stub Cables	2-7
2.12 Insertion Criteria	2-7
2.13 Personnel Safety	2-7
2.14 Human Engineering	2-8
3 Electrical Requirements	
3.1 Fusing Coordination	3-1
3.2 Contact Resistance	3-2
3.3 Contact Life	3-3
3.4 Insulation Resistance - Unprotected	3-3

3.5 Dielectric Withstand	3-4
3.6 Lightning Surge Immunity	3-4
3.7 AC Power Fault Immunity	3-5
3.8 Crosstalk	3-6
3.9 Current Carrying Capability of Grounding Connector	3-6

4 Environmental Requirements

4.1 High Temperature	4-1
4.2 Temperature Cycling with Humidity	4-1
4.3 Resistance to Chemicals	4-2
4.4 Fungus Resistance	4-2
4.5 Drop Test	4-3
4.6 Shock and Vibration	4-3
4.7 Salt Fog Tests (Intended for Uncontrolled Environment)	4-4
4.8 Airborne Contaminants (Intended for Controlled Environment)	4-4
4.9 Airborne Contaminants (Intended for Uncontrolled Environment)	4-5

5 High-Speed Digital Networks

5.1 Insertion Loss	5-1
5.2 Return Loss	5-2
5.3 Longitudinal Balance	5-2
5.4 Bit Error Rate (BER) Test	5-4

Appendix A: References

Appendix B: Protector Unit Pin and Socket Assembly

B.1 Gold Composition (Protector Pin)	B-1
B.2 Porosity (Protector Pin)	B-1
B.3 Adhesive Test (Protector Pin)	B-2
B.4 Appearance (Protector Pin)	B-2
B.5 Gold Composition (Protector Socket)	B-2
B.6 Porosity (Protector Socket)	B-2
B.7 Adhesive Test (Protector Socket)	B-2
B.8 Porosity Testing Procedure:	B-3
B.9 Gold Flash and Gold Palladium Finishes	B-4

Appendix C: Test Waveform Validation

Requirement-Object Index

Index

List of Figures

Figure 4-1	Temperature/Humidity Cycle with Relative Humidity at 90 to 95%	4-5
Figure 5-1	Bit Error Test (BER) Test Circuit	5-5
Figure C-1	Definition of Voltage Rate of Rise	C-2
Figure C-2	Definition of Double Exponential Impulse Waveform of Duration <i>a/b</i> Seconds	C-3

List of Tables

Table 2-1	Insertion and Withdrawal Force Limits	2-2
Table 3-1	Fusing Coordination	3-1
Table 3-2	Insulation Resistance	3-3
Table 3-3	Lightning Surge Immunity Requirement	3-4
Table 3-4	AC Power Fault Immunity	3-5
Table 3-5	Near End Cross Talk (NEXT)	3-6
Table 5-1	Test Times for BER Test	5-4