

## Contents

Preface . . . . .	Preface-1
1. Introduction . . . . .	1-1
1.1 General . . . . .	1-1
1.2 Purpose and Scope . . . . .	1-1
1.3 Related documents . . . . .	1-1
1.4 Target Audience . . . . .	1-2
1.5 Organization of This Document . . . . .	1-2
1.6 Summary of Changes . . . . .	1-3
1.6.1 Reasons for Reissue . . . . .	1-3
1.6.2 Highlights of Principal Revisions and Additions . . . . .	1-3
1.6.3 Change Bars . . . . .	1-3
1.7 Requirements Terminology . . . . .	1-4
1.8 Requirement Labeling Conventions . . . . .	1-4
1.8.1 Numbering of Requirement and Related Objects . . . . .	1-4
1.8.2 Requirement, Conditional Requirement, and Objective Object Identification . . . . .	1-5
2. CCS Network Interconnection Architecture for HSLs . . . . .	2-1
2.1 HSL Network Architecture Overview . . . . .	2-1
2.1.1 Use of High Speed Signaling Links . . . . .	2-1
2.1.1.1 HSL Deployment Drivers . . . . .	2-1
2.1.1.2 General Conversion Issues . . . . .	2-2
2.1.2 HSL Network Interconnection Architectures . . . . .	2-4
2.1.2.1 Interconnection Using STPs and D-Link Quads . . . . .	2-6
2.1.2.2 High Speed Link Interconnection Using A-Links . . . . .	2-8
2.1.2.3 Other Interconnection Arrangements . . . . .	2-8
2.1.2.4 Client company Network Access . . . . .	2-12
2.1.3 Transition Plan . . . . .	2-12
2.1.3.1 Transition Planning Considerations . . . . .	2-12
2.1.3.2 Transition Plan for Link Set Groupings . . . . .	2-12
2.2 HSL Protocol Architecture . . . . .	2-16
2.2.1 Physical Layer . . . . .	2-17
2.2.2 ATM Layer . . . . .	2-18
2.2.2.1 Overview of ATM Technology . . . . .	2-18
2.2.2.2 Application of ATM to HSLs . . . . .	2-19
2.2.3 Signaling ATM Adaptation Layer (SAAL) . . . . .	2-20
2.2.3.1 Common Part (CP) . . . . .	2-20
2.2.3.2 Service Specific Connection Oriented Protocol (SSCOP) . . . . .	2-20
2.2.3.3 Service Specific Coordination Function (SSCF) at the NNI . . . . .	2-20
2.2.3.4 SAAL Layer Management . . . . .	2-21
2.2.3.5 Signaling Network Layer (MTP - Level 3) . . . . .	2-21

3.	HSL Protocol Specification for the CCS Network Interface . . . . .	3-1
3.1	Physical Layer . . . . .	3-1
3.1.1	DS1 Parameters . . . . .	3-1
3.1.2	Synchronization . . . . .	3-2
3.2	ATM Layer . . . . .	3-3
3.2.1	ATM Layer Protocol . . . . .	3-4
3.2.2	ATM Layer Operations Flows . . . . .	3-4
3.3	SAAL at the NNI . . . . .	3-5
3.3.1	Overview . . . . .	3-5
3.3.2	AAL Common Part Protocol . . . . .	3-7
3.3.3	SSCOP Protocol . . . . .	3-7
3.3.4	SSCF . . . . .	3-8
3.3.5	Layer Management-Related Specifications . . . . .	3-9
3.4	MTP-3 . . . . .	3-10
3.4.1	Message Routing . . . . .	3-11
3.4.1.1	Message Length . . . . .	3-11
3.4.1.2	Signaling Link Selection . . . . .	3-12
3.4.2	Changeover Order Message Format . . . . .	3-12
3.4.3	Coding Conventions . . . . .	3-13
4.	Network Engineering . . . . .	4-1
4.1	Differences in Engineering MTP Level 2 Links and ATM HSLs . . . . .	4-1
4.2	Engineering of HSLs . . . . .	4-2
4.3	Transitional Issues . . . . .	4-3
5.	Performance . . . . .	5-1
5.1	Signaling Network Transport Time . . . . .	5-1
5.2	Signaling Network Availability and Signaling Link Diversity . . . . .	5-4
5.3	Lost Message Probability . . . . .	5-5
5.4	Undetected Error Probability . . . . .	5-5
5.5	Signaling Link Error Performance . . . . .	5-5
6.	Interface Provisioning, Operations, and Maintenance . . . . .	6-1
6.1	SSCOP Credit Determination . . . . .	6-1
6.2	Message Length . . . . .	6-1
6.3	ATM-Layer HSL Parameters . . . . .	6-2
6.4	ATM OAM Capabilities . . . . .	6-2
6.5	HSL Link Engineering . . . . .	6-3
	References . . . . .	References-1
	Glossary . . . . .	Glossary-1

## List of Figures

Figure 2-1.	Potential HSL Interconnection Topologies . . . . .	2-3
Figure 2-2.	Client Company STPs to ICN STPs High Speed Signaling Network Interconnection Architecture . . . . .	2-5
Figure 2-3.	Client Company STPs to ICN Signaling End Point High Speed Signaling Network Interconnection Architecture . . . . .	2-7
Figure 2-4.	Client Company STPs to ICN STP/Combined Node High Speed Signaling Network Interconnection Architecture . . . . .	2-9
Figure 2-5.	Client Company STPs to OLC ALC Signaling Network Interconnection Architecture . . . . .	2-11
Figure 2-6.	Suggested Replacement Sequence for MTP2 Links in an Internetwork D-Link Set Quad . . . . .	2-14
Figure 2-7.	High Speed Link Protocol Model . . . . .	2-17
Figure 2-8.	ATM Cell Structure . . . . .	2-18
Figure 3-1.	ATM NNI Cell Structure . . . . .	3-3
Figure 3-2.	SAAL for NNI Signaling . . . . .	3-6
Figure 3-3.	Format of the Changeover Message Containing the Extended Changeover Signals . . . . .	3-13
Figure 3-4.	General Format and Coding Conventions of Messages Conveying Peer-to-Peer Information for HSLs . . . . .	3-14
Figure 3-5.	General Format and Coding Conventions of Signaling Network Management Message for HSLs . . . . .	3-14
Figure 5-1.	Example of ISUP Message Transport . . . . .	5-4



## List of Tables

Table 3-1.	SSCOP Timers and Parameter Values . . . . .	3-7
Table 3-2.	SSCF Timers and Parameter Values . . . . .	3-8
Table 3-3.	Layer Management Parameters and Timers . . . . .	3-9
Table 4-1.	Equivalent ATM Cells Generated by MTP2 MSUs of Various Lengths . . . . .	4-2