
Generic Requirements for an Internet Call Router Node to Support an Internet Access Traffic Off-Load Architecture

Contents

Preface	Preface-1
1. Introduction	1-1
1.1 Purpose	1-1
1.2 Background	1-1
1.3 Related Documents	1-2
1.4 Potential Ownership of ICR and AS Network Elements	1-2
1.5 Overview of the Reference Network Architecture and Assumptions	1-3
1.6 Requirements Terminology	1-6
1.7 Requirement Labeling Conventions	1-7
1.7.1 Numbering of Requirements and Related Objects	1-7
1.7.2 Requirement, Conditional Requirement, and Objective Object Identification	1-8
2. Internet Call Router (ICR) Network Element	2-1
2.1 SS7 Interface Module	2-2
2.2 Call Controller (CC) Module	2-2
2.3 Circuit Connection Control (CCC) Module	2-2
2.4 Access Server Management (ASM) Module	2-3
2.5 Protocol Interworking (PI) Module	2-3
2.6 Protocol Stack (PS) Module	2-4
2.7 Access Server Interface (ASI) Module	2-4
2.8 Operations Functions Module (OFM)	2-4
2.9 Operations Systems Interfaces Module (OSIM)	2-5
3. Call Processing	3-1
3.1 Feature Operations (Call Setup)	3-2
3.1.1 Additional Statements for Feature Operations	3-4
3.1.2 Additional Requirements for Receiving an IAM	3-4
3.1.3 Additional Requirements for Responding to a Continuity Check Request	3-9
3.1.4 Additional Requirements for Receiving a COT	3-12
3.1.5 Additional Statements for Sending an ANM	3-12
3.2 Other Feature Operations	3-13
3.2.1 Additional Statements for Receiving a Test Call	3-14
3.2.2 Additional Statements for a CQR	3-14
3.2.3 Additional Requirements for Initiating a CVT	3-15
3.2.4 Additional Requirements for Receiving a CVT	3-15
3.2.5 Checking the Physical Appearance of a Circuit	3-15

3.3	Release Treatment.....	3-18
3.3.1	Additional Statements Regarding the Receipt of an REL.....	3-18
3.3.2	Sending a Disconnect Request; Receiving a Disconnect Confirmation	3-20
3.3.3	Additional Requirements for a Release Initiated by a Non-ISDN Called Subscriber	3-21
3.3.4	Release Initiated by the ICR	3-22
3.4	Error Treatment and Abnormal Events	3-23
3.4.1	Additional Requirements for Blocking and Unblocking Messages	3-24
3.4.2	Additional Requirements for the Reset Circuit Message.....	3-25
3.4.3	Additional Statements for Receiving a Reset Circuit Group Message.....	3-25
3.4.4	Additional Statements for Sending a Reset Circuit Group Message.....	3-26
3.4.5	Additional Statements for Receiving a UCIC.....	3-26
3.4.6	Additional Requirements for the Receipt of Unrecognized Message Type	3-26
3.4.7	Additional Requirements for the Receipt of Unrecognized Parameter Values	3-26
3.4.8	Additional Statements for the Receipt of Unrecognized Messages and Parameters Subsection	3-26
3.4.9	Additional Statements for the Inability to Release Subsection.....	3-27
3.5	Other Sections of GR-317-CORE.....	3-27
4.	Call Flows	4-1
4.1	Basic Call Flow	4-3
4.1.1	Connection-Related Call Flows	4-3
4.1.1.1	IS-Initiated Call Setup without COT Signaling with Virtual POP Connection (VPC).....	4-4
4.1.1.2	IS-Initiated Call Setup without COT Signaling with TCP/IP POP Connection (TPC).....	4-6
4.1.1.3	IS-Initiated Call Setup without COT Signaling with IP-Tunnel POP Connection (IPC)	4-7
4.1.1.4	IS-Initiated Call Setup with COT Signaling with Virtual POP Connection (VPC).....	4-8
4.1.1.5	IS-Initiated Call Clearing.....	4-9
4.1.1.6	PSDN-Initiated Call Clearing	4-9
4.1.2	Non-Call-Related Call Flows.....	4-9
4.1.2.1	Initial AS Start/Resource Registration.....	4-10
4.1.2.2	AS/ICR Shutdown	4-10
4.1.2.3	IS-Initiated Circuit/Circuit Group Blocking.....	4-11
4.1.2.4	IS/ICR-Initiated Circuit Query	4-11
4.2	User Authentication Procedure	4-12
4.3	Messages	4-13
4.3.1	IS-ICR Messages.....	4-14
4.3.2	ICR-AS Messages	4-14

5.	ICR Interface Specifications	5-1
5.1	ICR SS7 Links Interface Specification	5-1
5.1.1	General Requirements	5-1
5.1.2	ICR SS7 Link Interface	5-1
5.1.2.1	V.35 Signaling Data Link Interface	5-1
5.1.2.2	Digital Signal Zero Interface	5-2
5.2	ICR-AS Interface	5-2
5.2.1	Physical Interface	5-2
5.2.2	UDP/IP Layer	5-2
5.3	Message Transmission over UDP	5-3
5.3.1	Message Retransmission Timer (MRT)	5-3
5.3.2	Message Discard Timer (MDT)	5-4
6.	Internet Call Router Operations	6-1
6.1	Organization of Subsections	6-2
6.2	Assumptions and Background Requirements	6-3
6.3	Relevant Generic Requirements	6-4
6.4	Interfaces for Operations	6-4
6.4.1	Scope of Interface Requirements for Operations	6-4
6.4.2	Informational Flows Among Network Elements and TMN Layers ..	6-5
6.4.3	A Guidelines and Requirements for Operations Interfaces	6-6
6.5	Configuration Management (CM) and Memory Administration (MA)	6-8
6.5.1	SS7 Signaling Point Code (SPC) Assignment	6-9
6.5.2	SS7 Associated Data	6-9
6.5.2.1	Serving STP Related Data	6-9
6.5.2.2	STP Associated Link Set and Link Termination Data	6-10
6.5.3	SS7 Destination Addresses/Routing Tables	6-10
6.5.4	WAN Data Link Terminations	6-11
6.5.5	AS Related Data	6-11
6.5.5.1	SS7 ISUP/DSSS1 Signaling Interworking	6-11
6.5.5.2	Modem Availability Data	6-12
6.5.5.3	Trunk-Group and Trunk Availability Data	6-13
6.5.5.4	Data Connection and Bearer Type	6-13
6.5.6	ISP Related Data	6-14
6.5.6.1	ISP DN/PSDN Data Network Address Translations	6-14
6.5.6.2	ISP Dialed Number	6-14
6.5.6.3	ISP Connection Type and Relevant Associations	6-14
6.5.6.4	ISP Connection Thresholds for ICR Capacity Management	6-14
6.5.7	Data Related to the Local Authentication Server	6-15
6.5.8	Timing and Tolerances	6-15
6.6	Fault Management	6-16
6.6.1	Event Indications	6-16
6.6.2	Event Notifications	6-19
6.6.3	Test Functions	6-19

6.6.4	Start-up and Shutdown of an ICR	6-19
6.6.4.1	Start-up of an ICR.....	6-19
6.6.4.2	Shutdown of an ICR	6-20
6.7	Performance Management	6-20
6.7.1	ICR - Measurements and Data Generation	6-20
6.7.1.1	Data Retention	6-20
6.7.1.2	Data Distribution	6-21
6.7.2	ICR - Measurements and Data Collection	6-21
6.7.2.1	Measurements for the ICR Processors.....	6-21
6.7.2.2	Measurements for the ICR/AS Interface	6-22
6.7.2.3	Measurements for the ICR/SS7 Interface	6-22
6.7.2.4	Measurements for the ICR SS7 Links	6-23
6.7.2.5	Summary Measurements for Troubles.....	6-23
6.7.2.6	Detailed Measurements for Troubles.....	6-24
6.7.2.7	Trunk Groups from the Ingress Switch That Terminate on an Access Server.....	6-26
6.7.2.8	Modem Measurements.....	6-26
6.7.2.9	Verification Of ISP Service Objectives.....	6-27
6.7.2.10	Measurements for Sizing Modems	6-28
6.8	Security Management.....	6-28
6.9	Accounting Management	6-28
7.	Performance and Reliability Requirements	7-1
7.1	Performance Requirements	7-1
7.1.1	Response Time	7-1
7.1.2	Message Loss	7-3
7.1.3	Call Processing Capacity	7-3
7.2	Reliability Requirements.....	7-4
7.2.1	Total System Downtime Objectives	7-4
7.2.2	Hardware Downtime Requirements.....	7-5
7.3	Local Area Network/Wide Area Network	7-5
7.3.1	Performance Requirements	7-6
7.3.1.1	LAN	7-6
7.3.1.2	WAN.....	7-8
7.3.2	LAN/WAN Traffic Engineering Considerations	7-9
7.3.3	Reliability Requirements.....	7-10
Appendix A:	Recovery from Faults or Failure.....	A-1
A.1	Maintaining a Status Map	A-2
A.2	Mechanisms for Maintaining a Status Map	A-2
A.3	Frequency and Controls for Updating a Status Map.....	A-3
A.4	Test Conditions for Updating a Status Map.....	A-4
A.5	Performance for a Status Map.....	A-4
Requirement-Object List		ROL-1

Requirements Object Index	ROI-1
References	References-1
Glossary	Glossary-1
Index	Index-1

List of Figures

Figure 1-1.	The Internet Off-Load Reference Architecture	1-3
Figure 2-1.	ICR Functional Model	2-1
Figure 3-1.	Signaling between the ICR and AS to Set Up a Call.....	3-6
Figure 3-2.	Signaling between the ICR and AS to Set up and Release a Check-Loop or Transponder	3-10
Figure 3-3.	Call Release Initiated by the IS	3-19
Figure 3-4.	Release Initiated by the AS	3-22
Figure 3-5.	Call Release Initiated by the ICR	3-23
Figure 4-1.	End-to-End Call Routing Architectures	4-1
Figure 4-2.	IS-Initiated Call Setup without COT Signaling with VPC.....	4-5
Figure 4-3.	IS-Initiated Call Setup without COT Signaling with TCP/IP POP Connection.....	4-6
Figure 4-4.	IS-Initiated Call Setup without COT Signaling with IP-Tunnel POP Connection.....	4-7
Figure 4-5.	IS-Initiated Call Setup with COT Signaling with Virtual POP Connection... 4-8	
Figure 4-6.	IS-Initiated Call Clearing.....	4-9
Figure 4-7.	PSDN-Initiated Call Clearing	4-9
Figure 4-8.	Initial AS start/resource Registration	4-10
Figure 4-9.	AS/ICR Shutdown	4-10
Figure 4-10.	IS-Initiated Circuit/Circuit Group Blocking.....	4-11
Figure 4-11.	IS/ICR-Initiated Circuit Query	4-11
Figure 6-1.	Logical Flow of Primary Operations Data among the ICR, AS, and Local Authentication Server Server.....	6-6
Figure 6-2.	A Logical View of Operations Communications for ICRs and ASs	6-8

List of Tables

Table 3-1.	The Incremental Changes to Sections 3.1 through 3.1.1.9 of GR-317-CORE	3-2
Table 3-2.	General Location and Cause Values for the REL Message.....	3-5
Table 3-3.	General Location and Cause Location Values for the REL Message	3-8
Table 3-4.	The Incremental Changes to Sections 3.1.2.1 through 3.1.2.3 of GR-317-CORE	3-13
Table 3-5.	Circuit Query Actions - Busy/Idle States	3-15
Table 3-6.	The Incremental Changes to Sections 3.1.3.1 through 3.1.3.4 of GR-317-CORE	3-18
Table 3-7.	The Incremental Changes to Sections 3.1.4.1 through 3.1.4.12 of GR-317-CORE	3-23
Table 3-8.	The Incremental Changes to Sections 3.2 through 3.6 of GR-317-CORE	3-28
Table 7-1.	Objectives for SS7 Signaling Point Response Time or Cross-Office Transfer Time (ms)	7-2
Table 7-2.	Comparison of LANs and WANs.....	7-5
Table 7-3.	Data Rate and Error Rate Comparison	7-6
Table 7-4.	Example Mean Delay (ms) Performance for CSMA/CD.....	7-7
Table 7-5.	Example Mean Delay (ms) Performance for Token Ring.....	7-7
Table 7-6.	Service Level Objectives for Frame Relay Virtual Connection	7-8
Table 3-2.	General Location and Cause Values for the REL Message.....	ROL-2
Table 3-3.	General Location and Cause Location Values for the REL Message	ROL-3
Table 7-6.	Service Level Objectives for Frame Relay Virtual Connection	ROL-30