
Generic Requirements for an Access Server to Support an Internet Access Traffic Off-Load Architecture

Contents

Preface	Preface-1
1. Introduction.....	1-1
1.1 Purpose.....	1-1
1.2 Background	1-1
1.3 Related Documents	1-2
1.4 Potential Ownership of ICR and AS Network Elements	1-2
1.5 Overview of the Reference Network Architecture and Assumptions	1-3
1.6 Requirements Terminology.....	1-7
1.7 Requirement Labeling Conventions.....	1-7
1.7.1 Numbering of Requirements and Related Objects.....	1-7
1.7.2 Requirement, Conditional Requirement, and Objective Object Identification	1-8
2. Access Server Network Element.....	2-1
2.1 The ICR Interface Module	2-1
2.2 The AS Circuit Connection Control Module	2-2
2.3 The AS Call Manager Module	2-2
2.4 The Operation Functions Interface Module	2-2
2.5 The Data Communications Control Module	2-3
3. Call Processing.....	3-1
3.1 Call Setup	3-1
3.1.1 Call Setup Procedure—Connect Indication	3-1
3.1.2 Call Answered—Answer Request	3-3
3.1.3 Storing and Releasing Connect Indication Information.....	3-4
3.1.4 Circuit Continuity Check—Service Indication	3-4
3.2 Release Treatment.....	3-6
3.2.1 Release Initiated by the AS—Disconnect Request.....	3-6
3.2.2 Release Initiated by the ICR—Disconnect Indication	3-7
4. Call Flows	4-1
4.1 Basic Call Flow	4-3
4.1.1 Connection-Related Call Flows	4-3
4.1.1.1 IS-Initiated Call Setup without COT Signaling with Virtual POP Connection (VPC)	4-4
4.1.1.2 IS-Initiated Call Setup without COT Signaling with TCP/IP POP Connection (TPC).....	4-5

4.1.1.3	IS-Initiated Call Setup without COT Signaling with IP-Tunnel POP Connection (IPC).....	4-6
4.1.1.4	IS-Initiated Call Setup with COT Signaling with Virtual POP Connection (VPC)	4-7
4.1.1.5	IS-Initiated Call Clearing.....	4-8
4.1.1.6	PSDN-Initiated Call Clearing	4-9
4.1.2	Non-Call-Related Call Flows.....	4-9
4.1.2.1	Initial AS start/resource Registration.....	4-10
4.1.2.2	AS/ICR Shutdown	4-10
4.1.2.3	IS-Initiated Circuit/Circuit Group Blocking.....	4-11
4.1.2.4	IS/ICR-initiated Circuit Query	4-11
4.2	User Authentication Procedure	4-12
4.3	Messages	4-14
4.3.1	ICR-AS Messages	4-14
5.	AS Interface Specifications.....	5-1
5.1	ICR-AS Interface	5-1
5.1.1	Physical Interface	5-1
5.1.2	UDP/IP Layer.....	5-1
5.2	IS-AS Interface.....	5-1
5.2.1	Physical Layer Interface.....	5-1
5.3	AS-Data Network Interface.....	5-1
5.3.1	Physical Layer	5-1
5.3.2	ATM Layer	5-2
5.3.3	The Frame Relay Interface.....	5-2
5.3.4	The ATM interface.....	5-3
5.4	Message Transmission over UDP	5-5
5.4.1	Message RetransmissionTimer (MRT).....	5-5
5.4.2	Message Discard Timer (MDT).....	5-6
6.	Access Server Operations	6-1
6.1	Organization of Subsections	6-2
6.2	Assumptions and Background Requirements	6-3
6.3	Relevant Generic Requirements and Terminology	6-4
6.4	Interfaces for Operations.....	6-4
6.4.1	Scope of Interface Requirements for Operations.....	6-4
6.4.2	Informational Flows Among Network Elements and TMN Layers ..	6-5
6.4.3	A Guidelines and Requirements for Operations Interfaces	6-6
6.5	Configuration Management (CM) and Memory Administration (MA).....	6-8
6.5.1	LAN/WAN Data Link Terminations	6-9
6.5.2	AS Related Data.....	6-9
6.5.2.1	ICR and AS Addressing.....	6-9
6.5.2.2	SS7 Trunk Terminations.....	6-10
6.5.2.3	Modem Configuration Data.....	6-11
6.5.3	ISP Related Data	6-11

6.5.3.1	ISP Address Translations.....	6-11
6.5.3.2	PVC Call Delivery.....	6-11
6.5.3.3	PSDN PVCs.....	6-11
6.5.3.4	PSDN Data Link Terminations.....	6-12
6.5.4	Timing and Tolerances.....	6-12
6.5.5	Configuration Management for the AS/ATM Interface	6-12
6.5.6	Configuration Management for the AS/Frame Relay Interface.....	6-13
6.5.7	Software Management of Modems	6-14
6.6	Fault Management.....	6-14
6.6.1	Event Indications.....	6-15
6.6.2	Fault Management for Signaling and Message-Transport Interfaces	6-18
6.6.2.1	Fault Management for the AS/ICR Interface.....	6-18
6.6.2.2	Fault Management for the AS/ATM Interface	6-18
6.6.2.3	Fault Management for the AS/Frame Relay Interface.....	6-19
6.6.3	Event Notifications	6-21
6.6.4	Test Functions	6-22
6.6.5	Test and Modem Management.....	6-22
6.6.5.1	Trouble Detection of Modems.....	6-22
6.6.5.2	Trouble Notification for Modems.....	6-22
6.6.6	Start-up and Shutdown of an AS.....	6-23
6.6.6.1	Start-up of an AS	6-23
6.6.6.2	Shutdown of an AS.....	6-23
6.7	Performance Management	6-24
6.7.1	AS - Measurements and Data Generation.....	6-24
6.7.1.1	Data Retention	6-24
6.7.1.2	Data Distribution	6-24
6.7.2	AS - Measurements and Data Collection	6-25
6.7.2.1	Measurements Associated with the LAN/WAN.....	6-25
6.7.2.2	Summary Measurements for Troubles.....	6-25
6.7.2.3	Detailed Measurements for Troubles.....	6-26
6.7.2.4	Access Ports That Terminate the Trunk Groups from the Ingress Switches	6-26
6.7.2.5	The Modems	6-27
6.7.2.6	Performance Management for the AS/ATM Functions and Interface	6-28
6.7.2.7	Applicable GR-1327-CORE Requirements for Performance Management of Frame Relay	6-30
6.8	Security Management.....	6-31
6.8.1	Security Management for the AS/ATM Functions and Interface	6-31
6.8.2	Security Management for the AS/Frame Relay Functions and Interface	6-31
6.9	Accounting Management	6-32
7.	Performance and Reliability Requirements	7-1

7.1	Performance Requirements	7-1
7.1.1	Response Time	7-1
7.1.2	Modem Blocking.....	7-3
7.1.3	PSDN Blocking.....	7-4
7.1.4	Message Loss	7-4
7.1.5	Call Processing Capacity	7-5
7.2	Reliability Requirements.....	7-5
7.2.1	Total System Downtime Objectives	7-6
7.2.2	Hardware Downtime Requirements.....	7-6
7.3	Local Area Network/Wide Area Network	7-6
7.3.1	Performance Requirements	7-7
7.3.1.1	LAN.....	7-7
7.3.1.2	WAN.....	7-9
7.3.2	LAN/WAN Traffic Engineering Considerations	7-10
7.3.3	Reliability Requirements.....	7-11
Appendix A:	Recovery from Faults or Failure.....	A-1
A.1	Applying a Status Map.....	A-2
A.2	Maintaining a Status Map	A-2
A.3	Mechanisms for Maintaining a Status Map	A-2
A.4	Frequency and Controls for Updating a Status Map.....	A-3
A.5	Test Conditions for Updating a Status Map.....	A-3
A.6	Performance for a Status Map.....	A-3
Requirement-Object List	ROL-1	
Requirement-Object Index	ROI-1	
References	References-1	
Glossary.....	Glossary-1	
Index	Index-1	

List of Figures

Figure 1-1.	The Internet Off-Load Reference Architecture	1-3
Figure 2-1.	The AS Functional Model	2-1
Figure 4-1.	End-to-End Call Routing Architectures	4-1
Figure 4-2.	IS-Initiated Call Setup without COT Signaling with Virtual POP Connection (VPC)	4-5
Figure 4-3.	IS-Initiated Call Setup without COT Signaling with TCP/IP POP Connection (TPC).....	4-6
Figure 4-4.	IS-Initiated Call Setup without COT Signaling with IP-Tunnel POP Connection (IPC).....	4-7
Figure 4-5.	IS-Initiated Call Setup with COT Signaling with Virtual POP Connection (VPC)	4-8
Figure 4-6.	IS-Initiated Call Clearing.....	4-9
Figure 4-7.	PSDN-Initiated Call Clearing	4-9
Figure 4-8.	Initial AS start/resource Registration	4-10
Figure 4-9.	AS/ICR Shutdown	4-10
Figure 4-10.	IS initiated Circuit/Circuit Group Blocking	4-11
Figure 4-11.	IS/ICR-Initiated Circuit Query	4-12
Figure 6-1.	Logical Flow of Primary Operations Data among the ICR, AS, and Local Authentication Server.....	6-6
Figure 6-2.	A Logical View of Operations Communications for ICRs and ASs	6-8

List of Tables

Table 3-1.	Status Indicator Values for a Connect Response and a Service Response	3-2
Table 3-2.	Status_Indicator Values for a Disconnect Request or Disconnect Response	3-6
Table 6-1.	Requirements for Configuration Management of Frame Relay	6-13
Table 6-2.	Requirements for Alarm Monitoring of Frame Relay	6-20
Table 6-3.	Requirements for Physical Performance Management of Frame Relay	6-21
Table 6-4.	Requirements for Performance Management of Frame Relay	6-30
Table 6-5.	Requirements for Security Management of Frame Relay	6-31
Table 7-1.	Objectives for SS7 Signaling Point Response Time or Cross-Office Transfer Time (ms)	7-2
Table 7-2.	Comparison of LANs and WANs	7-6
Table 7-3.	Data Rate and Error Rate Comparison	7-7
Table 7-4.	Example Mean Delay (ms) Performance for CSMA/CD	7-8
Table 7-5.	Example Mean Delay (ms) Performance for Token Ring	7-9
Table 7-6.	Service Level Objectives for Frame Relay Virtual Connection	7-10