

---

# ISDN BRI Trunk Generic Requirements

## Contents

Preface .....	Preface-1
1. Introduction .....	1-1
1.1 Purpose and Scope .....	1-1
1.2 Target Audience .....	1-1
1.3 Relationship to Other Documents .....	1-2
1.4 Structure and Use of This Document .....	1-2
1.5 Requirements Terminology .....	1-3
1.6 Requirement Labeling Conventions .....	1-4
1.6.1 Numbering of Requirement and Related Objects .....	1-4
1.6.2 Requirement, Conditional Requirement, and Objective Object Identification .....	1-5
2. High-Level Description .....	2-1
2.1 Problem/Opportunity .....	2-1
2.2 General Description .....	2-1
2.3 Assumptions, Dependencies, and Constraints .....	2-4
2.4 Supporting Information .....	2-7
2.4.1 Point-To-Point, Point-To-Multipoint, and Passive Bus .....	2-7
2.4.2 Treatment Of Calling Party When Called ISDN Equipment Is Delaying Call Establishment .....	2-8
2.4.3 Calls Coming Into An ISDN Exchange From The PSTN .....	2-8
2.4.4 Use Of STATUS/STATUS ENquiry .....	2-9
2.5 Background .....	2-9
2.6 Terms and Definitions .....	2-10
3. Service Provider, Customer and CPE Perspectives .....	3-1
3.1 Service Provider Perspectives .....	3-1
3.2 Customer Perspectives .....	3-1
3.3 CPE Perspectives .....	3-2
4. Physical Layer .....	4-1
4.1 Assumptions .....	4-1
4.2 Physical Interface Requirements .....	4-1
4.3 Functional Requirements .....	4-2
4.4 Maintenance Requirements .....	4-3
4.5 Miscellaneous Physical Requirements .....	4-4
5. Link Layer .....	5-1
5.1 Link Layer Requirements for D-channel Call Control Signaling .....	5-1

---

6.	Network Layer .....	6-1
6.1	Introduction to ISDN Message Signaling .....	6-1
6.2	Message Sequence Summary .....	6-3
6.2.1	Originating Treatment.....	6-3
6.2.2	Terminating Message Sequences For Successful Call Establishment.....	6-4
6.2.3	Call Clearing Message Sequences .....	6-5
6.2.3.1	User-Initiated Call Clearing.....	6-5
6.2.3.2	Network-Initiated Call Clearing .....	6-6
6.3	Example Use Of Message Sequences And Requirements .....	6-7
6.4	Bearer Capabilities Supported.....	6-20
6.4.1	Circuit-Mode, 64-kbps Unrestricted Digital Transmission, 8-kHz Structured, Demand, Point-To-Point And Bidirectional Symmetric .....	6-21
6.4.2	Circuit-Mode, 64-kbps Unrestricted Digital Transmission-Rate Adapted From 56-kbps, 8-kHz Structured, Demand Point-to-Point and Bidirectional-Symmetric .....	6-22
6.4.3	Circuit-Mode, 64-kbps, 8-kHz Structured, Usable For Speech, Demand, Point-To-Point, and Bidirectional Symmetric .....	6-22
6.4.4	Circuit-Mode, 64-kbps, 8-kHz Structured, Usable For 3.1-kHz Audio Information Transfer, Demand, Point-To-Point, and Bidirectional Symmetric .....	6-22
6.5	Configurations.....	6-22
6.5.1	B-Channel Access .....	6-23
6.5.2	Discussion Of Example Configurations.....	6-24
6.6	Initialization Assumptions and Requirements .....	6-25
7.	Basic Call Control Procedures for Circuit-Mode Calls .....	7-1
7.1	General Rules For Message Processing .....	7-2
7.2	Origination Treatment.....	7-3
7.2.1	Origination From An ISDN Basic Rate Interface (BRI) Trunk.....	7-3
7.2.1.1	Overlap Sending .....	7-11
7.2.1.2	Enbloc Sending .....	7-14
7.2.1.3	Call Proceeding Indication Sent To Calling User Equipment .....	7-15
7.2.1.4	Misdialing Treatments .....	7-16
7.3	Termination Treatment.....	7-18
7.3.1	Termination To An ISDN BRI Trunk Group DN.....	7-19
7.3.1.1	Subscription Parameters .....	7-19
7.3.1.2	Interface Busy/Idle Status.....	7-19
7.3.1.3	Call Delivery.....	7-20
7.3.1.4	Expiration of Timer T303 .....	7-25
7.3.1.5	Call Rejected by the Called Party .....	7-27
7.3.1.6	Channel Indication.....	7-32
7.3.1.7	Call Proceeding Indication .....	7-34
7.3.1.8	Called Party Alerting .....	7-36

---

---

7.3.1.9	Additional Procedures for Incoming Calls .....	7-39
7.3.1.10	Called Party Answer .....	7-41
7.3.2	Termination To Non-ISDN Line.....	7-43
7.3.2.1	Ringing and Audible Ring Tone.....	7-43
7.3.2.2	Ringing Removal .....	7-43
7.3.3	Termination To Non-ISDN Trunk .....	7-44
7.3.3.1	Trunk Selection and Status .....	7-44
7.3.3.2	Answer .....	7-45
7.3.4	Termination Of Calls That Cannot Be Completed.....	7-45
7.3.4.1	Abandoned Calls.....	7-45
7.3.4.2	Busy Line Treatment .....	7-48
7.3.4.3	Intercept Treatment.....	7-49
7.3.4.4	Unavailable Equipment/Facilities, Internal or Other Failures .....	7-52
7.4	Call Clearing Requirements .....	7-54
7.4.1	Call Clearing Of Answered Calls.....	7-55
7.4.1.1	ISDN-to-ISDN Call .....	7-56
7.4.1.2	ISDN BRI Trunk-to-Non-ISDN Call.....	7-57
7.4.1.3	Non-ISDN-to-ISDN BRI Trunk Call.....	7-58
7.4.2	General Call Clearing Procedures for BRI Trunk.....	7-60
7.4.2.1	Call Clearing Request Received From an ISDN BRI Trunk Member BRI .....	7-61
7.4.2.2	SPCS Initiates Call Clearing to an ISDN BRI Trunk Member BRI.....	7-64
7.4.2.3	Clear Collision .....	7-66
7.5	Error Treatment.....	7-66
7.5.1	Protocol Error Treatment .....	7-67
7.5.1.1	Error Treatments Independent of Call State .....	7-67
7.5.1.2	Errors During Call Establishment.....	7-69
7.5.1.3	Errors During An Active Call.....	7-74
7.5.1.4	Errors During Call Clearing.....	7-74
7.5.1.5	Errors Not Associated With A Call .....	7-78
7.5.1.6	Protocol Error Counters .....	7-79
7.5.1.7	Nonlocking Shift Procedures .....	7-80
7.5.2	Layer 3 Actions Resulting From A Malfunctioning Data Link .....	7-80
7.5.2.1	Layer 3 Procedures .....	7-81
7.5.2.2	Call Clearing By Remote User During Recovery Timing .....	7-84
8.	Additional Circuit-Switched Procedures .....	8-1
8.1	Call Reference Administration.....	8-1
8.1.1	Allocation And Release Of Call References.....	8-1
8.1.2	Call References Used In Messages Sent By The SPCS.....	8-2
8.1.3	Call References In Messages Received By The SPCS .....	8-2
8.2	SPCS Channel Assignment .....	8-3

---

---

8.2.1	Originating B-Channel Selection .....	8-4
8.2.2	D/B-Channel Selection For Terminating Calls .....	8-6
8.2.2.1	Selection of a Member BRI .....	8-6
8.2.2.2	Bearer Capability Indicates Channel Type .....	8-7
8.2.2.3	Selection of a B-Channel .....	8-7
8.3	ISDN Code Interpretation .....	8-7
8.3.1	General .....	8-8
8.3.2	Address Transport Using The Keypad Information Element .....	8-9
8.3.2.1	General Use .....	8-9
8.3.2.2	ISDN Dialing Plan .....	8-9
8.3.3	Enbloc Signaling Method (Non-keypad) .....	8-11
8.3.3.1	General Use .....	8-11
8.3.3.2	Called Party Number Information Element Interpretation.....	8-11
8.3.3.3	Transit Network Selection Information Element Interpretation.....	8-14
8.3.3.4	Operator System Access Information Element Interpretation.....	8-15
8.3.4	Subaddressing .....	8-16
8.4	ISDN Routing.....	8-17
8.4.1	Circuit-Mode Bearer Capabilities .....	8-17
8.4.1.1	General Procedures for Call Originations.....	8-17
8.4.1.2	Called Party Number .....	8-18
8.4.1.3	Transit Network Selection .....	8-18
8.4.1.4	Operator System Service Request .....	8-19
8.4.1.5	Combination Routing Information .....	8-19
8.4.2	Special Conditions (Network Management).....	8-20
8.4.3	N11 Routing .....	8-20
8.4.4	Terminating Calls.....	8-21
8.4.4.1	Intersystem Incoming Call Destination Codes .....	8-21
8.4.4.2	Intercept Treatment.....	8-21
8.5	Network Determination of Interface Busy .....	8-21
8.5.1	Busy For Circuit-Switched Calls .....	8-21
8.5.1.1	Busy Limit for Originating Circuit-Switched Calls.....	8-22
8.5.1.2	Busy Limit for Terminating Circuit-Switched Calls .....	8-23
8.6	Timers .....	8-24
8.7	Tones And Announcements .....	8-27
8.7.1	Assumption For This Document .....	8-31
8.7.2	Timing of Inband Tones and Announcements Returned on an ISDN Call .....	8-31
8.7.3	Tones Associated With Call Origination .....	8-32
8.7.4	Tones Associated With The Attempted Completion Of A Call.....	8-33
8.7.5	Tone Associated With The Termination Of Completed Calls .....	8-34

---

8.7.6	Tones And Announcements Associated With The Termination Of Calls That Cannot Be Completed.....	8-35
8.8	ISDN Displays .....	8-38
9.	Common Procedures for Feature Support.....	9-1
9.1	ISDN Displays .....	9-1
9.2	Dial Access for Feature Control.....	9-1
10.	Feature Operation.....	10-1
10.1	Calling Number Identification Services (CNIS) .....	10-1
10.1.1	Number Provision .....	10-1
10.1.2	Number Screening.....	10-2
10.1.3	Number Privacy/Number Presentation .....	10-4
10.1.4	Calling Number Delivery.....	10-5
10.1.5	Calling Party Subaddress .....	10-5
10.1.6	CPN Selection for E9-1-1 Calls .....	10-5
10.1.7	Other Requirements .....	10-7
10.1.8	Common Channel Signaling.....	10-8
10.2	Redirecting Number Identification .....	10-8
10.3	Calling Name .....	10-9
10.3.1	Link BRI Calling Name Presentation to Calling Number Presentation.....	10-10
10.3.2	ISDN Calling Identity Delivery and Suppression (I-CIDS) .....	10-10
10.3.3	ISDN Calling Name Delivery (I-CNAM).....	10-11
10.3.4	ISDN Delivery Feature - Deactivation/Reactivation-Not Supported .....	10-12
10.3.5	ISDN Calling Name Display.....	10-12
10.3.6	Additional Requirements .....	10-13
10.3.7	Common Channel Signaling.....	10-14
10.4	Redirecting Name.....	10-14
10.5	Call Forwarding Subfeatures.....	10-14
10.5.1	Activation/Deactivation .....	10-15
10.5.2	Forwarding a Call.....	10-16
10.5.2.1	Originating SPCS Action.....	10-16
10.5.2.2	Base SPCS Action .....	10-16
10.5.2.3	Remote SPCS Action.....	10-17
10.5.2.4	Calls That Cannot Be Forwarded .....	10-18
10.5.3	Conditions on Forwarding .....	10-18
10.5.3.1	Busy .....	10-18
10.5.3.2	Don't Answer.....	10-19
10.5.3.3	Sequential Forwarding.....	10-19
10.5.3.4	Multiple Forwarding.....	10-20
10.5.3.5	Source of Call .....	10-20
10.5.3.6	Remote DN.....	10-20
10.5.4	Subfeature Construction.....	10-20

---

---

10.5.5	Other Requirements .....	10-21
11.	Feature Interactions.....	11-1
11.1	Additional Feature Interactions Between Features Assigned to an ISDN BRI Trunk Group .....	11-3
12.	Memory Administration (Service Changes/Subscription Parameters) .....	12-1
12.1	Overview of BRI Trunk Structure.....	12-1
12.2	BRI Trunk Group Parameters .....	12-2
12.2.1	Group Parameters for BRI Trunk Call Origination .....	12-3
12.2.2	Group Parameters for BRI Trunk Call Termination .....	12-6
12.2.2.1	Call Forwarding .....	12-6
12.3	BRI Trunk Interface Parameters .....	12-8
12.4	Provisioning <u>Sequence</u> .....	12-9
13.	Network Maintenance .....	13-1
13.1	Obtaining BRI Trunk Related Information .....	13-1
13.2	Surveillance.....	13-2
13.3	Testing.....	13-2
14.	Surveillance and Billing.....	14-1
14.1	Surveillance.....	14-1
14.1.1	Network Data Collection (NDC) .....	14-1
14.1.2	Network Traffic Management (NTM) .....	14-2
14.1.3	Billing and Comptroller .....	14-2
14.1.3.1	Information Transfer Billing.....	14-3
14.1.3.2	Billing for Number and Name Services.....	14-4
15.	Layer 3 Messages and Information Elements .....	15-1
15.1	Message Functional Definitions.....	15-1
15.1.1	Overview .....	15-1
15.1.2	Messages .....	15-2
15.1.2.1	ALERTing .....	15-3
15.1.2.2	CALL PROCeeding.....	15-5
15.1.2.3	CONNect .....	15-7
15.1.2.4	CONNect ACKnowledge .....	15-8
15.1.2.5	DISConnect.....	15-9
15.1.2.6	INFORmation.....	15-10
15.1.2.7	PROGress .....	15-12
15.1.2.8	RELease .....	15-14
15.1.2.9	RELease COMplete .....	15-16
15.1.2.10	SETUP .....	15-17
15.1.2.11	SETUP ACKnowledge .....	15-21
15.1.2.12	STATus.....	15-21
15.2	Message Structure .....	15-25
15.2.1	General Coding Rules .....	15-25
15.2.2	Protocol Discriminator.....	15-26

---

---

15.2.3	Call Reference.....	15-27
15.2.4	Message Type .....	15-28
15.2.5	Other Information Elements.....	15-29
15.2.5.1	Shift Information Element .....	15-31
15.2.5.2	Bearer Capability .....	15-33
15.2.5.3	Call State.....	15-35
15.2.5.4	Called Party Number .....	15-38
15.2.5.5	Called Party Subaddress .....	15-40
15.2.5.6	Calling Party Number .....	15-42
15.2.5.7	Calling Party Subaddress.....	15-46
15.2.5.8	Cause.....	15-48
15.2.5.9	Channel Identification .....	15-65
15.2.5.10	Endpoint Identifier.....	15-67
15.2.5.11	High Layer Compatibility.....	15-69
15.2.5.12	Information Request .....	15-70
15.2.5.13	Keypad.....	15-71
15.2.5.14	Low Layer Compatibility .....	15-72
15.2.5.15	Progress Indicator .....	15-74
15.2.5.16	Redirecting Number.....	15-76
15.2.5.17	Redirecting Subaddress .....	15-82
15.2.5.18	Service Profile Identification.....	15-83
15.2.5.19	Signal .....	15-84
15.2.5.20	Transit Network Selection .....	15-85
15.2.6	National-Specific Information Elements (Codeset 5).....	15-87
15.2.6.1	Display Text.....	15-87
15.2.6.2	Operator System Access .....	15-92
15.2.7	Network-Specific Information Elements (Codeset 6).....	15-93
Appendix A:	Data Dictionary for ISDN BRI Trunk .....	A-1
A.1	Scope and Definition.....	A-1
A.2	Allowed Data Values .....	A-2
A.3	Data Dictionary .....	A-3
A.3.1	Parameters Associated with the BRI Trunk Group.....	A-3
A.3.2	BRI Trunk Interface Parameters .....	A-13
A.3.3	BRI Trunk SPCS Parameters .....	A-13
Appendix B:	Originating Call Screening Procedures.....	B-1
References .....	References-1	
Ref.1	Bellcore Family of Requirements (FR).....	References-1
Ref.2	Bellcore Generic Requirements (GR) .....	References-1
Ref.3	Bellcore Special Reports .....	References-2
Ref.4	Bellcore Technical References.....	References-2
Glossary .....	Glossary-1	
Requirement-Object Index .....	ROI-1	

---



---

## List of Figures

Figure 1-1.	BRI Trunk Configuration Example .....	1-1
Figure 2-1.	BRI Trunk Configuration Example: Key System.....	2-2
Figure 2-2.	BRI Trunk Configuration Example: SOHO .....	2-2
Figure 6-1.	Message Sequence for User-Initiated Call Clearing.....	6-10
Figure 6-2.	ISDN-BRI Trunk-to-ISDN-BRI Trunk Intraswitch Call Example .....	6-11
Figure 6-3.	Originating SETUP Message Coding Example.....	6-12
Figure 6-4.	CALL PROCeeding Message Coding Example to Originating Party....	6-13
Figure 6-5.	Terminating SETUP Message Coding Example .....	6-14
Figure 6-6.	ALERTing Message Coding Example from Terminating Party .....	6-15
Figure 6-7.	ALERTing Message Coding Example to Originating Party .....	6-15
Figure 6-8.	CONNect Message Coding Example from Terminating Party .....	6-16
Figure 6-9.	CONNect ACKnowledge Message Coding Example to Terminating Party .....	6-16
Figure 6-10.	CONN Message Coding Example to Originating Party .....	6-17
Figure 6-11.	CONN ACKnowledge Message Coding Example from Originating Party .....	6-17
Figure 6-12.	DISconnect Message Coding Example from Originating Party .....	6-18
Figure 6-13.	DISconnect Message Coding Example to Terminating Party .....	6-18
Figure 6-14.	RELEase Message Coding Example to Originating Party .....	6-19
Figure 6-15.	RELEase COMplete Message Coding Example from Originating Party	6-19
Figure 6-16.	RELEase Message Coding Example from Terminating Party .....	6-20
Figure 6-17.	RELEase COMplete Message Coding Example to Terminating Party...	6-20
Figure 6-18.	Auto-SPID Can Assist in Administering B-Channel Searches at SPCS and CPE.....	6-26
Figure 15-1.	General Message Organization Example .....	15-26
Figure 15-2.	Protocol Discriminator Information Element .....	15-27
Figure 15-3.	Call Reference Information Element .....	15-27
Figure 15-4.	Null Call Reference .....	15-28
Figure 15-5.	Message Type .....	15-28
Figure 15-6.	Network-Specific Message Type.....	15-29
Figure 15-7.	Formats of Information Elements.....	15-30
Figure 15-8.	Locking Shift Information Element.....	15-32
Figure 15-9.	Nonlocking Shift Information Element .....	15-32
Figure 15-10.	Bearer Capability Information Element .....	15-33
Figure 15-11.	Call State Information Element .....	15-35
Figure 15-12.	Called Party Number Information Element.....	15-39
Figure 15-13.	Called Party Subaddress Information Element.....	15-41
Figure 15-14.	Calling Party Number Information Element .....	15-43
Figure 15-15.	Calling Party Subaddress Information Element .....	15-47

---

Figure 15-16. Cause Information Element .....	15-49
Figure 15-17. Channel Identification Information Element .....	15-65
Figure 15-18. Endpoint Identifier information element .....	15-67
Figure 15-19. High Layer Compatibility Information Element .....	15-69
Figure 15-20. Information Request Information Element .....	15-70
Figure 15-21. Keypad Information Element .....	15-71
Figure 15-22. Low Layer Compatibility Information Element .....	15-72
Figure 15-23. Progress Indicator Information Element.....	15-74
Figure 15-24. Redirecting Number Information Element .....	15-76
Figure 15-25. Redirecting Subaddress Information Element .....	15-82
Figure 15-26. Service Profile Identification Information Element .....	15-84
Figure 15-27. Signal Information Element.....	15-84
Figure 15-28. Transit Network Selection Information Element.....	15-85
Figure 15-29. Structure of Display Text Information Element .....	15-87
Figure 15-30. General Coding of Optional Control Tags .....	15-89
Figure 15-31. 3-Octet Optional Control Tag.....	15-90
Figure 15-32. Operator System Access Information Element .....	15-92
Figure B-1. Call Originating Screening Procedures for BRI Trunk Member.....	B-2

---

## List of Tables

Table 6-1.	Example Configurations .....	6-24
Table 7-1.	Call States, Originating Interface, Before Address Sending Complete..	7-71
Table 7-2.	Call States, Originating Interface, After Address Sending Complete ....	7-72
Table 7-3.	Call States, Terminating Interface .....	7-73
Table 7-4.	Call States Resulting From Call Clearing Events.....	7-77
Table 7-5.	Call Processing If User Equipment Is In A Clearing Call State .....	7-84
Table 8-1.	Correlation Between Signaling Methods.....	8-14
Table 8-2.	Operator System Request Interpretation.....	8-16
Table 8-3.	Combination of Routing Information .....	8-20
Table 8-4.	Timers At The SPCS .....	8-24
Table 8-5.	Inband Tones and the Corresponding Signal Information.....	8-29
Table 8-6.	Tones and Announcements Associated with Specific Cause Values .....	8-36
Table 8-7.	Recommended Announcements Associated with ISDN Specific Cause Values .....	8-38
Table 10-1.	Subfeature Construction for I-CFB .....	10-21
Table 10-2.	Subfeature Construction for I-CFDA .....	10-21
Table 11-1.	ISDN BRI Feature Assignments to a BRI Trunk Group .....	11-1
Table 11-2.	Feature Assignment and Operation Interactions for Features Assigned to a BRI Trunk Group.....	11-2
Table 11-3.	ISDN BRI Feature Assignment and Operation Interactions with BRI Trunk.....	11-2
Table 11-4.	ISDN TSP Assignment and Operation Interactions with the BRI Trunk feature.....	11-3
Table 15-1.	User-to-Network ALERTing Message Content .....	15-3
Table 15-2.	Network-to-User ALERTing Message Content .....	15-3
Table 15-3.	User-to-Network CALL PROCeeding Message Content.....	15-5
Table 15-4.	Network-to-User CALL PROCeeding Message Content.....	15-5
Table 15-5.	User-to-Network CONNect Message Content .....	15-7
Table 15-6.	Network-to-User CONNect Message Content .....	15-7
Table 15-7.	User-to-Network CONNect ACKnowledge Message Content .....	15-8
Table 15-8.	Network-to-User CONNect ACKnowledge Message Content .....	15-8
Table 15-9.	User-to-Network DISConnect Message Content .....	15-9
Table 15-10.	Network-to-User DISConnect Message Content .....	15-9
Table 15-11.	User-to-Network INFOrmation Message Content .....	15-10
Table 15-12.	Network-to-User INFOrmation Message Content .....	15-11
Table 15-13.	Network-to-User PROGress Message Content .....	15-12
Table 15-14.	User-to-Network RELease Message Content.....	15-14
Table 15-15.	Network-to-User RELease Message Content.....	15-14
Table 15-16.	User-to-Network RELease COMplete Message Content .....	15-16

---

Table 15-17. Network-to-User RELEase COMplete Message Content.....	15-16
Table 15-18. User-to-Network SETUP Message Content .....	15-17
Table 15-19. Network-to-User SETUP Message Content .....	15-19
Table 15-20. Network-to-User SETUP ACKnowledge Message Content .....	15-21
Table 15-21. User-to-Network STATus Message Content.....	15-22
Table 15-22. Network-to-User STATus Message Content.....	15-22
Table 15-23. Network-to-User STATus ENQuiry Message Content .....	15-23
Table 15-24. Message Types .....	15-29
Table 15-25. ITU-T Recommendation Q.931- and Q.932-Defined Information Element Identifier Coding (Codeset 0) .....	15-31
Table 15-26. Call State Values .....	15-36
Table 15-27. ITU-T Standardized Cause Values .....	15-52
Table 15-28. National Standardized Cause Values.....	15-54
Table 15-29. Network Specific Cause Values .....	15-54
Table 15-30. Use of ITU-T Standardized Cause Values .....	15-62
Table 15-31. Use of National Standardized Cause Values .....	15-64
Table 15-32. Use of Network Specific Cause Values.....	15-65
Table 15-33. Display Information (Relative Order of Octets 4, etc.) .....	15-88
Table 15-34. Coding of ASCII Characters.....	15-91
Table A-1. Allowed Values of FORM.....	A-2
Table A-2. BRI Trunk Group Parameters.....	A-3
Table A-3. BRI Trunk Interface Parameters .....	A-13
Table A-4. BRI Trunk SPCS Parameters.....	A-13