

Contents

Preface.....	Preface-1
1. Introduction.....	1-1
1.1 Purpose and Scope	1-2
1.2 Target Audience	1-3
1.3 Background	1-3
1.4 Assumptions	1-4
1.5 Requirements Terminology	1-7
1.6 Reason for Reissue	1-7
1.7 Requirement Labeling Conventions	1-8
1.7.1 Numbering of Requirement and Related Objects.....	1-8
1.7.2 Requirement, Conditional Requirement, and Objective Object Identification	1-8
2. User Perspective	2-1
3. PSAP Perspective	3-1
4. E9-1-1 Network Provider Perspective.....	4-1
4.1 E9-1-1 Network Architecture.....	4-1
4.2 E9-1-1 Information Exchange.....	4-3
4.3 Interworking.....	4-4
5. Requirements	5-1
5.1 Switch Requirements.....	5-1
5.1.1 Processing of Emergency Calls.....	5-1
5.1.1.1 Originating Wireline EO Requirements	5-1
5.1.1.1.1 Originating EO/SSP Requirements	5-1
5.1.1.1.2 Non-SSP Originating EO Requirements	5-7
5.1.1.2 Tandem Switch Requirements.....	5-10
5.1.1.2.1 Tandem/SSP Requirements	5-10
5.1.1.2.2 Non-SSP Tandem Requirements.....	5-20
5.1.1.3 Alternate Routing of Emergency Calls	5-20
5.1.1.4 Requirements on the Switch Serving the PSAP.....	5-22
5.1.1.4.1 Call Delivery to the PSAP	5-22
5.1.1.4.2 Call Transfer.....	5-28
5.1.2 Fault Handling Related to the Processing of Emergency Calls.....	5-30
5.1.3 Operations	5-31
5.1.3.1 Data Administration.....	5-31
5.1.3.2 Traffic Measurements.....	5-32
5.1.3.3 Network Traffic Management (NTM)	5-33
5.1.3.4 Maintenance.....	5-33
5.2 Signaling Requirements.....	5-33

5.2.1	SS7 Call Setup Signaling Requirements	5-33
5.2.1.1	IAMs Generated by a Wireline EO.....	5-34
5.2.1.1.1	Non-SSP EO - Emergency Call Routed Over Shared SS7-Supported Trunk to Tandem SSP.....	5-34
5.2.1.1.2	SSP EO - Emergency Call Routed Over Shared SS7-Supported Trunk Toward Switch Serving the PSAP	5-36
5.2.1.1.3	Non-SSP EO - Emergency Call Routed Over Dedicated SS7-Supported Trunk to Tandem SSP	5-39
5.2.1.2	IAMs Generated by a Wireless MSC.....	5-41
5.2.1.2.1	Wireless Emergency Call Routed Over Shared SS7-Supported Trunk from Non-SSP MSC to Access Tandem/SSP	5-42
5.2.1.2.2	Wireless Emergency Call Routed Over Shared SS7-Supported Trunk From an MSC/SSP to an Access Tandem	5-44
5.2.1.2.3	Wireless Emergency Call Routed Over Dedicated SS7-Supported Trunks From Non-SSP MSC to Access Tandem/SSP	5-45
5.2.1.3	IAMs Generated by a Tandem SSP.....	5-47
5.2.1.3.1	IAM Encoding for Wireline Emergency Calls From Tandem SSP Toward Serving Switch.....	5-47
5.2.1.3.2	IAM Encoding for Wireless Emergency Calls from Tandem SSP Toward Serving Switch.....	5-49
5.2.1.4	IAM Encoding for Transferred Emergency Calls	5-51
5.2.1.4.1	Wireline Emergency Calls.....	5-51
5.2.1.4.2	Wireless Emergency Calls	5-55
5.2.2	TCAP Signaling Requirements	5-60
5.2.2.1	Initial Call Routing Query from SSP	5-60
5.2.2.1.1	Trigger Based on Dialed/Called Party Number Digits	5-60
5.2.2.1.2	Trigger Based on Incoming Trunk Group.....	5-65
5.2.2.2	SCP Response to Initial Routing Query.....	5-69
5.2.2.3	SSP Request for Alternate Routing Instructions	5-73
5.2.2.4	SCP Response Containing Alternate Routing Instructions	5-83
5.2.2.5	Query From Serving Switch to Obtain Routing Information for Selective and Fixed Transfer	5-85

5.2.2.5.1	Query Associated With a Specific_Feature_Code or Public_Feature_Code Trigger	5-85
5.2.2.6	Response to Query to Obtain Routing Information for Selective and Fixed Transfer	5-89
5.2.2.6.1	Response to Info_Analyzed Message	5-89
5.3	SCP Requirements	5-92
5.3.1	Support for Selective Routing Function	5-94
5.3.2	Support for Automatic Location Identification (ALI) Function	5-99
5.3.2.1	ALI Data Storage	5-100
5.3.2.2	PSAP Query Support	5-101
5.3.2.3	ALI Steering	5-102
5.3.2.3.1	Request for Location (MPC Query)	5-102
5.3.2.3.2	ALI to ALI Steering	5-103
5.3.2.3.3	Communication Between SCP and ALI	5-103
6.	Network Impacts	6-1
6.1	Reliability and Quality	6-1
	References	References-1
	Glossary	Glossary-1

List of Figures

Figure 1-1. Representative AIN-Based Architecture for E9-1-1 Service 1-6