

Contents

Preface	xi
The Telcordia Technologies GR Process	xi
About GR-3028-CORE	xi
Funders of GR-3028-CORE, Issue 1, are:	xi
Relative Maturity Level	xii
To Submit Comments	xii
1 Introduction	
1.1 Purpose and Scope	1-5
1.2 Requirements Terminology	1-6
1.3 Requirement Labeling Conventions	1-6
1.3.1 Numbering of Requirement and Related Objects	1-6
1.3.2 Requirement, Conditional Requirement, and Objective Identification	1-7
1.4 Document Organization	1-7
1.5 Revisions	1-8
2 Equipment Cooling and EC-Classes	
2.1 Equipment-Cooling (EC) Classes	2-1
2.2 EC-Class Syntax	2-2
2.2.1 Duct Hook-Up	2-5
2.2.2 Liquid Hook-Up	2-5
2.2.3 Non-Standard EC-Class	2-6
2.2.4 Passive-Component EC-Class	2-6
2.3 Preferred EC-Classes	2-7
3 Room Cooling (RC) and Supplemental Cooling (SC) Classes	
3.1 Room-Cooling (RC) Classes	3-1
3.1.1 Legacy RC-Classes	3-2
3.1.1.1 RC-Class VOH (Vertical Overhead Air-Distribution)	3-2
3.1.1.2 RC-Class HOH (Horizontal Overhead Air-Distribution)	3-3
3.1.2 Non-Legacy RC-Classes	3-4
3.1.2.1 RC-Class HDP (Horizontal Displacement Air-Distribution)	3-4
3.1.2.2 RC-Class VUF (Vertical Under-Floor Air-Distribution)	3-5
3.1.2.3 RC-Class NOH (Natural Convection Overhead Air-Distribution)	3-6
3.2 Supplemental-Cooling (SC) Classes	3-8
3.2.1 SC-Class In-Room	3-8
3.2.2 SC-Class In-Frame	3-9
3.2.3 SC-Class Direct Return	3-10
4 Environmental Criteria	
4.1 Facility Operation	4-1

4.2 Human Thermal Comfort	4-2
4.3 Equipment Testing	4-3
4.4 Selected Modeling Baseline Criteria	4-3

5 Heat-Release Targets (HRT)

5.1 Heat-Release Targets and Optimal EC-Classes	5-1
5.2 Temporal Temperature Gradients	5-10

6 Equipment Specifications

6.1 Heat-Release Model	6-2
6.1.1 Algorithm Development (Step 1)	6-3
6.1.2 Demonstration of Algorithm Accuracy (Step 2)	6-3
6.1.3 Planning Value (Step 3)	6-4
6.1.4 Equipment Data Reporting	6-5
6.2 Reporting Format R/O	6-7

Appendix A: The Telecommunications Environment

Appendix B: Equipment Cooling and EC-Classes

B 2.1 Equipment-Cooling (EC) Classes	B-1
B 2.2 EC-Class Syntax	B-1

Appendix C: Room Cooling and RC- and SC-Classes

C 3.1.1 Legacy RC-Classes	C-2
C 3.1.1.1 RC-Class VOH (Vertical Overhead Air-Distribution)	C-2
C 3.1.1.2 RC-Class HOH (Horizontal Overhead Air-Distribution)	C-6
C 3.1.2 Non-Legacy RC-Classes	C-9
C 3.1.2.1 RC-Class HDP (Horizontal Displacement Air-Distribution)	C-9
C 3.1.2.2 RC-Class VUF (Vertical Under-Floor Air-Distribution)	C-12
C 3.1.2.3 RC-Class NOH (Natural Convection Overhead Air-Distribution)	C-16
C 3.2.1 SC-Class In-Room	C-18
C 3.2.2 SC-Class In-Frame	C-19
C 3.2.3 SC-Class Direct Return	C-19

Appendix D: Environmental Criteria

D 4.2 Human Thermal Comfort	D-3
D 4.4 Selected Modeling Baseline Criteria	D-4

Appendix E: Heat-Release Targets (HRT)

E 5.1 Heat-Release Targets and Optimal EC-Classes	E-1
E 5.2 Temporal Temperature Gradients	E-2

Appendix F: Equipment Specifications Form

F 6.2 Reporting Format R/O	F-1
--------------------------------------	-----

Appendix G: Heat-Transfer Fundamentals

Requirement-Object Index

List of Figures

Figure 1-1	Main Cornerstones of GR-3028-CORE	1-3
Figure 2-1	EC-Class Syntax: Face Definitions	2-2
Figure 2-2	EC-Class Syntax: Level Definitions	2-3
Figure 2-3	EC-Class Syntax: (S) F1-T Class	2-3
Figure 2-4	EC-Class Syntax: (S) F1-F3 Class	2-4
Figure 2-5	Class (S) F1-T (Exhaust hook-up)	2-5
Figure 2-6	Class (S) F1-T (Intake/exhaust hook-up)	2-5
Figure 2-7	Class (S) F1-T (Liquid hook-up)	2-6
Figure 2-8	Preferred EC-Classes	2-8
Figure 3-1	RC-VOH Class (for cable rack definitions, see Glossary)	3-3
Figure 3-2	RC-HOH Class (for cable rack definitions, see Glossary)	3-4
Figure 3-3	RC-HDP Class (for cable rack definitions, see Glossary)	3-5
Figure 3-4	RC-VUF Class (for cable rack definitions, see Glossary)	3-6
Figure 3-5	RC-NOH Class (for cable rack definitions, see Glossary)	3-7
Figure 3-6	SC-Class In-Room (typical temperatures)	3-9
Figure 3-7	SC-Class In-Frame (typical temperatures)	3-10
Figure 3-8	SC-Class Direct Return (typical temperatures)	3-11
Figure 4-1	Monitoring Volume	4-5
Figure 5-1	Environmental Parameters of Interest for the Normal HVAC Operation and the Catastrophic HVAC Outage Scenarios	5-1
Figure 5-2	Temperature Field Showing Poor Airflow Interaction	5-3
Figure 5-3	Estimated Trunk Duct Sizes to Serve 6 Building Bays (Assumes 2200 fpm (11 m/s) and 32°F (18°C) temperature differential)	5-4
Figure 5-4	Temperature Field Showing Real-World Conditions	5-5
Figure 5-5	Example of Real-World Conditions: Crowded Overhead Space	5-5
Figure 5-6	HVAC Outage--Analytical/Numerical	5-12
Figure 5-7	HVAC Outage--Numerical/NEBS Test	5-13
Figure 5-8	Add-on Rate-of-Change Test	5-14
Figure A1-1	Switch Environment	A-2
Figure A1-2	Toll Environment, Short	A-2
Figure A1-3	Toll Environment, Tall	A-3
Figure A1-4	Centralized Power Plant Environment	A-3
Figure A1-5	MDF (Main Distributing Frame) Environment	A-4
Figure A1-6	External View of Typical Central Office Building	A-4
Figure B2-1	Class (S) F1-R3. Front-bottom to rear-top	B-1
Figure B2-2	Class (S) F1-T. Front-bottom to Top	B-2
Figure B2-3	Class (S) F1-F3. Front-bottom to Front-top	B-2
Figure B2-4	Class (S) F1/R1-T. Front-bottom and rear-bottom to top	B-2
Figure B2-5	Class (S) F2-R2. Front to Rear	B-3
Figure B2-6	Class (S) F2-T/B. Front to Top and Bottom	B-3
Figure B2-7	Class (S) F3-F1. Front-top to Front-bottom	B-3
Figure B2-8	Class (S) B-SL/SR. Bottom to sides	B-3
Figure B2-9	Class (S) SL-SR. Side to Side	B-4
Figure C3-1	RC-VOH Class (Section)	C-4

Figure C3-2	RC-VOH Class (Plan)	C-4
Figure C3-3	CFD Representation of RC-Class VOH Near the HRT	C-5
Figure C3-4	Typical RC-VOH Class Air Distribution System	C-5
Figure C3-5	RC-HOH Class (Section)	C-7
Figure C3-6	RC-HOH Class (Plan)	C-7
Figure C3-7	CFD Representation of RC-Class HOH Near the HRT	C-8
Figure C3-8	Typical RC-HOH Air Distribution System	C-8
Figure C3-9	RC-HDP Class (Section)	C-10
Figure C3-10	RC-HDP Class (Plan)	C-11
Figure C3-11	CFD Representation of RC-Class HDP Near the HRT	C-11
Figure C3-12	Typical RC-HDP air distribution system	C-12
Figure C3-13	RC-VUF Class (Section)	C-14
Figure C3-14	RC-VUF Class (Plan)	C-14
Figure C3-15	CFD Representation of RC-Class VUF Near the HRT	C-15
Figure C3-16	Typical RC-VUF Air Distribution System	C-15
Figure C3-17	RC-NOH Class (Section)	C-17
Figure C3-18	Typical RC-NOH Air Distribution System	C-18
Figure E5-1	HVAC Outage-Numerical/Empirical	E-3
Figure E5-2	Add-on Rate-of-Change Test	E-4

List of Tables

Table 4-1	GR-3028-CORE Modeling Baseline Criteria	4-4
Table 5-1	Heat-Removal Capacity of Five RC-Classes--Up To and Including the Modeled Heat-Release Target (HRT)--and Optimal EC-Classes . .	5-6
Table 5-2	Equipment Maximum Heat Release	5-8
Table 5-3	First 10-Minute Temporal Temperature Gradient (No backup cooling and ventilation)	5-10
Table 5-4	Add on Rate of Change Test	5-14
Table D-1	Environmental Cross Reference and GR-3028-CORE Modeling Baseline Criteria	D-4
Table F-1	"Form" Frame Level Equipment Data Example	F-3
Table F-2	"Form" Shelf Level Equipment Data Example	F-4
Table F-3	"Form" Plug-In Level Equipment Data Example	F-5
Table F-4	"Form" Unit Level Equipment Data Example	F-6
Table F-5	"Form" Frame Level Equipment Data	F-9
Table F-6	"Form" Shelf Level Equipment Data	F-10
Table F-7	"Form" Plug-In Level Equipment Data	F-11
Table F-8	"Form" Unit Level Equipment Data	F-12
Table G-1	Conversion Factors Between English and Metric Units	G-2