

Contents

Preface	Preface-1
1. Introduction	1-1
1.1 Purpose and Scope	1-1
1.2 High-Level Overview	1-2
1.3 Target Audience	1-4
1.4 Relationship to Other NGN Documents	1-4
1.5 Structure and Use of This Document	1-5
1.6 Requirements Terminology	1-6
1.7 Requirement Labeling Conventions	1-7
1.7.1 Numbering of Requirement and Related Objects	1-7
1.7.2 Requirement, Conditional Requirement, and Objective Object Identification	1-8
2. NGN Architecture Overview	2-1
2.1 High-Level View of a Next Generation Network Architecture	2-1
2.2 Functional Elements	2-2
2.2.1 Core Network	2-4
2.2.2 Call Connection Agent	2-4
2.2.3 Signaling Gateway	2-4
2.2.4 Trunk Gateway	2-4
2.2.5 Access Gateway	2-5
2.2.6 Access Network	2-5
2.2.7 Customer Gateway	2-5
2.2.7.1 Residential/Small Business Gateway	2-6
2.2.7.2 PBX Gateway	2-6
2.2.7.3 Customer Gateway Interfaces	2-6
2.2.8 Network Mediation Gateway	2-8
2.2.9 Protocol Considerations	2-8
2.2.10 Applications Support	2-11
2.2.11 Services Consideration	2-12
2.3 Assumptions, Dependencies, and Constraints	2-13
3. Customer Gateway Architecture and High-Level Requirements	3-1
3.1 Overview of Customer Gateway Architecture	3-1
3.2 Physical Characteristics	3-2
3.2.1 Considerations for Physical Design of R/SB Gateways	3-2
3.2.1.1 R/SB GW Location	3-3
3.2.1.2 Powering Considerations	3-4
3.3 Size, Modularity, Scalability	3-5
3.4 Customer Gateway Functions	3-6
3.4.1 User Device Interface Function	3-6
3.4.1.1 PSTN Device Termination	3-6
3.4.1.2 Data Device Termination	3-7
3.5 Network Access Interface Function	3-7

3.6	Signaling Exchange Function	3-8
3.7	User Information Management Function	3-9
3.7.1	Speech Compression, Transcoding, and Packetization . . .	3-10
3.7.2	Silence Detection, Suppression, and Comfort Noise Insertion	3-11
3.7.3	Echo Cancellation	3-13
3.7.4	Receive Path Delay and Jitter Compensation	3-13
3.7.5	Fax/Modem Detection	3-14
4.	Protocols for Transport, Connection Management, Device Control and Call Control	4-1
4.1	CGW Transport Requirements	4-1
4.1.1	QoS Considerations	4-1
4.1.2	Requirements for ATM Access	4-2
4.1.3	Requirements for IP Access	4-4
4.1.3.1	QoS in an IP Access Network	4-4
4.2	Connection Management and Device Control Using H.248	4-5
4.2.1	Terminations, Contexts, and Edge-to-Edge Connections . . .	4-6
4.2.2	H.248 Semantics and Syntax	4-8
4.2.2.1	Message Structure and Content	4-8
4.2.2.2	Commands and Command Contents	4-9
4.2.2.3	Syntax and Encoding	4-10
4.2.2.4	Overview of Command Triggers and Send/Receive Requirements	4-11
4.2.3	Identifier Allocation, Release, and Management	4-19
4.2.3.1	Transaction Identifier	4-19
4.2.4	Termination Identifiers	4-20
4.2.5	Context Identifier [H.248 Based]	4-20
4.2.6	Context Identifiers [IUA Based]	4-21
4.2.7	Stream Identifiers (H.248 Based)	4-21
4.2.8	Properties, Events, Signals, Digit Map Specifications and Packages	4-22
4.2.9	Call Statistics	4-26
4.2.10	Device Control between the CCA and CGW	4-26
4.2.11	Support for ISDN	4-27
4.2.11.1	SCTP	4-27
4.2.12	Functional View of SCTP	4-28
4.2.13	SCTP Protocol Requirements	4-30
4.2.14	Others	4-33
5.	Call Processing	5-1
5.1	R/SB GW-to-R/SB GW Call, Analog Line Case	5-2
5.1.1	Call Establishment	5-2
5.2	Error Cases During Call Establishment	5-26
5.2.1	Error Case - Invalid Called Number	5-26
5.2.2	Error Case - Called User Busy	5-28
5.2.3	Error Case - Receiver Off-Hook After Dial Tone Expires . .	5-30

6.	Services	6-1
6.1	NGN Reference Model – Gateways, Networks, and Services	6-2
6.2	Defining NGN Services and Applications	6-5
6.3	Extending PSTN and ISDN Services to NGN	6-8
6.4	Third-Party Service Development for NGN Services	6-12
6.5	Voice, Data, Video, and Multimedia in an NGN	6-14
6.6	New NGN Applications for CGW End Users	6-16
7.	Customer Gateway Service Activation	7-1
7.1	Residential/Small Business Gateway Configuration and Installation	7-1
7.1.1	R/SB GW Configuration Parameters	7-2
7.1.1.1	Other Considerations	7-4
7.1.2	Installation	7-4
	Appendix A: IP Phones	A-1
A.1	General Description	A-1
A.2	Protocol	A-2
	Appendix B: CGW User-Side PSTN Interface Signaling and Supervision Requirements	B-1
B.1	Analog Line Supervision and Signaling Criteria	B-1
B.1.1	Loop-Start Signaling	B-1
B.1.1.1	Direct Current (dc) Supervisory Range	B-1
B.1.1.2	Loop-Start Signaling States Produced by a CGW	B-2
B.1.1.3	Loop-Start Signaling States Applied to a CGW	B-3
B.1.1.4	Loop-Start Call States	B-3
B.1.2	Ground-Start Signaling	B-4
B.1.2.1	Ground-Start Signaling States	B-4
B.1.2.2	Ground-Start Call States	B-6
B.1.3	Dial-Pulse Signals	B-7
B.1.4	Hits, Flash Signals, and Disconnect Signals	B-7
B.1.5	Alerting Signals	B-8
B.1.5.1	Alerting Signals Using Ringing	B-8
B.1.5.2	Alerting Signals Using Call-Waiting Tones	B-9
B.1.6	Call Progress Signals	B-9
B.1.6.1	Precise Tone Plan	B-9
B.1.6.2	Call Progress Tones	B-10
B.1.7	Dual-Tone Multifrequency (DTMF) Signaling	B-11
B.1.8	Multifrequency (MF) Signaling Requirements	B-12
B.1.9	Voiceband Data Transmission Interface	B-13
B.1.10	Transmission Criteria	B-13
B.2	Conventional DS1 Interface (Non-ISDN Trunks)	B-14
B.2.1	Common Trunk Types	B-15
B.2.1.1	Basic Trunks	B-15
B.2.1.2	DID/DOD Trunks	B-15
B.2.2	Physical Layer	B-16
B.2.3	Signaling and Supervision	B-17
B.2.3.1	E&M Signaling	B-18

B.2.3.1.1	E&M Signaling States	B-18
B.2.3.1.2	E&M Call States	B-18
B.2.3.1.3	Idle	B-19
B.2.3.1.4	Seizure	B-19
B.2.3.1.5	Addressing	B-21
B.2.3.1.6	Call Processing	B-23
B.2.3.1.7	Communication	B-24
B.2.3.2	Loop Reverse-Battery Signaling	B-25
B.2.3.2.1	Loop Reverse-Battery Signaling States	B-25
B.2.3.3	Loop Reverse-Battery Call States	B-27
B.2.4	Call Control Signals and Procedures	B-32
B.2.4.1	Addressing Control Signals	B-33
B.2.4.2	Glare Resolution	B-34
B.2.4.2.1	Controlling Interface	B-35
B.2.4.2.2	Release Interface	B-35
B.3	ISDN Primary Rate Interface	B-36
B.3.1	Physical Layer	B-36
B.3.2	Layer 2	B-37
B.3.3	Operations	B-37
References		References-1
Acronyms		Acronyms-1

List of Figures

Figure 2-1.	NGN Functional Architecture	2-1
Figure 2-2.	Overview of R/SB GW Physical Interfaces	2-7
Figure 2-3.	Overview of PBX GW Physical Interfaces	2-7
Figure 3-1.	Customer Gateway Functional Blocks	3-1
Figure 5-1.	Call Setup Between Two R/SB GWs, Two NMGWs, and Two CCAs	5-2
Figure 5-2.	Call Request Detection	5-3
Figure 5-3.	Digit Collection	5-4
Figure 5-4.	Determining the Next CCA	5-5
Figure 5-5.	Creating Access and Core Network Connections in CGW1 and NMGW1	5-6
Figure 5-6.	Route Call to Next CCA and Identify the Called NMGW and CGW	5-10
Figure 5-7.	Create Connections in NMGW2 and CGW2	5-11
Figure 5-8.	NMGW2 and CGW2 Acknowledge Call Setup to CCA2 and CCA1	5-16
Figure 5-9.	CCA1 Informs NMGW1 of NMGW2's CNLC Termination ID	5-17
Figure 5-10.	NMGW1 and CCA1 Confirm Core Network Connection	5-18
Figure 5-11.	CCA2 Tells NMGW2 to Provide Ringback to Calling Party and Tells CGW2 to Provide Power Ringing to Called Party	5-20
Figure 5-12.	NMGW2 Provides Ringback to Calling Party and CGW2 Provides Power Ringing to Called Party	5-21
Figure 5-13.	CGW2 Detects Off-Hook Condition (Called Party Answer) and Reports that Event to CCA2	5-22
Figure 5-14.	NMGW2 Removes Inband Audible Ringing from CNLC and Cuts-Through CNLC and Called Line to Calling Party	5-23
Figure 5-15.	NMGW and CGW2 Confirm Changes, and CCA2 Returns an Answer Indication to CCA1	5-24
Figure 5-16.	CCA1 Tells NMGW1 to Cut-Through the Call Path in Both Directions	5-25
Figure 5-17.	Error Treatment During Call Origination - Dialing	5-26
Figure 5-18.	Handling of Called User Busy - CCA Instructions	5-28
Figure 5-19.	Handling of Called User Busy - NMGW Response	5-29
Figure 5-20.	Error Treatment - Permanent Signal Treatment to Calling Line	5-31
Figure 6-1.	NGN Reference Model – Gateways and Networks	6-2
Figure 6-2.	NGN Reference Model – Services Impacts	6-4
Figure 6-3.	Third-Party Service Development for NGN Services	6-12

List of Tables

Table 4-1.	Summary of Command Triggers and Follow-on Actions . . .	4-12
Table 5-1.	Types of NGN Voice Calls involving CGWs, AGWs, and TGWs	5-2