

## Contents

Preface . . . . .	Preface-1
1. Introduction . . . . .	1-1
1.1 Purpose and Scope . . . . .	1-1
1.2 High-Level Overview . . . . .	1-2
1.3 Target Audience . . . . .	1-3
1.4 Relationship to Other NGN Documents . . . . .	1-3
1.5 Structure and Use of This Document . . . . .	1-4
1.6 Requirements Terminology . . . . .	1-4
1.7 Requirement Labeling Conventions . . . . .	1-5
1.7.1 Numbering of Requirement and Related Objects . . . . .	1-5
1.7.2 Requirement, Conditional Requirement, and Objective Object Identification . . . . .	1-6
2. NGN Architecture Overview . . . . .	2-1
2.1 High-Level View of a Next Generation Network Architecture . . . . .	2-1
2.2 Functional Elements . . . . .	2-2
2.2.1 Core Network . . . . .	2-4
2.2.2 Call Connection Agent . . . . .	2-4
2.2.3 Signaling Gateway . . . . .	2-4
2.2.4 Trunk Gateway . . . . .	2-5
2.2.5 Access Gateway . . . . .	2-5
2.2.6 Access Network . . . . .	2-5
2.2.7 Customer Gateway . . . . .	2-5
2.2.7.1 Residential/Small Business Gateway . . . . .	2-6
2.2.7.2 PBX Gateway . . . . .	2-6
2.2.8 Network Mediation Gateway . . . . .	2-6
2.2.8.1 Network Mediation Gateway Interfaces . . . . .	2-6
2.2.8.2 Protocol Considerations . . . . .	2-7
2.3 Assumptions, Dependencies, and Constraints . . . . .	2-9
3. NMGW Architecture and General Requirements . . . . .	3-1
3.1 Network Topologies and QoS Issues . . . . .	3-1
3.1.1 ATM-Access/ATM-Core Architecture . . . . .	3-1
3.1.1.1 Access Network-Side Capabilities . . . . .	3-1
3.1.1.1.1 AAL2 and AAL5 for the Bearer Content-Carrying PVC . . . . .	3-4
3.1.1.2 Core Network-Side Capabilities . . . . .	3-5
3.1.1.3 Generic Requirements . . . . .	3-6
3.1.2 ATM-Access/IP-Core Architecture . . . . .	3-8
3.1.2.1 Access Network-Side Capabilities . . . . .	3-9
3.1.2.2 Core Network-Side Capabilities . . . . .	3-9
3.1.2.3 Generic Requirements . . . . .	3-10
3.1.3 IP-Access/IP-Core Architecture . . . . .	3-12
3.1.3.1 Access Network-Side Capabilities . . . . .	3-12

3.1.3.2	Core Network-Side Capabilities . . . . .	3-13
3.1.3.3	Generic Requirements . . . . .	3-14
3.1.4	Other Architectures . . . . .	3-16
3.1.4.1	IP-Access/IP-Core with Centralized NMGW . . . . .	3-16
3.2	NMGW Functions . . . . .	3-17
3.2.1	General Message Processing . . . . .	3-17
3.2.1.1	Connection-Oriented CGW Authentication . . . . .	3-17
3.2.1.2	IP Address Masking and Mapping . . . . .	3-17
3.2.2	Connection Management . . . . .	3-18
3.2.2.1	Bearer Path Bridging and Routing . . . . .	3-18
3.2.2.2	Conferencing . . . . .	3-19
3.2.3	Other Functions . . . . .	3-19
3.2.3.1	Audible Ring Generation . . . . .	3-19
3.2.3.2	Network Announcements Generation . . . . .	3-20
3.2.3.3	Codec Conversions . . . . .	3-21
3.2.3.4	Value-Added Data Services . . . . .	3-21
4.	Protocols for Transport, Connection Management, and Call Control . . . . .	4-1
4.1	Transport . . . . .	4-1
4.1.1	Transport of NMGW-CCA Signaling towards the CCA . . . . .	4-1
4.1.2	Transport of NMGW-CCA Signaling Tunnel to carry CGW Signaling . . . . .	4-2
4.1.2.1	Use of SCTP . . . . .	4-3
4.1.3	Transport of Bearer Flow to CGW . . . . .	4-5
4.1.4	Transport of Bearer Flow to Remote Gateway . . . . .	4-6
4.1.4.1	IP Bearer Transport Interface . . . . .	4-6
4.1.4.2	ATM Bearer Transport Interface . . . . .	4-7
4.2	Connection Management and Control Using H.248 . . . . .	4-9
4.2.1	Terminations, Contexts and Edge-to-Edge Connections . . . . .	4-10
4.2.2	H.248 Semantics and Syntax . . . . .	4-12
4.2.2.1	Message Structure and Content . . . . .	4-12
4.2.2.2	Commands and Command Contents . . . . .	4-13
4.2.2.3	Syntax and Encoding . . . . .	4-14
4.2.3	Properties, Events, Signals, Digit Map Specifications, and Packages . . . . .	4-15
4.2.4	Call Statistics . . . . .	4-19
4.2.5	Device Control between the CCA and NMGW . . . . .	4-20
4.2.6	H.248 Commands/Replies . . . . .	4-20
4.2.6.1	Support of Add Command . . . . .	4-20
4.2.6.2	Support of Modify Command . . . . .	4-21
4.2.6.3	Support of Notify Command . . . . .	4-21
4.2.6.4	Support of Move Command . . . . .	4-21
4.2.6.5	Support of Subtract Command . . . . .	4-21
4.2.6.6	Registration with the CCA . . . . .	4-21
4.3	Identifier Allocation, Release, and Management . . . . .	4-22
4.3.1	Transaction Identifier . . . . .	4-22
4.3.2	Termination Identifiers . . . . .	4-22

4.3.3	Context Identifier [H.248 Based]	4-23
4.3.4	Bearer Network Connection (BNC) Identifier	4-24
4.3.5	Stream Identifiers (H.248 based)	4-24
5.	Call Processing	5-1
5.1	R/SB GW-to-R/SB GW Call, Analog Line Case	5-2
5.1.1	Call Establishment	5-2
5.2	Error Cases During Call Establishment	5-26
5.2.1	Error Case - Invalid Called Number	5-26
5.2.2	Error Case - Called User Busy	5-28
5.2.3	Error Case - Receiver Off-Hook After Dial Tone Expires	5-30
	References	References-1
	Acronyms	Acronyms-1



## List of Figures

Figure 2-1.	NGN Functional Architecture . . . . .	2-1
Figure 3-1.	ATM-Access/ATM-Core Architecture - Alternative 1 . . . . .	3-2
Figure 3-2.	ATM-Access/ATM-Core Architecture - Alternative 2 . . . . .	3-3
Figure 3-3.	RTP Multiplexed Packet Format for AAL5 . . . . .	3-5
Figure 3-4.	ATM-Access/IP-Core Architecture . . . . .	3-8
Figure 3-5.	IP-Access/IP-Core Architecture . . . . .	3-12
Figure 3-6.	IP-Access/IP-Core with Centralized NMGW . . . . .	3-16
Figure 4-1.	One NMGW Serving Several CGWs . . . . .	4-2
Figure 4-2.	Use of SCTP to Map Signaling from CGW to CCA . . . . .	4-4
Figure 5-1.	Call Setup Between Two R/SB GWs, Two NMGWs, and Two CCAs . . . . .	5-2
Figure 5-2.	Call Request Detection . . . . .	5-3
Figure 5-3.	Digit Collection . . . . .	5-4
Figure 5-4.	Determining the Next CCA . . . . .	5-5
Figure 5-5.	Creating Access and Core Network Connections in CGW1 and NMGW1 . . . . .	5-6
Figure 5-6.	Route Call to Next CCA and Identify the Called NMGW and CGW . . . . .	5-10
Figure 5-7.	Create Connections in NMGW2 and CGW2 . . . . .	5-11
Figure 5-8.	NMGW2 and CGW2 Acknowledge Call Setup to CCA2 and CCA1 . . . . .	5-16
Figure 5-9.	CCA1 Informs NMGW1 of NMGW2's CNLC Termination ID . . . . .	5-17
Figure 5-10.	NMGW1 and CCA1 Confirm Core Network Connection . . . . .	5-18
Figure 5-11.	CCA2 Tells NMGW2 to Provide Ringback to Calling Party and Tells CGW2 to Provide Power Ringing to Called Party . . . . .	5-20
Figure 5-12.	NMGW2 Provides Ringback to Calling Party and CGW2 Provides Power Ringing to Called Party . . . . .	5-21
Figure 5-13.	CGW2 Detects Off-Hook Condition (Called Party Answer) and Reports that Event to CCA2 . . . . .	5-22
Figure 5-14.	NMGW2 Removes Inband Audible Ringing from CNLC and Cuts-Through CNLC and Called Line to Calling Party . . . . .	5-23
Figure 5-15.	NMGW and CGW2 Confirm Changes, and CCA2 Returns an Answer Indication to CCA1 . . . . .	5-24
Figure 5-16.	CCA1 Tells NMGW1 to Cut-Through the Call Path in Both Directions . . . . .	5-25
Figure 5-17.	Error Treatment During Call Origination - Dialing . . . . .	5-26
Figure 5-18.	Handling of Called User Busy - CCA Instructions . . . . .	5-28
Figure 5-19.	Handling of Called User Busy - NMGW Response . . . . .	5-29
Figure 5-20.	Error Treatment - Permanent Signal Treatment to Calling Line . . . . .	5-31