

Contents

Preface	Preface-1
1. Introduction	1-1
1.1 Purpose	1-1
1.2 Scope	1-1
1.3 Related Documents	1-4
1.4 Organization of Document	1-5
1.5 Requirements Terminology	1-5
1.6 Changes from GR-3100-CORE, Issue 2 to Issue 3	1-6
1.7 Requirement Labeling Conventions	1-7
1.7.1 Numbering of Requirement and Related Objects	1-7
1.7.2 Requirement, Conditional Requirement, and Objective Object Identification	1-7
2. BICC Architecture	2-1
2.1 Network Model	2-1
2.2 Protocol Model	2-3
2.3 Definitions	2-5
3. Call Control Signaling Transport	3-1
3.1 BICC Transport Over MTP3	3-1
3.1.1 Signaling Transport Converter (STC) for MTP3	3-1
3.1.2 MTP3	3-3
3.1.3 Protocols for MTP2 Links	3-3
3.1.3.1 MTP2	3-3
3.1.3.2 MTP1	3-4
3.1.4 Protocols for ATM HSLs	3-4
3.1.5 Protocols for IPVHSLs	3-4
3.1.5.1 M2PA	3-4
3.1.5.2 SCTP	3-5
3.1.5.3 IP	3-5
3.2 BICC Transport Over SSCOP/SSCOPMCE	3-6
3.2.1 STC for BICC Transport Over SSCOP/SSCOPMCE	3-6
3.2.2 SSCOP	3-7
3.2.3 SSCOPMCE	3-7
3.2.4 Common Part - ATM Adaptation Layer (CP-AAL)	3-8
3.2.5 ATM	3-8
3.3 BICC Transport Over M3UA	3-8
3.3.1 STC for MTP3	3-8
3.3.2 MTP3-User Adaptation (M3UA) Protocol	3-9
3.3.3 SCTP	3-9
3.3.4 IP	3-9
3.4 BICC Transport Directly Over SCTP	3-9
4. Bearer Control Signaling Transport	4-1
4.1 Physical Layer	4-1

4.2	ATM Layer	4-1
4.3	Signaling ATM Adaptation Layer (SAAL)	4-2
4.3.1	Common Part	4-2
4.3.2	Service Specific Connection Oriented Protocol (SSCOP)	4-2
4.3.3	Service Specific Coordination Function (SSCF)	4-3
4.3.4	SAAL Layer Management	4-3
5.	Call Control	5-1
5.1	Call Flows	5-1
5.2	Network Configurations	5-6
5.3	Common Requirements	5-9
5.4	Intranetwork Call - Type 1 Call	5-12
5.4.1	Successful Call Set-Up	5-12
5.4.1.1	Forward Address Signaling	5-12
5.4.1.1.1	Actions Required at the O-SN and O-ISN	5-12
5.4.1.1.2	Actions Required at the D-SN and D-ISN	5-20
5.4.1.2	Address Complete Message	5-25
5.4.1.2.1	Actions Required at the D-SN and D-ISN	5-25
5.4.1.2.2	Actions Required at the O-SN and O-ISN	5-26
5.4.1.3	Answer Message	5-27
5.4.1.3.1	Actions Required at the D-SN and D-ISN	5-27
5.4.1.3.2	Actions Required at the O-SN and O-ISN	5-27
5.4.1.4	Call Progress Message	5-28
5.4.1.4.1	Actions Required at the D-SN and D-ISN	5-28
5.4.1.4.2	Actions Required at the O-SN and O-ISN	5-28
5.4.2	Unsuccessful Call Set-Up	5-28
5.4.2.1	General	5-28
5.4.2.2	Actions at SN Initiating a Release Message	5-29
5.4.2.3	Action at SN Receiving REL	5-29
5.4.2.4	Tones and Announcements	5-29
5.4.3	Suspend and Resume	5-31
5.4.3.1	Suspend	5-31
5.4.3.2	Resume	5-31
5.4.4	Normal Call Release	5-32
5.4.4.1	Release Initiated by the Calling Party	5-32
5.4.4.1.1	Actions at the O-SN and O-ISN	5-32
5.4.4.1.2	Actions at the D-SN and D-ISN	5-33
5.4.4.2	Release Initiated by the Called Party	5-33
5.4.4.2.1	Actions at the D-SN and D-ISN	5-33
5.4.4.2.2	Actions at the O-SN and O-ISN	5-33
5.4.4.3	Release Initiated by the Network	5-34
5.4.4.4	Release Sending Procedure	5-34
5.4.4.5	Release Reception Procedure	5-34
5.4.4.6	Collision of Release Messages	5-34
5.5	Internetwork Call - Type 2 Call	5-35
5.5.1	Successful Call Set-Up	5-37
5.5.1.1	Call Origination	5-37

5.5.1.2	Call Termination	5-37
5.5.1.3	Exit Message	5-37
5.5.2	Unsuccessful Call Set-Up	5-38
5.5.3	Suspend, Resume	5-38
5.5.4	Normal Call Release	5-38
5.6	Internetwork Call - Type 3 Call	5-38
5.6.1	Successful Call Set-Up	5-40
5.6.1.1	Forward Address Signaling	5-40
5.6.1.1.1	Actions Required at the O-SN and O-ISN in the Originating Network	5-40
5.6.1.1.2	Actions Required at the GSN in the Originating Network	5-40
5.6.1.1.3	Actions Required at the GSN in the Terminating Network	5-43
5.6.1.1.4	Actions Required at the D-SN and D-ISN in the Terminating Network	5-45
5.6.1.2	Address Complete Message	5-45
5.6.1.3	Answer Message	5-46
5.6.1.4	Call Progress Message	5-46
5.6.2	Unsuccessful Call Set-Up	5-46
5.6.3	Suspend, Resume	5-46
5.6.3.1	Suspend	5-46
5.6.3.2	Resume	5-46
5.6.4	Normal Call Release	5-46
5.6.4.1	Release Initiated by the Calling Party	5-46
5.6.4.2	Release Initiated by the Called Party	5-47
5.6.4.3	Release Initiated by the Network	5-47
5.6.4.4	Collision of Release Messages	5-47
5.7	Internetwork Call - Type 4 Call	5-48
5.7.1	Successful Call Set-Up	5-50
5.7.1.1	Call Origination	5-50
5.7.1.2	Call Termination	5-51
5.7.1.3	Exit Message	5-52
5.7.2	Unsuccessful Call Set-Up	5-52
5.7.3	Suspend, Resume	5-52
5.7.4	Normal Call Release	5-52
6.	Bearer Control	6-1
6.1	General	6-1
6.2	ATM Backbone Network	6-1
6.2.1	Interoperation Between Call Control and ATM Bearer Control Signaling	6-1
6.2.1.1	Mapping Functions Between BICC Signaling and UNI 4.0 or PNNI 1.0 Signaling	6-2
6.2.1.1.1	Binding Information	6-3
6.2.1.1.2	Bearer Service Information	6-3
6.2.1.1.3	Address Information	6-6

6.2.1.1.4	Cause Information	6-6
6.2.2	Successful ATM Bearer Connection Setup	6-7
6.2.2.1	Actions at the Originating BCF	6-7
6.2.2.2	Actions at the Destination BCF	6-8
6.2.3	Unsuccessful ATM Bearer Connection Setup	6-8
6.2.4	Normal ATM Bearer Connection Release	6-9
6.2.4.1	Release Initiated by a Connection Owner	6-9
6.2.4.1.1	Actions at the Originating BCF	6-9
6.2.4.1.2	Actions at the Destination BCF	6-9
6.2.5	Other Failure	6-10
6.3	IP Backbone Network	6-10
6.3.1	Interoperation Between Call Control and IP Bearer Control	6-10
6.3.1.1	Mapping Functions Between BICC Signaling and IPBCP Signaling	6-10
6.3.1.1.1	Channel Attributes Information	6-11
6.3.1.1.2	Address Information	6-12
6.3.1.1.3	Binding Information	6-12
6.3.1.1.4	Cause Information	6-12
6.3.2	Successful IP Bearer Establishment	6-13
6.3.3	IP Bearer Release	6-13
7.	Maintenance Control	7-1
7.1	General	7-1
7.2	Automatic Repeat Attempt	7-1
7.3	Blocking and Unblocking	7-1
7.4	CIC Query	7-2
7.5	Dual Seizure	7-2
7.6	CIC Reset and Group Reset	7-3
7.7	Receipt of Unreasonable and Unrecognized Signaling Information	7-3
7.8	Signaling Network Congestion	7-4
7.9	BICC Flow Control	7-4
7.10	Automatic Congestion Control	7-4
7.11	Unequipped CIC	7-5
7.12	Destination Availability	7-5
8.	BICC Operations	8-1
8.1	Configuration of Data	8-1
9.	BICC Evolution and Industry Status	9-1
9.1	High-Level Description of ANSI and ITU-T BICC CS 1	9-1
9.2	High-Level Description of ANSI BICC CS 1+ (ITU-T BICC CS 2)	9-2
9.3	High-Level Description of ITU-T BICC CS 3	9-5
9.4	Forward and Backward Compatibility	9-5
9.4.1	Backward Compatibility Rules	9-6
9.4.2	Forward Compatibility Mechanism	9-6
Appendix A:	BICC Message and Parameter Definitions	A-1
A.1	Application Transport Message (APM)	A-1
A.2	Application Transport Parameter (APP)	A-1

- A.3 Inter-Nodal Traffic Group Identifier A-2
- A.4 Global Call Reference A-2
- Appendix B: BICC Message Formats B-1
 - B.1 Message format B-1
 - B.2 CIC Allocation B-1
 - B.3 Messages B-1
 - B.3.1 Message Exceptions B-1
 - B.3.2 Message Renaming B-2
 - B.4 Application Transport Message B-2
 - B.5 Initial Address Message B-3
- Appendix C: BICC Parameter Formats C-1
 - C.1 Parameters C-1
 - C.1.1 Parameter Exceptions C-1
 - C.1.2 Parameter Renaming C-1
 - C.1.3 Parameter Coding C-1
 - C.2 Application Transport Parameter (APP) C-3
 - C.2.1 List of Identifiers C-9
 - C.2.2 Action Indicator C-10
 - C.2.3 Backbone Network Connection Identifier C-11
 - C.2.4 Interworking Function Address C-11
 - C.2.5 Codec List C-12
 - C.2.6 Single Codec C-12
 - C.2.7 BAT Compatibility Report C-12
 - C.2.8 Bearer Network Connection Characteristics C-13
 - C.2.9 Bearer Control Information C-14
 - C.2.10 Bearer Control Tunneling C-15
 - C.2.11 Bearer Control Unit Identifier C-15
 - C.2.12 Signal C-15
 - C.2.13 Bearer Redirection Capability C-15
 - C.2.14 Bearer Redirection Indicators C-15
 - C.2.15 Signal Type C-15
 - C.2.16 Duration C-16
 - C.3 Inter-Nodal Traffic Group Identifier C-16
 - C.4 Global Call Reference C-16
- Appendix D: BICC Timers D-1
- References References-1
- Glossary Glossary-1
- Requirement-Object Index ROI-1

List of Figures

Figure 1-1.	Scope of this GR Document	1-3
Figure 2-1.	Initial BICC Architecture	2-1
Figure 2-2.	BICC Network Model	2-2
Figure 2-3.	BICC Protocol Model	2-4
Figure 3-1.	BICC Transport Over MTP3	3-2
Figure 3-2.	BICC Transport Over SSCOP or SSCOPMCE	3-6
Figure 3-3.	BICC Transport M3UA	3-8
Figure 3-4.	BICC Transport Directly Over SCTP	3-9
Figure 4-1.	Protocol Reference Model	4-1
Figure 5-1.	Backward ATM Bearer Connection Set-up with COT - BICC at Tandem Level	5-2
Figure 5-2.	Backward ATM Bearer Connection Set-Up with COT and Gateway Serving Nodes - BICC at Tandem Level	5-3
Figure 5-3.	Backward IP Bearer Setup Using Bearer Control Tunneling with COT - BICC at Tandem Level	5-5
Figure 5-4.	Network Configuration Scenarios - BICC at End Office Level	5-7
Figure 5-5.	Network Configuration Scenarios - BICC at Tandem Level	5-8
Figure 5-6.	Intranetwork Call - Type 1 Call	5-13
Figure 5-7.	Internetwork Call - Type 2 Call	5-36
Figure 5-8.	Internetwork Call - Type 3 Call	5-39
Figure 5-9.	Internetwork Call - Type 4 Call	5-49
Figure 6-1.	Scope of BICC and ATM Signaling Protocols Mapping	6-2
Figure 6-2.	Scope of BICC and IP Bearer Control Protocols Mapping	6-11
Figure B-1.	CIC Field	B-1
Figure C-1.	Application Transport Parameter Field	C-3
Figure C-2.	Content of the APM-User Information Field	C-5
Figure C-3.	Content of the Originating Address (Destination Address) Field	C-6
Figure C-4.	Encapsulated Application Information Field	C-7
Figure C-5.	Length Indicator	C-7
Figure C-6.	Compatibility Information	C-8
Figure C-7.	Action Indicator	C-10
Figure C-8.	Backbone Network Connection Identifier	C-11
Figure C-9.	Interworking Function Address	C-11
Figure C-10.	BAT Compatibility Report	C-12
Figure C-11.	Diagnostics	C-13
Figure C-12.	Bearer Network Connection Characteristics	C-13
Figure C-13.	Bearer Control Information	C-14
Figure C-14.	Bearer Control Tunneling	C-15
Figure C-15.	Inter-Nodal Traffic Group Identifier Parameter Field	C-16
Figure C-16.	Global Call Reference Parameter Field	C-16

List of Tables

Table 5-1.	Mapping of Continuity Check Indicator from ISUP to Continuity Indicator in BICC at O-ISN	5-14
Table 5-2.	Mapping of Continuity Indicator from BICC to Continuity Check Indicator in ISUP at D-ISN	5-22
Table 5-3.	Mapping of Continuity Indicator at GSN	5-41
Table 6-1.	Mapping of Binding Information	6-3
Table 6-2.	UNI 4.0 or PNNI 1.0 Information Elements Required for the Mapping of Bearer Service Information	6-3
Table 6-3.	Mapping of the BICC USI Parameter and UNI 4.0 or PNNI 1.0 Information Elements	6-4
Table 6-4.	Mapping of BICC USI Codes and ATM Peak Cell Rates in the UNI 4.0 or PNNI 1.0 ATM Traffic Descriptor Information Element	6-5
Table 6-5.	Mapping of Address Information	6-6
Table 6-6.	Mapping of Cause Information (UNI 4.0 or PNNI 1.0 Signaling to BICC Signaling)	6-7
Table 6-7.	Mapping of Cause Information (BICC Signaling to UNI 4.0 or PNNI 1.0 Signaling)	6-7
Table 6-8.	Mapping of Channel Attributes Information	6-11
Table 6-9.	Mapping of User Service Information to RTP/AVP Payload Type	6-12
Table 6-10.	Mapping of Cause Information (IPBCP Signaling to BICC Signaling)	6-12
Table 9-1.	ITU-T and ANSI BICC Specifications - CS 1	9-2
Table 9-2.	ITU-T CS 2 and ANSI CS1+ BICC Specifications	9-4
Table B-1.	Renamed Messages	B-2
Table B-2.	Initial Address Message	B-3
Table C-1.	Renamed Parameters	C-1
Table C-2.	List of Identifiers	C-9