

Table of Contents

1 Introduction

1.1 Purpose and Scope	1-1
1.2 Target Audience	1-2
1.3 Background	1-2
1.3.1 E9-1-1 Service Description	1-2
1.3.2 Emergency Services Network Evolution	1-5
1.3.3 Evolution Toward IP Multimedia Subsystem (IMS)-Based Network Architectures	1-6
1.3.4 Definition of Terms	1-8
1.3.4.1 E9-1-1 Service Terminology	1-8
1.3.4.2 VoP/NGN Terminology	1-9
1.3.4.3 SIP Terminology	1-13
1.3.4.4 VoIP i2 Solution Terminology	1-14
1.3.4.5 VoIP i3 Solution Terminology	1-18
1.3.4.6 IMS Terminology	1-22
1.4 Requirements Terminology	1-25
1.5 Requirements Labeling Conventions	1-26
1.5.1 Numbering of Requirement and Related Objects	1-26
1.5.2 Requirement, Conditional Requirement, and Objective Identification . .	1-27
1.5.3 Requirements in This GR	1-27
1.6 Related Documents.	1-27

2 Network Interconnection Architectures

2.1. Interconnection with Originating VoP/NGN-Based Networks.	2-1
2.1.1 Routing of 9-1-1 Calls to Appropriate E9-1-1 Tandem by “Generic” NGN .	2-1
2.1.1.1 CCS Network Interconnection for E9-1-1 Service Call Control . . .	2-3
2.1.1.2 MF Interconnection for E9-1-1 Service Call Control	2-4
2.1.2 Routing of Emergency Calls Originating in i2 Solution-Based SIP Networks	2-4
2.1.2.1 Network Interconnection to Support the Flow of Caller Location Information in an i2 Solution Environment	2-6
2.1.2.2 CCS Network Interconnection for E9-1-1 Service Call Control . . .	2-8
2.1.2.3 MF Interconnection for E9-1-1 Service Call Control	2-8
2.1.3 NGN Access to AIN-Based Emergency Services Networks	2-9
2.1.3.1 CCS Network Interconnection for E9-1-1 Service Call Control . .	2-11
2.1.3.2 MF Interconnection for E9-1-1 Service Control	2-12
2.1.3.3 CCS Network Interconnection for Database Access	2-12
2.1.4 Disclosure of Routing and Addressing Information	2-12
2.1.5 Routing of Emergency Calls in an i3 Solution Environment	2-13
2.1.5.1 Non-IMS SIP Emergency Call Originations	2-13
2.1.5.2 Emergency Call Originations via an IMS-Based SIP Originating Network	2-16
2.1.5.3 Network Interconnection for Access to a Client Company ECRF .	2-19
2.2 Interconnection with IXC Networks	2-19
2.2.1 Interconnection with ISUP-Based IXC Networks	2-20
2.2.2 Interconnection with SIP-Based IXC Networks	2-21

3 Network Interconnection Interface Protocols

- 3.1 CCS Interface Protocols 3-1
 - 3.1.1 Call Control Interface 3-1
 - 3.1.1.1 MTP Signaling for 9-1-1 Call Setup 3-2
 - 3.1.1.2 ISUP Signaling for Wireline 9-1-1 Calls 3-3
 - 3.1.1.3 ISUP Signaling for Wireless 9-1-1 Calls 3-5
 - 3.1.1.4 Additional ISUP Signaling from SIP-Based IXC Network to Traditional Terminating Emergency Services Network 3-6
 - 3.1.2 Non-Circuit Related Signaling Using SCCP/TCAP 3-7
 - 3.1.2.1 MTP Information in Support of AIN-Based Selective Routing 3-7
 - 3.1.2.2 SCCP Information in Support of E9-1-1 Selective Routing 3-8
 - 3.1.2.3 TCAP Information in Support of AIN-Based Selective Routing 3-9
 - 3.1.3 Non-Circuit Related Signaling Protocol for Position Query 3-11
 - 3.1.3.1 Transaction Portion 3-11
 - 3.1.3.2 Component Portion 3-12
 - 3.1.4 Abnormal Conditions/Error Handling Related to TCAP Interactions 3-14
 - 3.1.4.1 SCCP Routing Failures 3-14
 - 3.1.4.2 TCAP Errors 3-15
- 3.2 SIP Protocol for E9-1-1 Call Setup 3-20
 - 3.2.1 SIP Request Messages Applicable to Emergency Calls 3-22
 - 3.2.2 SIP Response Messages Applicable to Emergency Calls 3-23
 - 3.2.3 SIP Message Headers 3-23
 - 3.2.4 E9-1-1 Call Originating in an i2 Solution-Based SIP Network and Terminating in a Traditional Client Company Emergency Services Network 3-24
 - 3.2.5 SIP Emergency Session Request Delivered to a Client Company ESInet 3-27
 - 3.2.6 Routing Query to a Client Company ECRF 3-28
 - 3.2.7 Transferred E9-1-1 Call Traversing a SIP-Based IXC Network 3-30

Appendix A: References

Appendix B: Acronyms



List of Figures

Figure 1-1	High-Level VoP Network Architecture	1-12
Figure 1-2	i2/i2.5 Solution Architecture	1-18
Figure 1-3	NENA LTD WG View of i3 Functional Architecture	1-21
Figure 1-4	Simplified IMS Functional Architecture.	1-22
Figure 1-5	Functional Entities Supporting IMS Emergency Session Requests	1-23
Figure 2-1	9-1-1 Calls Routed to Appropriate E9-1-1 Tandem in PSTN	2-2
Figure 2-2	i2/i2.5 Solution Location Information Flow	2-8
Figure 2-3	NGN Accesses a Client Company AIN-Based E9-1-1 Implementation	2-10
Figure 2-4	Example i3 Emergency Call Flow	2-15
Figure 2-5	Example i3 Call Flow Involving an IMS-Based Originating Network	2-17
Figure 2-6	Architecture for Interconnecting with ISUP-Based IXC Network	2-21
Figure 2-7	Architecture for Interconnecting with SIP-Based IXC Network	2-22
Figure 3-1	Protocol Stack for MPC-ALI Interface	3-11
Figure 3-2	SIP Protocol Stack	3-21