

# Table of Contents

<b>Generic Requirements Notice of Disclaimer</b>	iii
<b>List of Figures</b>	viii
<b>List of Tables</b>	ix
<b>Preface</b>	xi

## 1 Introduction

1.1 Purpose and Scope	1-1
1.2 Target Audience	1-1
1.3 Structure and Use of This Document	1-1
1.4 Requirements Terminology	1-2
1.5 Requirement Labeling Conventions	1-2
1.5.1 Numbering of Requirement and Related Objects	1-2
1.5.2 Requirement, Conditional Requirement, and Objective Identification	1-3

## 2 General Information

2.1 Product Description	2-1
2.2 Deployment Environments	2-3
2.3 Installation and Operating Environment	2-4
2.3.1 Connector Performance in Harsh Environments	2-5
2.4 Related Telcordia Documents	2-5
2.5 FDH Component Devices	2-5

## 3 General Requirements

3.1 Documentation	3-1
3.1.1 Practices	3-1
3.2 Markings, Packaging, and Shipping	3-1
3.2.1 Identification	3-1
3.2.1.1 General	3-1
3.2.1.2 Listing	3-2
3.2.2 Shipping Container and Packaging Arrangement	3-2
3.2.3 Package Label	3-2
3.3 Labels	3-2
3.4 Consumable Materials	3-3
3.5 Product Changes	3-3
3.6 Safety and Reliability Considerations	3-3
3.7 Installation Size and Weight	3-4
3.8 Maintenance	3-4
3.9 Components	3-4
3.10 Tools	3-5
3.11 Quality	3-5
3.12 Security	3-5

## 4 Functional Design Criteria

4.1 Materials	4-1
4.1.1 Metallic Materials	4-1



4.1.2 Polymeric and Other Non-Metallic Materials . . . . .	4-1
4.2 Cable Management Compartments . . . . .	4-1
4.2.1 Cable Entrance Capacity . . . . .	4-2
4.2.2 Cable Compatibility . . . . .	4-2
4.2.3 Cable Termination Hardware . . . . .	4-2
4.2.4 Bonding and Grounding Hardware . . . . .	4-2
4.3 Service Provider Splice Compartment . . . . .	4-3
4.3.1 Splice Storage Capacity . . . . .	4-3
4.3.2 Fiber and Splice Protection . . . . .	4-4
4.4 Connector Bulkhead . . . . .	4-5
4.4.1 Bulkhead Capacity . . . . .	4-5
4.4.2 Connector Sleeves . . . . .	4-5
4.4.3 Connector Requirements . . . . .	4-5
4.4.4 Pigtail Requirements . . . . .	4-6
4.5 Fundamental FDH Requirements . . . . .	4-6
4.5.1 Deployment Configurations . . . . .	4-6
4.5.2 Optical Power Monitoring . . . . .	4-6
4.5.3 FDH Mounting Hardware . . . . .	4-6
4.5.4 Door Restrainers . . . . .	4-7
4.5.5 Insect Resistance . . . . .	4-7
4.6 Finish . . . . .	4-8
4.6.1 Color . . . . .	4-8
4.6.2 Appearance . . . . .	4-8
4.6.3 Paint Adhesion . . . . .	4-9
4.6.4 Paint Adhesion After Exposure . . . . .	4-9
4.6.5 Flexibility . . . . .	4-9
4.7 Illumination . . . . .	4-9

## 5 Application-Specific Requirements

5.1 General . . . . .	5-1
5.1.1 Testing . . . . .	5-1
5.2 Electrical Criteria . . . . .	5-2
5.2.1 Bond Clamp Retention . . . . .	5-2
5.2.2 AC Fault Test . . . . .	5-2
5.3 Mechanical Criteria . . . . .	5-2
5.3.1 Cable Clamping . . . . .	5-5
5.3.2 Sheath Retention . . . . .	5-6
5.3.2.1 Sheath Retention Test Configuration . . . . .	5-7
5.3.3 Cable Flexing . . . . .	5-7
5.3.3.1 Cable Flexing Test Configuration . . . . .	5-8
5.3.4 Cable Torsion . . . . .	5-9
5.3.5 Vertical Drop . . . . .	5-10
5.3.5.1 Packaged Equipment Shock Criteria . . . . .	5-10
5.3.5.1.1 Category A Containers . . . . .	5-11
5.3.5.1.2 Category B Containers . . . . .	5-11
5.3.5.2 Unpackaged Equipment Shock Criteria . . . . .	5-14
5.3.6 Impact Resistance . . . . .	5-14
5.3.7 Central Member (CM) Protrusion . . . . .	5-15
5.4 Environmental Criteria . . . . .	5-16
5.4.1 Accelerated Thermal Aging . . . . .	5-17

5.4.2 Assembly . . . . .	5–17
5.4.3 Temperature and Humidity . . . . .	5–17
5.4.4 Water Resistance . . . . .	5–18
5.4.5 Wind Resistance: Door Restrainers (Vertically Hinged Doors) . . . . .	5–19
5.4.6 Wind Resistance: Horizontally Hinged Doors . . . . .	5–23
5.4.7 Corrosion Resistance . . . . .	5–24
5.4.7.1 Salt Fog . . . . .	5–24
5.4.8 Chemical Resistance . . . . .	5–24
5.4.9 Ultraviolet Resistance . . . . .	5–26
5.4.10 Fungus Resistance . . . . .	5–27
5.4.11 Rodent Resistance . . . . .	5–27
5.4.12 Compression . . . . .	5–28
5.4.13 Lifting Details . . . . .	5–28
5.4.14 Operational Movement . . . . .	5–29
5.4.15 External Icing . . . . .	5–29
5.5 Earthquake, Environmental Vibration, and Transportation Vibration . . . . .	5–29
5.5.1 Conformance Criteria . . . . .	5–30
5.5.1.1 Earthquake - Physical Performance Criteria . . . . .	5–31
5.5.1.2 Earthquake - Functional Performance Criteria . . . . .	5–31
5.5.1.3 Earthquake - FDH and Anchor Criteria . . . . .	5–32
5.5.1.4 Environmental Vibration Criteria . . . . .	5–33
5.5.1.5 Earthquake Test Method Details . . . . .	5–33
5.5.1.5.1 Environmental Vibration Test Procedure Details . . . . .	5–37
5.5.1.6 Transportation Vibration—Packaged Equipment Test Plan Details . . . . .	5–37
5.5.1.7 Static Test Procedure . . . . .	5–37
5.6 Craft Interaction . . . . .	5–39
5.6.1 Front Plane Connector Disconnect and Reconnect Test . . . . .	5–39
5.6.1.1 Conformance Criteria . . . . .	5–39
5.6.1.2 Measurements . . . . .	5–39
5.6.1.3 Disconnect and Reconnect Test Procedure . . . . .	5–40
5.6.1.4 Product Testers . . . . .	5–40
5.6.2 Rear-Plane Fiber Optic Terminal (FOT) Jumper Disconnect, Adapter Replacement and Reconnect Test . . . . .	5–41
5.6.2.1 Conformance Criteria . . . . .	5–42
5.6.2.2 Test Method . . . . .	5–42
5.6.2.3 Product Testers . . . . .	5–43

## 6 Components

### Appendix A: References

### Appendix B: Glossary

### Requirement-Object Index

## List of Figures

Figure 2-1	Schematic of the Fiber Distribution Hub Role . . . . .	2-2
Figure 2-2	Basic Fiber Distribution Hub . . . . .	2-2
Figure 5-1	Schematic of Feeder-Cable, Monitored Network for Cable Mechanical Tests . . . . .	5-4
Figure 5-2	Schematic of Distribution-Cable, Monitored Network for Cable Mechanical Tests . . . . .	5-4
Figure 5-3	Sheath Retention Test Configuration . . . . .	5-7
Figure 5-4	Cable Flexing Test Configuration . . . . .	5-8
Figure 5-5	Cable Torsion Test Configuration . . . . .	5-10
Figure 5-6	Packaged Drop Surfaces . . . . .	5-12
Figure 5-7	Packaged Drop Test Setup . . . . .	5-13
Figure 5-8	Test Setup for Category B Container, Corner Drop . . . . .	5-14
Figure 5-9	Central Member Protrusion Test Configuration . . . . .	5-16
Figure 5-10	Temperature Humidity Profile (Not to Scale) . . . . .	5-18
Figure 5-11	Dynamic Wind Test . . . . .	5-22
Figure 5-12	Chemical Resistance Test Configuration . . . . .	5-26
Figure 5-13	Test Bar Samples . . . . .	5-27
Figure 5-14	Earthquake Zone Map . . . . .	5-30
Figure 5-15	Earthquake Synthesized Waveform - VERTEQII . . . . .	5-34
Figure 5-16	Required Response Spectra . . . . .	5-35
Figure 5-17	Commercial Transportation Vibration Environment . . . . .	5-38
Figure 5-18	Anthropometric Hand Dimensions to Support Table 5-7 . . . . .	5-41
Figure 5-19	Anthropometric Hand Dimensions to Support Table 5-8 . . . . .	5-44

## List of Tables

Table 2-1	Deployment Environments for Fiber Distribution Hubs . . . . .	2-3
Table 5-1	Pass/Fail Criteria for Cable/FDH Mechanical Tests . . . . .	5-5
Table 5-2	Cable Pullout Criteria Levels . . . . .	5-6
Table 5-3	Category A Container Packaged Equipment Shock Criteria . . . . .	5-11
Table 5-4	Category B Container Packaged Equipment Shock Criteria . . . . .	5-11
Table 5-5	Unpackaged Equipment Shock Criteria . . . . .	5-14
Table 5-6	Impact Criteria Levels . . . . .	5-15
Table 5-7	Corrosion Resistance Criteria Levels . . . . .	5-24
Table 5-8	Test Result Document References . . . . .	5-27
Table 5-9	Recommended Hand Size of Product Tester . . . . .	5-41
Table 5-10	Recommended Hand Size of Product Tester . . . . .	5-44