

Table of Contents

Preface	xiii
1 Introduction	
1.1 Purpose and Scope	1-1
1.2 Reasons for GR-3150, Issue 3	1-2
1.3 Topics Not Addressed in This GR	1-2
1.4 GR-3150 Safety and Performance Compliance Levels	1-2
1.4.1 Level I - Safety and Compatibility	1-3
1.4.2 Level II - Safety and Limited Operability	1-4
1.4.3 Level III - Safety and Operability	1-4
1.5 Organization of This Document	1-7
1.6 Requirements Terminology	1-7
1.7 Requirement Labeling Conventions	1-8
1.7.1 Numbering of Requirement and Related Objects	1-8
1.7.2 Requirement, Conditional Requirement, and Objective Identification	1-9
1.7.3 Compliance Level Identification in the Numbering of Requirements and Related Objects	1-9
1.8 Test Criteria	1-9
1.8.1 General	1-9
1.8.2 Root Cause Analysis	1-10
1.8.3 Data Acquisition and Reporting	1-10
1.8.4 Sample Selection	1-11
1.8.5 Number of Samples To Be Tested	1-12
1.8.6 Pre- and Post-Test Functional Verification	1-12
1.8.7 Measuring	1-12
1.8.8 Telcordia Documents	1-13
2 General Product Information	
2.1 General Description	2-1
2.2 Chemistry	2-1
2.2.1 Metallic Lithium	2-2
2.2.2 Lithium Ion	2-2
2.2.3 Lithium Ion Polymer	2-2
2.3 Battery Management System (BMS)	2-4
2.4 Quality and Reliability	2-5
2.5 Safety	2-6
2.5.1 Thermal Runaway	2-6
2.6 Performance	2-7
2.7 Service Life	2-7
2.8 Deployment Considerations	2-8
2.8.1 Central Office (CO)	2-8
2.8.2 Outside Plant (OSP)	2-9
2.8.3 Customer Premises	2-10

3 General Product Criteria

3.1	Quality	3-1
3.1.1	Failure Mode and Effect Analysis (FMEA)	3-1
3.1.2	Product Samples	3-2
3.1.3	Product Changes	3-2
3.2	Reliability	3-3
3.2.1	Fail-Safe Design	3-3
3.3	Documentation and Training	3-3
3.4	Physical Design Criteria	3-5
3.4.1	Components	3-5
3.4.2	Use of Fire-Resistant Materials, Components, Wiring, and Cable	3-6
3.4.3	Containers	3-6
3.4.4	Terminals	3-6
3.4.5	Weight	3-7
3.4.6	Mounting Arrangements	3-7
3.4.7	Marking	3-7
3.4.8	Packaging	3-8
3.4.9	Handling	3-9
3.4.10	Pressure Release	3-9
3.4.10.1	Hazardous Materials	3-9
3.4.11	Voltage Measurement	3-10
3.5	Electrical Safety Criteria	3-10
3.6	Bonding and Grounding Criteria	3-10
3.7	Illumination Criteria for Network Equipment	3-11
3.8	Self-Heating and Surface Temperature	3-11
3.8.1	Self-Heating	3-11
3.8.2	Surface Temperature	3-11
3.9	BMS Criteria	3-12
3.9.1	Fail-Safe Design	3-12
3.9.2	Reliability	3-12
3.9.3	Features	3-13
3.9.4	Physical Design and Manufacturing	3-13
3.9.5	Status and Alarms	3-13
3.9.5.1	Status Indicators and Parameters	3-13
3.9.5.2	Alarms	3-14
3.9.6	Accuracy of Measurement	3-15

4 Safety Criteria

4.1	Acceptance Criteria	4-1
4.2	Precautions	4-2
4.3	Status Indicators and Alarms	4-2
4.4	Environmental Criteria	4-2
4.4.1	Fire Propagation and Projectile Hazard Characterization	4-2
4.4.2	Simulated Brush Fire	4-6
4.4.3	Simulated Telecom Environmental Cycles	4-7
4.4.4	Operating Altitude	4-10
4.4.5	Immersion (Flooded Conditions)	4-10
4.5	Electrical Criteria	4-13
4.5.1	Overcharge	4-14

4.5.2	Short Circuit	4-16
4.5.2.1	External Short Circuit	4-17
4.5.2.2	Internal Short Circuit	4-19
4.5.3	Reverse Polarity	4-19
4.5.4	Overdischarge	4-21
4.5.5	High-String Voltage	4-24
4.5.6	Electromagnetic Compatibility Criteria	4-24
4.5.6.1	System-Level ESD	4-25
4.5.6.2	System-Level Electrical Fast Transients (EFTs)	4-25
4.5.6.3	Electromagnetic Interference (EMI)	4-26
4.5.6.4	Lightning and AC Power Fault	4-27
4.6	Mechanical Criteria	4-28
4.6.1	Handling Resistance Criteria	4-28
4.6.1.1	Packaged Shock Criterion	4-28
4.6.1.2	Unpackaged Shock Criteria	4-28
4.6.2	Crush	4-30
4.6.3	Earthquake and Vibration	4-32
4.6.3.1	Earthquake	4-32
4.6.3.2	Transportation Vibration	4-32
4.6.3.3	Low-Level Vibration Resistance	4-32

5 Performance Criteria

5.1	Electrical Criteria	5-1
5.1.1	Float Voltage and Capacity	5-1
5.1.1.1	Float Voltage	5-1
5.1.1.2	Capacity	5-2
5.1.2	Recharge Time	5-3
5.1.3	End of Discharge (EOD) Voltage	5-4
5.1.4	Cycling	5-5
5.1.5	Shelf Life and Charge Retention	5-6
5.1.5.1	Shelf Life	5-6
5.1.5.2	Charge Retention	5-7
5.1.6	Extended Outages	5-8
5.2	Environmental Criteria	5-9
5.2.1	Temperature and Humidity Shock During Transportation and Storage	5-9
5.2.2	Particulate Contamination and Corrosive Gas Resistance	5-10
5.2.3	Salt Fog Exposure	5-10
5.2.4	Cold Temperature Start	5-10

6 Service Life Criteria

6.1	Arrhenius Equation for Accelerating Testing	6-1
-----	-------------------------------------------------------	-----

Appendix A: References

A.1	Telcordia Documents	A-1
A.2	Non-Telcordia Documents	A-1
A.3	Other Source Material	A-2
A.4	Telcordia Document Sets—Family of Requirements (FR)	A-3
A.5	To Obtain Additional Reference Material	A-4
A.6	Reference Notes	A-4

A.6.1 Contact Customer Service	A-4
A.6.2 Order Documents Online From the Telcordia SuperStore	A-5
A.6.3 Web Sites for Generic Requirements Information	A-6
A.6.4 Licensing Agreements for Telcordia Documents	A-6

Appendix B: Acronyms

Appendix C: Glossary

Requirement-Object Index

List of Figures

Figure 2-1	Lithium Ion Couple	2-3
Figure 2-2	Battery Management System (BMS)	2-5
Figure 4-1	Fire Propagation and Projectile Hazard Characterization	4-5
Figure 4-2	Simulated Telecom Environmental Cycles	4-9
Figure 4-3	Immersion Test	4-12
Figure 4-4	16-Foot Free-Fall Shock	4-30
Figure 4-5	Crush Test	4-31

List of Tables

Table 1	Participants in the Development of GR-3150, Issue 3	Preface–xiv
Table 1-1	GR-3150 General Product, Safety, and Performance Criteria Levels	1–6
Table 2-1	Common Rechargeable Lithium Electrochemical Systems	2–1
Table 4-1	GR-3150 Safety Hazards and Acceptance Criteria	4–1
Table 4-2	GR-3108 - Vibrational Stress Test Conditions from ETSI EN 300 019	4–33

