

# Table of Contents

<b>Generic Requirements Notice of Disclaimer</b> . . . . .	iii
<b>Preface</b> . . . . .	xv

## 1 Introduction

1.1 Purpose and Scope . . . . .	1-1
1.2 Telecommunications Carrier's Role . . . . .	1-2
1.3 Equipment Manufacturer Role . . . . .	1-2
1.4 Reason for Reissue . . . . .	1-3
1.5 Structure of This Document . . . . .	1-3
1.6 Use of This Document . . . . .	1-4
1.7 Requirements Terminology . . . . .	1-6
1.8 Requirement Labeling Conventions . . . . .	1-6
1.8.1 Numbering of Requirement and Related Objects . . . . .	1-6
1.8.2 Requirement, Conditional Requirement, and Objective Identification . . . . .	1-7

## 2 Telecommunications Data Center Facility Requirements

2.1 Site Selection Considerations . . . . .	2-1
2.2 Equipment Layout and Space Planning . . . . .	2-2
2.2.1 General . . . . .	2-2
2.2.2 Data Center Equipment Frames . . . . .	2-2
2.2.2.1 Data Center Doors . . . . .	2-3
2.2.2.2 Equipment Frame Lineups . . . . .	2-3
2.2.2.3 Equipment Frame Floor Loading . . . . .	2-4
2.2.3 Data Center Floor Capacity . . . . .	2-4
2.2.4 Floor Space Planning . . . . .	2-5
2.2.5 Floor Plan Data (FPD) . . . . .	2-7
2.2.6 Special Equipment Considerations . . . . .	2-9
2.2.6.1 Power Plant Equipment . . . . .	2-9
2.2.6.1.1 Centralized Power Plant Equipment . . . . .	2-10
2.2.6.1.2 Lineup or Frame-Mounted Power Equipment . . . . .	2-11
2.2.6.2 Data Center Cross-Connect Systems . . . . .	2-11
2.3 Data Center Facility Environmental Criteria . . . . .	2-12
2.3.1 General . . . . .	2-12
2.3.2 Temperature and Humidity . . . . .	2-12
2.3.3 Heat Dissipation . . . . .	2-13
2.3.4 Cooling . . . . .	2-14
2.3.4.1 Heating, Ventilation, and Air Conditioning (HVAC) Systems . . . . .	2-14
2.3.4.1.1 Central HVAC . . . . .	2-15
2.3.4.1.2 Distributed HVAC (Self-Contained HVAC Units) . . . . .	2-15
2.3.4.2 Air Distribution . . . . .	2-15
2.3.4.2.1 Underfloor Air Distribution . . . . .	2-16
2.3.4.2.2 Overhead Air Distribution . . . . .	2-17
2.3.4.3 Economizer Systems . . . . .	2-19
2.3.4.4 Management of Air Returns . . . . .	2-20
2.3.4.5 Liquid Cooling . . . . .	2-20
2.3.4.5.1 Liquid Cooling Considerations . . . . .	2-21

2.3.5	Data Center Room Filtration . . . . .	2-22
2.3.6	Emergency Facility Ventilation . . . . .	2-23
2.4	Power Requirements . . . . .	2-24
2.4.1	Introduction . . . . .	2-24
2.4.2	General . . . . .	2-25
2.4.3	AC Power System . . . . .	2-26
2.4.3.1	AC Distribution Grounding . . . . .	2-26
2.4.3.2	Isolated Ground Receptacles . . . . .	2-27
2.4.3.3	External AC Power Supplies . . . . .	2-28
2.4.3.4	Internal AC Power Supplies . . . . .	2-28
2.4.4	DC Power Systems . . . . .	2-28
2.4.4.1	Rectifiers . . . . .	2-29
2.4.4.2	Charging (Rectifiers) Equipment . . . . .	2-33
2.5	Batteries . . . . .	2-35
2.5.1	Flooded Lead Antimony and Lead Calcium Cells . . . . .	2-36
2.5.2	Engineering Guidelines . . . . .	2-37
2.5.3	Power System Alarms . . . . .	2-38
2.5.4	Inverter Usage . . . . .	2-39
2.5.5	Uninterruptible Power Supplies (UPS) . . . . .	2-39
2.5.6	Standby AC Power . . . . .	2-40
2.5.6.1	Automatic Transfer Switch . . . . .	2-44
2.5.6.2	Main Line Circuit Breaker . . . . .	2-45
2.5.6.3	Engine Bonding and Grounding . . . . .	2-45
2.5.6.4	Engine Room Environment . . . . .	2-46
2.5.6.5	Engine Acoustics . . . . .	2-46
2.5.6.6	Engine Enclosures . . . . .	2-46
2.6	Illumination . . . . .	2-46
2.6.1	Illumination Criteria for Lighting Systems . . . . .	2-47
2.6.1.1	Quantity of Light . . . . .	2-47
2.6.1.2	Luminance Ratios . . . . .	2-48
2.6.1.3	Color of Light . . . . .	2-48
2.6.1.4	Illumination Test Methods for Data Center Lighting Systems . . . . .	2-48
2.6.2	Test 1 – Work Station Illumination, Readability, and Glare Tests . . . . .	2-49
2.6.3	Test 2 – Lighting System Tests . . . . .	2-50
2.7	Data Center Raised Floor Requirements . . . . .	2-53
2.7.1	General . . . . .	2-53
2.7.2	Raised Floor Requirements . . . . .	2-53
2.7.3	Raised Floor Fastening . . . . .	2-54
2.7.4	Equipment Fastening on Raised Floors . . . . .	2-54
2.7.5	Raised Floor Fire Protection . . . . .	2-56
2.7.6	Raised Floor Bonding and Grounding . . . . .	2-56
2.8	Cabling and Data Center Cable Distribution Systems (CDSs) . . . . .	2-57
2.8.1	General . . . . .	2-57
2.8.2	Cable Selection Requirements . . . . .	2-57
2.8.3	Cabling Installation Requirements . . . . .	2-59
2.8.4	Cable Pathway Systems . . . . .	2-60
2.8.4.1	Common Underfloor and Overhead CDSs Requirements . . . . .	2-60
2.8.4.1.1	Fiber Protection Systems (FPS) Requirements . . . . .	2-60
2.8.4.2	Underfloor Cable Distribution Requirements . . . . .	2-62
2.8.4.3	Overhead Cable Distribution Requirements . . . . .	2-62

2.8.5	Cable Diversity Requirements . . . . .	2-63
2.8.6	Bonding and Grounding Conductor and Connection Requirements . . .	2-63
2.8.6.1	Bonding and Grounding Conductors . . . . .	2-63
2.8.6.2	Connections . . . . .	2-63
2.8.6.3	Connectors . . . . .	2-64
2.9	Fire Protection . . . . .	2-65
2.9.1	General . . . . .	2-65
2.9.2	Fire Suppression . . . . .	2-65
2.9.3	Fire Alarming . . . . .	2-66
2.9.4	Smoke Control . . . . .	2-66

### 3 Telecommunications Data Center Equipment Criteria

3.1	General Requirements . . . . .	3-1
3.2	Data Center Equipment Frame Requirements . . . . .	3-1
3.2.1	Equipment Frame Nomenclature . . . . .	3-1
3.2.2	Equipment Frame Floor Mounting . . . . .	3-3
3.2.3	Equipment Frame Junctioning . . . . .	3-5
3.2.4	Equipment Frame and Chassis Dimensions . . . . .	3-5
3.2.4.1	Equipment Frame Dimensions – Four-Post Racks and Cabinets . .	3-5
3.2.4.2	Equipment Frame Dimensions – Open-Style Two-Post Racks . . . .	3-6
3.2.4.3	Equipment Frame Dimensions – Special Cases . . . . .	3-6
3.2.5	Equipment Frame Cable Management Provisions . . . . .	3-6
3.2.6	Equipment Frame Doors . . . . .	3-7
3.2.7	Equipment Frame Interface with Cable Rack . . . . .	3-7
3.2.8	Equipment Frame Weight . . . . .	3-7
3.3	Equipment Chassis Mounting Requirements . . . . .	3-8
3.4	Temperature and Humidity Criteria . . . . .	3-9
3.4.1	Operating Temperature and Humidity Criteria . . . . .	3-9
3.4.1.1	Operating Temperature and Humidity Expanded Criteria . . . . .	3-10
3.4.2	Over-Temperature Mitigation and Temperature Margin Evaluation . . .	3-11
3.4.3	Heat Dissipation and Energy Efficiency . . . . .	3-11
3.4.4	Equipment Airflow . . . . .	3-12
3.4.5	Fan-Cooled Equipment Criteria . . . . .	3-13
3.4.5.1	Equipment Fan Performance Criteria . . . . .	3-13
3.4.6	Equipment – Fan Filters . . . . .	3-14
3.5	Fire Resistance . . . . .	3-15
3.5.1	Equipment Fire-Resistance Rationale . . . . .	3-15
3.5.2	Equipment Assembly Fire Test . . . . .	3-16
3.5.2.1	Frame-Level Fire-Resistance Criteria . . . . .	3-17
3.5.2.2	Shelf-Level Fire-Resistance Criteria . . . . .	3-18
3.5.2.3	Smoke and Self-Extinguishment Criteria . . . . .	3-19
3.5.3	Use of Fire-Resistant Materials, Components, Wiring, and Cable Within Equipment . . . . .	3-19
3.5.3.1	Material/Components Fire-Resistance Criteria . . . . .	3-19
3.5.3.2	Ignitability Requirements for Ancillary Materials . . . . .	3-22
3.5.4	Fire Resistance of Wire and Cable Between Frames . . . . .	3-23
3.5.5	Fire Resistance of Optical Fiber Cable Trays and Raceways . . . . .	3-24
3.6	Equipment Handling Criteria . . . . .	3-25
3.6.1	Large Package Handling Criteria . . . . .	3-25
3.6.2	Equipment Shock Criteria . . . . .	3-25

3.6.2.1	Packaged Equipment Shock Criteria . . . . .	3-25
3.6.2.1.1	Category A Containers . . . . .	3-26
3.6.2.1.2	Category B Containers . . . . .	3-26
3.6.2.2	Unpackaged Equipment Shock Criteria . . . . .	3-26
3.7	Earthquake and Office Vibration Resistance . . . . .	3-27
3.7.1	Earthquake Environment and Criteria . . . . .	3-27
3.7.1.1	Earthquake Environment . . . . .	3-27
3.7.2	Earthquake and Vibration Checklist . . . . .	3-27
3.7.3	Earthquake Testing Criteria . . . . .	3-28
3.7.3.1	Physical Performance Criteria . . . . .	3-31
3.7.3.2	Functional Performance . . . . .	3-31
3.7.3.3	Floor-Mounted Equipment Frame and Anchor Criteria . . . . .	3-32
3.7.3.4	Wall-Mounted Equipment Anchor Criterion . . . . .	3-32
3.7.4	Office Vibration Environment and Testing Criteria . . . . .	3-33
3.7.4.1	Office Vibration Environment . . . . .	3-33
3.7.4.2	Physical Performance Criteria . . . . .	3-33
3.7.4.3	Functional Performance Criteria . . . . .	3-33
3.8	Acoustic Noise . . . . .	3-34
3.9	Illumination Criteria for Data Center Equipment . . . . .	3-35
3.9.1	Surface Reflectance and Color . . . . .	3-36
3.10	System-Level Electrostatic Discharge . . . . .	3-37
3.10.1	Overview . . . . .	3-37
3.10.2	ESD Immunity Criteria . . . . .	3-37
3.10.2.1	Immunity Criteria – Normal Operation . . . . .	3-37
3.10.2.2	Immunity Criteria – Installation and Maintenance . . . . .	3-38
3.10.2.3	ESD Warning Label Requirements . . . . .	3-38
3.11	Electrical Fast Transient (EFT) . . . . .	3-38
3.12	Electromagnetic Emissions and Immunity . . . . .	3-39
3.12.1	Federal Communications Commission (FCC) Part 15 Criteria . . . . .	3-39
3.12.2	Emission Criteria . . . . .	3-39
3.12.2.1	Documentation . . . . .	3-40
3.12.3	Immunity Criteria . . . . .	3-40
3.12.3.1	Radiated Immunity Criteria . . . . .	3-41
3.12.3.1.1	Electric Fields Radiated Immunity Criteria With Doors and Covers Closed . . . . .	3-41
3.12.3.1.2	Electric Fields Radiated Immunity Criteria With Doors and Covers Open . . . . .	3-41
3.12.3.2	Conducted Immunity Criteria . . . . .	3-41
3.12.3.2.1	Conducted Immunity Criteria for AC and DC Power Ports . . . . .	3-41
3.12.3.2.2	Conducted Immunity Requirements for Metallic I/O Interfaces . . . . .	3-42
3.13	Lightning . . . . .	3-43
3.13.1	Overview . . . . .	3-43
3.13.2	Functional Lightning Criteria . . . . .	3-44
3.13.3	GR-1089 Intra-Building Lightning Surge Criteria . . . . .	3-44
3.13.3.1	Ports Connected to Unshielded Cables . . . . .	3-44
3.13.3.2	I/O Ports Connected to Shielded Cables . . . . .	3-45
3.13.4	GR-1089 Lightning Criteria for Equipment Interfacing with AC Power . . . . .	3-45
3.14	Equipment Powering . . . . .	3-46
3.15	Electrical Safety Criteria . . . . .	3-46

3.15.1 Listing Requirements . . . . .	3-46
3.16 Bonding and Grounding . . . . .	3-46
3.16.1 General Principles . . . . .	3-46
3.16.2 Equipment Grounding Systems . . . . .	3-47
3.16.3 Equipment Frame Bonding and Grounding . . . . .	3-47
3.16.4 Equipment Chassis Bonding and Grounding . . . . .	3-48
3.16.5 Equipment Frame and Chassis Bonding and Grounding Connectors . . . . .	3-49
3.16.6 DC Power System Grounding . . . . .	3-50
3.16.6.1 Centralized Power Sources . . . . .	3-50
3.16.6.2 Bonding of Battery Return (BR) Input Terminals . . . . .	3-50

## 4 Environmental Test Methods

4.1 Safety Precautions . . . . .	4-1
4.2 Temperature and Humidity Test Methods . . . . .	4-2
4.2.1 General Testing Requirements . . . . .	4-2
4.2.2 Operating Temperature – Minimum Condition Tests . . . . .	4-4
4.2.2.1 Operating Temperature – Minimum Conditions . . . . .	4-4
4.2.2.2 Temperature Margin Determination – Minimum Conditions . . . . .	4-5
4.2.2.3 Operation With Fan Failure – Minimum Conditions . . . . .	4-5
4.2.3 Operating Temperature – Expanded Condition Tests . . . . .	4-6
4.2.3.1 Operating Temperature – Expanded Conditions . . . . .	4-6
4.2.3.2 Temperature Margin Determination – Expanded Conditions . . . . .	4-7
4.2.3.3 Operation With Fan Failure – Expanded Test . . . . .	4-7
4.3 Fire Test Methods . . . . .	4-8
4.3.1 Sample Configuration . . . . .	4-8
4.3.2 Testing Clarification – Circuit Board Removal . . . . .	4-8
4.3.2.1 Adjacent Printed Wiring Boards (PWBs) in Close Proximity . . . . .	4-8
4.3.2.1.1 Case 1 – No Mezzanine Cards . . . . .	4-8
4.3.2.1.2 Case 2 – Mezzanine Card . . . . .	4-9
4.3.2.1.3 Case 3 – Larger or Multiple Mezzanine Cards . . . . .	4-10
4.3.2.2 Adjacent Printed Wiring Boards (PWBs) Not in Close Proximity . . . . .	4-11
4.3.3 ATIS-0600319 Test Deviation – Fan Powering Options . . . . .	4-12
4.3.4 Telcordia Needle Flame Test . . . . .	4-12
4.3.4.1 Application to Individual Components . . . . .	4-12
4.3.4.2 In-Situ Application to Individual Components . . . . .	4-13
4.3.4.3 Application to Multiple Aggregate Configurations . . . . .	4-13
4.3.5 Guidelines for Retesting to Address Product Changes . . . . .	4-13
4.3.6 Test Reporting – Additions . . . . .	4-14
4.4 Handling Test Methods . . . . .	4-15
4.4.1 Handling Drop Tests—Packaged Equipment . . . . .	4-16
4.4.1.1 Category A Container—Test Procedure . . . . .	4-16
4.4.1.2 Category B Container – Test Procedure . . . . .	4-20
4.4.2 Unpackaged Equipment Drop Tests . . . . .	4-22
4.4.3 Test Procedure – Equipment and Field Replaceable Units (FRUs) Weighing Less Than 25 kg (55.1 lb) . . . . .	4-22
4.4.4 Test Procedure – Equipment and Field Replaceable Units (FRUs) Weighing 25 kg (55.1 lb) or More . . . . .	4-24
4.5 Earthquake and Office Vibration Test Methods . . . . .	4-26
4.5.1 Earthquake Test Method . . . . .	4-26
4.5.1.1 Test Plan . . . . .	4-29

4.5.1.2	Laboratory Equipment . . . . .	4-29
4.5.1.3	Test Configuration . . . . .	4-31
4.5.1.4	Waveform Test Procedure . . . . .	4-33
4.5.1.5	Test Report . . . . .	4-34
4.5.2	Office Vibration Test Procedure . . . . .	4-35
4.5.2.1	Office Vibration Test Option 1 – Swept Sine . . . . .	4-35
4.5.2.2	Office Vibration Test Option 2 – Random Vibration . . . . .	4-35
4.6	Acoustical Measurement Methodology . . . . .	4-37
4.6.1	Procedure for Nominal Operating Conditions: Test Room at 27°C . . . . .	4-37
4.6.2	Procedure for Nominal Operating Conditions: Test Room at Other Than 27°C . . . . .	4-37
4.6.3	Procedure for Temperature Invariant Air-Moving Devices Operating Conditions . . . . .	4-38
4.6.4	Procedure for High-Temperature Operating Conditions . . . . .	4-38
4.7	Illumination Test Methods for Data Center Equipment . . . . .	4-38
4.7.1	Equipment Assembly – Readability, Glare, and Reflectance Tests . . . . .	4-39
4.7.1.1	Test Procedure – Equipment Assembly Readability and Glare . . . . .	4-39
4.7.1.2	Test Procedure – Equipment Surface Reflectance . . . . .	4-39
4.8	System-Level Electrostatic Discharge Test Method . . . . .	4-43
4.8.1	Method Summary . . . . .	4-43
4.8.2	ESD Test Site . . . . .	4-43
4.8.3	Operating Conditions . . . . .	4-43
4.8.4	Selection of Test Points . . . . .	4-44
4.8.4.1	Test Points – Normal Operation . . . . .	4-44
4.8.4.2	Test Points – Installation and Repair . . . . .	4-45
4.8.5	Test Sequence . . . . .	4-45
4.9	Electrical Fast Transient . . . . .	4-46
4.9.1	EFT Test Methods and Procedures . . . . .	4-46
4.10	Radiated and Conducted Immunity Test Method . . . . .	4-46
4.10.1	Scope . . . . .	4-46
4.10.2	Test Equipment . . . . .	4-46
4.10.2.1	Receivers . . . . .	4-46
4.10.2.2	Current Probes . . . . .	4-46
4.10.2.3	Antennas . . . . .	4-47
4.10.2.4	Signal Sources . . . . .	4-47
4.10.3	Test Conditions for Test Sample . . . . .	4-47
4.10.3.1	Test Sample Installation . . . . .	4-47
4.10.3.2	Test Sample Leads . . . . .	4-48
4.10.3.3	Test Sample Grounding . . . . .	4-50
4.10.3.4	DC Return . . . . .	4-50
4.10.3.5	Test Temperature . . . . .	4-50
4.10.3.6	Conditioning of the Test Sample . . . . .	4-50
4.10.3.7	Interfacing Units and Simulators . . . . .	4-50
4.10.4	Data Reporting Format . . . . .	4-51
4.10.5	Radiated Immunity Measurements . . . . .	4-51
4.10.5.1	Shielded Enclosures . . . . .	4-51
4.10.5.2	Subsystem Testing . . . . .	4-51
4.10.5.3	Measurement Procedures . . . . .	4-52
4.10.5.3.1	Test Sample and Antenna Positioning . . . . .	4-52
4.10.5.3.2	Calibration of Generated Fields . . . . .	4-52

4.10.5.3.3 Test Signal Modulation . . . . .	4-53
4.10.5.3.4 Frequencies and Amplitudes To Be Scanned . . . . .	4-53
4.10.6 Conducted Immunity Measurements . . . . .	4-55
4.10.6.1 Test Signal Modulation . . . . .	4-55
4.10.6.2 Frequency Scanning and Test Selection . . . . .	4-55
4.10.6.3 Calibration of Test Signal . . . . .	4-55
4.10.6.4 AC and DC Leads (Common-Mode Injection) . . . . .	4-55
4.10.6.5 Communications Ports – Signal Leads (Common-Mode Injection)	4-56
4.11 Lightning Test Method . . . . .	4-60
4.11.1 Overview . . . . .	4-60
4.11.2 Characterization of Test Generators and Test Equipment . . . . .	4-60
4.11.3 Testing Conditions . . . . .	4-61
4.11.3.1 Sample Grounding . . . . .	4-62
4.11.3.2 Sample DC Return . . . . .	4-62
4.11.3.3 Number of Samples to Be Tested . . . . .	4-62
4.11.4 Intra-Building Lightning Surge Test Procedure . . . . .	4-62
4.11.4.1 Ports Connected to Unshielded Cables . . . . .	4-64
4.11.4.2 Ports Connected to Paired Shielded Cables . . . . .	4-66
4.11.4.3 Ports Connected to Coaxial Cables . . . . .	4-68
4.11.5 Equipment Interfacing With AC Power Port Lightning Surge Test Procedure . . . . .	4-69

## **Appendix A: Definition of Double-Exponential Waveform**

### **Appendix B: References**

B.1 Telcordia Documents . . . . .	B-1
B.2 Other Referenced Material . . . . .	B-2
B.3 To Obtain Additional Reference Material . . . . .	B-6
B.4 Telcordia Reference Notes . . . . .	B-6
B.4.1 Contact Telcordia Customer Service . . . . .	B-6
B.4.2 Order Documents Online From the Telcordia Information SuperStore . .	B-7
B.4.3 Web Sites for Generic Requirements Information . . . . .	B-8
B.4.4 Licensing Agreements for Telcordia Documents . . . . .	B-8

### **Appendix C: Acronyms**

### **Requirement-Object Index**

## List of Figures

Figure 2-1	Example of a Work-Cell . . . . .	2-6
Figure 2-2	Typical DC Centralized Power Plant Equipment Area . . . . .	2-10
Figure 2-3	Mixed Inlet Air-Supply System . . . . .	2-18
Figure 2-4	Typical Power Distribution System . . . . .	2-30
Figure 2-5	Rectifier Plant . . . . .	2-31
Figure 2-6	Test 1 – Work Station Illumination, Readability, and Glare . . . . .	2-50
Figure 2-7	Test 2 – Lighting System Test – Equipment Areas . . . . .	2-51
Figure 2-8	Test 2 – Lighting System Test – Power and Battery Areas . . . . .	2-52
Figure 2-9	Toggle Bar Fastening Method in Isolated Ground Plane Environment . . . . .	2-55
Figure 3-1	Equipment Frame – Overall Dimensions . . . . .	3-2
Figure 3-2	Framework Base (Typical) – Floor-Anchoring Hole Pattern . . . . .	3-4
Figure 3-3	Example of Closed and Open Slots for Mounting Hardware . . . . .	3-8
Figure 3-4	Profile View of Conforming Equipment Airflow Schemes Conforming to This Section . . . . .	3-12
Figure 3-5	Telcordia Earthquake Zone Map . . . . .	3-30
Figure 4-1	Card Removed and Burner Inserted in Plane of PWB . . . . .	4-9
Figure 4-2	Parent PWB Removed and Burner Inserted – Mezzanine Card Left in Place . . . . .	4-10
Figure 4-3	Mezzanine Card Removed and Burner Inserted . . . . .	4-11
Figure 4-4	Drop Surfaces for Category A Container . . . . .	4-18
Figure 4-5	Test Set-Up for Category A Container . . . . .	4-19
Figure 4-6	Drop Surface for Category B Container . . . . .	4-20
Figure 4-7	Category B Container – Equipment Handling Drops . . . . .	4-21
Figure 4-8	Unpackaged Drop Test for Equipment or FRUs < 25 kg (55.1 lb) . . . . .	4-23
Figure 4-9	Unpackaged Equipment and FRU ≥ 25 kg (55.1 lb) Drop Surfaces . . . . .	4-25
Figure 4-10	Earthquake Synthesized Waveform – VERTEQII – Zone 4 . . . . .	4-27
Figure 4-11	Required Response Spectra . . . . .	4-28
Figure 4-12	Random Office Vibration Test Severity . . . . .	4-36
Figure 4-13	Equipment Assembly, Readability, and Glare . . . . .	4-41
Figure 4-14	Equipment Assembly, Surface Reflectance . . . . .	4-42
Figure 4-15	Cable Arrangement for Test Samples With Overhead Cables . . . . .	4-49
Figure 4-16	Injection Probe Calibration Setup . . . . .	4-57
Figure 4-17	Test Setup for Conducted Immunity Tests on AC and DC Power Ports . . . . .	4-58
Figure 4-18	Test Setup for Conducted Immunity Tests for Communications Ports . . . . .	4-59
Figure 4-19	Typical Lightning Test Generator . . . . .	4-61
Figure 4-20	Application of Lightning Surges . . . . .	4-63
Figure 4-21	Test Circuit for I/O Ports – Metallic Test (Applies to One Conductor at a Time) . . . . .	4-65
Figure 4-22	Test Circuit for I/O Ports – Longitudinal Test . . . . .	4-65
Figure 4-23	Test Circuit for Unshielded PoE Ports – Metallic Test (SW Sets Mode A or Mode B Testing) . . . . .	4-66
Figure 4-24	Test Circuit for Paired-Conductor Ports Providing a Connection Means for the Shielded Cable . . . . .	4-67



Figure 4-25	Test Circuit for Coaxial Cable Ports Providing a Connection Means for the Shielded Cable . . . . .	4-69
Figure A-1	Double Exponential Current Waveform of A/B for Surges of <a href="#">Table A-1</a> . . . . .	A-1
Figure A-2	Double Exponential Voltage Waveform of A/B for Surges of <a href="#">Table A-1</a> . . . . .	A-2

## List of Tables

Table 1-1	Application Guidelines for Equipment Criteria as a Function of Facility and Service . . . . .	1-4
Table 2-1	Typical Data Center Operating Limits . . . . .	2-13
Table 2-2	Minimum Maintained Illumination Level for Data Center Spaces . . . . .	2-47
Table 2-3	Equipment Fastening Considerations . . . . .	2-56
Table 3-1	Minimum Temperature and Humidity Limits . . . . .	3-10
Table 3-2	Expanded Temperature and Humidity Limits . . . . .	3-10
Table 3-3	Correlation of Earthquake Risks . . . . .	3-27
Table 3-4	Acoustical Noise Emission Limits . . . . .	3-35
Table 3-5	Conducted Immunity Requirements for AC and DC Power Ports . . . . .	3-42
Table 3-6	Conducted Immunity Requirements for Metallic I/O Interfaces . . . . .	3-43
Table 4-1	Variable Test Conditions Based on Effective Air-Inlet Location . . . . .	4-2
Table 4-2	Application Criteria for Needle Flame Test . . . . .	4-12
Table 4-3	Category A Container Packaged Equipment Shock Criteria . . . . .	4-18
Table 4-4	Unpackaged Free-Fall Shock Criteria for Equipment and FRUs < 25 kg (55.1 lb) . . . . .	4-23
Table 4-5	Unpackaged Equipment and FRU $\geq$ 25 kg (55.1 lb) Shock Criteria . . . . .	4-24
Table 4-6	Response Spectrum Analyzer Frequencies . . . . .	4-30
Table 4-7	Configuration Guidelines for Shelf-Level Testing . . . . .	4-32
Table 4-8	1 to 10 GHz Immunity Scan Rate and Step Size . . . . .	4-54
Table 4-9	Frequencies of Key Interest . . . . .	4-54
Table 4-10	Intra-Building Lightning Surge for I/O Ports . . . . .	4-64
Table 4-11	Intra-Building Lightning Surge for Paired Shielded Cable Ports . . . . .	4-67
Table 4-12	Intra-Building Lightning Surge for Coaxial Cable Ports . . . . .	4-68
Table 4-13	Lightning Surge (AC Power Port) . . . . .	4-70
Table A-1	Waveform Tolerances . . . . .	A-2