

# Table of Contents

<b>Preface</b> . . . . .	xi
<b>1 Introduction</b>	
1.1 Purpose and Scope . . . . .	1-1
1.2 Reasons for GR-3168-CORE, Issue 2 . . . . .	1-1
1.3 Topics Not Addressed in This GR . . . . .	1-2
1.4 GR-3168 Safety and Performance Compliance Levels . . . . .	1-2
1.4.1 Level I — Safety and Compatibility . . . . .	1-2
1.4.2 Level II — Safety and Limited Operability . . . . .	1-3
1.4.3 Level III — Safety and Full Operability . . . . .	1-4
1.5 Organization of This Document . . . . .	1-7
1.6 Requirements Terminology . . . . .	1-7
1.7 Requirement Labeling Conventions . . . . .	1-8
1.7.1 Numbering of Requirement and Related Objects . . . . .	1-8
1.7.2 Requirement, Conditional Requirement, and Objective Identification . . . . .	1-9
1.7.3 Compliance Level Identification in Numbering of the Requirements and Related Objects . . . . .	1-9
1.8 Test Criteria . . . . .	1-9
1.8.1 General . . . . .	1-10
1.8.2 Root Cause Analysis (RCA) . . . . .	1-10
1.8.3 Data Acquisition and Reporting . . . . .	1-11
1.8.4 Sample Selection . . . . .	1-11
1.8.5 Number of Samples To Be Tested . . . . .	1-12
1.8.6 Pre- and Post-Test Functional Verification . . . . .	1-12
1.8.7 Measuring . . . . .	1-12
1.8.8 Telcordia Documents . . . . .	1-13
<b>2 General Product Information</b>	
2.1 General Description . . . . .	2-1
2.2 Chemistry . . . . .	2-1
2.2.1 Electrolyte . . . . .	2-1
2.2.2 Positive Electrode—Nickel Hydroxide . . . . .	2-2
2.2.3 Negative Electrode—Metal Hydride . . . . .	2-3
2.3 Cell Design . . . . .	2-4
2.3.1 Cylindrical Cell Design . . . . .	2-5
2.3.2 Prismatic Cell Design . . . . .	2-6
2.4 Battery Module Design . . . . .	2-7
2.5 Battery Management System (BMS) . . . . .	2-9
2.6 Quality and Reliability (Q&R) . . . . .	2-10
2.7 Safety . . . . .	2-11
2.7.1 Thermal Runaway . . . . .	2-11
2.8 Performance . . . . .	2-12
2.9 Service Life . . . . .	2-12
2.10 Deployment Considerations . . . . .	2-12
2.10.1 Central Office (CO) . . . . .	2-12
2.10.2 Outside Plant (OSP) . . . . .	2-14

2.10.3 Customer Premises . . . . .	2-15
------------------------------------	------

### 3 General Product Criteria

3.1 Quality . . . . .	3-1
3.1.1 Failure Mode and Effect Analysis (FMEA) . . . . .	3-2
3.1.2 Product Samples . . . . .	3-2
3.1.3 Product Changes . . . . .	3-2
3.2 Reliability . . . . .	3-3
3.2.1 String Reliability . . . . .	3-3
3.2.2 Fail-Safe Design . . . . .	3-3
3.3 Documentation and Training . . . . .	3-4
3.4 Chemical Criteria . . . . .	3-6
3.4.1 Electrolyte . . . . .	3-6
3.5 Physical Design Criteria . . . . .	3-7
3.5.1 Components . . . . .	3-7
3.5.2 Use of Fire-Resistant Materials, Components, Wiring, and Cable . . . . .	3-7
3.5.3 Containers . . . . .	3-7
3.5.4 Covers . . . . .	3-8
3.5.5 Terminals . . . . .	3-8
3.5.6 Pressure-Relief Valves . . . . .	3-9
3.5.7 Electrodes . . . . .	3-10
3.5.8 Separators . . . . .	3-11
3.5.9 Weight . . . . .	3-11
3.5.10 Accessories . . . . .	3-11
3.5.11 Markings . . . . .	3-12
3.5.12 Packaging . . . . .	3-13
3.5.13 Mounting Arrangements . . . . .	3-13
3.5.14 Handling . . . . .	3-13
3.6 Electrical Safety Criteria . . . . .	3-14
3.7 Bonding and Grounding Criteria . . . . .	3-14
3.8 Illumination Criteria for Network Equipment . . . . .	3-14
3.9 Self-Heating and Surface Temperature . . . . .	3-14
3.9.1 Self-Heating . . . . .	3-14
3.9.2 Surface Temperature . . . . .	3-15
3.10 Battery Management System (BMS) Criteria . . . . .	3-15
3.10.1 Form-C Relay . . . . .	3-15
3.10.2 Fail-Safe Design . . . . .	3-16
3.10.3 Reliability . . . . .	3-16
3.10.4 Features . . . . .	3-16
3.10.5 Physical Design and Manufacturing . . . . .	3-17
3.10.6 Status and Alarms . . . . .	3-17
3.10.6.1 Status Indicators and Parameters . . . . .	3-17
3.10.6.2 Alarms . . . . .	3-18
3.10.7 Accuracy of Measurement . . . . .	3-19

### 4 Safety Criteria

4.1 Acceptance Criteria . . . . .	4-1
4.2 Precautions . . . . .	4-1
4.3 Chemical Criteria . . . . .	4-2
4.3.1 Gassing . . . . .	4-2

4.3.2 Thermal Runaway . . . . .	4-2
4.4 Status Indicators and Alarms . . . . .	4-3
4.5 Environmental Criteria . . . . .	4-4
4.5.1 Simulated Brush Fire . . . . .	4-4
4.5.2 Simulated Telecom Environmental Cycles . . . . .	4-5
4.5.3 Operating Altitude . . . . .	4-9
4.5.4 Immersion (Flooded Conditions) . . . . .	4-9
4.6 Electrical Criteria . . . . .	4-12
4.6.1 Overcharge . . . . .	4-13
4.6.2 Short Circuit . . . . .	4-15
4.6.2.1 External Short Circuit . . . . .	4-15
4.6.2.2 Internal Short Circuit . . . . .	4-17
4.6.3 Reverse Polarity . . . . .	4-17
4.6.4 Overdischarge . . . . .	4-19
4.6.5 Electromagnetic Compatibility (EMC) Criteria . . . . .	4-21
4.6.5.1 System-Level ESD . . . . .	4-21
4.6.5.2 System-Level Electrical Fast Transients (EFTs) . . . . .	4-22
4.6.5.3 Electromagnetic Interference (EMI) . . . . .	4-22
4.6.5.4 Lightning and AC Power Fault . . . . .	4-24
4.7 Mechanical Criteria . . . . .	4-24
4.7.1 Handling Resistance Criteria . . . . .	4-24
4.7.1.1 Packaged Shock Criterion . . . . .	4-24
4.7.1.2 Unpackaged Shock Criteria . . . . .	4-25
4.7.2 Earthquake and Vibration . . . . .	4-25
4.7.2.1 Earthquake . . . . .	4-25
4.7.2.2 Transportation Vibration . . . . .	4-25
4.7.2.3 Low-Level Vibration Resistance . . . . .	4-26

## 5 Performance Criteria

5.1 Electrical Criteria . . . . .	5-1
5.1.1 Float Voltage . . . . .	5-1
5.1.2 Capacity . . . . .	5-3
5.1.3 Charging . . . . .	5-4
5.1.4 Re-Charge Time . . . . .	5-5
5.1.5 Cycling . . . . .	5-6
5.1.6 Discharge Rate . . . . .	5-7
5.1.7 End of Discharge Voltage (EODV) . . . . .	5-8
5.1.8 Shelf Life and Charge Retention . . . . .	5-9
5.2 Environmental Criteria . . . . .	5-10
5.2.1 Temperature and Humidity Shock During Transportation and Storage . . . . .	5-10
5.2.2 Particulate Contamination and Corrosive Gas Resistance . . . . .	5-11
5.2.3 Salt Fog Exposure . . . . .	5-11
5.2.4 Cold Temperature Start . . . . .	5-12

## 6 Service Life Criteria

6.1 48-Volt NiMH Battery Age Test . . . . .	6-1
6.2 Arrhenius Log-Normal Life Model . . . . .	6-4
6.2.1 NiMH Cell Age Test . . . . .	6-5

## Appendix A: References

A.1	Telcordia Documents . . . . .	A-1
A.2	Other Referenced Documents, Books, and Materials . . . . .	A-2
A.2.1	Miscellaneous . . . . .	A-2
A.2.2	European Telecommunications Standards Institute (ETSI) . . . . .	A-2
A.2.3	Underwriters Laboratories (UL) Documents . . . . .	A-2
A.2.4	To Obtain Additional Reference Material . . . . .	A-2
A.3	Telcordia Document Sets—Family of Requirements (FR) and Family of Documents (FD) . . . . .	A-3
A.4	Telcordia Reference Notes . . . . .	A-4
A.4.1	Contact Telcordia Customer Service . . . . .	A-4
A.4.2	Order Documents Online From the Telcordia SuperStore . . . . .	A-4
A.4.3	Web Sites for Generic Requirements Information . . . . .	A-5
A.4.4	Licensing Agreements for Telcordia Documents . . . . .	A-5

## Appendix B: Acronyms

## Appendix C: Glossary

## Requirement-Object Index

## List of Figures

Figure 2-1	NiMH Cylindrical Cell Design . . . . .	2-5
Figure 2-2	NiMH Prismatic Cell Design . . . . .	2-6
Figure 2-3	NiMH 12 V Battery Module Design . . . . .	2-7
Figure 2-4	NiMH 48 V Battery Module Design With Internal Parallel Strings . .	2-7
Figure 2-5	NiMH Sealed Battery Design . . . . .	2-8
Figure 2-6	Battery Management System (BMS) . . . . .	2-10
Figure 4-1	Simulated Telecom Environmental Cycles . . . . .	4-8
Figure 4-2	Immersion Test . . . . .	4-11

## List of Tables

Table 1-1	GR-3168 General Product, Safety, Performance, and Service Life Criteria Levels . . . . .	1-6
Table 2-1	Common Re-Chargeable Nickel Metal Hydride Electrochemical Systems . . . . .	2-1
Table 4-1	GR-3168 Safety Hazards and Acceptance Criteria . . . . .	4-1
Table 4-2	GR-3108 (Table 6-1) Vibrational Stress Test Conditions from ETSI EN 300 019 . . . . .	4-27