

Table of Contents

1 Introduction

1.1 Product Description	1-1
1.2 Customer Premises Applications - Cable Types 59, 6, 7, and 11	1-2
1.3 Interconnecting Applications - Cable Types 724 Through 735	1-3
1.4 References	1-3
1.5 Units and Tolerances	1-3
1.6 History and Organization of This Document	1-4
1.6.1 Rationale for GR-3175	1-4
1.6.2 Document Organization	1-4
1.7 Requirements Terminology	1-5
1.8 Requirement Labeling Conventions	1-6
1.8.1 Numbering of Requirement and Related Objects	1-6
1.8.2 Requirement, Conditional Requirement, and Objective Identification	1-7

2 General Information

2.1 Ordering and User Options	2-1
2.2 Safety Considerations	2-1
2.3 Product Reliability and Quality Management Systems	2-2
2.3.1 Product Changes	2-3
2.3.2 Product Reliability	2-3
2.4 Comprehensive Tests	2-3

3 General Requirements - Packaging and Marking

3.1 Marking Requirements	3-1
3.1.1 Jacket Marking	3-1
3.1.2 Length Marking	3-1
3.1.3 Marking Height and Legibility	3-1
3.1.4 Marking Durability	3-2
3.2 Packaging Requirements	3-2
3.2.1 General	3-2
3.2.2 Package Marking	3-3
3.2.3 End Sealing	3-3
3.3 Durability of Printing and Marking Test	3-3

4 Mechanical Design and Test Requirements

4.1 Customer Premises Cables - Center Conductor	4-1
4.1.1 Copper-Clad Steel Conductor	4-1
4.1.2 Tensile Strength of Composite Conductor	4-2
4.1.3 Elongation of Composite Conductor	4-2
4.1.4 Adhesion of Copper	4-2
4.1.5 Copper Ductility	4-2
4.2 Interconnection Cables - Center Conductor	4-2
4.2.1 Center Conductors	4-3
4.2.2 Elongation	4-3
4.2.3 Special Requirements for Copper-Clad Steel	4-4

4.3	Foam - Dielectric	4-4
4.3.1	General	4-4
4.3.2	Material	4-4
4.3.3	Shrinkback	4-5
4.4	Solid - Dielectric	4-5
4.4.1	General Material	4-5
4.4.2	Voids	4-5
4.4.3	Shrinkback	4-5
4.5	Patching	4-6
4.6	Insulation Imperfections	4-6
4.7	Overall Shield - Customer Premises Application	4-6
4.7.1	General Information	4-6
4.7.2	Laminated Shielding Tape	4-6
4.7.2.1	Bonding Shielding Tape	4-6
4.7.2.2	Non-Bonding Shielding Tape	4-7
4.7.2.3	Shielding Tape Material	4-7
4.7.3	Average Core Diameter	4-7
4.7.4	Core Ovality	4-7
4.7.5	Shield Braid Wire	4-8
4.7.5.1	Material	4-8
4.7.5.2	Braid Coverage	4-8
4.8	Braid Shield - Interconnection Cable Applications	4-9
4.8.1	Outer Conductor (Shield)	4-9
4.8.2	Two-Layer Braids	4-10
4.8.3	Laminated Tape and Braid Shield	4-10
4.9	Cable Jacket	4-10
4.9.1	General	4-10
4.9.2	Material	4-11
4.9.3	Jacket Tensile Strength and Elongation	4-11
4.9.4	Aging Test	4-11
4.9.5	Jacket Thickness	4-11
4.9.6	Other Coverings	4-12
4.9.7	Diameter Over Jacket (DOJ)	4-12

5 Completed Cable Physical Tests

5.1	Cold Bend	5-1
5.2	Cable Impact Test	5-1
5.3	Jacket Longitudinal Shrinkage	5-1
5.4	Fire Resistance and Listing(s)	5-1

6 Completed Cable Electrical Requirements

6.1	Continuity and Shorts	6-1
6.2	Conductor Resistance	6-1
6.2.1	Premises Cables	6-1
6.2.2	Interconnection Cables	6-1
6.3	Impedance	6-2
6.4	Structural Return Loss (SRL)	6-2
6.4.1	Premises Cables	6-2
6.4.2	Interconnection Cables	6-2
6.5	Attenuation	6-3

6.6 Dielectric Strength Between Conductors 6-4
 6.7 Insulation Resistance 6-4

7 Coaxial Connector Compatibility

7.1 Compatibility With Hardware 7-1
 7.2 Mechanical Design 7-2
 7.2.1 Materials 7-2
 7.2.2 Cable Application 7-2
 7.2.3 Cable Interface Durability 7-3
 7.3 Marking and Packaging 7-3
 7.4 Electrical 7-4
 7.4.1 Insulation Resistance 7-4
 7.4.2 Dielectric Strength 7-4
 7.4.3 Insertion Loss 7-4
 7.4.4 Return Loss 7-5
 7.5 Vibration 7-5

Appendix A: References

A.1 Telcordia Documents A-1
 A.2 Non-Telcordia Documents A-1
 A.3 To Obtain Additional Reference Material A-4
 A.4 Telcordia Reference Notes A-5
 A.4.1 Contact Telcordia Customer Service A-5
 A.4.2 Order Documents Online From the Telcordia SuperStore A-5
 A.4.3 Web Sites for Generic Requirements Information A-6
 A.4.4 Licensing Agreements for Telcordia Documents A-6

Appendix B: Acronyms

Requirement-Object Index

List of Figures

Figure 4-1	Illustration of Wire Braid	4-9
Figure 4-2	Jacket Thickness Measurements - Cross-Section	4-12

List of Tables

Table 1-1	Types of Coaxial Cable	1-3
Table 4-1	Center Conductor Diameter and Material Properties	4-1
Table 4-2	Coaxial Cable Dimensional Requirements	4-3
Table 4-3	Average Core Diameter Over Tape	4-7
Table 4-4	Core Ovality - Maximum	4-7
Table 4-5	Diameter Over Jacket	4-12
Table 6-1	DC Loop Resistance at 20°C (68°F) - Maximum	6-1
Table 6-2	Structural Return Loss - Minimum dB	6-2
Table 6-3	Maximum Attenuation - Premises Cables	6-3
Table 6-4	Maximum Attenuation - Interconnection Cables	6-4

