

Table of Contents

Preface	xiii
1 Introduction	
1.1 Purpose and Scope of Document	1-1
1.2 Reasons for GR-3176-CORE, Issue 1	1-1
1.3 Topics Not Addressed in This GR	1-2
1.4 Organization of This Document	1-2
1.5 Requirements Terminology	1-3
1.6 Requirement Labeling Conventions	1-3
1.6.1 Numbering of Requirement and Related Objects	1-3
1.6.2 Requirement, Conditional Requirement, and Objective Identification	1-4
1.7 Test Criteria	1-4
1.7.1 General	1-4
1.7.2 Root Cause Analysis (RCA)	1-5
1.7.3 Data Acquisition and Reporting	1-5
1.7.4 Sample Selection	1-6
1.7.5 Number of Samples To Be Tested	1-7
1.7.6 Pre- and Post-Test Functional Verification	1-7
1.7.7 Measuring	1-7
1.7.8 Telcordia Documents	1-7
2 General Product Information	
2.1 General Description	2-1
2.2 Chemistry	2-2
2.3 Battery Module Design	2-3
2.4 Battery Management System (BMS)	2-4
2.5 Quality and Reliability (Q&R)	2-6
2.6 Safety	2-7
2.6.1 Thermal Runaway	2-7
2.7 Performance	2-7
2.8 Service Life	2-8
2.9 Deployment Considerations	2-8
2.9.1 Central Office (CO)	2-8
2.9.2 Outside Plant (OSP)	2-9
2.9.3 Customer Premises	2-10
3 General Product Criteria	
3.1 Quality	3-1
3.1.1 Failure Mode and Effect Analysis (FMEA)	3-2
3.1.2 Product Samples	3-2
3.1.3 Product Changes	3-2
3.2 Reliability	3-3
3.2.1 String Reliability	3-3
3.2.2 Fail-Safe Design	3-3
3.3 Documentation and Training	3-4
3.4 Chemical Criteria	3-6

3.4.1 Electrolyte	3-6
3.5 Physical Design Criteria	3-7
3.5.1 Components	3-7
3.5.2 Use of Fire-Resistant Materials, Components, Wiring, and Cable	3-7
3.5.3 Containers	3-7
3.5.4 Covers	3-8
3.5.5 Terminals	3-8
3.5.6 Electrodes	3-9
3.5.7 Separators	3-9
3.5.8 Weight	3-9
3.5.9 Accessories	3-10
3.5.10 Markings	3-10
3.5.11 Packaging	3-11
3.5.12 Mounting Arrangements	3-11
3.5.13 Handling	3-11
3.6 Electrical Safety Criteria	3-12
3.7 Bonding and Grounding Criteria	3-12
3.8 Illumination Criteria for Network Equipment	3-12
3.9 Self-Heating and Surface Temperature	3-12
3.9.1 Self-Heating	3-12
3.9.2 Surface Temperature	3-13
3.10 Battery Management System (BMS) Criteria	3-13
3.10.1 Form-C Relay	3-14
3.10.2 Fail-Safe Design	3-14
3.10.3 Reliability	3-14
3.10.4 Features	3-15
3.10.5 Physical Design and Manufacturing	3-15
3.10.6 Status and Alarms	3-15
3.10.6.1 Status Indicators and Parameters	3-16
3.10.6.2 Alarms	3-17
3.10.7 Accuracy of Measurement	3-18

4 Safety Criteria

4.1 Acceptance Criteria	4-1
4.2 Precautions	4-1
4.3 Chemical Criteria	4-2
4.3.1 Gassing	4-2
4.3.2 Thermal Runaway	4-2
4.4 Status Indicators and Alarms	4-2
4.5 Environmental Criteria	4-2
4.5.1 Simulated Brush Fire	4-2
4.5.2 Simulated Telecom Environmental Cycles	4-4
4.5.3 Operating Altitude	4-7
4.5.4 Immersion (Flooded Conditions)	4-7
4.5.5 16-Foot Free-Fall Shock	4-9
4.5.6 Crush	4-10
4.6 Electrical Criteria	4-12
4.6.1 Overcharge	4-13
4.6.2 Short Circuit	4-15
4.6.2.1 External Short Circuit	4-15

4.6.2.2 Internal Short Circuit	4-17
4.6.3 Reverse Polarity	4-17
4.6.4 Overdischarge	4-18
4.6.5 Electromagnetic Compatibility (EMC) Criteria	4-20
4.6.5.1 System-Level ESD	4-21
4.6.5.2 System-Level Electrical Fast Transients (EFTs)	4-21
4.6.5.3 Electromagnetic Interference (EMI)	4-22
4.6.5.4 Noise on DC Bus	4-23
4.6.5.5 Lightning and AC Power Fault	4-23
4.6.5.6 Criteria for DC Power Port of Telecommunications Load Equipment	4-24
4.6.5.6.1 Input DC Voltage	4-24
4.6.5.6.2 Overvoltage (Steady State)	4-24
4.6.5.6.3 Overvoltage Transient	4-25
4.6.5.6.4 Protective Device Operation Transient	4-25
4.7 Mechanical Criteria	4-25
4.7.1 Handling Resistance Criteria	4-25
4.7.1.1 Packaged Shock Criterion	4-25
4.7.1.2 Unpackaged Shock Criteria	4-25
4.7.1.2.1 GR-63 Unpackaged Equipment Shock Criteria	4-25
4.7.2 Earthquake and Vibration	4-26
4.7.2.1 Earthquake	4-26
4.7.2.2 Transportation Vibration	4-26
4.7.2.3 Low-Level Vibration Resistance	4-26

5 Performance Criteria

5.1 Electrical Criteria	5-1
5.1.1 Float Voltage	5-1
5.1.2 Capacity	5-3
5.1.3 Charging	5-4
5.1.4 Re-Charge Time	5-5
5.1.5 Cycling	5-6
5.1.6 Discharge Rate	5-7
5.1.7 End of Discharge Voltage (EODV)	5-8
5.1.8 Shelf Life and Charge Retention	5-9
5.2 Environmental Criteria	5-10
5.2.1 Temperature and Humidity Shock During Transportation and Storage	5-10
5.2.2 Particulate Contamination and Corrosive Gas Resistance	5-11
5.2.3 Salt Fog Exposure	5-11
5.2.4 Cold Temperature Start	5-11
5.3 Service Life	5-12

Appendix A: References

A.1 Telcordia Documents	A-1
A.2 Other Referenced Documents, Books, and Materials	A-2
A.2.1 Miscellaneous	A-2
A.2.2 European Telecommunications Standards Institute (ETSI)	A-2
A.2.3 Underwriters Laboratories (UL) Documents	A-2
A.3 To Obtain Additional Reference Material	A-3

A.4 Telcordia Document Sets—Family of Requirements (FR) and Family of Documents (FD)	A-4
A.5 Reference Notes	A-5
A.5.1 Contact Customer Service	A-5
A.5.2 Order Documents Online From the Telcordia SuperStore	A-5
A.5.3 Web Sites for Generic Requirements Information	A-6
A.5.4 Licensing Agreements for Telcordia Documents	A-6

Appendix B: Acronyms

Appendix C: Glossary

Requirement-Object Index (ROI)

List of Figures

Figure 2-1	Charge Transfer and Cell Design	2-2
Figure 2-2	Sodium Nickel Chloride 48 V Battery Module Design	2-3
Figure 2-3	Internal Cells in a Sodium Nickel Chloride Sealed Battery Design	2-4
Figure 2-4	Battery Management System (BMS)	2-6
Figure 4-1	Simulated Telecom Environmental Cycles	4-6
Figure 4-2	Immersion Test	4-8
Figure 4-3	16-Foot Free-Fall Shock	4-10

List of Tables

Table 2-1	Common Re-chargeable Sodium Nickel Chloride Electrochemical Systems	2-2
Table 4-1	Safety Hazards and Acceptance Criteria	4-1
Table 4-2	GR-3108 (Table 6-1) Vibrational Stress Test Conditions from ETSI EN 300 019	4-28

