

Table of Contents

Preface	xi
1 Introduction	
1.1 Purpose and Scope	1-1
1.2 Target Audience	1-2
1.3 Structure and Use of This Document	1-2
1.4 Changes from Issue 3 of GR-326-CORE	1-3
1.5 Requirements Terminology	1-4
1.6 Requirement Labeling Conventions	1-4
1.6.1 Numbering of Requirement and Related Objects	1-4
1.6.2 Requirement, Conditional Requirement, and Objective Object Identification	1-5
2 General Information	
2.1 Description	2-1
2.2 Connector Applications	2-2
3 General Requirements	
3.1 Documentation	3-1
3.2 Packaging and Shipping	3-2
3.3 Design Features	3-2
3.3.1 Materials	3-2
3.3.2 Cleanability	3-4
3.4 Intermateability	3-4
3.4.1 Specific Intermateability Criteria	3-5
3.4.2 Latching Intermateability Requirements for Push-Pull Type Connectors	3-8
3.5 Product Marking	3-9
3.5.1 Keying	3-9
3.6 Safety	3-10
4 Connector Tests and Criteria	
4.1 Test Samples	4-2
4.1.1 Definitions	4-2
4.1.2 Population	4-3
4.2 Criteria	4-4
4.2.1 Overview of Optical Performance Criteria	4-4
4.2.2 Modifications and Conditions	4-5
4.2.2.1 Measurement Error	4-5
4.2.2.2 Jumper Cable Assembly Measurements	4-6
4.2.2.3 Reflectance Increase Criteria Applicability	4-6
4.2.2.4 Reflectance Criteria Applicability	4-7
4.2.2.5 Handling of Nonconformance	4-7
4.2.3 Damage Criteria	4-8
4.3 Cleaning Procedures	4-8
4.3.1 Cleaning Procedure A	4-8

- 4.3.2 Cleaning Procedure B 4-9
- 4.4 Statement of Criteria 4-9
 - 4.4.1 Performance of New Product 4-9
 - 4.4.2 Temperature, Humidity, and Condensation Tests 4-11
 - 4.4.2.1 Thermal Age Test 4-12
 - 4.4.2.2 Thermal Cycle Test 4-13
 - 4.4.2.3 Humidity Aging Test 4-14
 - 4.4.2.4 Humidity/Condensation Cycling Test 4-15
 - 4.4.2.5 Dry-Out Step 4-16
 - 4.4.2.6 Post-Condensation Thermal Cycle Test 4-16
 - 4.4.3 Mechanical Tests 4-17
 - 4.4.3.1 Vibration Test 4-17
 - 4.4.3.2 Flex Test 4-18
 - 4.4.3.3 Twist Test 4-18
 - 4.4.3.4 Proof Test 4-19
 - 4.4.3.5 Transmission With Applied Tensile Load 4-21
 - 4.4.3.6 Equilibrium Tensile Loading 4-24
 - 4.4.3.7 Impact Test 4-24
 - 4.4.3.8 Durability 4-25
 - 4.4.3.9 End of Test Criteria 4-27
 - 4.4.4 Materials and Environmental Tests 4-28
 - 4.4.4.1 Dust Test 4-28
 - 4.4.4.2 Adhesive Testing 4-32
 - 4.4.4.3 Airborne Contaminants 4-32
 - 4.4.4.4 Salt Spray 4-34
 - 4.4.4.5 Immersion/Corrosion Test 4-36
 - 4.4.4.6 Groundwater Immersion 4-37
 - 4.4.5 Geometry Requirements 4-38
 - 4.4.5.1 Ferrule Endface Geometry for Non-Angled Physical Contact Connectors 4-38
 - 4.4.5.2 Endface Geometry Requirements for Angled Physical Contact (APC) Connectors 4-40
 - 4.4.5.3 Discussion of Values Presented in IEC 61755-3-1 and IEC 61755-3-2 4-41
 - 4.4.5.3.1 IEC Criteria for UPC Connectors 4-42
 - 4.4.5.3.2 IEC Criteria for APC Connectors 4-43
 - 4.4.5.4 Endface Geometry Measurement Areas 4-44
 - 4.4.6 Connector Installation 4-45

5 Facilities for Product Testing

- 5.1 Ambient Laboratory Conditions 5-1
- 5.2 Optical Measurements 5-1
 - 5.2.1 Transmission Measurement Facility 5-2
 - 5.2.1.1 Measurement of Optical Loss with a Transmission Measurement Facility 5-3
 - 5.2.1.2 Measurement of Reflectance with a Transmission Measurement Facility 5-4
 - 5.2.2 OTDR Measurement Facility 5-5
 - 5.2.2.1 Measurement of Optical Loss with an OTDR 5-7
 - 5.2.2.2 Measurement of Reflectance with an OTDR 5-8

5.3 Product Test Facilities	5-9
5.3.1 Environmental Tests	5-9
5.3.2 Vibration Test	5-9
5.3.3 Jumper Tension Test Fixture	5-10
5.3.4 Durability Test	5-11
5.3.5 Impact Test	5-11
5.3.6 Adhesive Test	5-12
5.3.7 Dust Test	5-13
5.3.8 Groundwater Immersion Test	5-14
6 Service Life Tests	
6.1 Service Life Tests	6-1
6.2 New Product Measurements	6-2
6.3 Tensile Tests	6-2
7 Extended Service Life Tests	
7.1 Description of Extended Service Life Tests	7-1
7.2 Extended Service Life Test Samples	7-2
7.2.1 Type of Sample	7-2
7.2.2 Sample Size	7-2
7.3 Criteria to be Applied to Extended Service Life Tests	7-3
8 Reliability Assurance Program	
8.1 Reliability Testing	8-1
8.2 Manufacturing and Process Control	8-1
8.2.1 Materials and Components	8-1
8.2.1.1 Quality Levels	8-2
8.2.1.2 Materials and Components Requirements	8-2
8.2.1.2.1 Vendor Qualification	8-2
8.2.1.2.2 Part Qualification	8-3
8.2.1.2.3 Qualification of Epoxies	8-4
8.2.1.2.4 Raw Material Specifications	8-4
8.2.1.2.5 Determination of Acceptability of Raw Materials	8-4
8.2.1.2.6 Reliability Controls	8-6
8.2.1.2.7 Feedback and Corrective Action	8-6
8.2.2 Physical Design	8-6
8.2.2.1 Contact of Dissimilar Metals	8-7
8.2.2.2 Flammability	8-7
8.2.3 Manufacturing and Assembly	8-7
8.2.3.1 Training	8-8
8.2.3.2 Product Documentation	8-8
8.2.3.3 Product Inspection	8-9
8.2.3.3.1 Segregation of Nonconforming Material	8-9
8.2.3.3.2 Storage and Handling of the Product	8-9
8.2.3.4 Product Assembly	8-10
8.2.3.5 Product Traceability	8-10
8.2.3.6 Customer Complaints	8-10
8.2.3.7 Field Trials	8-11
8.2.3.8 Statistical Process Control and Quality Data	8-11

- 8.2.4 Manufacturer Testing 8-12
 - 8.2.4.1 Test Documentation 8-12
 - 8.2.4.2 In-Process Testing 8-13
 - 8.2.4.3 Finished Goods Testing 8-13
 - 8.2.4.3.1 Test Data 8-13
 - 8.2.4.3.2 Connector Adapters 8-14
 - 8.2.4.3.3 Replacement of Testing Parts 8-14
 - 8.2.4.4 Calibration 8-15
 - 8.2.4.5 Product Qualification Testing 8-16
 - 8.2.4.5.1 Repeat of Initial Qualification Testing 8-16
 - 8.2.4.5.2 Periodic Requalification Test Schedule 8-17

9 Requalification for Product/Manufacturing Changes

Appendix A: References

- A.1 Telcordia Documents A-1
- A.2 Non-Telcordia Reference Documents A-1
- A.3 Websites for Non-Telcordia Reference Documents A-4
- A.4 Telcordia Reference Notes A-4

Appendix B: Glossary

- B.1 Acronyms B-1
- B.2 Definition of Terms B-2

Requirement-Object Index

List of Figures

Figure 2-1	Sample Connector Assembly with One Plug Removed	2-1
Figure 3-1	SC Connector Plug	3-5
Figure 3-2	FC Connector Plug	3-6
Figure 3-3	SC Connector Adapter Reference Plane	3-6
Figure 3-4	FC Connector Adapter Reference Plane	3-7
Figure 3-5	The Latch Spacing in SC Adapters	3-7
Figure 4-1	Pigtail Assembly	4-2
Figure 4-2	Jumper Cable Assembly	4-3
Figure 4-3	Thermal Cycle Profile	4-13
Figure 4-4	Temperature/Humidity Profile for Humidity/Condensation Test	4-15
Figure 4-5	Dust Test Flow Chart	4-30
Figure 4-6	Ferrule Endface Geometry	4-39
Figure 4-7	The Maximum Allowed Fiber Undercut for a Ferrule Radius of Curvature Between 7 mm and 25 mm	4-39
Figure 4-8	Dome Offset for APC Connectors	4-41
Figure 4-9	The IEC-61755-3-1 Maximum Allowable Fiber Undercut for a 2.5-mm Ferrule	4-43
Figure 4-10	The Connector Endface Geometry Measurement Areas	4-44
Figure 4-11	Connector Installation Test	4-46
Figure 5-1	Transmission Measurement Facility	5-2
Figure 5-2	Cutback Measurement Location (Transmission)	5-4
Figure 5-3	OTDR Measurement Facility	5-6
Figure 5-4	OTDR Response to a Connector	5-7
Figure 5-5	Cutback Measurement Location (OTDR)	5-8
Figure 5-6	Jumper Test Facility	5-10
Figure 5-7	Impact Test Facility	5-11
Figure 5-8	Adhesive Test Facility	5-12
Figure 5-9	Dust Exposure Sample Groups	5-13
Figure 5-10	Dust Test Facility	5-14

List of Tables

Table 1-1	Changes from GR-326-CORE, Issue 3 to Issue 4	1-3
Table 3-1	Reflectance Color Code	3-9
Table 4-1	List of Connector Tests	4-1
Table 4-2	Summary of Optical Performance Criteria: Loss	4-4
Table 4-3	Summary of Optical Performance Criteria: Reflectance	4-5
Table 4-4	Test Conditions for the Thermal Age Test	4-12
Table 4-5	Test Conditions for the Thermal Cycle Test	4-13
Table 4-6	Test Conditions for the Humidity Aging Test	4-14
Table 4-7	Test Conditions for the Humidity/Condensation Cycling Test	4-15
Table 4-8	Number of Turns for Twist Test	4-19
Table 4-9	Tensile Loads for Transmission with Applied Load	4-21
Table 4-10	Small Form Factor Connector Tensile Loads for Transmission with Applied Load	4-22
Table 4-11	Airborne Contaminants Test Gases	4-33
Table 4-12	Operating Parameters for the Salt Spray Test	4-34
Table 6-1	Service Life Tests	6-1
Table 7-1	Extended Service Life Tests	7-1
Table 7-2	Lot Tolerance Percent Defective Table	7-3
Table 8-1	Definition of Quality Levels	8-3
Table 9-1	Suggested Test Plan for Various Product Change Scenarios	9-2
Table 9-2	Test Plan #1	9-3
Table 9-3	Test Plan #2	9-4
Table 9-4	Test Plan #3	9-5