

# Table of Contents

## 1 Introduction

|   |     |
|---|-----|
| 1.1 Reason for Reissue . . . . .                      | 1-1 |
| 1.2 Structure and Use of This Document . . . . .      | 1-2 |
| 1.3 Requirements Terminology . . . . .                | 1-2 |
| 1.4 Requirement Object Labeling Conventions . . . . . | 1-3 |
| 1.4.1 Numbering of Requirement Objects . . . . .      | 1-3 |
| 1.4.2 Requirement Object Identification . . . . .     | 1-4 |

## 2 Synchronization in Telecommunications Applications

|   |      |
|---|------|
| 2.1 Synchronization Definitions . . . . .                                   | 2-1  |
| 2.1.1 Frequency Synchronization . . . . .                                   | 2-1  |
| 2.1.2 Phase Synchronization . . . . .                                       | 2-1  |
| 2.2 The Need for Network Synchronization . . . . .                          | 2-2  |
| 2.2.1 Switched DS0 Applications . . . . .                                   | 2-2  |
| 2.2.2 DS0A Applications . . . . .   | 2-3  |
| 2.2.3 DS1 Signal Retiming Applications . . . . .                            | 2-4  |
| 2.2.4 DS <sub>n</sub> Transport Applications . . . . .                      | 2-5  |
| 2.2.5 Voice Compression Applications . . . . .                              | 2-5  |
| 2.2.6 IPTV Applications . . . . .   | 2-6  |
| 2.2.7 Mobile Wireless Applications . . . . .                                | 2-6  |
| 2.2.7.1 Frequency Synchronization in Mobile Wireless Applications . . . . . | 2-6  |
| 2.2.7.2 Phase Synchronization in Mobile Wireless Applications . . . . .     | 2-6  |
| 2.2.7.2.1 Phase Synchronization in CDMA Applications . . . . .              | 2-6  |
| 2.2.7.2.2 Phase Synchronization in TDD Wireless Applications . . . . .      | 2-7  |
| 2.2.7.2.3 E911 Geo-Location Applications . . . . .                          | 2-7  |
| 2.2.8 Synchronization Distribution Applications . . . . .                   | 2-8  |
| 2.2.9 ToD Synchronization for Network Operations . . . . .                  | 2-8  |
| 2.3 NE Timing Modes . . . . .   | 2-8  |
| 2.4 Signals Used for Synchronization . . . . .                              | 2-10 |
| 2.4.1 Frequency-Specific Signals . . . . .                                  | 2-10 |
| 2.4.1.1 DS1 Signals . . . . .   | 2-10 |
| 2.4.1.2 SONET Signals . . . . .   | 2-11 |
| 2.4.1.3 Synchronous Ethernet . . . . .                                      | 2-13 |
| 2.4.1.4 Synchronization Status Messages . . . . .                           | 2-14 |
| 2.4.2 Signals for Both Frequency and Phase . . . . .                        | 2-15 |
| 2.4.3 ToD Signals and Protocols . . . . .                                   | 2-15 |
| 2.4.3.1 PTP . . . . .   | 2-16 |
| 2.4.3.1.1 PTPv2 Accuracy Considerations . . . . .                           | 2-18 |
| 2.4.3.1.2 Telecommunications Applications and Profiles . . . . .            | 2-19 |
| 2.4.3.2 NTP . . . . .   | 2-20 |
| 2.4.3.3 DTI . . . . .   | 2-21 |
| 2.4.3.4 IRIG Serial Time Codes . . . . .                                    | 2-23 |
| 2.4.3.5 ASCII-Based Time Codes and 1 pps Signals . . . . .                  | 2-24 |
| 2.4.3.5.1 NTP Type 4 . . . . .  | 2-25 |
| 2.4.3.5.2 Cisco Serial ToD Format . . . . .                                 | 2-25 |
| 2.4.3.6 PTTI . . . . .  | 2-26 |

|          |   |      |
|----------|---|------|
| 2.5      | Slips . . . . .   | 2-27 |
| 2.5.1    | Controlled Slips . . . . .  | 2-27 |
| 2.5.2    | Uncontrolled Slips . . . . .  | 2-28 |
| 2.6      | Phase Variations . . . . .  | 2-28 |
| 2.6.1    | Jitter . . . . .  | 2-29 |
| 2.6.2    | Wander . . . . .  | 2-29 |
| 2.6.3    | Phase Transients . . . . .  | 2-30 |
| 2.7      | Timing Loops . . . . .  | 2-30 |
| 2.8      | Circuit Emulation Services . . . . .                                      | 2-30 |
| 2.9      | Additional Information . . . . .  | 2-32 |
| 2.9.1    | On Frequency Synchronization Methods at Wireless Base Stations . . . . .  | 2-32 |
| 2.9.2    | On Phase Sync Methods at Wireless Base Stations . . . . .                 | 2-32 |
| 2.9.3    | On the Use of SONET-Transported DS1s for Timing Purposes . . . . .        | 2-32 |
| 2.9.4    | On Inter-Site Phase Synchronization . . . . .                             | 2-33 |
| 2.9.5    | On Additional PTP Profiles . . . . .                                      | 2-33 |
| 2.9.6    | On Mobile Wireless . . . . .  | 2-33 |
| <br>     |   |      |
| <b>3</b> | <b>The Stratum Hierarchy</b>  |      |
| 3.1      | Performance Characteristics . . . . .                                     | 3-1  |
| 3.2      | Stratum Levels . . . . .  | 3-2  |
| 3.2.1    | Stratum 1 and PRS . . . . .   | 3-2  |
| 3.2.1.1  | PRS Technologies . . . . .  | 3-3  |
| 3.2.1.2  | PRS Classes . . . . .   | 3-3  |
| 3.2.2    | Stratum 2 . . . . .   | 3-4  |
| 3.2.3    | Stratum 3E . . . . .  | 3-4  |
| 3.2.4    | Stratum 3 . . . . .   | 3-5  |
| 3.2.5    | SMC . . . . .   | 3-5  |
| 3.2.6    | Stratum 4 and 4E . . . . .  | 3-5  |
| <br>     |   |      |
| <b>4</b> | <b>Synchronization Distribution Strategies</b>                            |      |
| 4.1      | Hierarchical Distribution . . . . .                                       | 4-1  |
| 4.1.1    | Traditional Frequency and Phase Distribution . . . . .                    | 4-1  |
| 4.1.2    | ToD Distribution . . . . .  | 4-3  |
| 4.2      | Intra-Site Synchronization Distribution – The BITS Plan . . . . .         | 4-4  |
| 4.2.1    | Recommended BITS Implementation . . . . .                                 | 4-5  |
| 4.2.1.1  | ToD Distribution Considerations . . . . .                                 | 4-7  |
| 4.2.1.2  | Capacity Considerations . . . . .   | 4-9  |
| 4.2.2    | Other Possible BITS Implementations . . . . .                             | 4-11 |
| 4.2.2.1  | Conceptual BITS . . . . .   | 4-11 |
| 4.2.2.2  | Redundant BITS . . . . .  | 4-11 |
| 4.2.3    | Integration of Nonconforming NEs Into the BITS Plan . . . . .             | 4-12 |
| 4.3      | Synchronization Network Rearrangement and Timing Loop Avoidance . . . . . | 4-13 |
| 4.3.1    | Inherently Loop-Free Synchronization Network Design . . . . .             | 4-13 |
| 4.3.2    | Synchronization Network Design for Networks Utilizing SSMS . . . . .      | 4-15 |
| 4.3.3    | Real-Time OS Management of Network to Avoid Timing Loops . . . . .        | 4-15 |
| <br>     |   |      |
| <b>5</b> | <b>Engineering the Synchronization Network</b>                            |      |
| 5.1      | PRS Deployment . . . . .  | 5-2  |
| 5.1.1    | Historical Perspective and Economic Considerations . . . . .              | 5-2  |

- 5.1.2 Minimal PRS Deployment . . . . . 5-3
- 5.1.3 PRS at All Stratum 2 BITS Clock Sites . . . . . 5-4
- 5.1.4 PRS at COs with Multiple Rings . . . . . 5-4
- 5.1.5 PRS In Every Other CO . . . . . 5-5
- 5.1.6 PRS in Every CO . . . . . 5-6
- 5.1.7 PRS at Every Timing Point . . . . . 5-6
- 5.1.8 PRS Site Redundancy . . . . . 5-7
- 5.2 Stratum Clock Deployment . . . . . 5-8
  - 5.2.1 Holdover Performance and Wander Filtering . . . . . 5-8
  - 5.2.2 Hierarchical Position . . . . . 5-9
  - 5.2.3 SSMS and Hierarchical Distribution . . . . . 5-10
- 5.3 Intra-Site Synchronization Network Design . . . . . 5-10
  - 5.3.1 BITS Output Diversity . . . . . 5-10
  - 5.3.2 CC Output Polarity Considerations . . . . . 5-10
- 5.4 Synchronization Distribution Network Design . . . . . 5-11
  - 5.4.1 Facilities . . . . . 5-11
  - 5.4.2 Timing Distribution in Access Networks . . . . . 5-12
    - 5.4.2.1 Timing Distribution In Access Networks with SSMS . . . . . 5-13
    - 5.4.2.2 Timing Distribution in Access Networks Without SSMS . . . . . 5-16
  - 5.4.3 Interoffice Timing Distribution . . . . . 5-18
    - 5.4.3.1 Interoffice Timing Distribution with SSMS . . . . . 5-19
    - 5.4.3.2 Interoffice Timing Distribution without SSMS . . . . . 5-23
    - 5.4.3.3 Additional Considerations . . . . . 5-23
  - 5.4.4 PTPv2 Network Configurations . . . . . 5-24

**6 Synchronization Network Planning and Operation**

- 6.1 Planning the Synchronization Network . . . . . 6-1
- 6.2 Implementing the Synchronization Network . . . . . 6-1
- 6.3 Maintaining the Synchronization Network . . . . . 6-1
- 6.4 Miscellaneous Synchronization Activities . . . . . 6-2

**7 Synchronization Network Operations**

- 7.1 NE to OS Operations Interfaces . . . . . 7-1
- 7.2 Provisioning . . . . . 7-1
  - 7.2.1 Configuring NE Options . . . . . 7-1
  - 7.2.2 Tracking BITS Resources . . . . . 7-2
  - 7.2.3 Tracking Synchronization Systems . . . . . 7-2
- 7.3 Performance Monitoring . . . . . 7-2
  - 7.3.1 Slip Performance Monitoring . . . . . 7-2
  - 7.3.2 Pointer Justification Count Performance Monitoring . . . . . 7-3
  - 7.3.3 Synchronization Performance Monitoring . . . . . 7-3
  - 7.3.4 BITS Clock-Based PM . . . . . 7-4
- 7.4 Alarms and Maintenance . . . . . 7-7
  - 7.4.1 Detection of Impaired Synchronization . . . . . 7-7
    - 7.4.1.1 BITS Indications of Sync Impairments . . . . . 7-7
    - 7.4.1.2 Slave Clock Indication of Sync Impairments . . . . . 7-8
    - 7.4.1.3 Slip Alarms . . . . . 7-8
    - 7.4.1.4 Pointer Adjustment Alarms . . . . . 7-8
    - 7.4.1.5 Synchronization Performance Monitoring Alarms . . . . . 7-8
    - 7.4.1.6 Alarm Correlation . . . . . 7-8

|  |      |
|--|------|
| 7.4.2 Restoring the Network . . . . .  | 7–9  |
| 7.4.2.1 Restoration of Inter-Building Failures . . . . .                                       | 7–9  |
| 7.4.2.2 Restoration of Intra-Building Failures . . . . .                                       | 7–9  |
| <b>8 Synchronization Interfaces Between Networks</b>   |      |
| 8.1 Modes of Operation at Network Interfaces . . . . .   | 8–1  |
| 8.1.1 Plesiochronous Operation . . . . .   | 8–1  |
| 8.1.2 Provide/Receive PRS Traceable Timing . . . . .   | 8–2  |
| 8.1.2.1 Special Engineering and Synchronization Status Messages . . . . .                      | 8–2  |
| 8.1.2.2 Special Engineering Example – Derived DS1 from a SONET NE . . . . .                    | 8–2  |
| 8.1.2.3 Special Engineering Example – Retiming Slip Buffer . . . . .                           | 8–3  |
| 8.1.2.4 Special Engineering Example – PRS . . . . .  | 8–4  |
| 8.1.2.5 Special Engineering Example – Asynchronous Facilities . . . . .                        | 8–4  |
| 8.1.3 Asynchronous Operation . . . . .   | 8–4  |
| 8.1.4 DS1 Timing Transparent Operation . . . . .   | 8–4  |
| 8.1.5 ToD Transport . . . . .  | 8–5  |
| 8.2 Synchronization Status Messages at Network Interfaces . . . . .                            | 8–6  |
| 8.3 Performance Criteria for Synchronization References . . . . .                              | 8–7  |
| 8.3.1 Synchronization Performance Parameters . . . . .   | 8–7  |
| 8.3.2 Synchronization Performance at Customer Interfaces . . . . .                             | 8–9  |
| <b>9 Synchronization Testing</b>   |      |
| 9.1 First Application Test . . . . .   | 9–1  |
| 9.2 Equipment Installation Test . . . . .  | 9–1  |
| 9.3 Network Performance Test . . . . .   | 9–2  |
| 9.4 Generic Synchronization Test Setup . . . . .   | 9–2  |
| <b>10 Synchronization Criteria for Network Elements</b>  |      |
| 10.1 PRS Synchronization Criteria . . . . .  | 10–1 |
| 10.2 DS1 Synchronization Criteria . . . . .  | 10–1 |
| 10.3 Composite Clock and DS0A Synchronization Criteria . . . . .                               | 10–2 |
| 10.4 SONET NE Synchronization Criteria . . . . .   | 10–2 |
| 10.5 Synchronization Criteria for Other Technologies and Services . . . . .                    | 10–3 |
| 10.5.1 Traditional Frequency Synchronization . . . . .   | 10–3 |
| 10.5.2 Packet-Based Synchronization . . . . .  | 10–4 |
| <b>Appendix A: Slip Calculations</b>   |      |
| A.1 Basic Calculations . . . . .   | A–1  |
| <b>Appendix B: References</b>  |      |
| B.1 Telcordia Documents . . . . .  | B–1  |
| B.1.1 Generic Requirements (GRs) . . . . .   | B–1  |
| B.1.2 Technical References (TRs) and Technical Advisories (TAs) . . . . .                      | B–2  |
| B.2 Non-Telcordia Documents . . . . .  | B–2  |
| B.3 To Obtain Additional Reference Material . . . . .  | B–4  |
| B.4 Telcordia Document Sets—Family of Requirements (FR) and Family of Documents (FD) . . . . . | B–5  |
| B.5 Telcordia Reference Notes . . . . .  | B–6  |

B.5.1 Contact Telcordia Customer Service . . . . . B-6  
B.5.2 Order Documents Online From the Telcordia SuperStore . . . . . B-7  
B.5.3 Web Sites for Generic Requirements Information . . . . . B-8  
B.5.4 Licensing Agreements for Telcordia Documents . . . . . B-8

**Appendix C: Acronyms**

## List of Figures

|             |  |      |
|-------------|--|------|
| Figure 2-1  | DS0A and Composite Clock Timing . . . . .  | 2-4  |
| Figure 2-2  | External Timing Example (SONET ADM) . . . . .                                    | 2-9  |
| Figure 2-3  | Line Timing Example (SONET ADM) . . . . .  | 2-9  |
| Figure 2-4  | Through Timing Example (SONET Regenerator) . . . . .                             | 2-9  |
| Figure 2-5  | Positive STS Pointer Adjustment Operation (Increment) . . . . .                  | 2-13 |
| Figure 2-6  | SONET NE and BITS Interactions with SSMs . . . . .                               | 2-15 |
| Figure 2-7  | CBR Transport in ATM Networks . . . . .  | 2-31 |
| Figure 4-1  | Hierarchical Timing Distribution Example . . . . .                               | 4-2  |
| Figure 4-2  | Example of an Allowed Exception to Hierarchical Timing<br>Distribution . . . . . | 4-3  |
| Figure 4-3  | Recommended BITS Implementation with DS1 Timing<br>Distribution . . . . .        | 4-6  |
| Figure 4-4  | BITS Implementation Example with SONET Timing Distribution . . . . .             | 4-7  |
| Figure 4-5  | Recommended Parallel Configuration for Subtending TSGs . . . . .                 | 4-10 |
| Figure 4-6  | Serial Configuration NOT Recommended for Subtending TSGs . . . . .               | 4-10 |
| Figure 4-7  | Conceptual BITS - No Longer Recommended . . . . .                                | 4-11 |
| Figure 4-8  | Substrata Example - No Timing Loops . . . . .                                    | 4-14 |
| Figure 4-9  | Substrata Example - Timing Loop Identified . . . . .                             | 4-15 |
| Figure 5-1  | PRS In Every Other CO - Linear Chain Example . . . . .                           | 5-5  |
| Figure 5-2  | PRS In Every Other CO - Ring Example . . . . .                                   | 5-6  |
| Figure 5-3  | PRS Site Redundancy Example . . . . .  | 5-7  |
| Figure 5-4  | Rearrangement Example in SONET Access Ring with SSMs . . . . .                   | 5-15 |
| Figure 5-5  | Timing Loop Formation in a SONET Access Ring without SSMs . . . . .              | 5-17 |
| Figure 5-6  | SONET Access Ring without SSMs - Failure Scenario 1 . . . . .                    | 5-17 |
| Figure 5-7  | SONET Access Ring without SSMs - Failure Scenario 2 . . . . .                    | 5-18 |
| Figure 5-8  | Rearrangement Example in SONET Access Ring with SSMs . . . . .                   | 5-21 |
| Figure 5-9  | Rearrangement Example in SONET Access Ring with<br>SSMs (cont.) . . . . .        | 5-22 |
| Figure 5-10 | Example of the Mesh Nature of Timing Distribution Networks . . . . .             | 5-24 |
| Figure 5-11 | Example Network for Frequency Distribution According to<br>G.8265.1 . . . . .    | 5-25 |
| Figure 5-12 | Example Network for ToD Distribution According to G.8275.1 . . . . .             | 5-26 |
| Figure 5-13 | Example of ToD Distribution to Non-Interacting Groups of NEs . . . . .           | 5-28 |
| Figure 7-1  | Monitoring with a PRS in Every Other Office . . . . .                            | 7-5  |
| Figure 7-2  | Site Redundancy with PRS Pairs . . . . .   | 7-5  |
| Figure 7-3  | Back-Up for PRS Pairs – Not Recommended . . . . .                                | 7-6  |
| Figure 7-4  | Site Redundancy with PRSs in Triplicate . . . . .                                | 7-6  |
| Figure 7-5  | Back-up Using PRSs in Triplicate . . . . .                                       | 7-7  |
| Figure 8-1  | Plesiochronous Operation Example . . . . .                                       | 8-1  |
| Figure 8-2  | Retiming Slip Buffer . . . . .   | 8-3  |
| Figure 8-3  | Example of Distributed PTPv2 Transparent Clock Function . . . . .                | 8-6  |
| Figure 8-4  | MTIE Specification for Synchronization Reference Signals . . . . .               | 8-8  |
| Figure 8-5  | Time Deviation Specification for Synchronization Reference<br>Signals . . . . .  | 8-8  |
| Figure 9-1  | Generic Synchronization Test Configuration . . . . .                             | 9-2  |
| Figure 9-2  | Telcordia Synchronization Test Configuration . . . . .                           | 9-3  |

## List of Tables

|           |  |      |
|-----------|--|------|
| Table 2-1 | PTPv2 Option Usage . . . . .                                   | 2-20 |
| Table 3-1 | Stratum Clock Criteria Summary . . . . .                       | 3-2  |
| Table 5-1 | Worst-Case Slip Performance in Holdover . . . . .              | 5-9  |
| Table A-1 | Values Associated with Slip Performance Calculations . . . . . | A-2  |

