

Table of Contents

Preface	xiii
1 Introduction	
1.1 Relationship to Other Telcordia Technical Documents	1-1
1.2 Reason for Reissue	1-2
1.3 Changes from Issue 1 to Issue 2	1-2
1.4 Scope of Document	1-3
1.5 Overview of Surveillance-Based Maintenance	1-4
1.6 Telecommunications Management Network (TMN) Perspective	1-5
1.7 Organization of Document	1-6
1.8 Requirements Terminology	1-7
1.9 Requirement Labeling Conventions	1-7
1.9.1 Numbering of Requirement and Related Objects	1-7
1.9.2 Requirement, Conditional Requirement, and Objective Identification	1-8
2 Criteria Common to All NEs	
2.1 Trouble Detection	2-1
2.1.1 Status Monitoring	2-1
2.1.2 Performance Monitoring	2-2
2.1.2.1 Performance Counters	2-2
2.1.2.2 Analog Measurements	2-3
2.1.2.2.1 Recording Analog Measurements	2-4
2.1.2.2.2 Exception Reporting for Analog Measurements	2-4
2.1.2.3 Performance Monitoring Controls	2-5
2.1.2.3.1 Disabling Performance Monitoring	2-5
2.1.2.3.2 Inhibition of Performance Monitoring Messages	2-5
2.1.2.3.3 Start of Day for Performance Monitoring	2-6
2.1.2.4 Grade of Service	2-7
2.2 Trouble Notification	2-8
2.2.1 Types of Trouble Notifications	2-8
2.2.2 General Message Criteria for Trouble Notifications	2-9
2.2.2.1 Automatic Output Message Criteria	2-9
2.2.2.1.1 <i>Single Indication of Trouble</i>	2-10
2.2.2.1.2 <i>Time Stamping and Trouble Identification</i>	2-10
2.2.2.1.3 <i>Inhibition of Automatic Messages</i>	2-11
2.2.2.2 Criteria for Response to Input Commands	2-11
2.2.3 Alarmed Trouble Notification Severity	2-12
2.2.3.1 Configuration of Condition Type Severity	2-12
2.2.3.1.1 Equipment and Signal Failures	2-12
2.2.3.1.2 Environmental Conditions	2-13
2.2.3.1.3 Transient Conditions	2-14
2.2.3.2 Priority of Notification by Alarm Level	2-15
2.2.3.3 NE Display — Visual Assignments and Meanings	2-16
2.2.3.4 Clearing of Alarmed Conditions	2-16
2.2.4 Alarm Report Control	2-16
2.2.4.1 Qualified Inhibition	2-20

2.2.4.2	Timed Inhibition	2-21
2.2.4.3	Indefinite Inhibition	2-22
2.2.4.4	Entering ARC	2-22
2.2.4.5	Exiting ARC	2-23
2.2.5	Central Office Alarm Subsystem	2-24
2.2.5.1	Central Office Visual Alarms	2-25
2.2.5.2	Central Office Audible Alarms	2-25
2.2.5.3	Central Office Audible/Visual Alarm Cut-Off	2-26
2.2.6	Alarm Indication Signal	2-26
2.2.7	Synchronization	2-27
2.3	Service Recovery	2-27
2.3.1	Automatic Service Recovery	2-27
2.3.1.1	Automatic Restoration	2-28
2.3.1.2	Automatic Protection Switching	2-28
2.3.2	Manual Service Recovery	2-30
2.4	Trouble Verification	2-30
2.4.1	Current Problem List	2-30
2.4.2	Trouble Log	2-31
2.4.3	Message Log	2-31
2.5	Trouble Isolation	2-32
2.5.1	Manual Maintenance Actions	2-33
2.6	Repair	2-33
2.7	Maintenance Person — NE Interface	2-34
2.7.1	Centralization of Maintenance Functions	2-34
2.7.2	Forced Commands	2-35
2.7.3	Command Error Handling	2-36
2.7.3.1	Command Denial	2-36
2.7.3.2	Command Failure	2-38
2.7.4	Environmental Controls	2-38
2.7.5	General Controls	2-39
2.7.5.1	System Initialization	2-39
2.7.5.2	Time-of-Day	2-40
2.7.6	Common Physical Control/Status Interface Criteria	2-40
2.7.7	Maintenance Documentation	2-41

3 Criteria for Switching System NEs

3.1	Trouble Detection	3-1
3.1.1	Trouble Detection Tests	3-1
3.1.2	Other System Strategies for Trouble Detection	3-8
3.1.3	Trouble Detection Inhibition	3-9
3.2	Trouble Notification	3-9
3.2.1	General Message Criteria for Trouble Notifications	3-10
3.2.1.1	Automatic Output Message Criteria	3-10
3.2.1.2	Criteria for Input Commands	3-11
3.2.2	Alarmed Trouble Notification Severity	3-11
3.2.2.1	Reporting of Notifications for Internal Failures	3-12
3.2.2.2	Single Indication of Alarmed Troubles	3-12
3.2.2.3	Hourly Status Message Criteria	3-12
3.2.2.4	Alarm Inhibition	3-13
3.2.3	CO Alarm Subsystem	3-13

- 3.2.3.1 Other Audible/Visible Alarms 3-13
- 3.2.3.2 CO Alarm Release Controls 3-14
- 3.2.3.3 Alarm Transfer 3-14
- 3.2.3.4 Building Alarm Hourly Status Message 3-14
- 3.3 Service Recovery 3-15
 - 3.3.1 Automatic Service Recovery 3-15
 - 3.3.1.1 Conditions that Generate Alarms 3-15
 - 3.3.1.2 Treatment for Call Completions 3-16
 - 3.3.1.3 Minimizing Effects on Customers and Subsequent Usage 3-16
 - 3.3.1.4 Automatic Treatment of Errors and Faults 3-16
 - 3.3.1.5 Automatic Escalating Levels of Switching System Initializations 3-17
 - 3.3.1.6 Service Degradation Containment 3-17
 - 3.3.2 Manual Service Recovery 3-17
 - 3.3.3 Hardware Redundancy 3-18
- 3.4 Trouble Verification 3-18
 - 3.4.1 Periodic Automatic Verification 3-19
 - 3.4.2 Demand Verification Capabilities 3-19
- 3.5 Trouble Isolation 3-19
 - 3.5.1 Trouble Isolation Procedure 3-20
 - 3.5.2 Fuse Trouble Isolation 3-20
 - 3.5.3 Diagnostic Raw Data Report 3-20
 - 3.5.4 Error Analysis 3-21
 - 3.5.4.1 Automatic OOS State Transitioning 3-21
 - 3.5.4.2 Discrimination Between Voice/Data and Signaling Errors 3-22
- 3.6 Repair 3-22
 - 3.6.1 OOS State Criteria 3-22
 - 3.6.2 Assurance of OOS before Repair 3-22
 - 3.6.3 Power Removal before Repair 3-23
 - 3.6.4 Physical Repair 3-23
 - 3.6.5 Restoration of Equipment to Active or Standby State 3-24
 - 3.6.6 Mean Time to Repair 3-24
- 3.7 Maintenance Person — NE Interface for Switching NEs 3-25
 - 3.7.1 Switching System Centralization of Maintenance Functions 3-25
 - 3.7.2 Switching System Physical Control/Status Interface Criteria 3-25
 - 3.7.2.1 Switching System Initialization Control 3-26
 - 3.7.2.2 Status Indicators 3-26
 - 3.7.2.3 Remote Test Capability 3-27
 - 3.7.2.4 Controls and Displays Test Capability 3-27
 - 3.7.2.5 Portable Test Equipment 3-28
 - 3.7.2.6 Testing and Calibration of Test Circuits 3-28
 - 3.7.3 Switching System Maintenance Messages Interface 3-28
 - 3.7.4 Changes and Verifications to Switching System Software 3-28
 - 3.7.5 Voice Communications 3-29
 - 3.7.6 Extended Maintenance Capabilities (Beltline) 3-29
 - 3.7.7 Physical Design for Maintenance 3-29
 - 3.7.7.1 Engineering of Controls and Indicators 3-30
 - 3.7.7.2 Interlocks to Prevent Errors 3-30
 - 3.7.7.3 Protection Against Wrong Circuit Pack Insertion 3-30
 - 3.7.7.4 Hazard Warnings 3-30
 - 3.7.7.5 Equipment Aisle Design for Maintenance 3-31

4 Criteria for Circuit Switching NEs

4.1	Trouble Detection	4-1
4.2	Trouble Notification	4-1
4.2.1	Output Message Categories	4-1
4.3	Service Recovery	4-1
4.4	Trouble Verification	4-1
4.5	Trouble Isolation	4-1
4.6	Repair	4-2
4.6.1	Software Repair	4-2
4.7	CS Maintenance-Person — NE Interface	4-2

5 Criteria for Packet Switching NEs

5.1	Trouble Detection	5-1
5.2	Trouble Notification	5-1
5.3	Service Recovery	5-1
5.3.1	Automatic Treatment of Faults	5-1
5.3.2	Automatic Escalating Levels of PS Initializations	5-2
5.4	Trouble Verification	5-2
5.5	Trouble Isolation	5-2
5.6	Repair	5-2
5.6.1	Software Repair	5-2
5.7	PS Maintenance-Person — NE Interface	5-2
5.7.1	PS Centralization of Maintenance Functions	5-2
5.7.2	PS Physical Control/Status Interface Criteria	5-3
5.7.3	Maintenance USI Device Criteria	5-3
5.7.4	Remote I/O Message Capability	5-3

6 Criteria for Common Channel Signaling NEs

6.1	Trouble Detection	6-1
6.1.1	Trouble Detection Speed and Impact on Service	6-1
6.1.2	Trouble Detection Strategy Order	6-1
6.2	Trouble Notification	6-1
6.2.1	Alarm Classification	6-1
6.2.2	Hourly Status Message Report	6-2
6.3	Service Recovery	6-2
6.3.1	Automatic Service Recovery	6-2
6.3.2	Hardware Redundancy	6-2
6.4	Trouble Verification	6-2
6.5	Trouble Isolation	6-2
6.6	Repair	6-2
6.7	CCS Maintenance Person — NE Interface	6-2
6.7.1	CCS Centralization of Maintenance Functions	6-2
6.7.2	CCS Physical Control/Status Interface Criteria	6-3

7 Criteria for ISDN NEs

7.1	Trouble Detection	7-1
7.1.1	Physical, Data Link, and Network Layer Surveillance	7-1
7.1.2	Intrawitch Path Error Analysis and Diagnosis	7-1
7.1.2.1	Intrawitch Path Error Functions	7-2

- 7.1.2.2 B-Channel and D-Channel Data Path Checkpoints 7-2
- 7.1.2.3 Path Error Analysis 7-2
- 7.2 Trouble Notification 7-4
 - 7.2.1 Service-Affecting Resources 7-4
- 7.3 Trouble Verification, Isolation, and Repair Verification 7-4
 - 7.3.1 Call Trace 7-4
 - 7.3.2 Testing 7-6
 - 7.3.3 Embedded Operations Channels 7-7

8 Criteria for Transport NEs

- 8.1 Trouble Detection 8-1
- 8.2 Trouble Notification 8-2
 - 8.2.1 Multipling of Trouble Notifications 8-2
 - 8.2.2 Alarmed Trouble Notification Severity 8-2
 - 8.2.3 Telemetry Trouble Notifications 8-2
 - 8.2.4 Line Equipment Requirements 8-3
 - 8.2.4.1 Notification of Trouble Location 8-4
 - 8.2.5 Path Equipment Requirements 8-4
 - 8.2.5.1 Carrier Group Alarm Applications 8-4
 - 8.2.5.2 Terminal Loopback Capabilities 8-5
 - 8.2.6 Failure of Processor-Based Controller 8-5
- 8.3 Service Recovery 8-5
 - 8.3.1 Trouble Notifications for Protection Switches 8-6
 - 8.3.2 Failure of Protection Switching Equipment 8-6
 - 8.3.3 Inhibition of Protection Switching 8-6
 - 8.3.4 Completion of Protection Switching 8-6
- 8.4 Trouble Verification 8-7
- 8.5 Trouble Isolation 8-7
 - 8.5.1 Tandem Connection Maintenance (TCM) 8-7
 - 8.5.1.1 TCM Management 8-7
 - 8.5.1.2 TCM Self-Monitoring 8-7
 - 8.5.1.3 TCM Signal Monitoring 8-8
- 8.6 Repair 8-8
 - 8.6.1 Local Output 8-8
 - 8.6.2 Maintaining Service During Repair 8-8

Appendix A: References

- A.1 Telcordia Documents A-1
- A.2 Non-Telcordia Documents A-3
- A.3 Telcordia Reference Notes A-3

Appendix B: Glossary

Requirement-Object Index

List of Figures

Figure 1-1	Where Trouble Indications Appear	1-5
Figure 1-2	TMN Layers and MFAs Addressed	1-6
Figure 2-1	Alarm Report Control State Diagram	2-17

List of Tables

Table 2-1	Visible CO Alarm Color Assignments	2-25
Table 3-1	Test Frequency and Significant Outage Criteria	3-2
Table 3-2	Mean Time to Repair	3-25
Table 7-1	Errored Seconds Threshold	7-3