

# Contents

## Telcordia GR-793-Documentation Information

<b>Preface</b> . . . . .	xv
<b>1 Introduction</b>	
1.1 Purpose . . . . .	1-1
1.2 Scope . . . . .	1-1
1.3 The Layer 2 Model . . . . .	1-2
1.4 ISDN D-Channel Services . . . . .	1-3
1.4.1 User Device Addressing Services . . . . .	1-4
1.4.2 Data Link Layer Service . . . . .	1-5
1.5 Reference Architectures . . . . .	1-5
1.5.1 Layer 1 Architectures . . . . .	1-5
1.5.2 Layer 2 Architectures . . . . .	1-6
1.5.3 Layer 2 Termination in a Local Area Network . . . . .	1-7
1.6 Related Documents . . . . .	1-8
1.7 Organization Of This Document . . . . .	1-8
<b>2 Frame Structure</b>	
2.1 Numbering Conventions . . . . .	2-1
2.2 Frame Format Types . . . . .	2-2
2.2.1 Type I Frame Format . . . . .	2-3
2.2.2 TYPE U FRAME FORMAT . . . . .	2-4
2.2.3 Type S Frame Format . . . . .	2-4
2.3 Frame Field Types . . . . .	2-5
2.3.1 Flags . . . . .	2-6
2.3.2 Address . . . . .	2-7
2.3.2.1 Address Field Extension Bit . . . . .	2-8
2.3.2.2 Command/Response Field Bit . . . . .	2-8
2.3.2.3 Service Access Point Identifier . . . . .	2-8
2.3.2.4 Terminal Endpoint Identifier . . . . .	2-9
2.3.2.4.1 Dynamic TEIs . . . . .	2-9
2.3.2.4.2 Broadcast TEI . . . . .	2-9
2.3.2.4.3 Fixed TEIs . . . . .	2-10
2.3.3 Frame Check Sequence . . . . .	2-10
2.3.4 Control Field . . . . .	2-11
2.3.4.1 N(S) Sub-Field . . . . .	2-11
2.3.4.2 N(R) Sub-Field . . . . .	2-12
2.3.4.3 Poll/Final Sub-Field . . . . .	2-12
2.3.4.4 Supervisory Function Sub-Field . . . . .	2-12
2.3.4.5 Reserved Sub-Field . . . . .	2-12
2.3.4.6 Modifier Sub-Field . . . . .	2-13
2.3.5 Information Field . . . . .	2-13
2.4 State Variables . . . . .	2-13
2.4.1 Send State Variable V(S) . . . . .	2-14

2.4.2	Acknowledge State Variable V(A)	2-14
2.4.3	Receive State Variable V(R)	2-14
2.4.4	Recovery State Variable V(M)	2-15
2.5	Frame Coding and Decoding	2-15
2.5.1	Zero-Bit Stuffing and Removal (Transparency)	2-15
2.5.2	FCS Processing	2-16
2.5.3	Frame Type Decoding and Octet Counts	2-17
2.5.4	Address Decoding	2-17
2.6	Invalid Frames	2-17
2.6.1	Frame Delimiting	2-18
2.6.1.1	Idle Codes	2-18
2.6.1.2	Flag Detection and Processing	2-18
2.6.1.3	Abort Code	2-19
2.6.2	Zero-Bit Decoding	2-19
2.6.3	FCS Calculation	2-19
2.6.4	Valid Frame Length	2-19
2.6.5	Valid Frame Type Check	2-20
2.6.6	Address Field Check	2-21
2.6.7	DLCI Check	2-21
2.6.7.1	Currently Active	2-21
2.6.7.2	Change to Active	2-22
2.6.7.3	Deactivate	2-23

### 3 Commands and Responses

3.1	Type I Command	3-2
3.2	Type U Commands and Responses	3-2
3.2.1	Set Asynchronous Balanced Mode Extended Command	3-2
3.2.1.1	SABME Transmitted by SPCS	3-2
3.2.1.2	SPCS Receives SABME	3-3
3.2.2	Disconnect Command	3-3
3.2.2.1	SPCS Receives DISC	3-4
3.2.2.2	DISC Transmitted by SPCS	3-4
3.2.3	Unnumbered Information Command	3-5
3.2.3.1	Identity Request	3-5
3.2.3.2	Identity Assigned	3-6
3.2.3.3	Identity Denied	3-7
3.2.3.4	Identity Check Request	3-7
3.2.3.5	Identity Check Response	3-8
3.2.3.6	Identity Remove	3-9
3.2.3.7	Identity Verify	3-9
3.2.4	Unnumbered Acknowledgement Response	3-10
3.2.5	Disconnected Mode Response	3-10
3.2.6	Frame Reject Response	3-11
3.2.6.1	SPCS Receives FRMR	3-11
3.2.6.2	SPCS Transmits FRMR	3-12
3.2.7	Exchange Identification Command/Response	3-14

3.2.7.1	XID Format and Protocol	3-14
3.2.7.2	Automatic Notification	3-15
3.3	Type S Commands/Responses	3-16
3.3.1	Receive Ready Command/Response	3-16
3.3.2	Reject Command/Response	3-17
3.3.3	Receive Not Ready Command/Response	3-18

## 4 Exchange of Information

4.1	Unacknowledged Frame Transfer	4-1
4.2	Acknowledged Frame Transfer	4-1
4.2.1	Initiating Multiple Frame Operation	4-3
4.2.1.1	SPCS Requests Multiple Frame Operations	4-3
4.2.1.2	User Requests Multiple Frame Operations	4-4
4.2.1.3	Checking Subscription Limits	4-4
4.2.1.3.1	Active	4-5
4.2.1.3.2	Inactive	4-5
4.2.1.3.3	Disabled	4-6
4.2.1.3.4	Out-of-Service	4-6
4.2.1.4	Establishment Procedures	4-6
4.2.1.4.1	SPCS-Originated Establishment Procedures	4-6
4.2.1.4.2	Timer T200 Expiration	4-8
4.2.1.4.3	User-Originated Establishment Procedures	4-8
4.2.1.4.4	Information Transfer	4-9
4.2.1.4.5	Unsolicited DM Response	4-9
4.2.2	Information Transfer During Multiple Frame Operations	4-9
4.2.2.1	Transmitting I Frames	4-9
4.2.2.2	Receiving I Frames	4-10
4.2.2.3	Sending and Receiving Acknowledgments	4-11
4.2.2.4	Receiving REJ Frames	4-12
4.2.2.4.1	Multiple Frame Operations	4-12
4.2.2.4.2	Test N(R)	4-12
4.2.2.4.3	Valid N(R)	4-12
4.2.2.4.4	I-Frame Re-Transmission	4-13
4.2.2.4.5	Other than Multiple Frame State	4-13
4.2.2.5	Receiving RNR Frames	4-14
4.2.2.5.1	While in Multiple Frame Operations	4-14
4.2.2.5.2	While in Timer Recovery	4-14
4.2.2.5.3	Other States	4-15
4.2.2.6	Polls	4-15
4.2.2.7	Link Controller Own Receiver Busy Condition	4-15
4.2.2.8	T200 Expiration	4-16
4.2.2.9	Clearing Timer Recovery	4-16
4.2.3	Termination of Multiple Frame Operation	4-17
4.2.3.1	T200 Expiration	4-17
4.2.3.2	T203 Expiration	4-18
4.2.3.3	TEI Removal	4-19

- 4.2.3.4 Layer 1 Failure . . . . . 4-19
- 4.2.3.5 User-Transmitted DISC . . . . . 4-19
- 4.2.3.6 User-Transmitted FRMR . . . . . 4-20
- 4.2.4 TEI Assigned State . . . . . 4-20
- 4.2.5 Link Monitor Function . . . . . 4-20
  - 4.2.5.1 Start Timer T203 . . . . . 4-21
  - 4.2.5.2 Stop Timer T203 . . . . . 4-21
  - 4.2.5.3 Expiration of Timer T203 . . . . . 4-21

## 5 Data Link Connection Identifier (DLCI) Management

- 5.1 Active DLCI Table . . . . . 5-1
- 5.2 SPCS TEI Management . . . . . 5-2
  - 5.2.1 TEI Assignment Procedures . . . . . 5-2
    - 5.2.1.1 Identity Request . . . . . 5-4
    - 5.2.1.2 Identity Assigned . . . . . 5-4
    - 5.2.1.3 Identity Denied . . . . . 5-5
  - 5.2.2 TEI Check Procedures . . . . . 5-5
    - 5.2.2.1 Query for a Specific TEI Value . . . . . 5-6
    - 5.2.2.2 Query for Redundant TEIs . . . . . 5-7
    - 5.2.2.3 Query to Perform a TEI Audit . . . . . 5-8
  - 5.2.3 TEI Removal . . . . . 5-12
  - 5.2.4 TEI Identity Verify . . . . . 5-13

## 6 Error Detection and Recovery

- 6.1 N(S) Sequence Error . . . . . 6-1
- 6.2 N(R) Sequence Error . . . . . 6-2
- 6.3 Lost Transmitted Frames . . . . . 6-3
- 6.4 Frame Rejection . . . . . 6-3
- 6.5 Unsolicited Response Frames . . . . . 6-3

## 7 The SPCS Layer 2 System

- 7.1 Specification and Description Language . . . . . 7-1
  - 7.1.1 Layer 2 as a System . . . . . 7-1
  - 7.1.2 States . . . . . 7-2
  - 7.1.3 Queues . . . . . 7-3
    - 7.1.3.1 Awaiting Transmission Queue . . . . . 7-3
    - 7.1.3.2 Awaiting Acknowledgment Queue . . . . . 7-4
    - 7.1.3.3 Other Layer 2 System Queues . . . . . 7-4
- 7.2 The Layer 3 Interface . . . . . 7-4
  - 7.2.1 Call Control Abort Signal . . . . . 7-5
  - 7.2.2 Call Control Abort Mapping Function . . . . . 7-5
    - 7.2.2.1 Inability to Begin Message Transmissions . . . . . 7-5
    - 7.2.2.2 Interruption of Message Transmissions . . . . . 7-6
    - 7.2.2.3 Failure to Recover from Timer Expirations . . . . . 7-6
    - 7.2.2.4 Time-in-Queue Fault . . . . . 7-7

7.2.3 Model of the Interlayer Controller . . . . .	7-7
7.3 The Layer 1 Interface . . . . .	7-8
7.3.1 Status Commands . . . . .	7-9
7.3.2 Model of the Channel Controller . . . . .	7-9
7.3.3 Control of User Access . . . . .	7-11
7.3.3.1 Link Access Authorization States . . . . .	7-11
7.3.3.2 Changes in Link Access Authorization . . . . .	7-11
7.3.3.3 Updating Subscription Counters . . . . .	7-13
7.4 The Signaling Address Controller . . . . .	7-14
7.5 The Link Controllers . . . . .	7-14

## 8 Services

8.1 ISDN Exchange Access Signaling Service . . . . .	8-1
8.1.1 Number of Signaling Links (nsl) . . . . .	8-2
8.1.2 Fixed Link Option ( <i>flo</i> ) . . . . .	8-2
8.1.3 Dynamic Links ( <i>dyn</i> ) . . . . .	8-3
8.1.4 Packet Links (pal) . . . . .	8-4
8.1.5 Signaling Parameter Negotiation (spn) . . . . .	8-5
8.1.6 Diagnostic Error Signaling ( <i>des</i> ) . . . . .	8-5
8.1.7 Automatic Notification (anot) . . . . .	8-6
8.2 Timers . . . . .	8-6
8.2.1 Timer T200 . . . . .	8-7
8.2.2 Timer T201 . . . . .	8-7
8.2.3 Timer T203 . . . . .	8-8
8.2.4 Timer TM20 . . . . .	8-8
8.3 Counters . . . . .	8-8
8.3.1 Retry Counter (RC) and N200 . . . . .	8-9
8.3.2 Octet Counter (OC) and N201 . . . . .	8-10
8.3.3 Number of Outstanding I Frames (OI) and k . . . . .	8-10
8.3.4 Number of Links (nsl) and Number of Signaling Links (nsl) . . . . .	8-10
8.3.5 Number of User-Assigned Call Control Links (nd1) and d1 . . . . .	8-11
8.3.6 Number of SPCS-Assigned Call Control Links (nd2) and d2 . . . . .	8-11
8.3.7 Number of User-Assigned X.25 Packet Links (np1) and p1 . . . . .	8-12
8.3.8 Number of SPCS-Assigned X.25 Packet Links (np2) and p2 . . . . .	8-12
8.3.9 Number of XID Transmission Retries (nxid) and NM20 . . . . .	8-12

## Appendix A: References

Note . . . . .	A-2
To Contact Telcordia Customer Service or to Order Documents . . . . .	A-2
To Order Documents From Within Telcordia (Employees Only) . . . . .	A-2



## List of Figures

Figure 1-1	An SDL Model of the Layer 2 System . . . . .	1-2
Figure 1-2	An SDL Model of the Layer 2 Subsystems . . . . .	1-3
Figure 1-3	The Fixed Links Option . . . . .	1-4
Figure 1-4	A Dynamic Links Option . . . . .	1-5
Figure 1-5	ISDN Layer 1 Exchange Access Architectures . . . . .	1-6
Figure 1-6	ISDN Layer 2 Exchange Access Architectures . . . . .	1-7
Figure 1-7	ISDN D-Channel Layer 2 Accessing LAN Nodes . . . . .	1-9
Figure 2-1	Frame Numbering Conventions . . . . .	2-1
Figure 2-2	Field Mapping Convention . . . . .	2-2
Figure 2-3	FCS Field Mapping Exception . . . . .	2-2
Figure 2-4	Type I Frame Format . . . . .	2-3
Figure 2-5	Type U Frame Format . . . . .	2-4
Figure 2-6	Type S Frame Format . . . . .	2-5
Figure 2-7	Layer 2 Frame Flag Fields . . . . .	2-6
Figure 2-8	Format of the Layer 2 Frame Address Field . . . . .	2-7
Figure 2-9	Format of the FCS Field . . . . .	2-10
Figure 2-10	Format of the Information Field . . . . .	2-13
Figure 2-11	Frame Decoding in the Channel Controller . . . . .	2-16
Figure 3-1	I Field Format for UI Frames . . . . .	3-6
Figure 3-2	Identity Request UI Sub-Fields . . . . .	3-8
Figure 3-3	Identity Assigned WI Sub-Fields . . . . .	3-9
Figure 3-4	Identity Denied UI Sub-Fields . . . . .	3-11
Figure 3-5	Identity Check Request UI Sub-Fields . . . . .	3-12
Figure 3-6	Identity Check Response UI Sub-Fields . . . . .	3-13
Figure 3-7	Identity Remove UI Sub-Fields . . . . .	3-14
Figure 3-8	Identity Verify UI Sub-Fields . . . . .	3-15
Figure 3-9	I Field Format for FRMR Frames . . . . .	3-17
Figure 4-1	Transmission Paths for UI Frames . . . . .	4-2
Figure 4-2	Reception Paths for UI Frames . . . . .	4-3
Figure 5-1	SPCS TEI Assignment . . . . .	5-3
Figure 5-2	SPCS Query for a Specific TEI . . . . .	5-7
Figure 5-3	SPCS Query for Redundant TEI Usage . . . . .	5-9
Figure 5-4	An SPCS TEI Audit . . . . .	5-10
Figure 7-1	Layer 2 as an SDL System . . . . .	7-2
Figure 7-2	An SDL State Transition . . . . .	7-3
Figure 7-3	Exchanges at the Layer 2 - Layer 3 Interface . . . . .	7-4
Figure 7-4	Model of the Inter-Layer Controller (ILC) . . . . .	7-8
Figure 7-5	Exchanges at the Layer 2 - Layer 1 Interface . . . . .	7-9
Figure 7-6	Model of the Channel Controller (CC) . . . . .	7-10
Figure 7-7	Link Access Control States . . . . .	7-12
Figure 7-8	Changes in Link Accessibility, TEIs 0-63 . . . . .	7-12
Figure 7-9	Changes in Link Accessibility, TEIs 64-126 . . . . .	7-13
Figure 7-10	Updating Link Access Subscription Counters . . . . .	7-14
Figure 7-11	Model of the Signaling Address Controller (SAC) . . . . .	7-16

Figure 7-12	Overall Model of a Link Controller (LC) . . . . .	7-18
Figure 7-13	Key to SDL/GR Symbols . . . . .	7-19
Figure 7-14	TEI Unassigned (State 1) . . . . .	7-20
Figure 7-15	TEI Assigned (State 2) . . . . .	7-21
Figure 7-16	Awaiting Multiple Frame Operation (State 3) (Sheet 1 of 2) . . . . .	7-22
Figure 7-17	Awaiting Multiple Frame Operation (State 3) (Sheet 2 of 2) . . . . .	7-23
Figure 7-18	Multiple Frame Operations (State 4) (Sheet 1 of 6) . . . . .	7-24
Figure 7-19	Multiple Frame Operations (State 4) (Sheet 2 of 6) . . . . .	7-25
Figure 7-20	Multiple Frame Operations (State 4) (Sheet 3 of 6) . . . . .	7-26
Figure 7-21	Multiple Frame Operations (State 4) (Sheet 4 of 6) . . . . .	7-27
Figure 7-22	Multiple Frame Operations (State 4) (Sheet 5 of 6) . . . . .	7-28
Figure 7-23	Multiple Frame Operations (State 4) (Sheet 6 of 6) . . . . .	7-29
Figure 7-24	Timer Recovery (State 5) (Sheet 1 of 4) . . . . .	7-30
Figure 7-25	Timer Recovery (State 5) (Sheet 2 of 4) . . . . .	7-31
Figure 7-26	Timer Recovery (State 5) (Sheet 3 of 4) . . . . .	7-32
Figure 7-27	Timer Recovery (State 5) (Sheet 4 of 4) . . . . .	7-33
Figure 7-28	Awaiting Release (State 6) . . . . .	7-34



## List of Tables

Table 3-1	Commands and Responses . . . . .	3-1
Table 3-2	UI Frames Used for TEI Management . . . . .	3-7
Table 3-3	Format of the I Field of XID . . . . .	3-18
Table 5-1	Structure of the Active DLCI Table . . . . .	5-1
Table 5-2	Availability of TEI Value for Assignment . . . . .	5-3
Table 5-3	Changes to Active DLCI Table by TEI Assignment . . . . .	5-5
Table 5-4	Possible Actions Resulting from a TEI Audit (TEI=64-126) . . . . .	5-12
Table 5-5	Result of TEI Removal on the Active DLCI Table . . . . .	5-13
Table 6-1	Disposition of Unsolicited Responses . . . . .	6-3
Table 7-1	Cross References in Figure 7-12 . . . . .	7-17
Table 8-1	Subscription Parameters and Default Values . . . . .	8-1
Table 8-2	Initial Active DLCI Table for the Fixed Links Option . . . . .	8-3
Table 8-3	Initial Active DLCI Table for the Dynamic Links Option . . . . .	8-4
Table 8-4	Initial Active DLCI Table for the Dynamic Packet Links Option . . . . .	8-5
Table 8-5	Timers Required Per Interface . . . . .	8-7
Table 8-6	Counters Required Per Interface . . . . .	8-9
Table 8-7	Default Values for Limiting Parameter, k . . . . .	8-10