
Network Maintenance: Access and Testing - Integrated Services Digital Network (ISDN)

CONTENTS

[Telcordia GR-823-Documentation Information](#)

Preface	Preface- 1
1. Introduction	1-1
1.1 Document History	1-1
1.2 Changes In This Document	1-1
1.3 Requirements Terminology	1-2
1.4 Graphical Conventions for Figures in FR-476	1-2
2. Overview of the Generic Test Architecture	2-1
2.1 Architecture Configurations	2 - 2
2.2 DLC Test Architectures	2-4
2.3 Interface Technology	2-8
2.4 Terminology Used in FR-476	2-8
3. ISDN Basic Rate Access (BRA) Testing	3-1
3.1 Overview of ISDN Basic Rate Access	3-1
3.1.1 DSL Technology	3-2
3.1.2 DSL Transport System	3-3
3.1.3 BRA Bandwidth Allocation and Frame Structure	3-5
3.1.4 Embedded Operations Channel	3-5
3.1.5 BRA Configurations	3-5
3.2 Overview of BRA PM	3-6
3.2.1 Layer IPM	3-7
3.2.2 Location of PM Data and Thresholding	3-8
3.2.3 The Simple DSL Configuration	3-8
3.2.4 The DLC System Configurations	3-8
3.3 Testing Architecture	3-14
3.3.1 ISDN BRA Testing Architecture	3-14
3.3.2 The Simple DSL Testing Architecture	3-16
3.3.3 The UDLC Testing Architecture	3-17
3.3.4 The IDLC Testing Architecture	3-19
3.3.5 The Tandem Testing Architectures	3-21
3.3.5.1 BRA Configurations	3-22
3.3.5.2 Overview of BRA PM	3-24
3.3.6 Testing Configurations	3-33
3.3.6.1 ISDN BRA Testing Configurations on Tandem Architecture	3-33

3.3.6.2 The Single TSC Testing Configuration	3-33
3.3.6.3 The Dual TSC Testing Architecture	3-36
3.3.7 Test Functions	3-36
3.3.8 Detailed Testing Requirements	3-37
3.4 Detailed Access and Testing Functional Requirements	3-41
3.4.1 Test Access Functions	3-41
3.4.2 Detailed Test Access Requirements	3-43
3.4.3 Test Functions	3-47
3.4.4 Detailed Testing Requirements	3-52
3.5 Detailed Access and Testing Procedures Using TL 1	
Messages	3-58
3.5.1 ISDN Test Configurations	3-58
3.5.2 General Test System Functions	3-58
3.5.3 Test Initiation Procedure	3-59
3.5.4 Test Termination Procedure	3-65
3.5.4.1 Additional Requirements for Test Configurations	
Using the Generic Test Access Interface	3-65
3.5.5 Control of NT1 Test Mode	3-66
3.5.6 Alarm and Alert Reporting	3-66
3.5.7 Additional Functions Required for Testing	3-66
3.5.7.1 Additional Requirements for Test Configurations	
Using the Generic Test Access Interface	3-67
3.5.8 Specific Testing Capabilities	3-67
3.5.9 Multimeter Measurements	3-68
3.5.9.1 Additional Requirements for Test Configurations	
Using the Generic Test Access Interface	3-69
3.5.10 Noise Measurements	3-69
3.5.10.1 Additional Requirements for Test Configurations	
Using the Generic Test Access Interface	3-70
3.5.11 Loop Performance Verification	3-71
3.5.11.1 Additional Requirements for Test Configurations	
Using the Generic Test Access Interface	3-71
3.5.12 LT or LULT Cold-Start Capability Verification	3-72
3.5.12.1 Additional Requirements for Test Configurations	
Using the Generic Test Access Interface	3-72
3.5.13 LT or LULT Sealing Current Measurement	3-73
3.5.13.1 Additional Requirements for Test Configurations	
Using the Generic Test Access Interface	3-73
3.5.14 Basic Line Monitoring Function Testing	3-75
3.5.14.1 Verify Ability to Detect/Count BEs, ESs, and	
SESS	3-75
3.5.14.2 Verify Thresholding Capability	3-80
3.5.14.3 Verify Alarm-Reporting Capability	3-83
3.5.14.4 Verify Power Status Recognition	
Capability	3-84
3.5.15 Loopback Testing	3-87

3.5.15.1 Additional Requirements for Test Configurations Using the Generic Test Access Interface	3-88
Appendix: Network Flow Diagrams	Appendix- 1
References	References- 1
Glossary	Glossary-1

LIST OF FIGURES

Figure 1-1. Conventions for FR-476	1-3
Figure 2-1. A Generic Test Achitecture	2-3
Figure 2-2. Example of a Generic Test Architecture Using the DCN	2-4
Figure 2-3. Generic Test Architecture - IDLC System	2-6
Figure 2-4. Generic Test Architecture - UDLC System	2-7
Figure 3-1. Test Configurations	3-2
Figure 3-2. DSLTransport System	3-3
Figure 3-3. ISDN Basic Rate Access Configurations	3-4
Figure 3-4. Simple DSL Performance Monitoring	3-9
Figure 3-5. Generic Segmented Performance Monitoring: IDLC	3-10
Figure 3-6. Interim Path Performance Monitoring: UDLC	3-11
Figure 3-7. Interim Segmented Performance Monitoring: UDLC	3-12
Figure 3-8. Generic Segmented Performance Monitoring: UDLC	3-13
Figure 3-9. ISDN Basic Rate Access Generic Testing Model	3-15
Figure 3-10. Simple DSL Testing Architecture	3-16
Figure 3-11. The UDLC Testing Architecture-1	3-18
Figure 3-12. The UDLC Testing Architecture-2	3-19
Figure 3-13. The IDLC Testing Architecture-1	3-20
Figure 3-14. The IDLC Testing Architecture -2	3-21
Figure 3-15. Worst-Case ISDN BRA Configurations	3-23
Figure 3-16. Generic Segmented PM on Tandem-1 Architecture	3-26
Figure 3-17. Generic Segmented PM on Tandem-2 Architecture	3-27
Figure 3-18. Interim Segmented PM on Tandem- 1 Configuration	3-29
Figure 3-19. Interim Segmented PM on Tandem-2 Configuration	3-30
Figure 3-20. Interim Path PM on Tandem-1 Configuration	3-31
Figure 3-21. Interim Path PM on Tandem-2 Configuration	3-32
Figure 3-22. Tandem Testing Architecture Configuration with a Single TSC	3-34
Figure 3-23. Tandem Testing Architecture Configuration with Dual TSCs	3-35

Figure 3-24. LILO Metallic Test Access Configurations (or Modes)	3-42
Figure 3-25. DTAU for the ISDN Switch	3-46
Figure 3-26. Example of Message Sequence for Digital Testing	3-62
Figure 3-27. Example of Message Sequence for Metallic Testing via the MTAU	3-63
Figure 3-28. Example of Message Sequence for Metallic Testing via the LILT3-64

LIST OF TABLES

Table 3-1. Location Parameter and Control Link Identifier	3-39
Table 3-2. Line Unit (LU) Needed to Generate Corrupted crcs	3-40
Table 3-3. TSC/RTU Requirements for Single Test System and Dual TSC/RTUs	3-53
Table 3-4. Multimeter Ranges Measurable by TSU/RTU	3-54
Table 3-5. Location Parameter And Control Link Identifier	3-61
Table 3-6. Line Unit (LU) Needed to Generate Corrupted crcs	3-78
Table 3-7. NTI Power Status Bit Assignments and Definitions	3-86
Table 3-8. Interface Messages OS-to-TSC/RTU	3-91
Table 3-9. Interface Messages TSC/RTU-to-NE	3-92