

# Table of Contents

<b>Generic Requirements Notice Of Disclaimer</b> . . . . .	iii
<b>List of Figures</b> . . . . .	viii
<b>List of Tables</b> . . . . .	ix
<b>Preface</b> . . . . .	xi

## 1 Introduction

1.1 Reason for GR-937-CORE, Issue 1 . . . . .	1-1
1.2 General Product Description . . . . .	1-2
1.3 Application of This Document . . . . .	1-2
1.4 Requirements Terminology . . . . .	1-3
1.5 Requirement Labeling Conventions . . . . .	1-4
1.5.1 Numbering of Requirement and Related Objects . . . . .	1-4
1.5.2 Requirement, Conditional Requirement, and Objective Identification . . . . .	1-5

## 2 General Requirements

2.1 Product Samples . . . . .	2-1
2.2 Product Changes . . . . .	2-1
2.3 Network Side . . . . .	2-1
2.3.1 Termination Capacity . . . . .	2-2
2.3.2 Exit Cable Seal . . . . .	2-2
2.3.3 Connectorized Input . . . . .	2-2
2.3.4 Cable Entrance . . . . .	2-2
2.4 Protector System . . . . .	2-2
2.4.1 Protector Panel and Associated Protector Units . . . . .	2-3
2.4.2 Protector Panel Ground Bus Integrity . . . . .	2-3
2.4.3 Protector Block Installation/Removal Orientation . . . . .	2-3
2.4.4 Protector Output Conductors . . . . .	2-4
2.4.5 Color Coding and Marking . . . . .	2-4
2.5 Optional Features . . . . .	2-5
2.5.1 Replaceable Parts . . . . .	2-5
2.5.2 Cross-Connect Field . . . . .	2-5
2.6 Wire Wrap Terminals . . . . .	2-5
2.7 Grounding Connectors . . . . .	2-5
2.8 Listing . . . . .	2-5
2.9 Materials . . . . .	2-6
2.10 Safety and Reliability Considerations . . . . .	2-7
2.11 Building Entrance Terminal Layout . . . . .	2-7
2.12 Distribution Interface Module . . . . .	2-7
2.12.1 Ventilation and Drain Port . . . . .	2-8
2.13 Documentation . . . . .	2-8
2.14 Marking, Packaging and Shipping . . . . .	2-9
2.15 Installation and Maintenance . . . . .	2-10
2.16 Subscriber Distribution List . . . . .	2-10
2.17 Quality . . . . .	2-10
2.18 Seals and Gaskets . . . . .	2-11
2.19 Strain Relief and Wire Ties . . . . .	2-11

- 2.20 Security . . . . . 2-11
- 2.21 Flammability . . . . . 2-12
- 2.22 Additional Components . . . . . 2-13
- 2.23 Finish . . . . . 2-13
  - 2.23.1 Color . . . . . 2-13
  - 2.23.2 Appearance . . . . . 2-14
  - 2.23.3 Paint Adhesion . . . . . 2-14
  - 2.23.4 Flexibility . . . . . 2-15
  - 2.23.5 Paint Adhesion After Exposure . . . . . 2-15
  - 2.23.6 Ultraviolet Resistance (Outdoor BETs) . . . . . 2-15
- 2.24 Wire and Cable and Components . . . . . 2-15
- 2.25 Stub Cable . . . . . 2-16
  - 2.25.1 Cable Construction . . . . . 2-16
  - 2.25.2 Cable Attachment . . . . . 2-16
  - 2.25.3 Flame Retardant Stub Cables . . . . . 2-16
- 2.26 Modular Jacks and Plugs . . . . . 2-17
  - 2.26.1 Contact Construction . . . . . 2-17
  - 2.26.2 Contacts . . . . . 2-17
  - 2.26.3 Insertion Criteria . . . . . 2-19
  - 2.26.4 Go/No Go . . . . . 2-19
- 2.27 Hardware and Components . . . . . 2-20

**3 Electrical Requirements**

- 3.1 Dielectric Withstand of Network Interface Module . . . . . 3-1
- 3.2 Dielectric Withstand of BET . . . . . 3-1
- 3.3 Product Series Resistance . . . . . 3-2
- 3.4 Input Connector Series Resistance . . . . . 3-2
  - 3.4.1 Series Resistance . . . . . 3-2
  - 3.4.2 Network Interface Device Connector Series Resistance . . . . . 3-2
- 3.5 Insulation Resistance . . . . . 3-3
- 3.6 Longitudinal Balance . . . . . 3-3
- 3.7 Fusing Coordination . . . . . 3-4
- 3.8 Transmission . . . . . 3-5
  - 3.8.1 Attenuation . . . . . 3-5
  - 3.8.2 Crosstalk . . . . . 3-5
  - 3.8.3 T-1 Carrier System Crosstalk . . . . . 3-6
  - 3.8.4 High-Speed Data . . . . . 3-7
- 3.9 Current Carrying Capability of Grounding Connector . . . . . 3-7
- 3.10 Network Interface Device (NID) Module Current Capacity . . . . . 3-8
- 3.11 Contact Resistance of Grounding Connector . . . . . 3-9
- 3.12 First and Second Level Surge and AC Power Fault Tests . . . . . 3-9
- 3.13 Surge Test (20,000 A) . . . . . 3-10
- 3.14 Connector Surge Requirement . . . . . 3-10
- 3.15 Shield Bond Ampacity . . . . . 3-10

**4 Environmental Requirements**

- 4.1 Temperature Extremes . . . . . 4-1
- 4.2 Temperature Cycling with Humidity . . . . . 4-2
- 4.3 Shock and Vibration . . . . . 4-4
- 4.4 Ground Conductor Pull-Out . . . . . 4-4



4.5 Torque Test . . . . . 4-4  
4.6 Rain Test (OBET) . . . . . 4-4  
4.7 Salt Fog Test (OBET) . . . . . 4-5  
4.8 Sunshine (UV) Test (Polymer OBET) . . . . . 4-5  
4.9 Chemical Resistance . . . . . 4-6  
4.10 Protection Panel Contact Resistance . . . . . 4-7  
4.11 Bullet Resistance . . . . . 4-8  
4.12 Impact Resistance . . . . . 4-8  
4.13 Sand and Dust . . . . . 4-9

**5 Test Waveform Validation**

**Appendix A: Paint Defect Test Procedure**

**Appendix B: Protector Unit Pin and Socket Assembly**

**Appendix C: Component Requirements for BET Products Covered in GR-937**

**Appendix D: References**

**Appendix E: Glossary**

**Requirement-Object Index**

## List of Figures

Figure 3-1	Longitudinal-to-Metallic Balance Performance . . . . .	3-4
Figure 3-2	T-1 Crosstalk . . . . .	3-7
Figure 3-3	A BET with a Mated Modular Jack and Plug . . . . .	3-9
Figure 4-1	Circuit for Environmental Tests . . . . .	4-1
Figure 4-2	600 Foot Cable Loop Simulator . . . . .	4-3
Figure 4-3	Temperature/Humidity Cycle with Relative Humidity at 90 to 95% . . . . .	4-3
Figure 5-1	Definition of Voltage Rate of Rise . . . . .	5-2
Figure 5-2	Definitions of Double Exponential Waveform of Duration A/B Seconds . . . . .	5-3
Figure A-1	Paint Defect Testing Arrangement . . . . .	A-2
Figure A-2	Test Circuit for Paint Test . . . . .	A-3



## List of Tables

Table 2-1	Insertion and Withdrawal Force Limits . . . . .	2-4
Table 2-2	Color Coding . . . . .	2-4
Table 3-1	Maximum Average Attenuation . . . . .	3-5
Table 3-2	Near End Crosstalk (NEXT) . . . . .	3-5
Table C-1	Wire-Related Test Requirements for a BET Product . . . . .	C-2
Table C-2	Wire Harness Test Requirements . . . . .	C-4