

Table of Contents

1 Introduction

1.1 Reasons for Issue 2 1-1

2 Definitions

2.1 Transmission Levels Measurements 2-1
2.2 Digital Loop Carrier Configuration 2-1
2.3 dBm0 2-1
2.4 Supervision and Signaling Protocol 2-1
2.5 Bidirectional Communication Channels 2-2
2.6 DC Biasing of Tip and Ring of the Line Units 2-2
2.7 Maximum Subscriber Loop 2-3

3 Line Unit Test Plan

3.1 Transmission Characteristics 3-1
3.1.1 Loss [D6.1.7, D6.1.8 and F5.7, F5.8] 3-2
3.1.2 Amplitude Tracking [D6.1.11, F5.13] 3-2
3.1.3 Idle Channel Noise [D6.1.13, F5.14] 3-3
3.1.4 Signal-to-Distortion [D6.1.14, F5.15] 3-3
3.1.5 System Generated Tones [D6.1.18, F5.19] 3-3
3.1.6 Frequency Response and 60-Hz Loss [D6.1.9, D6.1.10 and F5.11, F5.12] 3-5
3.1.7 Return Loss [D6.1.3, D6.1.4, F5.3 and N3.2.4] 3-5
3.1.8 Single Frequency Distortion Spectrum [D6.1.17, F5.19 and N3.2.4] 3-7
3.1.9 Impulse Noise [D6.1.15, F5.16] 3-8
3.1.10 Intermodulation Distortion [D6.1.16, F5.17] 3-9
3.1.11 Channel Crosstalk [D6.1.20, F5.22] 3-9
3.1.12 8-kHz Messaging Noise [V3.1.4] 3-10
3.1.13 Longitudinal Balance [D6.1.5, D6.1.6, F5.5, F5.6 and N3.2.4] 3-10
3.1.14 P/AR [D6.1.19, F5.21] 3-11
3.2 Electronic Business Service Signaling Characteristics 3-11
3.2.1 Alerting Signal Transmission Levels [N3.2.3.b] 3-12
3.2.2 COT LU Transmit/Receive Levels [N3.2.4] 3-13
3.2.3 RT LU Transmit/Receive Levels [N3.2.4] 3-16
3.2.4 8-kHz ASK Characterization [N3.2.4] 3-18
3.2.5 Active Protocol LU Message Processing [N4] 3-20
3.2.6 End-to-End Delay 3-24
3.2.7 DC Characteristics [N2.4, N3.2.5] 3-25
3.2.8 Signaling/VF Interference 3-28
3.3 60-Hz (50-Vac) Induction Immunity [D11.6, F14.2] 3-30
3.4 Level I AC Survivability [D11.6, F14.1] 3-31
3.5 Line Showering Immunity [D5.1.16, F4.1.11] 3-32
3.6 RT Line-to-Line Short Immunity [D11.6, F14.1] 3-32
3.7 Customer Premises Level II AC [D11.6, F14.1] 3-33
3.8 First Level Lightning Tests [D11.6, F14.1] 3-34
3.9 Call Processing 3-35
3.10 Temperature Testing [D10.1, F15.2] 3-35

Appendix A: Typical Test Equipment

Appendix B: EBS Commands

Appendix C: References

Appendix D: Acronyms

List of Figures

Figure 2-1	EBS Universal Digital Loop Carrier Configuration	2-1
Figure 3-1	DLC VF Transmission Test Configuration	3-1
Figure 3-2	Current Sink	3-2
Figure 3-3	System Generated Tones at the COT - Test Configuration	3-4
Figure 3-4	System Generated Tones at the RT - Test Configuration	3-5
Figure 3-5	Single Frequency Distortion at the COT- Test Configuration	3-7
Figure 3-6	Single Frequency Distortion at the RT- Test Configuration	3-8
Figure 3-7	Longitudinal Balance Test Configuration	3-10
Figure 3-8	8-kHz ASK Transmitter	3-12
Figure 3-9	COT to RT Transmit Configuration	3-13
Figure 3-10	RT to COT Transmit Configuration	3-15
Figure 3-11	COT DC Leakage Signature Test Box	3-25
Figure 3-12	ASK Receiver	3-29
Figure 3-13	COT to RT VF/Signaling Interference Test Configuration	3-29
Figure 3-14	RT to COT VF/Signaling Interference Test Configuration	3-30
Figure 3-15	60-Hz Induction Test Configuration	3-30
Figure 3-16	Level 1 AC Survivability Test Configuration	3-32
Figure 3-17	Level 2 AC Test Configuration	3-34

List of Tables

Table 3-1	Environmental Test Connections	3-31
Table 3-2	First Level Surge Tests	3-35
Table B-1	CO to CPE Commands (for Primary Set - Address 0)	B-1
Table B-2	CO to Feature Key Indicator Commands (for Address 0)	B-1
Table B-3	CPE to CO Commands (from Primary Set - Address 0)	B-3
Table B-4	CPE Feature Key Commands to CO (from Address 0)	B-3