

## Contents

## Telcordia SR-3546-Documentation Information

### 1 Executive Summary

### 2 Introduction

2.1 Scope and Purpose . . . . .	2-1
2.2 Assumptions . . . . .	2-1
2.3 Structure of Document . . . . .	2-2
2.4 Terminology . . . . .	2-2

### 3 Overview

3.1 NOP-Based PCS Network Access Services . . . . .	3-1
3.1.1 PASC Service . . . . .	3-1
3.1.2 NOP Architecture . . . . .	3-1
3.1.3 C Interface . . . . .	3-2
3.1.4 Radio Personal Terminal . . . . .	3-2
3.1.5 Radio System . . . . .	3-2
3.1.6 AM . . . . .	3-4
3.1.7 AIN/ISDN Switch . . . . .	3-4
3.1.8 Serving SCP . . . . .	3-4
3.1.9 VLR . . . . .	3-4
3.1.10 HLR . . . . .	3-5
3.2 DCS 1900 . . . . .	3-5
3.2.1 General . . . . .	3-5
3.2.2 Radio System . . . . .	3-5
3.2.3 Architecture . . . . .	3-6
3.2.4 Interfaces and Protocols . . . . .	3-7
3.2.5 Subscriber Identification . . . . .	3-8
3.2.6 Roaming . . . . .	3-8
3.2.7 Services . . . . .	3-9

### 4 ISDN-Based DCS 1900 Architecture

4.1 Functional Architecture . . . . .	4-1
4.1.1 Overview . . . . .	4-1
4.1.2 PS . . . . .	4-1
4.1.3 RS . . . . .	4-1
4.1.4 AM . . . . .	4-3
4.1.5 AIN/ISDN Switch . . . . .	4-3
4.1.6 Serving SCP . . . . .	4-3
4.1.7 Visitor SCP . . . . .	4-4
4.1.8 VLR . . . . .	4-4
4.1.9 HLR . . . . .	4-4
4.1.10 EIR . . . . .	4-4
4.2 Possible Physical Architectures . . . . .	4-4

- 4.2.1 Implementation of VLR and HLR . . . . . 4-5
- 4.2.2 Transport of Mobility Management Messages . . . . . 4-5
  - 4.2.2.1 AM - AM . . . . . 4-6
  - 4.2.2.2 AM - Associated VLR . . . . . 4-6
  - 4.2.2.3 AM - HLR . . . . . 4-7
  - 4.2.2.4 AM - EIR . . . . . 4-7
- 4.2.3 Example Configurations . . . . . 4-8
  - 4.2.3.1 "SS7 - LEC VLR" Configuration (Configuration A) . . . . . 4-8
  - 4.2.3.2 "SS7-PSP VLR" Configuration (Configuration A') . . . . . 4-9
  - 4.2.3.3 "ISDN/NCAS - LEC VLR" Configuration (Configuration B) . . . . . 4-11
  - 4.2.3.4 "ISDN/NCAS - PSP VLR" Configuration (Configuration B') . . . . . 4-11
  - 4.2.3.5 "ISDN / Gateway - LEC VLR" Configuration (Configuration C) . . . . . 4-13
  - 4.2.3.6 "ISDN/Gateway - PSP VLR" Configuration (Configuration C') . . . . . 4-14
  - 4.2.3.7 Other Configurations . . . . . 4-15

## 5 Mobility Management

- 5.1 Location Registration . . . . . 5-1
  - 5.1.1 Location Updating . . . . . 5-1
  - 5.1.2 Location Cancellation . . . . . 5-3
  - 5.1.3 Periodic Location Updating . . . . . 5-3
  - 5.1.4 Purge PS . . . . . 5-4
  - 5.1.5 IMSI Detach . . . . . 5-5
  - 5.1.6 IMSI Attach . . . . . 5-6
- 5.2 Security . . . . . 5-7
  - 5.2.1 Subscriber Identity Confidentiality . . . . . 5-7
  - 5.2.2 Authentication . . . . . 5-7
  - 5.2.3 Confidentiality of Signaling and User Data . . . . . 5-8
  - 5.2.4 Terminal Identification . . . . . 5-8
- 5.3 Subscriber Data Management . . . . . 5-9
- 5.4 Routing Information Provision . . . . . 5-11
  - 5.4.1 Routing Information Request . . . . . 5-11
  - 5.4.2 Roaming Number Allocation . . . . . 5-11
- 5.5 Service Validation . . . . . 5-13
  - 5.5.1 Outgoing Call . . . . . 5-13
  - 5.5.2 Incoming Call . . . . . 5-13
- 5.6 Paging . . . . . 5-14
- 5.7 Subscriber Identity Handling . . . . . 5-15
  - 5.7.1 Provide IMSI . . . . . 5-15
- 5.8 Subscriber Activity Tracing . . . . . 5-15
  - 5.8.1 Tracing Activation . . . . . 5-15
  - 5.8.2 Tracing De-activation . . . . . 5-16
- 5.9 Fault Recovery . . . . . 5-16
  - 5.9.1 Reset of HLR . . . . . 5-16
  - 5.9.2 Call to User Unknown in VLR . . . . . 5-17
  - 5.9.3 Check of Supplementary Service Information . . . . . 5-18
- 5.10 Handover . . . . . 5-19

## 6 Call Control

6.1	Outgoing Call Setup	6-2
6.2	Incoming Call Setup	6-2
6.3	Mobile Originated Call Clearing	6-2
6.4	Network Originated Call Clearing	6-3
6.5	DCS 1900 Call Control Messages Not in National-ISDN	6-3
6.5.1	Support for In-Call Modification of Bearer Capability	6-7
6.5.2	Support for User-to-User Signaling	6-8
6.6	DCS 1900 Call Control Information Elements Not in National-ISDN	6-10
6.6.1	Impacts of Not Supporting DCS 1900 Call Control IEs in National ISDN	6-12
6.6.1.1	Non-Locking Shift IE	6-12
6.6.1.2	Repeat Indicator, Bearer Capability, Low Layer Compatibility, & High Layer Compatibility	6-12
6.6.1.3	More Data and User-User	6-13
6.6.1.4	CLIR Suppression & CLIR Invocation	6-13
6.6.1.5	Reverse Call Setup Direction	6-14
6.6.1.6	Auxiliary States	6-14
6.6.1.7	Connected Number & Connected Subaddress	6-15
6.6.1.8	SS Version Indicator	6-15

## 7 Detailed Signaling Flows

7.1	Location Registration	7-2
7.2	Mobile Originated Call	7-4
7.3	Mobile Terminating Call	7-6
7.3.1	Case 1: Paging before Call Setup	7-6
7.3.2	Case 2: Paging after Call Setup	7-9
7.4	Call Clearing	7-12
7.4.1	Mobile Originated Call Release	7-12
7.4.2	Network Originated Call Release	7-13
7.5	Handover	7-13
7.5.1	Basic Handover	7-13
7.5.2	Subsequent Handover	7-16
7.5.3	Subsequent Handover back to Anchor Radio System	7-19
7.6	Call Forwarding - Unconditional	7-19
7.7	Call Forwarding - Not Found	7-20
7.8	Call Forwarding - No Answer	7-20
7.9	Call Forwarding on Busy	7-24

## 8 Impacts of Options

8.1	SS7	8-1
8.1.1	SS7 Point Code Assignment and Administration	8-2
8.1.2	STP Routing and GTT Table Impacts	8-2
8.1.3	SS7 Network Capacity and PSP/LEC Interconnection	8-3
8.2	AIN Impacts	8-4
8.2.1	Location of VLR	8-4

8.2.2 NCAS vs. SS7 . . . . .	8-5
8.3 Traffic/Capacity Impacts . . . . .	8-5
8.3.1 AIN/ISDN Switch Processing Loads . . . . .	8-6
8.3.2 SCP Processing Loads . . . . .	8-8
8.3.3 SCP Performance . . . . .	8-10
8.3.4 Signaling Traffic . . . . .	8-10
8.3.5 Overload Control Issues . . . . .	8-11
8.3.5.1 SCPs . . . . .	8-12
8.3.5.2 AIN-Switches . . . . .	8-12
8.3.6 Comparison with NOP . . . . .	8-13
8.4 Summary of Physical Configurations Trade-Offs . . . . .	8-14

**9 Open Issues and Areas for Further Work**

9.1 Issues Related to DCS 1900, but not specific to the C Interface . . . . .	9-1
9.1.1 Transport of DCS 1900 MAP Over ANSI SS7 . . . . .	9-1
9.1.2 Support of Some DCS 1900 Call Control Features Over National ISDN and PSTN . . . . .	9-1
9.2 Issues Specific to the C Interface . . . . .	9-2
9.3 Additional Areas for Further Study . . . . .	9-2

**10 Acknowledgments**

**Appendix A: Numbering, Addressing, and Identification**

A.1 Composition of International Mobile Subscriber Identification (IMSI) . . . . .	A-1
A.2 Structure of a E.164 Number . . . . .	A-1
A.3 Structure of Location Area Identifier (LAI) . . . . .	A-1

**Appendix B: Types of Routing Information Used by DCS 1900 MAP**

**Appendix C: References**

**Appendix D: Glossary**

## List of Figures

Figure 3-1	NOP Architecture . . . . .	3-3
Figure 3-2	System Architecture of DCS 1900 . . . . .	3-6
Figure 3-3	High Layer Access Protocol Architecture of DCS 1900 . . . . .	3-8
Figure 4-1	Interfaces and Protocols for Mobility Management . . . . .	4-2
Figure 4-2	SS7 - LEC VLR Configuration . . . . .	4-9
Figure 4-3	SS7 - PSP VLR Configuration . . . . .	4-10
Figure 4-4	ISDN / NCAS-LEC VLR Configuration . . . . .	4-11
Figure 4-5	ISDN / NCAS-PSP VLR Configuration . . . . .	4-12
Figure 4-6	ISDN / Gateway - LEC VLR Configuration . . . . .	4-13
Figure 4-7	ISDN / Gateway - PSP VLR Configuration . . . . .	4-14
Figure 5-1	Case 1: Location Update to a New AM . . . . .	5-3
Figure 5-2	Case 2: Location Update to a New AM Under a New VLR . . . . .	5-4
Figure 5-3	Purge Initiated by AM . . . . .	5-5
Figure 5-4	Purge Initiated by VLR . . . . .	5-5
Figure 5-5	IMSI Detach . . . . .	5-6
Figure 5-6	IMSI Attach . . . . .	5-6
Figure 5-7	Subscriber Identity Confidentiality . . . . .	5-7
Figure 5-8	Authentication . . . . .	5-8
Figure 5-9	Terminal Identification Initiated by AM . . . . .	5-9
Figure 5-10	Download of Subscriber Data . . . . .	5-10
Figure 5-11	Deletion of Subscriber Data . . . . .	5-10
Figure 5-12	Separate Roaming Number and DN . . . . .	5-12
Figure 5-13	DN Used as Roaming Number . . . . .	5-12
Figure 5-14	Service Validation - Outgoing Call . . . . .	5-13
Figure 5-15	Service Validation - Incoming Call . . . . .	5-14
Figure 5-16	Paging . . . . .	5-15
Figure 5-17	Tracing Activation . . . . .	5-16
Figure 5-18	Tracing Deactivation . . . . .	5-16
Figure 5-19	Reset of HLR . . . . .	5-17
Figure 5-20	Restoration Initiated by VLR . . . . .	5-17
Figure 5-21	Restoration Initiated by AM . . . . .	5-18
Figure 5-22	Authentication Data Missing from AM . . . . .	5-19
Figure 5-23	Check of Supplementary Services Information . . . . .	5-20
Figure 6-1	Outgoing Call Setup . . . . .	6-2
Figure 6-2	Incoming Call Setup . . . . .	6-3
Figure 6-3	Mobile Originated Call Clearing . . . . .	6-4
Figure 6-4	Network Originated Call Clearing . . . . .	6-4
Figure 7-1	Location Registration . . . . .	7-3
Figure 7-2	Mobile Originated Call . . . . .	7-4
Figure 7-3	Mobile Terminating Call - Case 1 (1 of 2) . . . . .	7-7
Figure 7-4	Mobile Terminating Call - Case 1 (2 of 2) . . . . .	7-8
Figure 7-5	Mobile Terminating Call - Case 2 (1 of 2) . . . . .	7-10
Figure 7-6	Mobile Terminating Call - Case 2 (2 of 2) . . . . .	7-11
Figure 7-7	Mobile Originated Call Release . . . . .	7-13

Figure 7-8	Network Originated Call Release . . . . .	7-14
Figure 7-9	Basic Handover . . . . .	7-15
Figure 7-10	Subsequent Handover (1 of 2) . . . . .	7-17
Figure 7-11	Subsequent Handover (2 of 2) . . . . .	7-18
Figure 7-12	Call Forwarding - Unconditional . . . . .	7-19
Figure 7-13	Call Forwarding - Not Found . . . . .	7-21
Figure 7-14	Call Forwarding - No Answer (1 of 2) . . . . .	7-22
Figure 7-15	Call Forwarding - No Answer (2 of 2) . . . . .	7-23
Figure 7-16	Call Forwarding on Busy (1 of 2) . . . . .	7-25
Figure 7-17	Call Forwarding on Busy (2 of 2) . . . . .	7-26
Figure 7-18	Call Forwarding on Busy - AIN 0.1 Alternative . . . . .	7-27
Figure 8-1	Format of SS7 Point Code . . . . .	8-2

## List of Tables

Table 6-1	DCS 1900 Call Control Messages Not in NI . . . . .	6-5
Table 6-2	DCS 1900 Call Control IEs Not in NI . . . . .	6-11
Table 8-1	AIN/ISDN Switch Processing Sub-Tasks: LEC VLR . . . . .	8-6
Table 8-2	AIN/ISDN Switch Processing Sub-Tasks: PSP VLR . . . . .	8-7
Table 8-3	LEC SCP Processing Loads . . . . .	8-9
Table 8-4	Summary of Physical Configuration Tradeoffs . . . . .	8-14