

# Operator Services Originating Connection Using SS7: A Proposed Strategy

## Contents

## [Telcordia SR-4572-Documentation Information](#)

Executive Summary.....	ES-1
1. Introduction.....	1-1
1.1 Purpose.....	1-2
1.2 Background.....	1-2
1.3 Definitions.....	1-4
1.4 Organization.....	1-5
2. Benefits of SS7 ISUP Signaling for Operator Services.....	2-1
2.1 Trunk Savings.....	2-1
2.2 Additional Information from EO to OSS.....	2-2
2.3 Capability to Implement RTP.....	2-3
2.4 Operator Work Time Savings.....	2-4
2.5 Routing Calls from EOs to OSSs via Intermediate Switches.....	2-5
3. Routing Calls to OSS Using SS7.....	3-1
3.1 Alternative 1: Basic SS7 Call Setup.....	3-2
3.1.1 Procedures at an Originating EO.....	3-3
3.1.1.1 Called Number Input by Caller Without User Input Carrier Identification.....	3-3
3.1.1.2 Called Number and Carrier Identification Not Input by Caller.....	3-7
3.1.1.3 User Input Carrier Identifier.....	3-8
3.1.2 Intercept Service.....	3-9
3.1.3 Intermediate Switch Procedures.....	3-10
3.1.3.1 Routing to IXC OSS.....	3-10
3.1.3.2 Routing to LSP OSS.....	3-11
3.2 Alternative 2: ANSI Operator Services Originating Connection.....	3-14
3.2.1 Procedures at Originating EO.....	3-15
3.2.2 Procedures at Intermediate Switch.....	3-16
3.3 Alternative 3: Translations at Intermediate Switches.....	3-17
3.3.1 0+/ABS for Local Calls and IntraLATA Toll Calls With No Presubscription.....	3-18
3.3.2 DA or Other Information Service.....	3-19
3.3.3 0- Services.....	3-19
3.3.4 Intercept Calls and 1+Screened Local Calls and IntraLATA Toll Calls With No Presubscription.....	3-19

---

---

3.3.5	0+/ABS and 1+Screened InterLATA Calls and IntraLATA Toll Calls With Presubscription.....	3-19
3.4	Alternative 4: OSS Routing Identifier.....	3-20
4.	SS7 Parameters Signaled to OSS .....	4-1
4.1	Alternative 1: Basic SS7 Call Setup.....	4-1
4.2	Alternative 2: ANSI Operator Services Originating Connection.....	4-3
4.3	Alternative 3: Translations at Intermediate Switch.....	4-3
4.4	Alternative 4: OSS Routing Identifier.....	4-3
5.	Evaluation of SS7 Signaling Alternatives.....	5-1
5.1	Alternative 1: Basic SS7 Call Setup.....	5-1
5.1.1	EO Upgrades .....	5-1
5.1.2	Intermediate Switch Upgrades .....	5-2
5.1.3	OSS Upgrades .....	5-2
5.1.4	ISUP Protocol Modifications .....	5-2
5.1.5	Routing Efficiencies.....	5-2
5.2	Alternative 2: ANSI Operator Services Originating Connection.....	5-2
5.2.1	EO Upgrades .....	5-3
5.2.2	Intermediate Switch Upgrades .....	5-3
5.2.3	OSS Upgrades .....	5-3
5.2.4	ISUP Protocol Modifications .....	5-3
5.2.5	Routing Efficiencies.....	5-4
5.3	Alternative 3: Translations at Intermediate Switch.....	5-4
5.3.1	EO Upgrades .....	5-4
5.3.2	Intermediate Switch Upgrades .....	5-4
5.3.3	OSS Upgrades .....	5-4
5.3.4	ISUP Protocol Modifications .....	5-5
5.3.5	Routing Efficiencies.....	5-5
5.4	Alternative 4: OSS Routing Identifier.....	5-5
5.4.1	EO Upgrades .....	5-5
5.4.2	Intermediate Switch Upgrades .....	5-6
5.4.3	OSS Upgrades .....	5-6
5.4.4	ISUP Protocol Modifications .....	5-6
5.4.5	Routing Efficiencies.....	5-6
5.5	Summary of Alternatives .....	5-6
6.	Proposed Strategy for Using SS7 ISUP Signaling for Operator Services .....	6-1
	References .....	References-1
	Glossary .....	Glossary-1

---

## List of Figures

Figure 2-1.	Example of Routing Calls to ILEC Prior to Local Competition .....	2-5
Figure 2-2.	Example of Routing Calls to ILEC OSS with Local Competition .....	2-6
Figure 2-3.	Example of Routing from ILEC EO to Non-ILEC OSP OSS .....	2-7
Figure 2-4.	Dedicated Trunk Groups for Operator Services Traffic Using MF Signaling 2-8	
Figure 3-1.	Routing Procedures at Originating EO for Operator Services Local Calls 3-5	
Figure 3-2.	LSP Provides Operator Services for IntraLATA Toll IXC .....	3-6
Figure 3-3.	LSP Provides DA Service to Its Customers .....	3-8
Figure 3-4.	Example of Routing Calls to IXC OSS .....	3-11
Figure 3-5.	Alternative 1: Basic SS7 Call Setup .....	3-13
Figure 3-6.	Example of Nailed Up Trunk Groups for CLEC OSSs.....	3-17
Figure 3-7.	Translations at the Intermediate Switch .....	3-18
Figure 3-8.	Example of Routing Operator Services Calls Using OSS Routing Identifier 3-21	