

Section 1 Introduction

Contents

1. Introduction.....	1-1
1.1 Purpose and Scope	1-1
1.2 Background	1-2
1.2.1 Availability Information	1-2
1.3 Requirements Terminology.....	1-3
1.3.1 CPE Guidelines Terminology	1-3
1.3.2 Network Terminology.....	1-3
1.3.3 Numbering of Requirements and Related Objects.....	1-4
1.3.4 Requirement, Conditional Requirement, and Objective Object Identification	1-4
1.4 Relationship to Other Telcordia Documentation	1-4
1.4.1 National ISDN PRI CPE Guidelines.....	1-4
1.4.2 ISDN PRI Generic Requirements	1-5
1.5 National ISDN PRI Features and Capabilities	1-6
1.5.1 PRI Access, Call Control, and Signaling	1-6
1.5.2 ISDN Circuit-Mode Services	1-7
1.5.3 ISDN Packet-Mode Services	1-7

Section 2 Bearer Services and Interface Configuration

Contents

2.	Bearer Services and Interface Configuration	2-1
2.1	Bearer Services Supported	2-1
2.1.1	Circuit-Mode, 64-kbps, 8-kHz Structured, Speech, Demand	2-2
2.1.2	Circuit-Mode, 64-kbps, 8-kHz Structured, 3.1-kHz Audio Information Transfer, Demand	2-2
2.1.3	Circuit-Mode, 64-kbps, 8-kHz Structured, Unrestricted Digital Transmission-Rate Adapted from 56-kbps, Demand.....	2-3
2.1.4	Circuit-Mode, 64-kbps, 8-kHz Structured, Unrestricted Digital Transmission (64-kbps), Demand	2-3
2.1.5	Circuit-Mode, nx64-kbps ($2 \leq n \leq 24$), 8-kHz Structured, Unrestricted Digital Transmission, Demand	2-4
2.1.6	Packet-Mode, Unrestricted Digital Information, Virtual Call and Permanent Virtual Circuit Service	2-4
2.2	Interface Configuration	2-4
2.2.1	Physical Interface Configuration	2-4
2.2.2	Functional Interface Configuration.....	2-7

Section 3 Physical Layer

Contents

3.	Physical Layer.....	3-1
3.1	Scope of Physical Layer Specifications	3-1
3.2	Terminating Impedance	3-1
3.2.1	Impedance and Return Loss	3-1
3.2.2	Longitudinal Balance	3-2
3.3	Transmission Rate and Synchronization	3-2
3.4	Line Code	3-4
3.5	Interface Signal Characteristics.....	3-4
3.5.1	Standard Pulse Characteristics	3-4
3.5.2	NI Signal Characteristics	3-5
3.5.3	S and T Reference Point Transmit/Receive Signal Characteristics	3-8
3.6	Wander	3-9
3.6.1	Receive Signal Wander	3-10
3.6.2	Transmit Signal Wander	3-11
3.7	Jitter.....	3-12
3.7.1	PUB 43801 Jitter Requirements.....	3-13
3.7.2	ANSI T1.408 Jitter Recommendations	3-13
3.8	Phase Transients.....	3-14
3.8.1	Receive Signal Transients	3-15
3.8.2	Transmit Signal Transients	3-15
3.9	Powering Arrangements.....	3-16
3.10	ESF Frame Format and Channel Combinations.....	3-16
3.10.1	Framing Bit Allocation	3-17
3.10.2	Cyclic Redundancy Check (CRC)	3-17
3.10.3	Channel Time-Slot Assignment Rules	3-18
3.10.4	Bit Transmission Order	3-19
3.10.5	Codes for Idle Channels and Idle Time Slots	3-19
3.11	Physical Characteristics	3-20
3.11.1	Interface Cable Requirements	3-20
3.11.2	Wiring Polarity Integrity	3-21
3.11.3	Connector	3-21
3.11.4	Interworking of DSX-1 and ANSI T1.408 Interfaces.....	3-22

Section 4

Link Layer Protocol

Contents

4. Link Layer Protocol	4-1
4.1 Link Layer Requirements for D-Channel Call Control Signaling	4-1
4.2 Timers and Counters	4-3

Section 5 Call Control Procedures for Circuit-Switched Calls

Contents

5.1	Inband Tones and Announcements	5-1
5.1.1	Provision of Tones and Announcements	5-1
5.1.2	Intercept Announcements	5-4
5.2	Interworking	5-5
5.2.1	Call Origination - Interworking Within the Customer's Premises	5-5
5.2.2	Call Origination - Interworking Within the Network	5-6
5.2.3	Call Termination - Interworking Within the Network	5-7
5.2.4	Call Termination - Interworking Within the Customer's Premises	5-7
5.3	Delay Procedures	5-8
5.3.1	Delay Procedures Performed by the Network	5-8
5.3.2	Delay Procedures Performed by the CPE	5-9
5.4	B-Channel Selection	5-9
5.4.1	B-Channel Selection Algorithm	5-9
5.4.2	Originating B-Channel Selection	5-10
5.4.3	Terminating B-Channel Selection	5-10
5.5	Addressing Information - En Bloc Signaling	5-11
5.5.1	Called Party Number	5-11
5.5.2	Transit Network Selection	5-13
5.5.3	Operator System Access	5-13
5.6	Timers	5-14
5.7	Preference of Calling Party Number on Origination of 911 Calls	5-15
5.8	Called Party Number Digit Deletion and Prefix on Call Termination	5-16

Section 6 Switching and Signaling for Circuit-Switched Calls

Contents

6.	Switching and Signaling for Circuit-Switched Calls	6-1
6.1	Call Origination.....	6-1
6.1.1	Call Reference Selection	6-2
6.1.2	Bearer Service Selection	6-2
6.1.3	B-Channel Selection	6-3
6.1.4	B-Channel Cut-Through	6-4
6.1.5	Misdialing Treatments	6-4
6.1.6	Expiration of Timer T303	6-6
6.1.7	Call Proceeding	6-7
6.1.8	Notification of Interworking	6-7
6.1.9	Notification of Delay	6-8
6.1.10	Call Confirmation Indication	6-8
6.1.11	Call Connected.....	6-9
6.1.12	Call Rejection.....	6-9
6.2	Call Termination	6-11
6.2.1	Compatibility Checking	6-12
6.2.2	Additional Compatibility Check	6-13
6.2.3	Channel Selection	6-14
6.2.4	CPE Determined Busy	6-14
6.2.5	Call Confirmation	6-15
6.2.6	Active Indication.....	6-17
6.2.7	Notification of Interworking at the Terminating Interface	6-18
6.2.8	Call Failure.....	6-18
6.3	Call Clearing	6-20
6.3.1	Exception Conditions	6-21
6.3.2	Normal Call Clearing Initiated by the CPE	6-22
6.3.3	Normal Call Clearing Initiated by the SPCS	6-24
6.3.4	Clear Collision	6-25
6.4	Error Procedures.....	6-25
6.4.1	Protocol Discriminator Error	6-25
6.4.2	Message Too Short.....	6-26
6.4.3	Call Reference Procedural Errors	6-26
6.4.4	Message Type or Message Sequence Errors.....	6-27
6.4.5	Information Element Errors	6-28
6.4.6	Mandatory Information Element Errors.....	6-28
6.4.7	Non-Mandatory Information Element Error	6-29
6.4.8	Data Link Failure	6-30
6.4.9	STATus ENquiry Procedure	6-32
6.4.10	Receiving a STATus message.....	6-33
6.4.11	Restart Procedures.....	6-33
6.4.12	SPCS-Detected Error Conditions.....	6-39

Section 7 Packet-Switched Call Control Procedures

Contents

7.	Packet-Switched Call Control Procedures	7-1
7.1	Call Origination.....	7-1
7.1.1	Semi-Permanent B-Channel.....	7-1
7.1.2	On-Demand B-Channel Connection	7-3
7.2	Call Offering	7-4
7.2.1	No Notification	7-5
7.2.2	Conditional Notification	7-6
7.3	Call Clearing	7-8
7.3.1	Semi-Permanent B-Channel.....	7-9
7.3.2	On-Demand B-Channel.....	7-10
7.4	Error Procedures.....	7-11
7.5	Packet Layer Requirements.....	7-12
7.5.1	Logical Channels.....	7-12
7.5.2	Packet Window Size	7-12
7.5.3	Packet Size	7-12
7.5.4	Throughput Class	7-13
7.5.5	Type of Number/Numbering Plan Identification	7-13
7.6	Packet Level Timers.....	7-13

Section 8 Layer 3 Messages and Information Elements

Contents

8.	Layer 3 Messages and Information Elements	8-1
8.1	Message Functional Definitions	8-1
8.1.1	Overview	8-1
8.1.2	Messages	8-3
8.1.3	Non-Call-Associated Messages	8-29
8.2	Message Structure	8-31
8.2.1	Overview	8-31
8.2.2	Protocol Discriminator	8-33
8.2.3	Call Reference	8-33
8.2.4	Message Type	8-36
8.2.5	Other Information Elements.....	8-37
8.2.6	National-Specific Information Elements	8-122
8.2.7	Network-Specific Information Elements	8-125
8.3	Components.....	8-128
8.3.1	Invoke Component	8-129
8.3.2	Return Result Component	8-129
8.3.3	Return Error Component.....	8-130
8.3.4	Reject Component.....	8-130
8.3.5	Interpretation Component	8-131
8.3.6	Network Protocol Profile Component.....	8-131
8.4	Data Elements	8-131
8.4.1	Component Type (Table 8-132).....	8-132
8.4.2	Invoke Identifier	8-133
8.4.3	Linked Identifier	8-133
8.4.4	Null Identifier.....	8-134
8.4.5	Operation Value	8-135
8.4.6	Sequence	8-136
8.4.7	Error Value.....	8-136
8.4.8	Problem Value.....	8-137
8.4.9	Length	8-139
8.4.10	Object Identifier Value.....	8-140
8.4.11	Interpretation Value	8-141
8.4.12	Network Protocol Profile Value.....	8-142
8.4.13	Notification Value	8-143
8.5	ASN.1 Descriptions.....	8-144

Section 9 D-Channel Backup

Contents

9.	D-Channel Backup.....	9-1
9.1	Introduction.....	9-1
9.2	General Protocol Description.....	9-2
9.2.1	Non-facility Associated Signaling with Backup D-Channel	9-2
9.2.2	Primary and Backup D-Channels.....	9-3
9.2.3	D-Channel States.....	9-6
9.2.4	Difference Between Active and Standby D-Channels.....	9-7
9.2.5	Conditions for D-Channel Switchover.....	9-8
9.2.6	General Protocol Guidelines	9-9
9.3	Protocol Descriptions at Layer 2 and 3.....	9-11
9.3.1	Initialization	9-11
9.3.2	Connection Verification Procedure on a Standby D-Channel	9-12
9.3.3	Verification of an Active D-Channel	9-13
9.3.4	Switchover Procedure	9-13
9.3.5	Timers	9-19
9.3.6	SERV and SERV ACK Messages in the D-Channel Backup Protocol.....	9-20
9.4	Messages and Information Elements	9-21

Section 10 Maintenance

Contents

10. Maintenance	10-1
10.1 NT2 Layer-1 Maintenance Functions	10-4
10.1.1 Generate CRC	10-5
10.1.2 Monitor CRC.....	10-5
10.1.3 Recognize LOF	10-5
10.1.4 Recognize LOS	10-6
10.1.5 Recognize AIS	10-6
10.1.6 Generate RAI	10-7
10.1.7 Recognize RAI.....	10-8
10.1.8 Command/Response and Priority Messaging on the EOC	10-8
10.1.9 Generate PRM on the EOC.....	10-11
10.1.10 Monitor PRM on the EOC	10-13
10.1.11 Calculate/Store PM Data.....	10-14
10.1.12 Line Loopback at I _a Interface.....	10-20
10.1.13 Test Lines at I _a Interface	10-22
10.1.14 Payload Loopback at the I _a Interface	10-22
10.1.15 Carrier Group Alarm (CGA).....	10-24
10.2 NT1 Layer-1 Maintenance Functions	10-26
10.2.1 Monitor Incoming DS1 Signal at I _a and I _b Interface	10-27
10.2.2 Recognize LOS	10-27
10.2.3 Generate AIS.....	10-28
10.2.4 Monitor Embedded Operations Channel.....	10-28
10.2.5 Monitor PRM	10-28
10.2.6 Calculate/Store PM Data.....	10-28
10.2.7 Line Loopback at the I _a Interface.....	10-30
10.2.8 Line Loopback at the I _b Interface	10-32
10.3 User Initiated Maintenance Capabilities	10-32
10.4 NT2 Provided Maintenance Indications to the User	10-33
10.5 NT1 Provided Maintenance Indications to the User	10-34

Section 11 Circuit Mode Services

Contents

11. Circuit Mode Services.....	11-1
11.1 ISDN Calling Number Identification Services (I-CNIS).....	11-1
11.1.1 Background and Service Description.....	11-1
11.1.2 Service-Specific Requirements for CPE Using I-CNIS.....	11-7
11.2 Call-by-Call Service Selection.....	11-21
11.2.1 Foreign Exchange Selection.....	11-22
11.2.2 Tie Trunk Selection.....	11-25
11.2.3 OUTWATS Selection	11-29
11.2.4 INWATS Selection	11-33
11.2.5 Error Procedures	11-34
11.2.6 Hotel/Motel Service Selection	11-35
11.2.7 Selective Class of Call Screening (SCOCS) Service Selection	11-37
11.2.8 Call-by-Call Access to Interexchange Carrier (IXC) Services	11-39
11.3 Switched DS1/Switched Fractional DS1 (SWF-DS1)	11-42
11.3.1 Introduction.....	11-42
11.3.2 SWF-DS1 Call Control Procedures and Parameters.....	11-44
11.3.3 SWF-DS1 Call Processing and Signaling.....	11-50
11.4 Called Party Subaddress.....	11-52
11.4.1 Called Party Subaddress Information	11-52
11.4.2 Called Party Subaddress Delivery.....	11-53
11.5 PRI Two B-Channel Transfer	11-53
11.5.1 Background and Service Description.....	11-54
11.5.2 Service-Specific Requirements for CPE Using TBCT	11-55
11.6 ISDN Calling Name Identification Services for PRIs.....	11-71
11.6.1 Background for CPE Using ISDN Calling Name Identification Services	11-71
11.6.2 Service-Specific Guidelines for ISDN Calling Name Identification Services.....	11-72
11.6.3 Significant SPCS Subscription Parameters for CPE Using ISDN Calling Name Identification Services for PRIs	11-77
11.6.4 Description of ISDN Calling Name Identification Services for PRIs From the User's Perspective	11-77
11.7 B-Channel Availability Control	11-78
11.7.1 B-Channel Status Categories	11-78
11.7.2 Sending a SERVICE Message.....	11-80
11.7.3 Receiving a SERVICE Message.....	11-81
11.7.4 Collisions	11-82
11.7.5 Status Audits	11-84
11.7.6 Status on Provisioning	11-85
11.7.7 Error Conditions.....	11-85

11.7.8	Relationship with Restart Procedures	11-88
11.7.9	D-Channel Switchover and B-Channel Availability Control	11-92
11.8	D-Channel Message Performance Monitoring and Control (DCMPMC) ..	11-93
11.8.1	DCMPMC Background.....	11-93
11.8.2	Service-Specific Requirements for a CPE Using DCMPMC	11-95
11.8.3	Significant Switch Subscription Parameters for DCMPMC	11-102
11.8.4	Description of DCMPMC from a User's Perspective.....	11-103
11.9	PRI as a Member of a Business Group	11-104
11.9.1	Background and Service Description.....	11-105
11.9.2	Service-Specific Requirements for CPE Using PRI as a Member of a Business Group.....	11-106
11.9.3	Significant Switch Subscription Parameters for PRI as a Member of a Business Group.....	11-111
11.9.4	Description of PRI as a Member of a Business Group from the User's Perspective	11-112
11.9.5	ASN.1 Description for Traveling Class Mark	11-113
11.10	PRI Call Deflection	11-114
11.10.1	Background and Service Description.....	11-114
11.10.2	Service Specific Requirements for PRI CPE Using I-CD	11-115
11.10.3	Significant Switch Subscription Parameters	11-122
11.10.4	Description of Service From a User's Perspective	11-123

Section 12 ISDN X.25 Based Packet-Mode Services

Contents

12. ISDN X.25-Based Packet-Mode Services	12-1
12.1 Flow Control Parameter Negotiation	12-2
12.2 Throughput Class Negotiation	12-3
12.3 Transit Delay	12-4
12.4 User Testing	12-6
12.5 Closed User Group (CUG) Services	12-7
12.6 Reverse Charging Services	12-8
12.7 Recognized Private Operating Agency (RPOA) Selection	12-9
12.8 Fast Select Services	12-9
12.9 Basic Business Group (BBG).....	12-10
12.10 Network User Identification (NUI)	12-11
12.11 Call Deflection	12-12
12.12 Calling Line Identification	12-13
12.12.1 Number Provision	12-13
12.12.2 Number Screening.....	12-14
12.12.3 Number Delivery.....	12-14
12.13 ITU-T-Specified DTE Facilities to Support the OSI Network Service	12-14

Section 13 ROSE Component Signaling Procedures

Contents

13. ROSE Component Signaling Procedures.....	13-1
13.1 Invoke Component.....	13-1
13.1.1 Receipt of Invoke Component.....	13-1
13.1.2 Sending of an Invoke Component.....	13-4
13.2 Return Result.....	13-5
13.2.1 Receipt of Return Result Component.....	13-6
13.2.2 Sending of a Return Result Component.....	13-7
13.3 Return Error Component.....	13-7
13.3.1 Receipt of a Return Error Component.....	13-7
13.3.2 Sending of a Return Error Component.....	13-9
13.4 Reject Component.....	13-9
13.4.1 Receipt of Reject Component.....	13-9
13.4.2 Sending of a Reject Component.....	13-10
13.5 Operation Class.....	13-12
13.6 Invoke Identifier Administration.....	13-13
13.6.1 Allocation and Release of Invoke Identifiers.....	13-13
13.6.2 Invoke Identifiers Used in Components Sent by the CPE.....	13-13
13.6.3 Invoke Identifiers in ROSE Components Received by the CPE.....	13-14
13.7 Problem Value Definition.....	13-14
13.8 Parameters.....	13-16

Section 14 Generic Functional Procedures for PRI Services

Contents

14. Generic Functional Procedures for PRI Services.....	14-1
14.1 Call-Associated Common Element Procedures	14-1
14.1.1 Signaling During Call Origination.....	14-2
14.1.2 Signaling During Call Termination.....	14-4
14.1.3 Signaling During an Active Call.....	14-6
14.1.4 Signaling During Call Clearing.....	14-7
14.1.5 Error Procedures for the Call-Associated Common Element Procedures	14-10
14.2 Generic Notification Procedures	14-15
14.2.1 Call-Associated Notification Procedures	14-15
14.2.2 Non-Call-Associated Notification Procedures.....	14-16
14.2.3 ASN.1 Encoded Notification Indicator Information Element	14-16
14.2.4 Error Procedures for the Generic Notification Procedures	14-17