

Contents

Telcordia SR-5074-Documentation Information

1.	Introduction	1-1
1.1	Background	1-1
1.2	Motivation for Next Generation Networks	1-2
1.3	Moving Towards NGN in Service Provider's Networks	1-3
1.4	Purpose and Scope of Document	1-5
1.5	Document Organization	1-6
2.	Industry Status of NGN	2-1
2.1	Status of NGN in Carrier Networks	2-1
2.1.1	Overview	2-1
2.1.2	Current and Planned Offerings ^[32]	2-2
2.1.2.1	AT&T	2-2
2.1.2.2	MCI WorldCom TM	2-3
2.1.2.3	Sprint	2-3
2.1.2.4	Qwest	2-4
2.1.2.5	Level 3	2-5
2.1.2.6	Williams Network ^[32]	2-5
2.1.2.7	Other Service Offerings ^[27]	2-6
2.2	VOP/NGN Activity in Industry Bodies	2-8
2.2.1	Internet Engineering Task Force (IETF)	2-8
2.2.2	ITU	2-10
2.2.2.1	H.248	2-10
2.2.2.2	H.323	2-12
2.2.2.3	Bearer Independent Call Control	2-13
2.2.2.4	Study Group 4	2-15
2.2.3	ETSI TIPHON	2-16
2.2.4	T1S1	2-18
2.2.5	ATM Forum	2-18
2.2.5.1	ATM Forum - Network Management WG	2-19
2.2.6	MSF	2-20
2.2.7	International Softswitch Consortia	2-21
2.2.8	IMTC	2-21
2.2.9	TeleManagement Forum (TM)	2-22
2.2.10	Multimedia Cable Network System	2-23
2.2.11	Ordering and Billing Forum (OBF)	2-23
2.2.12	DMTF	2-23
2.2.13	QoS Forum	2-24
2.2.14	MWIF	2-24
2.2.15	3GPP and 3GPP2	2-25
3.	Defining an Infrastructure for VOP in NGN	3-1
3.1	Current Status of Architecture for VOP Defined in GR Program	3-1
3.1.1	Functional Architecture	3-1
3.1.1.1	Interfaces and Protocols	3-5
3.1.1.2	Signaling and Control Architecture	3-7

3.1.1.3	Call Types	3-8
3.1.1.4	Resource Management	3-8
3.1.1.5	Transport Through the Core Network	3-10
3.1.1.6	Support for Announcements	3-11
3.1.2	Trunk Gateway	3-12
3.1.3	Signaling Gateway	3-12
3.1.4	Access Gateway	3-13
3.1.5	VOP Services	3-15
3.1.6	VOP Performance	3-17
3.1.7	VOP Accounting Management	3-18
3.1.8	VOP Operations	3-20
3.2	Enhancements to VOP Framework Architecture	3-21
4.	Enhancing the VOP Architecture Towards NGN	4-1
4.1	Interworking of NGN VOP Networks with H.323 Equipment	4-1
4.1.1	Overview of ITU-T Recommendation H.323	4-1
4.1.2	Relationship Between the VOP Network and H.323 Entities	4-5
4.1.2.1	CCA Directly Responsible for H.323 Interworking	4-5
4.1.2.1.1	The VOP Network as a Terminal	4-6
4.1.2.1.2	The CCA as a Gatekeeper	4-7
4.1.2.2	Interworking via H.323 Customer Gateway	4-10
4.1.3	Interconnection of CCAs Supporting H.323	4-12
4.1.4	Signaling and Call Control	4-14
4.1.5	Addressing and Configuration	4-16
4.1.6	Transport	4-16
4.1.7	Usage Measurement and Billing	4-16
4.1.8	IETF SIP Interworking	4-17
4.1.9	Conclusions	4-17
4.2	New Gateways and CPEs to be Supported for NGN	4-18
4.2.1	Overview of Customer Premises Equipment	4-18
4.2.2	Functionality Needed from Customer Gateways	4-20
4.2.2.1	Functions Needed to Support Voice	4-20
4.2.2.2	Functions Needed to Support Data	4-21
4.2.3	Customer Gateway Interfaces	4-22
4.2.3.1	CPE Connectivity to Customer Gateways	4-22
4.2.3.2	Access Networks for Customer Gateway - Core Packet Network Interconnection	4-23
4.2.3.3	Signaling and Control Interfaces	4-26
4.3	Numbering and Addressing Issues	4-29
4.3.1	Scenarios for IP Telephony	4-30
4.3.2	Numbering Alternatives for IP Terminals	4-32
4.3.3	ATM Addressing for End Users	4-32
4.4	Security in NGN	4-33
4.4.1	Introduction	4-33
4.4.2	Network Security Issues	4-35
4.4.3	Communication and Control Protocols Security Issues	4-36
4.4.3.1	TCP/IP	4-36

4.4.3.2	Signaling System Number 7	4-37
4.4.3.3	Call Control Protocols	4-38
4.4.4	Functional Element Security Issues	4-38
4.4.4.1	Access Gateway (Customer and Business Gateways)	4-39
4.4.4.2	Billing Agent	4-39
4.4.4.3	Call Connection Agent	4-39
4.4.4.4	Operations Support Systems	4-40
4.4.4.5	Routing and Translation Server	4-40
4.4.4.6	Signaling Gateway	4-41
4.4.4.7	Service Agent	4-41
4.4.4.8	Trunk Gateway	4-41
4.4.4.9	Miscellaneous Feature Servers	4-41
4.4.4.10	Security Framework	4-41
4.5	Reliability in VOP/NGN	4-42
4.5.1	Issues	4-44
4.5.1.1	Metrics	4-44
4.5.1.2	System Reliability Models	4-44
4.5.1.3	Failure Modes	4-45
4.5.1.4	Reliability Through Redundancy	4-46
4.5.1.4.1	Core Network	4-46
4.5.1.4.2	Access Network	4-46
4.5.1.4.3	Billing Agent	4-46
4.5.1.4.4	Call Connection Agent	4-46
4.5.1.4.5	Service Agent	4-47
4.5.1.4.6	Gateways	4-47
4.5.1.4.7	Modeling Element Reliability	4-47
4.5.1.5	Software Reliability Requirements	4-48
4.5.1.6	Outage Reporting	4-49
4.5.1.7	Statistical Analysis and Control of Failures and Outages	4-49
4.5.2	Continuity with Existing Requirements	4-50
4.5.3	Continuity with Standards Bodies	4-51
5.	Wireless Evolution to NGN	5-1
5.1	Migration to Third Generation Wireless Networks	5-1
5.1.1	Existing Wireless Network Model	5-2
5.1.2	IMT-2000 Network	5-5
5.2	Wireless Next Generation Network (WNGN)	5-9
5.3	Framework Architecture for WNGN	5-11
5.3.1	Definition of Functional Elements	5-13
5.3.1.1	Wireless Call Connection Agent (WCCA)	5-13
5.3.1.2	Radio Access Network Gateway (RAN-GW)	5-15
5.3.1.3	2G Gateway (2G-GW)	5-16
5.3.1.4	Trunk Gateway (T-GW)	5-16
5.3.1.5	Signaling Gateway (S-GW)	5-16
5.3.1.6	Packet Gateway	5-17

5.3.1.7	Home Subscriber Server (HSS)	5-17
5.3.1.8	Application Servers (AppSs)	5-18
5.3.2	Description of Interfaces	5-18
5.3.2.1	HSS - WCCA/SA	5-18
5.3.2.2	WCCA - MS	5-18
5.3.2.3	HSS - S-GW	5-18
5.3.2.4	WCCA - Multimedia IP networks	5-18
5.3.2.5	WCCA - S-GW	5-19
5.3.2.6	WCCA - WCCA	5-19
5.3.3	Quality of Service (QoS)	5-19
5.3.4	Handoff	5-19
5.3.5	Radio Network Optimization	5-20
5.3.6	Call Control	5-20
5.3.7	Security	5-21
5.3.8	Sample Call Flows	5-21
5.3.8.1	Assumptions	5-22
5.3.8.2	Successful Mobile Terminated Call Originated from PSTN	5-22
5.3.8.3	Location Registration	5-23
5.4	Summary	5-24
6.	Features and Services for NGN	6-1
6.1	Services in VOP/NGN	6-1
6.1.1	Residential Gateway Services	6-1
6.1.2	Advanced Network-Based Services	6-10
6.1.3	Architectural Requirements of the NGN to Support Multiple Services	6-12
6.1.3.1	Architectural Layering	6-12
6.1.3.2	Open Services Interface/API	6-13
6.1.3.3	Distributed Network Intelligence	6-14
6.1.4	Network Functions/Elements Needed to Support NGN Services	6-15
6.1.5	Example Advanced Services Implementation - Virtual Private Networking	6-15
6.2	Key Network Features Likely To Be Mandated for VOP/NGN	6-17
6.2.1	Local Number Portability (LNP)	6-17
6.2.1.1	LNP Feature Operation	6-17
6.2.1.2	VOP Network Impacts Associated with LNP Call Setup	6-18
6.2.1.2.1	IXC With VOP Capabilities	6-19
6.2.1.2.2	Calls to Ported Users that Originate in the VOP Network	6-20
6.2.1.2.3	Calls to Ported Users that Terminate in the VOP Network	6-21
6.2.1.3	VOP Network Impacts Associated with Routing Service- Related Messages	6-21
6.2.1.4	Other Considerations	6-22

6.2.1.4.1	Billing Impacts of Number Portability . . .	6-23
6.2.2	Enhanced 9-1-1 (E9-1-1) Service	6-24
6.2.2.1	E9-1-1 Service Description	6-24
6.2.2.2	VOP Network Impacts	6-25
6.2.2.2.1	All E9-1-1 Calls Routed to a Specified E9-1-1 Tandem in the PSTN	6-26
6.2.2.2.2	Specialized Routing of E9-1-1 Calls to the Appropriate E9-1-1 Tandem	6-27
6.2.2.2.3	Accessing an IN-Based E9-1-1 Service Implementation in the PSTN	6-28
6.2.2.2.4	Support of All E9-1-1 Functionality by the VOP Network	6-30
6.2.3	CALEA	6-33
6.2.3.1	Background	6-33
6.2.3.2	VOP Network Impacts	6-35
6.3	Operator Services in VOP/NGN	6-39
6.3.1	Introduction	6-39
6.3.2	Description of Operator Services	6-40
6.3.3	Description of Current Operator Services Architecture . . .	6-43
6.3.4	Providing Operator Services to VOP/NGN Customers Using Existing OSSs	6-46
6.3.5	Migration of OSS Components	6-49
6.3.6	Migration of OSS Core Switch, EO Operator Services Capabilities, and Feature Nodes	6-50
7.	VOP/NGN Operations	7-1
7.1	Introduction	7-1
7.1.1	Business Drivers	7-1
7.2	Operations Goals	7-4
7.2.1	Auto-Inventory of the Network	7-5
7.2.2	SLA and QoS Management	7-5
7.2.3	Policy Based Management	7-5
7.2.4	Customer-Self Service	7-5
7.2.5	Auto-Configuration of CPE	7-6
7.2.6	Customer and Carrier Inter-Enterprise Network Management	7-6
7.2.7	Flow-Through of Key Business Processes	7-6
7.2.8	Cross-Domain Network Management	7-7
7.2.9	Integrated Service Management	7-7
7.2.10	Bandwidth Management	7-7
7.2.11	Mobility Management	7-8
7.3	Key Business Processes	7-8
7.3.1	TeleManagement Forum Telecom Operations Map	7-9
7.3.2	Service Fulfillment	7-9
7.3.2.1	Customer Interface Management	7-9
7.3.2.2	Sales	7-10
7.3.2.3	Ordering	7-10
7.3.2.4	Service Configuration	7-10

7.6.6.2	SNMP	7-41
7.6.6.3	CMIP	7-43
7.6.6.4	Bulk Data Transfer	7-44
7.6.6.5	Physical Architecture Framework and Packaging	7-44
7.7	Gap Assessment of Industry VOP/NGN Operations Activities	7-45
Appendix A: Proposed 3GPP and 3GPP2 All IP Architectures A-1		
A.1	Proposed 3GPP All IP Architecture	A-1
A.1.1	3GPP PLMN and Interfaces	A-1
A.1.1.1	3GPP All IP Network Reference Model - Option 1	A-4
A.1.1.2	3GPP All IP Network Reference Model - Option 2	A-9
A.1.2	Functional Elements in 3GPP Network Model	A-10
A.1.2.1	Call State Control Function (CSCF)	A-10
A.1.2.2	Home Subscriber Server (HSS)	A-11
A.1.2.3	Transport Signaling Gateway Function (T-SGW)	A-13
A.1.2.4	Roaming Signaling Gateway Function (R-SGW)	A-13
A.1.2.5	Composite Gateway	A-13
A.1.2.6	Media Gateway Control Function (MGCF)	A-13
A.1.2.7	Media Gateway Function (MGW)	A-14
A.1.2.8	Multimedia Resource Function (MRF)	A-14
A.1.2.9	MSC Server	A-14
A.1.2.10	Gateway MSC Server	A-15
A.1.3	Description of Reference Points	A-15
A.1.3.1	C _x Reference Point (HSS - CSCF)	A-15
A.1.3.2	G _m Reference Point (CSCF - UE)	A-15
A.1.3.3	M _c Reference Point (MGCF - MGW)	A-15
A.1.3.4	M _h Reference Point (HSS - R-SGW)	A-16
A.1.3.5	M _w Reference Point (CSCF - CSCF)	A-16
A.1.3.6	N _c Reference Points (MSC Server - GMSC Server)	A-16
A.1.3.7	N _b Reference Points (MGW-MGW)	A-16
A.1.3.8	SGSN to Applications and Services	A-16
A.1.4	General Considerations for Protocol Stack for MAP/CAP	A-17
A.2	Proposed 3GPP2 All IP Network	A-17
A.3	Alignment of 3GPP and 3GPP2 All-IP Architectures	A-21
References		References-1
Acronyms		Acronyms-1

List of Figures

Figure 3-1.	High-Level VOP Network Architecture	3-2
Figure 4-1.	H.323 Components and Architecture	4-1
Figure 4-2.	Protocol Relationships in H.323	4-4
Figure 4-3.	Direct- and Gatekeeper-Routed Call Models of H.323	4-4
Figure 4-4.	Terminal-to-Terminal	4-6
Figure 4-5.	H.323 with Gatekeeper	4-7
Figure 4-6.	Distributed Signaling	4-8
Figure 4-7.	Gatekeeper-Routed Signaling	4-9
Figure 4-8.	Directly-Homed H.323 Terminal	4-9
Figure 4-9.	Interworking Via an H.323 Customer Gateway	4-11
Figure 4-10.	Signaling for Multiple CCA Gatekeepers	4-13
Figure 4-11.	Customer Gateway Controlled via a Customer Gateway Controller	4-27
Figure 4-12.	Relationship of Customer Gateway Controller to Call Connection Agent	4-28
Figure 5-1.	Existing Wireless Network	5-3
Figure 5-2.	IMT-2000 Physical interfaces	5-5
Figure 5-3.	IMT-2000 Functional Communication	5-6
Figure 5-4.	IMT-2000 Information Flow Architecture	5-9
Figure 5-5.	Wireless NGN Functional Architecture	5-10
Figure 5-6.	WNGN Architecture	5-12
Figure 5-7.	WNGN Reference Model	5-13
Figure 5-8.	WCCA Functional Model	5-14
Figure 5-9.	Mobile Terminated Call Example	5-22
Figure 5-10.	Location Registration and Update	5-23
Figure 6-1.	Architectural Requirements of the NGN to Support Multiple Services	6-13
Figure 6-2.	Architectural Layering	6-14
Figure 6-3.	Virtual Private Networking Architecture	6-17
Figure 6-4.	E9-1-1 Calls Routed to E9-1-1 Tandem in PSTN	6-27
Figure 6-5.	Access to IN-Based E9-1-1 Service Implementation in the PSTN	6-30
Figure 6-6.	Support for E9-1-1 Functionality in VOP Network	6-31
Figure 6-7.	OSS Architecture	6-43
Figure 7-1.	TMN Logical Architecture	7-24
Figure 7-2.	Telcordia TMN Analysis/Design Methodology	7-26
Figure 7-3.	TMN Functional Layering	7-28
Figure 7-4.	The TMN Functional Matrix	7-31
Figure 7-5.	TMN Management Application Functions	7-32
Figure 7-6.	VOP/NGN EMS - Management Interfaces	7-33
Figure 7-7.	VOP/NGN CCA - Control Interfaces	7-33
Figure 7-8.	VOP/NGN Logical Management Architecture	7-35
Figure 7-9.	Primary Components in the OMG Reference Model Architecture	7-38

Figure 7-10.	Primary Components in the CORBA ORB Architecture	7-39
Figure 7-11.	A Typical CORBA Implementation Stack	7-41
Figure 7-12.	A Typical SNMP Implementation Stack	7-42
Figure 7-13.	TCP/IP Protocol Stacks	7-43
Figure A-1.	Configuration of a PLMN and Interfaces	A-2
Figure A-2.	GPRS Transmission Plane	A-3
Figure A-3.	Reference Architecture- Option 1	A-7
Figure A-4.	Reference Architecture - Option 2	A-10
Figure A-5.	Example of a Generic HSS Structure and Basic Interfaces . .	A-12
Figure A-6.	Example of HSS Structure with UMS Specific Functionality .	A-12
Figure A-7.	All IP-Network Protocol Stack for MAP/CAP	A-17
Figure A-8.	3GPP2 Wireless IP Functional Model	A-18
Figure A-9.	3GPP2 Protocol Reference Model for Simple IP	A-18
Figure A-10.	3GPP2 Protocol Reference Model for Mobile IP Control . . .	A-19
Figure A-11.	3GPP2 Protocol Reference Model for Mobile IP User Data . .	A-19
Figure A-12.	3GPP2 Accounting Model	A-20
Figure A-13.	A Proposed 3GPP2 All-IP-Network Reference Model	A-20

List of Tables

Table 4-1.	Relationship Between End-User CPE and Customer Gateway Access Interface	4-22
Table 4-2.	Differences Between DSL Bit Rate and System (Local Loop) Range	4-24
Table 5-1.	Wireless Network Elements	5-3
Table 5-2.	Interfaces in Existing Wireless Networks	5-4
Table 5-3.	Wireless Network Evolution	5-5
Table 5-4.	IMT-2000 Network Elements	5-6
Table 5-5.	IMT-2000 Interfaces	5-7
Table 7-1.	VOP/NGN - Management vs. Control	7-34