

Contents

Foreword.....	Foreword-1
1. Overview	1-1
1.1 Purpose and Scope	1-1
1.2 Definition of Terms.....	1-1
1.3 History of 9-1-1 Service.....	1-4
1.3.1 How 9-1-1 Service Works.....	1-4
1.3.2 The Benefits of 9-1-1 Service	1-5
1.4 Wireless and 9-1-1 Service	1-6
1.4.1 Location Technologies.....	1-9
1.4.1.1 Angle of Arrival (AOA)	1-9
1.4.1.2 Time Difference of Arrival (TDOA).....	1-10
1.4.1.3 Global Positioning System (GPS)	1-10
1.4.2 Location Technology Issues.....	1-11
1.4.2.1 Wireless Network Reliability	1-11
1.4.2.2 Multipath Errors.....	1-11
1.4.2.3 Roaming.....	1-11
1.4.2.4 Business/Legal Issues	1-12
2. Current 9-1-1 Network Architecture.....	2-1
2.1 Wireline 9-1-1 Service Architecture	2-1
2.2 Wireless E9-1-1 Service.....	2-3
2.2.1 Phase-II Using Call Associated Signaling (CAS) and Hybrid Approaches.....	2-5
2.2.2 Phase-II Using Non-Call Associated Signaling (NCAS) Approach	2-10
2.2.2.1 NCAS Wireline Compatibility Approach.....	2-10
2.2.2.2 NCAS Wireless Scenario.....	2-14
2.2.2.3 Summary of NCAS Scenarios and SS7 Call Setup Information	2-17
2.3 E9-1-1 Tandem to PSAP Interface.....	2-20
2.4 PSAP to ALI Interface	2-21
3. Evolution of the E9-1-1 Network.....	3-1
3.1 AIN-Based E9-1-1 Service Architecture	3-1
3.1.1 Wireline E9-1-1 Service.....	3-4
3.1.2 Wireless E9-1-1 Service.....	3-5
3.1.2.1 Call Associated Signaling (CAS) Architecture for Wireless Emergency Calls.....	3-6
3.1.2.2 Non-Call Associated Signaling (NCAS) Architecture for Wireless Emergency Calls.....	3-8
3.2 Next Generation Network E9-1-1 Service Architecture	3-9
4. Summary and Conclusions.....	4-1

Bibliography and References References-1
Glossary Glossary-1

List of Figures

Figure 2-1. E9-1-1 Architecture for Wireline Emergency Calls	2-2
Figure 2-2. Wireless E9-1-1 Phase-I	2-3
Figure 2-3. Wireless E9-1-1 Phase-II	2-4
Figure 2-4. MSC Delivers Phase-I and Phase-II Information to E9-1-1 Tandem	2-5
Figure 2-5. Timeout Waiting for Delivery of Position Information	2-7
Figure 2-6. Hybrid Approach	2-8
Figure 2-7. NCAS Wireline Compatibility Scenario	2-11
Figure 2-8. Routing Based on ESRK	2-12
Figure 2-9. Architecture for NCAS Wireless Scenario	2-15
Figure 2-10. NCAS Wireless Information Flow	2-16
Figure 2-11. PSAP to ALI Interface	2-21
Figure 2-12. Automatic Location Identification (ALI) Steering Function	2-24
Figure 3-1. Representative AIN-Based E9-1-1 Service Architecture	3-3
Figure 3-2. Example of AIN Architecture for Wireline E9-1-1 Service	3-5
Figure 3-3. Wireless E9-1-1 CAS Solution (AIN SCP Supports ALI Steering)	3-7
Figure 3-4. Wireless 9-1-1 NCAS Solution (ALI Not Part of AIN SCP)	3-8
Figure 3-5. An E9-1-1 Evolutionary Step Toward the Next Generation Network (NGN)	3-10
Figure 3-6. Next Generation Network (NGN) Interconnection with the Emergency Services Network	3-11
Figure 3-7. Next Generation E9-1-1 Network	3-12
Figure 3-8. Long-Term Vision of a Next Generation Network (NGN)	3-14

List of Tables

Table 2-1. ISUP IAM Parameter Contents for CAS and Hybrid	2-9
Table 2-2. MF Signaling Information.....	2-14
Table 2-3. MF Signaling Information for NCAS Wireless Scenario	2-17
Table 2-4. Wireless E9-1-1 Scenario.....	2-18
Table 2-5. ISUP Initial Address Message Parameter Contents for NCAS Modes.....	2-19