

## ContentsTelcordia

Special Report Notice Of Disclaimer . . . . .	iii
List of Figures . . . . .	ix
List of Tables . . . . .	xi
Foreword . . . . .	xiii
1. Introduction . . . . .	1-1
1.1 Purpose of Document . . . . .	1-2
1.2 Structure of Document . . . . .	1-2
2. Overview of xDSL . . . . .	2-1
2.1 Background . . . . .	2-1
2.2 DSL Technology Generic Overview . . . . .	2-1
2.3 Brief Overview of the Outside Plant (OSP) . . . . .	2-5
2.4 Modulation Techniques . . . . .	2-9
2.4.1 Quadrature Amplitude Modulation (QAM) . . . . .	2-9
2.4.2 Carrierless Amplitude Phase Modulation (CAP) . . . . .	2-10
2.4.3 Discrete Multitone Modulation (DMT) . . . . .	2-10
2.5 Limitations of xDSL . . . . .	2-10
2.5.1 Distance . . . . .	2-10
2.5.2 Load Coils . . . . .	2-11
2.5.3 Bridged Taps . . . . .	2-12
2.5.4 Location . . . . .	2-12
2.5.5 Copper Cable . . . . .	2-13
2.5.6 Interference and Crosstalk . . . . .	2-13
2.6 DSL Loop Qualification . . . . .	2-17
2.7 Summary of xDSL Advantages and Disadvantages . . . . .	2-18
2.8 The Family of DSL Technologies . . . . .	2-19
3. ADSL . . . . .	3-1
3.1 Typical Market Deployment . . . . .	3-1
3.2 Typical Service Offering . . . . .	3-2
3.3 Technology Specifics . . . . .	3-2
3.3.1 Full-Rate ADSL . . . . .	3-2
3.3.1.1 Typical Architecture . . . . .	3-3
3.3.1.2 Frequency Spectrum Utilized . . . . .	3-4
3.3.1.3 Bandwidth Available . . . . .	3-4
3.3.1.4 Advantages of the Technology . . . . .	3-5
3.3.1.5 Disadvantages of the Technology . . . . .	3-5
3.3.1.6 Standards Activities for Full-Rate ADSL . . . . .	3-6
3.3.1.7 Future of Full-Rate ADSL . . . . .	3-7
3.3.2 ADSL-Lite . . . . .	3-8
3.3.2.1 Typical Architecture . . . . .	3-8
3.3.2.2 Frequency Spectrum Utilized . . . . .	3-9
3.3.2.3 Bandwidth Available . . . . .	3-9
3.3.2.4 Advantages of the Technology . . . . .	3-10
3.3.2.5 Disadvantages of the Technology . . . . .	3-10

3.3.2.6 Standards Activities . . . . .	3-10
3.3.2.7 Future of ADSL-Lite . . . . .	3-11
4. IDSL . . . . .	4-1
4.1 Typical Market Deployment . . . . .	4-1
4.2 Typical Service Offering . . . . .	4-1
4.3 Technology Specifics . . . . .	4-2
4.3.1 Typical Architecture . . . . .	4-2
4.3.2 Frequency Spectrum Utilized . . . . .	4-3
4.3.3 Bandwidth Available . . . . .	4-3
4.3.4 Advantages of the Technology . . . . .	4-3
4.3.5 Disadvantages of the Technology . . . . .	4-4
4.3.5.1 Loop Distance . . . . .	4-4
4.3.5.2 Premises Deployment Issues . . . . .	4-4
4.3.6 Standards Activities . . . . .	4-4
4.3.7 Future of IDSL . . . . .	4-4
5. SDSL . . . . .	5-1
5.1 Typical Market Deployment . . . . .	5-1
5.2 Typical Service Offering . . . . .	5-1
5.3 Technology Specifics . . . . .	5-2
5.3.1 Typical Architecture . . . . .	5-3
5.3.2 Frequency Spectrum Utilized . . . . .	5-4
5.3.3 Bandwidth Available . . . . .	5-4
5.3.4 Advantages of the Technology . . . . .	5-4
5.3.5 Disdvantages of the Technology . . . . .	5-5
5.3.5.1 Loop Distance . . . . .	5-5
5.3.5.2 Premises Deployment Issues . . . . .	5-5
5.3.5.3 Spectrum Management . . . . .	5-6
5.3.6 Standards Activities . . . . .	5-6
5.3.7 Future of SDSL . . . . .	5-7
6. HDSL(1-2) . . . . .	6-1
6.1 Typical Market Deployment . . . . .	6-1
6.2 Typical Service Offering . . . . .	6-1
6.3 Technology Specifics . . . . .	6-2
6.3.1 Typical Architecture . . . . .	6-3
6.3.2 Frequency Spectrum Utilized . . . . .	6-4
6.3.3 Bandwidth Available . . . . .	6-4
6.3.4 Advantages of the Technology . . . . .	6-4
6.3.5 Disadvantages of the Technology . . . . .	6-5
6.3.5.1 Loop Distance . . . . .	6-5
6.3.5.2 Deployment Issues . . . . .	6-5
6.3.5.3 Spectrum Management . . . . .	6-6
6.3.6 Standards Activities . . . . .	6-6
6.3.7 Future of HDSL . . . . .	6-7
7. VDSL . . . . .	7-1
7.1 Typical Market Deployment . . . . .	7-1
7.2 Typical Service Offering . . . . .	7-2

7.3 Technology Specifics . . . . .	7-3
7.3.1 Typical Architecture . . . . .	7-3
7.3.2 Frequency Spectrum Utilized . . . . .	7-5
7.3.3 Bandwidth Available . . . . .	7-5
7.3.4 Advantages of the Technology . . . . .	7-6
7.3.5 Disadvantages of the Technology . . . . .	7-7
7.3.5.1 Loop Distance . . . . .	7-8
7.3.5.2 Deployment Issues . . . . .	7-8
7.3.5.3 Spectrum Management . . . . .	7-9
7.3.6 Standards Activities . . . . .	7-9
7.3.7 Future of VDSL . . . . .	7-10
8. xDSL Security Overview . . . . .	8-1
8.1 Introduction . . . . .	8-1
8.2 Security Framework . . . . .	8-1
8.3 Security Issues . . . . .	8-2
8.4 Security Directions . . . . .	8-3
8.5 Subscriber Security Measures . . . . .	8-3
8.6 Security Products . . . . .	8-4
Appendix A: Alternatives to DSL for Broadband Data Access . . . . .	A-1
A.1 HFC Networks and Cable Modems . . . . .	A-1
A.2 Fiber-Based Access Technologies . . . . .	A-3
A.3 Wireless Access Technologies . . . . .	A-5
Appendix B: xDSL Vendors and Products . . . . .	B-1
B.1 Semiconductor Equipment Suppliers . . . . .	B-1
B.2 Modem Equipment Suppliers . . . . .	B-2
B.3 Access Network Equipment Suppliers . . . . .	B-3
Appendix C: Bibliography and References . . . . .	C-1
C.1 Telcordia Documents . . . . .	C-1
C.2 ANSI Documents . . . . .	C-3
C.3 ETSI Document . . . . .	C-3
C.4 ITU-T Document . . . . .	C-4
C.5 Miscellaneous Publications . . . . .	C-5
C.6 Assorted Internet Sites . . . . .	C-6
Appendix D: Glossary . . . . .	D-1



## List of Figures

Figure 2-1	High-Level View of a Typical xDSL Architecture . . . . .	2-2
Figure 2-2	High-Level View of the xDSL Architecture with a Digital Loop Carrier (DLC) . . . . .	2-3
Figure 2-3	ADSL and POTS Frequency Spectrum . . . . .	2-4
Figure 2-4	High-Level View of the Outside Plant (OSP) . . . . .	2-6
Figure 2-5	Outside Plant (OSP) Architecture . . . . .	2-7
Figure 2-6	Bridged Tap - from the CO to the Customer Premises . . . . .	2-8
Figure 2-7	Photograph of a Binder Group . . . . .	2-9
Figure 2-8	Graph of Available Data Rates (Mbps) versus Loop Length [kilofeet (kft)] for 24-Gauge Cable . . . . .	2-11
Figure 2-9	Diagram of Near-End Crosstalk (NEXT) - Interference Occurs on the Same Side of the Binder Group . . . . .	2-15
Figure 2-10	Diagram of Far-End Crosstalk (FEXT) - Interference Occurs at Opposite Sides of the Binder Group . . . . .	2-15
Figure 2-11	Diagram of Ingress. Ingress Occurs when External Signals, Such as those from Radio Stations, Leak into Unshielded Wiring . . . . .	2-16
Figure 3-1	ADSL over Copper Loop Typical Architecture . . . . .	3-4
Figure 3-2	ADSL-Lite over Copper Loop Typical Architecture . . . . .	3-9
Figure 4-1	IDSL over Copper Loop Typical Architecture . . . . .	4-3
Figure 5-1	SDSL over Copper Loop Typical Architecture . . . . .	5-3
Figure 6-1	HDSL over Copper Loop Typical Architecture . . . . .	6-3
Figure 7-1	Diagram of VDSL Off of Fiber to the Node . . . . .	7-4
Figure A-1	High-Level View of a Hybrid Fiber-Coaxial Network . . . . .	A-3



## List of Tables

Table 2-1	Types of DSL and General Information about Each . . . . .	2-20
Table 3-1	Downstream Data Speeds for Full-Rate ADSL . . . . .	3-6
Table 7-1	Physical Bandwidth Proposed for VDSL . . . . .	7-6
Table 7-2	Loop Lengths and Data Rates for VDSL . . . . .	7-8
Table 8-1	Hardware Firewall Security Products . . . . .	8-4
Table 8-2	Software Firewall Security Products . . . . .	8-5
Table B-1	Chart of Selected xDSL Vendors and Products . . . . .	B-4