

## Contents

Special Report Notice of Disclaimer . . . . .	iii
1. Introduction . . . . .	1-1
2. National ISDN . . . . .	2-1
2.1 Steps Toward National ISDN . . . . .	2-1
2.2 National ISDN-1 . . . . .	2-1
2.3 National ISDN-2 . . . . .	2-2
2.4 National ISDN-3 . . . . .	2-3
3. National ISDN-2 - Detailed Content . . . . .	3-1
3.1 Access, Call Control, and Signaling . . . . .	3-2
3.1.1 Primary Rate Interface Switching and Signaling Capabilities . . . . .	3-3
3.1.2 Primary Rate Interface Interworking with SS7 . . . . .	3-3
3.2 Uniform Interface Configurations for Basic Rate Interfaces . . . . .	3-3
3.2.1 Support of More Than Two B-Channel Terminals on a BRI . . . . .	3-4
3.2.2 Support of DN Sharing over Multiple Call Types on an Integrated Terminal . . . . .	3-4
3.3 Uniformity of Basic Rate Interface Services . . . . .	3-4
3.3.1 Electronic Key Telephone Service . . . . .	3-4
3.3.2 ISDN Call Forwarding . . . . .	3-5
3.3.3 ISDN Call Hold . . . . .	3-5
3.3.4 Additional Call Offering . . . . .	3-5
3.3.5 Flexible Calling . . . . .	3-6
3.3.6 Calling Number Identification Services for BRI . . . . .	3-6
3.3.7 ISDN Display Service . . . . .	3-6
3.4 Primary Rate Interface Capabilities . . . . .	3-7
3.4.1 Call-by-Call Service Selection . . . . .	3-7
3.4.2 Calling Number Identification Services for PRI . . . . .	3-7
3.4.3 Switched DS1/Switched Fractional DS1 Service Capability . . . . .	3-8
3.4.4 Interworking With Private Networks . . . . .	3-8
3.5 Improved Data Capabilities . . . . .	3-8
3.5.1 User-Originated, On-Demand B-Channel Packet on BRI . . . . .	3-8
3.5.2 Public Packet-Switched Network Capabilities . . . . .	3-8
3.5.3 ISDN X.25 Local Charging Prevention . . . . .	3-9
3.6 Operations Support Capabilities . . . . .	3-9
3.6.1 Parameter Downloading . . . . .	3-9
3.6.2 Priority Items from the Operations Feature Matrix . . . . .	3-9
3.6.2.1 Trouble Verification - TEI Assignment Abnormality Log (OFM 5) . . . . .	3-10
3.6.2.2 Data Link (Layer 2) Transmission Performance Monitoring (OFM 13) . . . . .	3-10
3.6.2.3 Layer 2 and 3 Service Disruption/High Abnormality Rate Monitoring (OFM 14) . . . . .	3-10
3.6.2.4 Layer 2 and 3 Protocol Abnormality Log (OFM 15) . . . . .	3-11
3.6.2.5 Logging and Processing TEI Abnormalities (OFM 18) . . . . .	3-11

- 3.6.2.6 Automatic Internal Administration for Packet Handlers (OFM 126) . . . . . 3-11
- 3.6.2.7 PRI Service Disruption D-Channel Backup Monitoring (OFM 130) . . . . . 3-11
- 3.6.2.8 PRI Performance Monitoring/Surveillance (OFM 131) . . . . . 3-12
- 3.6.2.9 PRI Access and Testing (OFM 132) . . . . . 3-12
- 3.6.2.10 Protocol Capture TL1 Messages (OFM 133) . . . . . 3-12
- 3.6.2.11 Protocol Abnormality Log Retrieval (OFM 134) . . . . . 3-13
- 3.6.2.12 PRI Surveillance Layers 2 and 3 (OFM 135) . . . . . 3-13
- 3.6.2.13 Maintenance Operations for PRI D-Channel Backup (OFM 137) . . . . . 3-13
- 3.6.2.14 Message Service Maintenance (OFM 147) . . . . . 3-13
- 3.6.2.15 Service Profile Identifier Provisioning (OFM 150) . . . . . 3-13
- 3.7 Billing Capabilities . . . . . 3-14
  - 3.7.1 Usage Measurements for Basic Rate Interface Features . . . . . 3-14
  - 3.7.2 Usage Measurements for Primary Rate Interface Features . . . . . 3-14
  - 3.7.3 Single Stream for Circuit-Mode and Packet-Mode AMA . . . . . 3-15
  - 3.7.4 Usage Measurements for Packet-Switched Data Services . . . . . 3-15
- Appendix A: Listing of NI-2 Network Features (Matrix Form) . . . . . A-1
- Appendix B: Detailed Definition of NI-2 Content . . . . . B-1
  - B.1 Access, Call Control, and Signaling . . . . . B-1
    - B.1.1 Primary Rate Interface Switching and Signaling Requirements . . . . . B-1
      - B.1.1.1 Circuit-Mode Voice (Speech/3.1 kHz Audio) Call Control . . . . . B-1
      - B.1.1.2 Circuit-Mode Data (56/64 kbps) Call Control . . . . . B-1
      - B.1.1.3 Packet-Mode Data (Provisioned B-Channel) Call Control . . . . . B-2
      - B.1.1.4 Multiple DS1 Facilities Controlled by a Single D-Channel . . . . . B-2
      - B.1.1.5 D-Channel Backup . . . . . B-2
      - B.1.1.6 Access to Selected Primary Rate Services on a Per-Call Basis . . . . . B-2
      - B.1.1.7 TR-NWT-001268 Exceptions Acceptable for NI-2 . . . . . B-2
    - B.1.2 Primary Rate Interworking with Signaling System #7 . . . . . B-3
  - B.2 Uniform Interface Configurations for Basic Rate Interfaces . . . . . B-4
    - B.2.1 Support of More Than Two B-Channel Terminals on a BRI . . . . . B-4
    - B.2.2 Support of DN Sharing over Multiple Call Types on an Integrated Terminal . . . . . B-5
  - B.3 Uniformity of Basic Rate Interface Services . . . . . B-5
    - B.3.1 Electronic Key Telephone Service . . . . . B-6
      - B.3.1.1 Multiple Directory Numbers per Terminal . . . . . B-6
      - B.3.1.2 Analog Member in an EKTS Group . . . . . B-6
      - B.3.1.3 Multiple Directory Number Appearances/Call Appearance Call Handling . . . . . B-6
      - B.3.1.4 Hold/Retrieve . . . . . B-7
      - B.3.1.5 Bridging/DN-Bridging . . . . . B-7
      - B.3.1.6 Intercom Calling . . . . . B-7
      - B.3.1.7 Membership in a Multiline Hunt Group . . . . . B-7
      - B.3.1.8 Abbreviated Ringing and Delayed Ringing . . . . . B-8
      - B.3.1.9 Automatic and/or Manual Bridged Call Exclusion . . . . . B-8
    - B.3.2 ISDN Call Forwarding . . . . . B-8
      - B.3.2.1 Call Forwarding Variable . . . . . B-9

B.3.2.2	Call Forwarding Interface Busy . . . . .	B-9
B.3.2.3	Call Forwarding Don't Answer . . . . .	B-10
B.3.3	ISDN Call Hold . . . . .	B-10
B.3.3.1	Hold and Retrieve . . . . .	B-10
B.3.3.2	B-Channel Reservation (Excluding Release) . . . . .	B-10
B.3.4	Additional Call Offering (Circuit-Mode Only) . . . . .	B-11
B.3.4.1	Additional Call Offering - Unrestricted . . . . .	B-11
B.3.4.2	Notification Busy Limit . . . . .	B-11
B.3.5	Flexible Calling . . . . .	B-11
B.3.5.1	Conference Calling (Three-Port and Six-Port) . . . . .	B-11
B.3.5.2	Consultation Hold . . . . .	B-12
B.3.5.3	Implicit Call Transfer . . . . .	B-12
B.3.5.4	Explicit Call Transfer . . . . .	B-12
B.3.5.5	Drop Last Call on Conference . . . . .	B-13
B.3.6	Calling Number Identification Services for BRI . . . . .	B-13
B.3.6.1	Delivery of Network-Provided Calling Number . . . . .	B-13
B.3.6.2	Privacy of Calling Number . . . . .	B-14
B.3.6.3	Delivery of Redirecting Number . . . . .	B-14
B.3.6.4	Privacy of Redirecting Number . . . . .	B-14
B.3.6.5	Delivery of Redirecting Reason . . . . .	B-14
B.3.6.6	Ability to Segregate Number Delivery on Inter-BBG/Intra-BBG Basis . . . . .	B-15
B.3.7	ISDN Display Service . . . . .	B-15
B.3.7.1	Uniform Text (For NI-2 Uniform Services) . . . . .	B-15
B.4	Primary Rate Interface Capabilities . . . . .	B-15
B.4.1	Call-by-Call Service Selection . . . . .	B-15
B.4.2	Calling Number Identification Services (PRI) . . . . .	B-16
B.4.2.1	Delivery of Network-Provided Calling Number . . . . .	B-17
B.4.2.2	Privacy of Calling Number . . . . .	B-17
B.4.2.3	Delivery of Redirecting Number . . . . .	B-17
B.4.2.4	Privacy of Redirecting Number . . . . .	B-18
B.4.2.5	Delivery of Redirecting Reason . . . . .	B-18
B.4.2.6	Screening Functions . . . . .	B-18
B.4.3	Switched DS1/Switched Fractional DS1 Service Capability . . . . .	B-18
B.4.4	Interworking with Private Networks . . . . .	B-19
B.5	Improved Data Capabilities . . . . .	B-20
B.5.1	User-Originated, On-Demand B-Channel Packet on BRI . . . . .	B-20
B.5.2	Public Packet-Switched Network Capabilities . . . . .	B-20
B.5.2.1	Clearing Subnetwork Identification for X.75' . . . . .	B-20
B.5.2.2	Transit Subnetwork Count for X.75' . . . . .	B-20
B.5.2.3	Multilink Procedures on X.75/X.75' . . . . .	B-21
B.5.2.4	Support of X.75 End Office Connections . . . . .	B-21
B.5.3	ISDN X.25 Local Charging Prevention . . . . .	B-21
B.6	Operations Support Capabilities . . . . .	B-22
B.6.1	Parameter Downloading . . . . .	B-22
B.6.2	Priority Items from the Operations Feature Matrix . . . . .	B-22
B.6.2.1	Trouble Verification - TEI Assignment Abnormality Log (OFM 5) . . . . .	B-24

B.6.2.2	Data Link (Layer 2) Transmission Performance Monitoring (OFM 13)	B-24
B.6.2.3	Layer 2 and Layer 3 Service Disruption/High Abnormality Rate Monitoring (OFM 14)	B-24
B.6.2.4	Layer 2 and Layer 3 Protocol Abnormality Log (OFM 15)	B-25
B.6.2.5	Logging and Processing TEI Abnormalities (OFM 18)	B-25
B.6.2.6	Automatic Internal Administration for Packet Handlers (OFM 126)	B-25
B.6.2.7	Primary Rate Interface Service Disruption D-Channel Backup Monitoring (OFM 130)	B-26
B.6.2.8	Primary Rate Interface Performance Monitoring/Surveillance (OFM 131)	B-26
B.6.2.9	Primary Rate Interface Access and Testing (OFM 132)	B-26
B.6.2.10	Protocol Capture TL1 Messages (OFM 133)	B-27
B.6.2.11	Protocol Abnormality Log/Retrieval Messages (OFM 134)	B-27
B.6.2.12	Primary Rate Interface Surveillance Layers 2 and 3 (OFM 135)	B-27
B.6.2.13	Maintenance Operations for Primary Rate Interface D-Channel (Backup (OFM 137)	B-27
B.6.2.14	Message Service Maintenance (OFM 147)	B-28
B.6.2.15	Service Profile Identifier Provisioning (OFM 150)	B-28
B.7	Billing Capabilities	B-28
B.7.1	Usage Measurements for Basic Rate Interface Features	B-28
B.7.1.1	Basic Business Group Dial Access Subfeatures	B-29
B.7.1.2	Calling Number Identification Services without Intra-BBG/Inter-BBG Segregation	B-29
B.7.2	Usage Measurements for Primary Rate Interface Features	B-29
B.7.2.1	Basic Call Control and Signaling	B-29
B.7.2.2	Switched DS1/Switched Fractional DS1 Service Capability	B-29
B.7.3	Single Stream for Circuit-Mode and Packet-Mode Automatic Message Accounting	B-29
B.7.4	Usage Measurements for Packet-Switched Data Services	B-30
B.7.4.1	ISDN X.25 Local Charging Prevention	B-30
B.7.4.2	X.75 and X.75' Utility Support	B-30
B.7.4.3	User-Originated, On-Demand B-Channel Packet on BRI	B-30
B.7.4.4	Single Automatic Message Accounting for Intra-Network, Multi-Supplier Packet Calls	B-31
Appendix C:	Description of Service Uniformity Concepts and Terms	C-1
C.1	Introduction	C-1
C.2	Feature Operations	C-2
C.3	Documented Feature Interactions	C-3
C.4	Undocumented Feature Interactions	C-3
Appendix D:	Operations Feature Matrix (OFM)	D-1
Appendix E:	Glossary	E-1
Appendix F:	References	F-1