

Table of Contents

1 Introduction

1.1 Purpose and Scope	1-1
1.2 Scope	1-1
1.3 Relationship to Other Telcordia Documentation	1-1
1.3.1 ISDN Primary Rate Interface	1-1
1.3.2 ISDN Basic Rate Access	1-2
1.4 CPE Guidelines Terminology	1-2
1.5 Network Terminology	1-3

2 Bearer Services and Interface Configuration

2.1 Bearer Services Supported	2-1
2.1.1 Circuit-Mode, 64-kbps, 8-kHz Structured, Speech, Demand	2-2
2.1.2 Circuit-Mode, 64-kbps, 8-kHz Structured, 3.1-kHz Audio Information Transfer, Demand	2-2
2.1.3 Circuit-Mode, 64-kbps, 8kHz Structured, Unrestricted Digital Transmission- Rate Adapted from 56-kbps, Demand	2-3
2.1.4 Circuit-Mode, 64-kbps, 8-kHz Structured, Unrestricted Digital Transmission (64 kbps), Demand	2-3
2.1.5 Circuit-Mode, nx64-kbps ($2 \leq n \leq 24$) 8-kHz Structured, Unrestricted Digital Transmission, Demand	2-3
2.1.6 Packet-Mode, Unrestricted Digital Information, Virtual Call and Permanent Virtual Circuit Service	2-4
2.2 Interface Configuration	2-4
2.2.1 Physical Interface Configuration	2-4
2.2.2 Functional Interface Configuration	2-7
2.2.2.1 Non-Facility Associated Signaling	2-7
2.2.2.2 D-Channel Backup	2-7
2.2.2.3 Simulated Facility Group for Direct Inward/Outward Dial (DID/DOD)	2-8

3 Physical Layer

3.1 Scope of Physical Layer Specifications	3-1
3.2 Terminating Impedance	3-1
3.2.1 Impedance and Return Loss	3-1
3.2.2 Longitudinal Balance	3-2
3.3 Transmission Rate and Synchronization	3-2
3.4 Line Code	3-3
3.5 Interface Signal Characteristics	3-4
3.5.1 Standard Pulse Characteristics	3-4
3.5.2 NI Signal Characteristics	3-5
3.5.2.1 Network Signal Characteristics at the NI	3-5
3.5.2.2 CPE Signal Characteristics at the NI	3-5
3.5.2.3 U Reference Point I_a Receiver Operation	3-6
3.5.3 S and T Reference Point Transmit/Receive Signal Characteristics	3-7
3.5.3.1 S and T Reference Point DSX-1 Signal Characteristics	3-7

3.5.3.2 S and T Reference Point I_a/I_b Transmit/Receive Signal Characteristics	3-7
3.6 Wander	3-8
3.6.1 Receive Signal Wander	3-9
3.6.2 Transmit Signal Wander	3-10
3.7 Jitter	3-11
3.7.1 PUB 43801 Jitter Requirements	3-11
3.7.2 ANSI T1.408 Jitter Recommendations	3-12
3.7.2.1 Receive Signal Jitter	3-12
3.7.2.2 Transmit Signal Jitter	3-12
3.8 Phase Transients	3-13
3.8.1 Receive Signal Transients	3-13
3.8.2 Transmit Signal Transients	3-14
3.9 Powering Arrangements	3-14
3.10 ESF Frame Format and Channel Combinations	3-14
3.10.1 Framing Bit Allocation	3-15
3.10.2 Cyclic Redundancy Check (CRC)	3-15
3.10.3 Channel Time Slot Assignment Rules	3-16
3.10.4 Bit Transmission Order	3-17
3.10.5 Codes for Idle Channels and Idle Time Slots	3-17
3.11 Physical Characteristics	3-17
3.11.1 Interface Cable Requirements	3-18
3.11.2 Wiring Polarity Integrity	3-18
3.11.3 Connector	3-19
3.11.4 Interworking of DSX-1 and ANSI T1.408 Interfaces	3-19

4 Link Layer Protocol

4.1 Link Layer Requirements for D-Channel Call Control Signaling	4-1
4.2 Timers and Counters	4-2

5 Call Control Procedures for Circuit-Switched Calls

5.1 Inband Tones and Announcements	5-1
5.1.1 Provision of Tones and Announcements	5-1
5.1.2 Intercept Announcements	5-2
5.2 Interworking	5-3
5.2.1 Call Origination - Interworking within the Customer's Premises	5-3
5.2.2 Call Origination - Interworking within the Network	5-4
5.2.3 Call Termination - Interworking within the Network	5-4
5.2.4 Call Termination - Interworking within the Customer's Premises	5-5
5.3 Delay Procedures	5-6
5.3.1 Delay Procedures Performed by the Network	5-6
5.3.2 Delay Procedures Performed by the CPE	5-6
5.4 B-Channel Selection	5-6
5.4.1 B-Channel Selection Algorithm	5-6
5.4.2 Originating B-Channel Selection	5-7
5.4.3 Terminating B-Channel Selection	5-7
5.5 Addressing Information - En Bloc Signaling	5-7
5.5.1 Called Party Number	5-8
5.5.2 Transit Network Selection	5-9
5.5.3 Operator System Access	5-9

5.6 Timers	5-10
----------------------	------

6 Call Control Switching and Signaling for Circuit-Switched Calls

6.1 Call Origination	6-1
6.1.2 Call Reference Selection	6-1
6.1.3 Bearer Services Selection	6-2
6.1.4 B Channel Selection	6-2
6.1.5 B Channel Cut-Through	6-2
6.1.6 Mis dialing Treatments	6-3
6.1.7 Expiration of Timer T303	6-5
6.1.8 Call Proceeding	6-5
6.1.9 Notification of Interworking	6-5
6.1.10 Notification of Delay	6-6
6.1.11 Call Confirmation Indication	6-6
6.1.12 Call Connected	6-7
6.1.13 Call Rejection	6-7
6.2 Call Termination	6-7
6.2.1 Compatibility Checking	6-8
6.2.1.1 Addressing Information Compatibility Check	6-8
6.2.1.2 Bearer Service Compatibility Check	6-8
6.2.2 Additional Compatibility Check	6-9
6.2.3 Channel Selection	6-9
6.2.4 CPE Determined Busy	6-10
6.2.5 Call Confirmation	6-10
6.2.5.1 Call Proceeding Indication	6-10
6.2.5.2 Call Received Indication	6-11
6.2.5.3 Call Accept	6-11
6.2.6 Active Indication	6-12
6.2.7 Notification of Interworking at the Terminating Interface	6-12
6.2.8 Call Failure	6-13
6.3 Call Clearing	6-14
6.3.1 Exception Conditions	6-14
6.3.2 Normal Call Clearing Initiated by the CPE	6-16
6.3.3 Normal Call Clearing Initiated by the SPCS	6-16
6.3.4 Clear Collision	6-17
6.4 Error Procedures	6-17
6.4.1 Protocol Discriminator Error	6-17
6.4.2 Message Too Short	6-17
6.4.3 Call Reference Procedural Errors	6-17
6.4.4 Message Type or Message Sequence Errors	6-19
6.4.5 Information Element Errors	6-19
6.4.6 Mandatory Information Element Errors	6-19
6.4.6.1 Mandatory Information Element Missing	6-19
6.4.6.2 Mandatory Information Element Content Error	6-20
6.4.7 Non-Mandatory Information Element Error	6-20
6.4.7.1 Unrecognized Information Elements	6-20
6.4.7.2 Information Element Content Error	6-21
6.4.7.3 Unexpected Recognized Information Element	6-21
6.4.8 Data Link Failure	6-21
6.4.9 STATus ENquiry Procedure	6-22

6.4.10	Receiving a STATus Message	6-22
6.4.11	Restart Procedures	6-23
6.4.11.1	Sending REStart Message	6-23
6.4.11.2	Receipt of a REStart Message	6-24
7	Packet-Switched Call Control Procedures	
7.1	Call Origination	7-1
7.1.1	Semi-Permanent B Channel	7-1
7.1.2	On-Demand B-Channel Connection	7-2
7.2	Call Offering	7-3
7.2.1	No Notification	7-4
7.2.2	Conditional Notification	7-5
7.2.3	Unconditional Notification	7-6
7.3	Call Clearing	7-10
7.3.1	Semi-Permanent B Channel	7-11
7.3.2	On-Demand B Channel	7-11
7.4	Packet Layer Requirements	7-12
7.4.1	Logical Channels	7-12
7.4.2	Packet Window Size	7-13
7.4.3	Packet Size	7-13
7.4.4	Throughput Class	7-13
7.4.5	Type of Number/Numbering Plan Identification	7-13
7.5	Packet Level Timers	7-14
8	Layer 3 Messages And Information Elements	
8.1	Message Functional Definitions	8-1
8.1.1	Overview	8-1
8.1.2	Messages	8-2
8.1.2.1	ALERTing	8-4
8.1.2.2	CALL PROcEeding	8-5
8.1.2.3	CONNect	8-6
8.1.2.4	CONNect ACKnowledge	8-7
8.1.2.5	DISConnect	8-7
8.1.2.6	PROGress	8-8
8.1.2.7	RELease	8-9
8.1.2.8	RELease COMplete	8-10
8.1.2.9	REStart	8-11
8.1.2.10	REStart ACKnowledge	8-12
8.1.2.11	SERVice	8-13
8.1.2.12	SERVice ACKnowledge	8-14
8.1.2.13	SETUP	8-16
8.1.2.14	STATus	8-21
8.1.2.15	STATus ENQuiry	8-22
8.2	Message Structure	8-22
8.2.1	Overview	8-23
8.2.2	Protocol Discriminator	8-24
8.2.3	Call Reference	8-24
8.2.4	Message Type	8-26
8.2.5	Other Information Elements	8-27
8.2.5.1	Locking Shift Information Elements	8-30

8.2.5.2 Bearer Capability	8-30
8.2.5.3 Call State	8-35
8.2.5.4 Called Party Number	8-38
8.2.5.5 Called Party Subaddress (F)	8-40
8.2.5.6 Calling Party Number	8-41
8.2.5.7 Calling Party Subaddress (F)	8-44
8.2.5.8 Cause	8-45
8.2.5.9 Channel Identification	8-53
8.2.5.10 Closed User Group (F)	8-56
8.2.5.11 End-to-End Transit Delay (F)	8-58
8.2.5.12 High-Layer Compatibility	8-59
8.2.5.13 Information Rate (F)	8-63
8.2.5.14 Low-Layer Compatibility	8-66
8.2.5.15 Network-Specific Facilities	8-77
8.2.5.16 Packet-Layer Binary Parameters (F)	8-80
8.2.5.17 Packet-Layer Window Size (F)	8-82
8.2.5.18 Packet Size (F)	8-83
8.2.5.19 Progress Indicator	8-84
8.2.5.20 Redirecting Number	8-86
8.2.5.21 Redirecting Subaddress (F)	8-90
8.2.5.22 Restart Indicator	8-91
8.2.5.23 Reverse Charging Indication (F)	8-93
8.2.5.24 Transit Delay Selection and Indication (F)	8-93
8.2.5.25 Transit Network Selection	8-95
8.2.6 National-Specific Information Elements	8-96
8.2.6.1 Change Status	8-96
8.2.6.2 Operator System Access (F)	8-96

9 D-Channel Backup

9.1 Introduction	9-1
9.2 General Protocol Description	9-2
9.2.1 Non-Facility Associated Signaling with Backup D Channel	9-2
9.2.2 Primary and Backup D Channels	9-4
9.2.3 D-Channel States	9-5
9.2.4 Difference Between Active and Standby D Channels	9-7
9.2.5 Conditions for D-Channel Switchover	9-7
9.2.6 General Protocol Guidelines	9-8
9.3 Protocol Descriptions at Layer 2 And 3	9-10
9.3.1 Initialization	9-10
9.3.2 Connection Verification Procedure on a Standby D Channel	9-11
9.3.3 Verification of an Active D Channel	9-11
9.3.4 Switchover Procedure	9-11
9.3.5 Timers	9-15
9.3.6 SERV and SERV ACK Messages in the D-Channel Backup Protocol	9-16
9.4 Messages and Information Elements	9-17

10 Maintenance

10.1 NT2 Layer-1 Maintenance Functions	10-4
10.1.1 Generate CRC	10-5
10.1.2 Monitor CRC	10-5

10.1.3	Recognize LOF	10-5
10.1.4	Recognize LOS	10-6
10.1.5	Recognize AIS	10-6
10.1.6	Generate RAI	10-6
10.1.7	Recognize RAI	10-7
10.1.8	Command/Response and Priority Messaging on the EOC	10-7
10.1.8.1	Bit-Patterned Messages	10-8
10.1.8.2	EOC Idle Code	10-9
10.1.9	Generate PRM on the EOC	10-9
10.1.9.1	Transmission Error Events	10-10
10.1.9.2	Format of Performance Report Message	10-10
10.1.10	Monitor PRM on the EOC	10-11
10.1.11	Calculate/Store PM Data	10-12
10.1.11.1	Path Monitoring Function	10-12
10.1.11.2	Line Monitoring Function	10-15
10.1.12	Line Loopback at I _a Interface	10-17
10.1.13	Test Lines at I _a Interface	10-18
10.1.14	Payload Loopback at the I _a Interface	10-18
10.1.15	Carrier Group Alarm	10-19
10.1.15.1	CFA Declaration	10-20
10.1.15.2	Trunk Conditioning	10-20
10.1.15.3	Removal From Service	10-20
10.1.15.4	Service Restoration	10-20
10.2	NT1 Layer-1 Maintenance Functions	10-21
10.2.1	Monitor Incoming DS1 Signal at I _a and I _b Interface	10-21
10.2.2	Recognize LOS	10-21
10.2.3	Generate AIS	10-22
10.2.4	Monitor Embedded Operations Channel	10-22
10.2.5	Monitor PRM	10-22
10.2.6	Calculate/Store PM Data	10-22
10.2.7	Line Loopback at the I _a Interface	10-24
10.2.8	Line Loopback at the I _b Interface	10-25
10.3	User Initiated Maintenance Capabilities	10-25
10.4	NT2 Provided Maintenance Indications to the User	10-26
10.5	NT1 Provided Maintenance Indications to the User	10-27

11 ISDN Calling Number Identification Services, I-CNIS

11.1.1	Background and Service Description	11-1
11.1.1.1	Number Provision (CPNs and RNs)	11-1
11.1.1.2	Number Screening (CPNs and RNs)	11-3
11.1.1.3	Number Privacy (CPNs and RNs)	11-3
11.1.1.4	Number Delivery (CND and RND)	11-3
11.1.1.5	Delivery of Redirecting Reason	11-4
11.1.1.6	Assignment of I-CNIS Parameters on a Per-Group-of-DNs Basis (F)	11-4
11.1.2	Service-Specific Requirements for CPE Using I-CNIS	11-5
11.1.2.1	Circuit-Mode Originating Calls	11-5
11.1.2.2	Circuit-Mode Terminating Calls	11-10
11.2	Call-by-Call Service Selection	11-15
11.2.1	Foreign Exchange Selection	11-16

11.2.1.1	Origination Treatment	11-17
11.2.1.2	Termination Treatment	11-18
11.2.1.3	Release Treatment	11-19
11.2.1.4	Simulated Facility Groups	11-19
11.2.2	Tie Trunk Selection	11-19
11.2.2.1	Origination Treatment	11-20
11.2.2.2	Termination Treatment	11-21
11.2.2.3	Release Treatment	11-22
11.2.2.4	Simulated Facility Groups	11-22
11.2.3	OUTWATS Selection	11-22
11.2.3.1	Origination Treatment	11-23
11.2.3.2	Release Treatment	11-25
11.2.3.3	Simulated Facility Groups	11-25
11.2.4	INWATS Selection	11-25
11.2.4.1	Termination Treatment	11-25
11.2.4.2	Release Treatment	11-26
11.2.4.3	Simulated Facility Groups	11-26
11.2.5	Error Procedures	11-26
11.3	Switched DS1/Switched Fractional DS1 (SWF-DS1)	11-26
11.3.1	Introduction	11-26
11.3.1.1	Bearer Capabilities Supported	11-27
11.3.1.2	Assumptions and Restrictions	11-27
11.3.1.3	Definition of Terms	11-27
11.3.2	SWF-DS1 Call Control Procedures and Parameters	11-28
11.3.2.1	SWF-DS1 Channel Selection and Subscription Parameters	11-29
11.3.2.2	SWF-DS1 Channel Selection and Channel Selection Algorithms	11-31
11.3.2.3	SWF-DS1 Specific Cause Codes	11-32
11.3.2.4	Network Determined Busy	11-33
11.3.2.5	Tones and Announcements	11-34
11.3.3	SWF-DS1 Call Processing and Signaling	11-34
11.3.3.1	Call Origination	11-34
11.3.3.2	Call Termination	11-34
11.3.3.3	Termination of Calls That Cannot be Completed	11-34
11.3.3.4	Call Clearing	11-35
11.3.3.5	Error Procedures	11-35

12 ISDN X.25-Based Packet-Mode Services

12.1	Flow Control Parameter Negotiation	12-2
12.2	Throughput Class Negotiation	12-3
12.3	Transit Delay	12-4
12.4	User Testing	12-5
12.5	Closed User Group Services	12-6
12.6	Reverse Charging Services	12-7
12.7	Recognized Private Operating Agency (RPOA) Selection	12-8
12.8	Fast Select Services	12-8
12.9	Basic Business Group	12-9
12.10	Network User Identification (NUI)	12-9
12.11	Call Deflection	12-11
12.12	Calling Line Identification	12-11
12.12.1	Number Provision	12-12

12.12.2 Number Screening 12-12
 12.12.3 Number Delivery 12-13
 12.13 CCITT-Specified DTE Facilities to Support the OSI Network Service . . . 12-13

13 Glossary

Appendix A: B-Channel Availability Control

A.1 B-Channel Status Categories A-1
 A.1.1 In-Service A-2
 A.1.2 Out-of-Service A-2
 A.2 Relationship with Restart Procedures A-3
 A.3 Sending a SERVICE Message A-3
 A.4 Receiving a SERVICE Message A-4
 A.5 Collisions A-5
 A.5.1 SERVICE Message Collision A-5
 A.5.2 SETUP Message Collision A-7
 A.6 Status Audits A-7
 A.7 Status upon Provisioning A-8
 A.8 Error Conditions A-8
 A.8.1 Receipt of a Solicited Message with Invalid Contents A-8
 A.8.2 Unsolicited SERV ACK Message A-8



List of Figures

Figure 2-1	ISDN PRI Functional Reference Configuration	2-5
Figure 2-2	ISDN PRI Configuration with BRI TEs	2-5
Figure 2-3	ISDN PRI Configuration Utilizing Internal NT1 in NT2	2-6
Figure 2-4	ISDN PRI Configuration without NT2	2-6
Figure 2-5	ISDN PRI Configuration Utilizing Internal NT1 in TE without NT2	2-7
Figure 3-1	ISDN Primary Rate Functional Reference Configuration	3-20
Figure 3-2	Standard Pulse Template and Corner Points For The Determination of NI and I_a/I_b Signal Characteristics	3-21
Figure 3-3	Pulse Amplitude Envelope with 60 Hz Longitudinal Currents	3-22
Figure 3-4	PUB 43801 Jitter Mask	3-23
Figure 3-5	ANSI T1.408 Frequency Weighting Functions for Jitter Specifications	3-24
Figure 3-6	Bit Assignments Within DS1 Frames	3-25
Figure 3-7	Illustration of Connecting Cord, Interface Cable, and Extension Cord	3-25
Figure 3-8	8-Position Non-keyed Connector	3-26
Figure 3-9	DSX-1 Compatible Interface Locations	3-27
Figure 8-1	General Message Organization Example	8-24
Figure 8-2a	Protocol Discriminator	8-24
Figure 8-2b	Maintenance Protocol Discriminator	8-24
Figure 8-3	Call Reference Information Element	8-25
Figure 8-4	Examples of the Global Call Reference Coding	8-26
Figure 8-5	Message Type	8-26
Figure 8-6	Formats of Information Elements	8-28
Figure 8-7	Locking Shift Information Element	8-30
Figure 8-8	Bearer Capability Information Element	8-31
Figure 8-9	Call State Information Element	8-36
Figure 8-10	Called Party Number Information Element	8-38
Figure 8-11	Called Party Subaddress Information Element	8-40
Figure 8-12	Calling Party Number Information Element	8-42
Figure 8-13	Calling Party Subaddress Information Element	8-44
Figure 8-14	Cause Information Element	8-46
Figure 8-15	Channel Identification Information Element	8-53
Figure 8-16	Closed User Group Information Element	8-57
Figure 8-17	End-to-End Transit Delay Information Element	8-58
Figure 8-18	High-Layer Compatibility Information Element	8-60
Figure 8-19	Information-Rate Information Element	8-64
Figure 8-20	Low-Layer Compatibility Information Element	8-67
Figure 8-21	Network-Specific Facilities Information Element	8-78
Figure 8-22	Packet-Layer Binary Parameters Information Element	8-81
Figure 8-23	Packet-Layer Window Size Information Element	8-82
Figure 8-24	Packet Size Information Element	8-83
Figure 8-25	Progress Indicator Information Element	8-84
Figure 8-26	Redirecting Number Information Element	8-87
Figure 8-27	Redirecting Subaddress Information Element	8-90
Figure 8-28	Restart Indicator Information Element	8-92
Figure 8-29	Reverse Charging Indication Information Element	8-93

Figure 8-30	Transit Delay Selection and Indication Information Element . . .	8-94
Figure 8-31	Transit Network Selection Information Element	8-95
Figure 8-32	Change Status Information Element	8-96
Figure 8-33	Operator Access Information Element	8-97
Figure 9-1	Example of Non-Facility Associated Signaling Controlling Three DS1 Facilities	9-2
Figure 9-2	Example of Non-Facility Associated Signaling with Backup D Channel Controlling Three DS1 Facilities	9-3
Figure 9-3	Example of Facility Associated Signaling on Each of Three Primary Rate Interfaces	9-3
Figure 9-4	Conceptual Architecture of PRI Interface with D-Channel Backup .	9-4
Figure 9-5	Connection Verification Procedure	9-5
Figure 9-6	D-Channel Backup - Normal Operation	9-7
Figure 9-7	Normal Switch-over (State Diagram)	9-8
Figure 9-8	Initialization Procedure	9-10
Figure 9-9	Declaring an Active D Channel as Failed	9-12
Figure 9-10	Normal Switchover (Sequence Diagram)	9-13
Figure 10-1	Performance Report Message (PRM) Structure	10-28
Figure 10-2	Carrier Failure Alarm (CFA) Timing	10-29
Figure 11-1	Dedicated Facilities Configuration	11-15
Figure 11-2	Call-by-Call Service Selection Configuration	11-16



List of Tables

Table 3-1	Extended Superframe Format Bit Assignments	3-28
Table 3-2	Contact Assignments for 8-Position Plug and Jack	3-29
Table 5-1	Relationship Between E.164 and Unknown Numbering Plans	5-8
Table 5-2	Operator Request	5-9
Table 5-3	Layer 3 Timers	5-10
Table 6-1	Misdial Cause Values	6-3
Table 6-2	Prefix Errors	6-4
Table 8-1	Messages	8-3
Table 8-2	ALERTing Message Content	8-4
Table 8-3	ALERTing Message Content	8-4
Table 8-4	CALL PROCeeding Message Content	8-5
Table 8-5	CALL PROCeeding Message Content	8-5
Table 8-6	CONNect Message Content	8-6
Table 8-7	CONNect Message Content	8-6
Table 8-8	CONNect ACKnowledge Message Content	8-7
Table 8-9	CONNect ACKnowledge Message Content	8-7
Table 8-10	DISConnect Message Content	8-7
Table 8-11	DISConnect Message Content	8-8
Table 8-12	PROGress Message Content	8-8
Table 8-13	PROGress Message Content	8-9
Table 8-14	RELease Message Content	8-9
Table 8-15	RELease Message Content	8-10
Table 8-16	RELease COMplete Message Content	8-10
Table 8-17	RELease COMplete Message Content	8-11
Table 8-18	REStart Message Content	8-11
Table 8-19	REStart Message Content	8-12
Table 8-20	REStart ACKnowledge Message Content	8-12
Table 8-21	REStart ACKnowledge Message Content	8-13
Table 8-22	SERvice Message Content	8-13
Table 8-23	SERvice Message Content	8-14
Table 8-24	SERvice ACKnowledge Message Content	8-14
Table 8-25	SERvice ACKnowledge Message Content	8-15
Table 8-26	SETUP Message Content (Sheet 1 of 2)	8-16
Table 8-27	SETUP Message Content (Sheet 1 of 3)	8-18
Table 8-28	STATus Message Content	8-21
Table 8-29	STATus Message Content	8-21
Table 8-30	STATus ENquiry Message Content	8-22
Table 8-31	STATus ENquiry Message Content	8-22
Table 8-32	Message Types	8-27
Table 8-33	Information Element Identifier Codings Defined in CCITT Recommendations - Codeset 0 (Sheet 1 of 2)	8-29
Table 8-34	Cause Classes	8-47
Table 8-35	Diagnostics	8-47
Table 8-36	CCITT-Standardized Cause Values	8-48
Table 8-37	National Specific Cause Values	8-49
Table 8-38	Network Specific Cause Value	8-49
Table 10-1	Assigned Bit-Oriented EOC Codewords	10-30

Table 10-2	Reserved Bit-Oriented EOC Codewords	10-31
Table 10-3	Example of Performance Report Message (PRM)	10-32
Table 10-4	Description of CPE Loopbacks for ISDN PRI	10-33
Table 11-1	“CPN Provision Necessary” Treatment	11-2
Table 11-2	Type of Number/Numbering Plan versus Number of Digits	11-7
Table 11-3	Type of Number/Numbering Plan vs Length of Delivered RN Value	11-13
Table 11-4	Subscription Parameters Supported by the SPCS per Interface for SWF- DS1	11-29
Table 11-5	SWF-DS1 Cause Codes	11-33
Table A-1	SERVICE Message Collisions	A-6