

Table of Contents

Special Report Notice of Disclaimer	iii
List of Figures	viii
List of Tables	ix
Executive Summary	xi

1 Introduction and Motivation

2 Applications of DCSs in the Transport Network

2.1 SONET DCSs	2-1
2.1.1 B-DCS	2-1
2.1.2 W-DCS	2-2
2.2 Specific Applications	2-3
2.2.1 Centralized and Automated OAM&P	2-3
2.2.2 Grooming	2-4
2.2.3 Add/Drop	2-5
2.2.4 Facility Rolling	2-7
2.2.5 Broadcast of Digital Signals	2-7
2.2.6 Multicasting	2-7
2.2.7 Customer-Controlled Networks	2-8
2.2.7.1 OS-Controlled Bandwidth Management Architecture	2-8
2.2.7.2 Switch-Controlled DCS Architecture	2-9
2.2.7.3 SS7-Controlled Bandwidth Management Architecture	2-9
2.2.8 DCS as a Transport SONET Gateway	2-9
2.3 Deployment of a DCS versus ADMs	2-9
2.4 Summary	2-10

3 Network Restoration Objectives

3.1 Introduction	3-1
3.2 Network Service Groupings	3-2
3.3 Network Restoration Time Objectives	3-3
3.4 Application Guidelines	3-6
3.5 Summary	3-7

4 Transport Network Architectures Using DCSs

4.1 DCS Rings	4-1
4.2 DCS Mesh	4-3
4.2.1 Point-To-Point Protection	4-3
4.2.2 Restoration by DCS Reconfiguration	4-4
4.2.2.1 Detection and Notification	4-5
4.2.2.2 Identification	4-5
4.2.2.3 Route Selection	4-5
4.2.2.4 Rerouting	4-7
4.2.2.5 Return-to-Normal	4-7
4.2.2.6 Summary of DCS Reconfiguration Methods	4-7
4.3 Summary	4-8

5 Survivability Analysis of Transport Network Architectures

5.1 Metrics of Survivability	5-1
5.2 Testbed Network, Demand and Capacity Assignment	5-2
5.3 Test Architectures	5-3
5.4 Computations	5-5
5.5 Results of the SRA	5-6

6 Cost Analysis of DCS Transport Network Architectures

6.1 Study Methodology	6-4
6.1.1 General Network Cost Characteristics	6-6
6.2 Study Results	6-7
6.2.1 Demand Sensitivity	6-7
6.2.1.1 15-Node Network	6-7
6.2.1.2 53-Node Network	6-9
6.2.2 Sensitivity to Network Connectivity	6-10
6.2.3 Cost Sensitivity	6-11
6.2.4 Worst Case Survivability (WCS)	6-12
6.3 Dual Homing Results	6-12
6.4 Conclusions	6-14

7 Distributed Control Restoration - Performance Analysis

7.1 Comparison of Five Proposals	7-2
7.1.1 General Description	7-2
7.1.2 Description of Five Algorithms Under Study	7-3
7.1.3 Method of Comparison	7-5
7.1.3.1 Study Network	7-6
7.1.3.2 Node Model	7-10
7.1.4 Algorithm Parameters	7-11
7.1.5 Failure Scenarios	7-13
7.1.6 Metrics of Comparison	7-13
7.1.7 Simulation Results	7-13
7.1.7.1 Single Link Failures	7-14
7.1.7.2 Double Link Failures	7-18
7.1.7.3 Node Failures	7-20
7.1.8 Discussion	7-23
7.2 Overall DCS Restoral Performance Issues	7-24
7.2.1 DCS Performance Effects	7-25
7.2.1.1 Generic Architecture of Present Broadband DCSs	7-25
7.2.1.2 Restoration Times Using Present DCSs	7-27
7.2.1.3 Priority Restoration	7-30
7.2.1.4 DCS Enhancements	7-33
7.3 Signaling Channel Options	7-35
7.3.1 SONET Signaling Channel Alternatives for DCS Distributed Restoration	7-36
7.3.1.1 Use of the Section Data Communications Channel	7-36
7.3.1.2 Use of the Line Data Communications Channel	7-39
7.3.1.3 Use of a Dedicated SONET Overhead Channel	7-39
7.3.1.4 Other Alternatives for SONET NE/NE Signaling	7-43
7.3.1.5 Recommendations for SONET Signaling	7-43

7.3.2 Hybrid (SONET/Asynch) Signaling Channel Alternatives for	
DCS Distributed Restoration	7-43
7.3.2.1 NE/NE Signaling Using Embedded DS1s or DS3s	7-45
7.3.2.2 NE/NE Signaling Using Compatible EOCs	7-45
7.3.2.3 Dedicated, Out-of-Band NE/NE Signaling	7-45
7.3.2.4 Other Alternatives	7-46
7.3.2.5 Recommendations for SONET/Asynchronous Signaling	7-46
7.3.3 Summary of Signaling Channel Options	7-46
7.4 Conclusions	7-47

8 Architecture Interworking

8.1 Interconnecting Ring and Mesh Architectures	8-1
8.2 Restoration Procedures in Hybrid Networks	8-4

Appendix A: References

Appendix B: Glossary

List of Figures

Figure 2-1	Functional Block Diagram of a B-DCS	2-2
Figure 2-2	Functional Block Diagram of a W-DCS	2-3
Figure 2-3	Example of Using the Add/Drop Functionality for DCSs - Conventional Method vs. DCS Approach	2-6
Figure 3-1	Restoration Time Impact on Customers	3-4
Figure 4-1	DCS Ring Network	4-2
Figure 4-2	Centralized and Distributed Control	4-4
Figure 4-3	Line and Path Restoration	4-6
Figure 5-1	Interoffice Testbed Network	5-4
Figure 5-2	Worst Case Survivability (WCS)	5-7
Figure 5-3	Expected Loss of Traffic (ELT)	5-7
Figure 5-4	Average Expected Downtime of Connection (AEDC)	5-8
Figure 5-5	Probability Distribution of Downtime of Connection (PDDC)	5-8
Figure 6-1	Example of a Topology of a 9-Node Network	6-2
Figure 6-2	Six Architecture Alternatives Using the 9-Node Network (Alternatives a-f)	6-2
Figure 6-3	Cost Sensitivity - Region of Applicability for Alternative A vs. B	6-11
Figure 7-1	Testbed Network Topology	7-7
Figure 7-2	DCS Model for Distributed Restoration	7-11
Figure 7-3	Single Link Failures (X1 Demand)	7-15
Figure 7-4	Single Link Failures (X4 Demand)	7-16
Figure 7-5	Double Link Failures (X1 Demand)	7-19
Figure 7-6	Double Link Failures (X4 Demand)	7-20
Figure 7-7	Single Node Failures (X1 Demand)	7-21
Figure 7-8	Single Node Failures (X4 Demand)	7-22
Figure 7-9	An Existing DCS Architecture Model	7-25
Figure 7-10	Cross-Connection Effect (Link Failures)	7-28
Figure 7-11	Cross-Connection Effect (Node Failures)	7-29
Figure 7-12	Individual STS-1 Restoration (cc=100)	7-31
Figure 7-13	Individual STS-1 Restoration (cc=20)	7-32
Figure 7-14	Priority Restoration	7-33
Figure 7-15	Parallel Cross-Connection Effect	7-35
Figure 7-16	SONET Transport and Path Overhead Byte Designations	7-40
Figure 7-17	Full 7-Layer Protocol Stack for SONET DCCs	7-41
Figure 7-18	DCC Communication Using OSI/CMISE	7-41
Figure 7-19	An Example of Using the DCC	7-42
Figure 7-20	Protocol Handling Effect	7-42
Figure 7-21	Example of SONET/Asynchronous DCS Network	7-44
Figure 8-1	Interconnection Between a DCS Mesh and a Dual Homing Ring Architecture	8-3

List of Tables

Table 3-1	Restoration Time Targets	3-4
Table 5-1	Failure Modes and Data Used in Study	5-5
Table 5-2	SRA Results	5-6
Table 6-1	Equipment and Fiber Costs	6-5
Table 6-2	Cost Comparisons of Alternatives as a Function of Demand (15-Node Network)	6-8
Table 6-3	Cost Comparisons of Alternatives (53-Node Network)	6-9
Table 6-4	Connectivity Tradeoffs in DCS Mesh Alternative	6-10
Table 6-5	Connectivity Tradeoffs in DCS Mesh Alternative (15-Node Subnetwork of 53-Node Network)	6-10
Table 6-6	Dual Homing Sensitivity (1x Baseline DS0 Demand)	6-13
Table 7-1	Traffic Demand	7-8
Table 7-2	Working/Spare Assignment	7-9
Table 7-3	Single Link Failures-Baseline Demand	7-16
Table 7-4	Single Link Failures - X4 Demand	7-17
Table 7-5	Single Node Failures-Baseline Demand	7-22
Table 7-6	Single Node Failures - X4 Demand	7-23