

Generic Requirements for High-Bit-Rate Digital Subscriber Lines

CONTENTS

| | |
|--|------|
| 1. Introduction | 1-1 |
| 1.1 Purpose | 1-1 |
| 1.2 HDSL as a Repeaterless T1 within a CSA | 1-1 |
| 1.2.1 Timely Service Provisioning | 1-2 |
| 1.2.2 Cost-Saving Opportunities | 1-2 |
| 1.3 Document Organization..... | 1-3 |
| 1.4 Requirements Definition and Conventions..... | 1-3 |
| 2. HDSL Overview and Related Technical References..... | 2-1 |
| 2.1 Description of the HDSL Technology | 2-1 |
| 2.2 HDSL Technology as a T1 Line Alternative | 2-2 |
| 2.2.1 Customer Service Access Configurations..... | 2-2 |
| 2.2.2 Digital Loop Carrier | 2-4 |
| 3. Loop Plant Environment..... | 3-1 |
| 3.1 CSA Loop Make-Up Criteria..... | 3-1 |
| 3.2 CSA Loop Plant Characteristics | 3-1 |
| 4. Spectrum Compatibility..... | 4-1 |
| 4.1 Crosstalk | 4-1 |
| 5. HDSL System Requirements | 5-1 |
| 5.1 Dual Duplex HDSL Architecture Requirements | 5-1 |
| 5.1.1 Normal Two-Loop Operation | 5-1 |
| 5.1.2 DS1 Signal Description | 5-2 |
| 5.1.3 General HTU Description..... | 5-3 |
| 5.1.4 HDSL Transport of DS1 Signals | 5-4 |
| 5.1.5 DS1 Signal Multiplexing in the HDSL | 5-4 |
| 5.1.6 Optional Single Loop 784 kb/s Operation..... | 5-5 |
| 5.1.7 HDSL Start-Up Procedure | 5-5 |
| 5.2 External HDSL Interfaces..... | 5-6 |
| 5.2.1 Network Side DSX-1 Interface..... | 5-6 |
| 5.2.2 Customer Side DS1 Interface | 5-6 |
| 5.2.3 Timing Reference Interface | 5-6 |
| 5.2.4 Power and Direct Current Interfaces | 5-7 |
| 5.2.5 Sealing Current..... | 5-9 |
| 5.2.6 HDSL Line Interface | 5-11 |
| 5.3 HTU Environmental Requirements | 5-11 |
| 6. Transmission Characteristics | 6-1 |
| 6.1 Transmission Method | 6-1 |

| | | |
|-------|--|------|
| 6.2 | Line Code | 6-1 |
| 6.2.1 | Characteristics of Pulses | 6-1 |
| 6.2.2 | Power Spectrum of the Transmitted Signal | 6-2 |
| 6.3 | Baud Rate | 6-3 |
| 6.4 | Jitter | 6-3 |
| 6.4.1 | HTU-R Input Signal Jitter Tolerance | 6-3 |
| 6.4.2 | HTU-R Output Jitter Limitation | 6-3 |
| 6.4.3 | HTU-C Input Signal Jitter Tolerance | 6-4 |
| 6.4.4 | HTU-C Output Jitter Limitation | 6-4 |
| 6.5 | Transmitter Linearity | 6-4 |
| 6.6 | Line Interface | 6-4 |
| 6.6.1 | Impedance and Return Loss | 6-5 |
| 6.6.2 | Longitudinal Output Voltage | 6-5 |
| 6.6.3 | HTU-R Longitudinal Balance | 6-5 |
| 6.6.4 | HTU-C Longitudinal Balance | 6-5 |
| 6.7 | HDSL Signal Frame Structure | 6-5 |
| 6.7.1 | Pictorial Quaternary View of the HDSL Frame Structure | 6-6 |
| 6.7.2 | HDSL Frame Bit Assignments | 6-6 |
| 6.7.3 | HDSL Overhead Function Requirements | 6-9 |
| 6.7.4 | Stuffing Quat/Bit Values | 6-12 |
| 6.7.5 | Summary of Proposed HDSL Overhead Function Bandwidths | - |
| | 6-13 | |
| 6.8 | Scrambling Method | 6-14 |
| 7. | Laboratory Measurement of Bit Error Ratio | 7-1 |
| 7.1 | Test Set-Up | 7-1 |
| 7.2 | Simulated Crosstalk | 7-1 |
| 7.2.1 | Calibration of Crosstalk Simulation Filter | 7-2 |
| 7.2.2 | Measurement of Simulated NEXT Power and PSD | 7-2 |
| 7.3 | Longitudinal Noise | 7-3 |
| 7.4 | Power-Related Metallic Noise | 7-3 |
| 7.5 | Test Procedure | 7-3 |
| 7.6 | Margin | 7-4 |
| 7.7 | Notes on NEXT Filter | 7-4 |
| 7.8 | Test Loops for BER Measurement | 7-5 |
| 7.8.1 | Loss Characterization of the Test Loops | 7-6 |
| 8. | HDSL Operations: Administration, Maintenance & Provisioning (OAM&P) | 8-1 |
| 8.1 | General HDSL Systems Maintenance | 8-1 |
| 8.1.1 | DS1 Service Maintenance and the DS1 Interface Connector | - |
| | 8-3 | |
| 8.1.2 | HDSL Application of DSL-type Maintenance Tools | 8-3 |
| 8.1.3 | Possible New HDSL Operations Tools | 8-4 |
| 8.2 | HDSL Operations Features and Functions | 8-4 |
| 8.3 | Out-of-Service Testing | 8-5 |
| 8.3.1 | Candidate Out-of-Service Testing Functions | 8-5 |
| 8.3.2 | HDSL Self-Tests: System and HTU Levels | 8-6 |
| 8.4 | In-Service Performance Monitoring | 8-6 |

| | | |
|--------|--|------|
| 8.5 | HDSL Maintenance Functions in Overhead Bandwidth | 8-7 |
| 8.5.1 | Embedded Operations Channel (eoc) | 8-8 |
| 8.5.2 | Candidate Overhead Bit Indicators and Bit-Invoked Functions | 8-9 |
| 8.5.3 | Cyclic Redundancy Check (crc) Code Bits | 8-10 |
| 8.5.4 | Far End Block Error (febe) Bit | 8-12 |
| 8.5.5 | Alarm Indicator Bit (aib) | 8-12 |
| 8.5.6 | DS1 Error Bit (ds1e) | 8-12 |
| 8.5.7 | Power Status (ps) Bits | 8-12 |
| 8.5.8 | HDSL Repeater Unit Present (hrp) Indicator Bit | 8-13 |
| 8.6 | Internal HDSL HTU-to-HTU Communications | 8-13 |
| 8.7 | HTU Maintenance Personnel Interface and Faceplate Features | 8-14 |
| 8.7.1 | On-site HTU Control Interface | 8-15 |
| 8.8 | Metallic Testing | 8-16 |
| 8.8.1 | Metallic Test Access | 8-16 |
| 8.8.2 | HTU-R Quiet Mode | 8-16 |
| 8.8.3 | Insertion Loss Measurement Test (ILMT) | 8-16 |
| 8.8.4 | HTU-R DC Termination | 8-16 |
| 8.9 | HDSL System Start-Up | 8-17 |
| 8.10 | HDSL Common Equipment Mounting Arrangements | 8-17 |
| 8.10.1 | Powering and Fusing | 8-18 |
| 8.10.2 | Office Alarm Contact Closures | 8-18 |
| 8.10.3 | Common Maintenance Interface | 8-18 |
| 8.10.4 | Operation System (OS) Interface | 8-18 |
| 8.10.5 | Maintainability Features for a Common Controller | 8-18 |
| 8.10.6 | Metallic Test Access to HDSL Loops | 8-18 |
| 8.10.7 | Metallic Access to the DS1 Facilities | 8-19 |
| 9. | Topics for Further Study | 9-1 |
| 9.1 | HDSL Outside Plant Line Repeater | 9-1 |
| 9.2 | Integration of HDSL into Network Elements | 9-1 |
| 10. | Miscellaneous Common Requirements | 10-1 |
| 10.1 | Physical Requirements | 10-1 |
| 10.1.1 | Shock and Vibration | 10-1 |
| 10.1.2 | HTU-C Frame | 10-1 |
| 10.1.3 | HTU-R Cabinet Housings | 10-1 |
| 10.1.4 | Human Factors | 10-1 |
| 10.1.5 | Fire Resistance | 10-1 |
| 10.2 | Environmental Requirements | 10-1 |
| 10.2.1 | Temperature and Humidity | 10-1 |
| 10.2.2 | Altitude | 10-2 |
| 10.2.3 | HTU-C Heat Dissipation | 10-3 |
| 10.2.4 | Acoustical Noise | 10-3 |
| 10.2.5 | Airborne Contaminants | 10-3 |
| 10.2.6 | Environmental Impact and Conservation | 10-3 |
| 10.2.7 | Lightning and AC Power Faults | 10-3 |
| 10.2.8 | Electromagnetic Emission and Immunity Requirements and Objectives | 10-3 |

| | | |
|--|---|------|
| 10.2.9 | Electrostatic Discharge | 10-4 |
| 10.2.10 | Steady-State Power Induction | 10-4 |
| 10.3 | Electrical Safety | 10-4 |
| 10.3.1 | Battery Safety | 10-4 |
| 10.4 | Quality and Reliability | 10-5 |
| 10.4.1 | Hardware Reliability Predictions..... | 10-5 |
| 10.4.2 | Device Reliability | 10-5 |
| 10.4.3 | Physical Design | 10-5 |
| 10.4.4 | Software Quality | 10-6 |
| 10.4.5 | Manufacturing Process | 10-6 |
| 10.4.6 | Product Support | 10-6 |
| 10.4.7 | Verification of Quality and Reliability | 10-6 |
| 10.5 | System Administration | 10-7 |
| 10.5.1 | Documentation and Supplier Information | 10-7 |
| 10.5.2 | Transmission Performance Information | 10-7 |
| REFERENCES | | R-1 |
| APPENDIX A: GLOSSARY OF ACRONYMS | | A-1 |
| APPENDIX B: CHARACTERISTICS OF THE LOOP PLANT WITHIN A CSA..... | | B-1 |

LIST OF FIGURES

| | |
|--|------|
| Figure 2-1. Dual Duplex High-bit-rate Digital Subscriber Line (HDSL) System..... | 2-5 |
| Figure 2-2. Simplified Echo-Canceler-with-Hybrid (ECH) Transceiver Structure..... | 2-6 |
| Figure 2-3. Repeaterless DS1 Access: Stand-alone HTUs..... | 2-7 |
| Figure 2-4. ISDN Primary Rate Access: Stand-alone HTUs..... | 2-7 |
| Figure 2-5. Repeaterless DS1 Access: Extension From Fiber..... | 2-8 |
| Figure 2-6. UDLC Transport: Stand-alone HTUs | 2-9 |
| Figure 2-7. IDLC Transport: Integrated HTUs..... | 2-9 |
| Figure 2-8. DLC Transport..... | 2-10 |
| Figure 4-1. Models of 1% NEXT for 18 kft of 22-AWG PIC Cable, Terminated with the Characteristic Impedance at each Frequency (NEXT Disturbance in the same Cable Binder Unit of 50 Pairs). | 4-3 |
| Figure 5-1. Signal Paths in an HDSL Terminal Unit (HTU)..... | 5-12 |
| Figure 5-2. Example Loop-side DC Characteristics of the HTU-R..... | 5-13 |
| Figure 5-3. Possible Dual Duplex HDSL Loop-Side Metallic Connections: Preliminary View | 5-14 |
| Figure 5-4. Possible Provisioned-Single-Loop HDSL Loop-Side Metallic Connections: Preliminary View | 5-15 |
| Figure 6-1. Example of 2B1Q Quaternary Symbols | 6-15 |
| Figure 6-2. Normalized Pulse from HTU-R or HTU-C Transmitter..... | 6-16 |
| Figure 6-3. Upper Bound of Power Spectral Density of Signal from HTU-R or HTU-C Transmitter..... | 6-17 |
| Figure 6-4. Range of Permissible Sinusoidal Jitter, Signal Originating from HTU-C..... | 6-18 |
| Figure 6-5. Measurement of HDSL Transmitter Linearity..... | 6-19 |
| Figure 6-6. Minimum Return Loss | 6-20 |
| Figure 6-7. HTU-R and HTU-C Longitudinal Balance..... | 6-21 |
| Figure 6-8. Pictorial Quaternary View of HDSL Frame Structure..... | 6-22 |
| Figure 6-9. Scrambler and Descrambler..... | 6-23 |

| | |
|---|------|
| Figure 7-1. HDSL Transceiver NEXT Performance Test Set-Up | 7-7 |
| Figure 7-2. PSD for Simulated Near End Crosstalk (NEXT)..... | 7-8 |
| Figure 7-3. Waveform for Longitudinal Noise..... | 7-9 |
| Figure 7-4. Power Spectral Density (PSD) of Assumed Interferers | 7-10 |
| Figure 7-5. HDSL CSA-Type Test Loops #0 to #4..... | 7-11 |
| Figure 7-6. HDSL CSA-Type Test Loops #5 to #8..... | 7-12 |
| Figure 7-7. HDSL Extended CSA-type Test Loops #9 & #10 | 7-13 |
| Figure 7-8. Loop ABCD Parameters, Impedances, and Load Voltage | 7-17 |
| Figure 8-1. HDSL crc-based In-Service Performance Monitoring..... | 8-11 |

LIST OF TABLES

| | |
|---|------|
| Table 5-1. Power Budget With Ohmic Loss of the Loops | 5-8 |
| Table 5-2. Power Budget for the HTU-R and CSU..... | 5-9 |
| Table 6-1. 2B1Q Mapping Table..... | 6-1 |
| Table 6-2. HDSL Overhead Structure Bit Assignment | 6-7 |
| Table 6-3. HDSL Overhead Structure Bit Assignment (Cont.)..... | 6-8 |
| Table 6-4. Legend of Symbols for Figure 6-8, Tables 6-2 and 6-3 | 6-9 |
| Table 6-5. Seven-Quat Barker Code Synchronization Words (SW) Patterns | 6-9 |
| Table 6-6. Quaternary-to-Binary Coding Used by HDSL Framer/De-framer..... | 6-10 |
| Table 6-7. Proposed HDSL Overhead Functions and Bandwidth Allocations | 6-13 |
| Table 7-1. $Z_L=Z_S=135\Omega$ (IL=Insertion Loss, MSL=Mean Squared Loss), Forward Direction (HTU-C to HTU-R), at 70° F..... | 7-14 |
| Table 7-2. $Z_L=Z_S=135\Omega$ (IL=Insertion Loss, MSL=Mean Squared Loss), Reverse Direction (HTU-RD to HTU-C), at 70° F..... | 7-14 |
| Table 7-3. $Z_L=Z_S=135\Omega$ (IL=Insertion Loss, MSL=Mean Squared Loss), Forward Direction (HTU-C to HTU-R), at 90° F..... | 7-15 |
| Table 7-4. $Z_L=Z_S=135\Omega$ (IL=Insertion Loss, MSL=Mean Squared Loss), Reverse Direction (HTU-RD to HTU-C), at 90° F..... | 7-15 |
| Table 7-5. $Z_L=Z_S=135\Omega$ (IL=Insertion Loss, MSL=Mean Squared Loss), Forward Direction (HTU-C to HTU-R), at 120° F..... | 7-16 |
| Table 7-6. $Z_L=Z_S=135\Omega$ (IL=Insertion Loss, MSL=Mean Squared Loss), Reverse Direction (HTU-RD to HTU-C), at 120° F..... | 7-16 |
| Table 8-1. Power Status Bit Assignments and Definitions..... | 8-13 |