

Generic Requirements for Frame Relay Access to SMDS

Contents

| | | |
|-------|---|-----|
| 1. | Introduction | 1-1 |
| 1.1 | Purpose and Scope | 1-1 |
| 1.2 | Document Organization | 1-2 |
| 1.3 | Key References | 1-2 |
| 1.4 | Requirements Terminology | 1-3 |
| 2. | Background | 2-1 |
| 2.1. | SMDS Overview | 2-1 |
| 2.1.1 | SMDS Access | 2-1 |
| 2.1.2 | The Relationship Between SMDS Access and XA-SMDS | 2-2 |
| 2.2. | Motivation for Frame Relay Access to SMDS | 2-2 |
| 2.3 | SIP Relay Interface Overview | 2-3 |
| 3. | SMDS Features | 3-1 |
| 3.1. | Feature Support for Frame Relay Access to SMDS | 3-1 |
| 3.2. | Feature Deviations for Frame Relay Access to SMDS | 3-1 |
| 3.2.1 | Number of Individual Addresses per SRI PVC | 3-1 |
| 3.2.2 | Group Address Composition Associated with an SRI PVC | 3-2 |
| 3.2.3 | Access Classes Associated with an SRI PVC | 3-2 |
| 3.2.4 | Multiple Concurrent Data Units in Transit Across an SRI PVC | 3-3 |
| 4. | SIP Relay Interface | 4-1 |
| 4.1 | Definition of the SIP Relay Interface | 4-1 |
| 4.2 | SIP Relay Interface Protocol | 4-2 |
| 4.3 | Frame Size in Support of the SRI | 4-3 |
| 4.4 | Status Signaling in Support of the SRI | 4-3 |

Contents--Continued

| | | |
|---------|--|-----|
| 5. | Architecture for Frame Relay Access to SMDS | 5-1 |
| 5.1 | Access Server (AS) Architecture | 5-2 |
| 5.1.1 | AS Interface Support | 5-2 |
| 5.1.2 | AS Interface Capacities | 5-2 |
| 5.1.3 | AS Processing Delay | 5-3 |
| 5.2 | Access Server Support of the SRI/UNI | 5-3 |
| 5.3 | The Frame Relay-to-Access Server Interface (FSI) | 5-4 |
| 5.4 | The SMDS-to-Access Server Interface (SSI) | 5-5 |
| 5.5 | Access Server Feature Support | 5-5 |
| 5.5.1 | Supporting Frame Relay Feature Processing | 5-6 |
| 5.5.2 | Supporting SMDS Feature Processing | 5-6 |
| 5.5.2.1 | Individually Addressed SMDS Data Unit Transport | 5-7 |
| 5.5.2.2 | Group Addressed SMDS Data Unit Transport | 5-7 |
| 5.6 | Modifications to SMDS SS Requirements | 5-9 |
| 6. | Operations Technology Criteria | 6-1 |
| 6.1 | Operations Communications Architecture | 6-1 |
| 6.2 | Memory Administration | 6-2 |
| 6.2.1 | Provisioning-Driven Functions | 6-3 |
| 6.2.2 | System Administration Functions | 6-3 |
| 6.2.3 | Memory Administration Data for Access Servers | 6-4 |
| 6.2.3.1 | Access Server Frame Size | 6-4 |
| 6.2.3.2 | Frame Relay Access Provisioning | 6-5 |
| 6.2.3.3 | SSI Provisioning | 6-7 |
| 6.2.3.4 | Address Screening | 6-8 |
| 6.2.3.5 | Group Addressing | 6-8 |
| 6.2.3.6 | Administered Data to Support Usage Measurements for Billing | 6-8 |

Contents--Continued

| | | |
|-----------|--|------|
| 6. | Operations Technology Criteria -- Continued | |
| 6.3 | Maintenance | 6-9 |
| 6.3.1 | Alarm Monitoring..... | 6-9 |
| 6.3.2 | Performance Monitoring | 6-10 |
| 6.3.2.1 | Common Performance Monitoring Criteria | 6-10 |
| 6.3.2.2 | Level 3 Protocol Monitoring | 6-10 |
| 6.3.2.3 | Level 2 Protocol Monitoring | 6-12 |
| 6.3.2.3.1 | Protocol Monitoring on SRI/UNIs and FSIs | 6-12 |
| 6.3.2.3.2 | SIP L2_PDU Protocol Monitoring..... | 6-14 |
| 6.3.2.4 | Physical Level Performance Monitoring | 6-14 |
| 6.3.3 | Testing | 6-15 |
| 6.4 | Network Traffic Management and Network Data Collection Criteria | 6-15 |
| 6.4.1 | General Criteria for Network Data Collection | 6-15 |
| 6.4.2 | SIP Level 3 NDC Criteria | 6-16 |
| 6.4.3 | NDC Level 2 Scheduled Measurements | 6-18 |
| 6.4.4 | Congestion Management | 6-18 |
| 6.5 | Order of Precedence Criteria..... | 6-19 |
| 6.5.1 | Order of Precedence for SRI PVCs at Ingress | 6-19 |
| 6.5.2 | Order of Precedence for SRI PVCs at Egress | 6-22 |
| 6.5.3 | Order of Precedence for SSIs | 6-23 |
| 6.6 | Operations Interface Criteria..... | 6-23 |
| 6.7 | SMDS SS Operations Impacts Related to Section 5.6 | 6-24 |
| 7. | Performance and Quality of Service | 7-1 |
| 7.1 | Availability Objectives | 7-1 |
| 7.2 | Accuracy Objectives | 7-1 |
| 7.3 | L3_PDU Delay Objectives | 7-1 |

Contents--Continued

| | |
|--|-----|
| 8. Miscellaneous | 8-1 |
| 8.1 Usage Information to Support Billing | 8-1 |
| 8.2 Miscellaneous Generic Requirements | 8-2 |
| References | R-1 |
| Acronyms and Abbreviations | A-1 |

List of Figures

| | |
|--|-----|
| Figure 2.1 DQDB-based SMDS Access | 2-2 |
| Figure 2.2 Relationship of Services | 2-2 |
| Figure 2.3 SIP Relay | 2-4 |
| Figure 2.4 Frame Relay and SMDS Communications | 2-4 |
| Figure 4.1 Frame Relay Access to SMDS | 4-1 |
| Figure 4.2 The SRI Protocol | 4-2 |
| Figure 5.1 Access Server Architecture | 5-1 |
| Figure 6.1 Potential Operations Architecture for Frame Relay Access to SMDS | 6-2 |
| Figure 7.1 Reference Connection for Delay | 7-2 |

List of Tables

| | |
|---|------|
| Table 6-1 Order-of-Precedence for SRI PVCs at Ingress | 6-21 |
| Table 6-2 Order-of-Precedence for SRI PVCs at Egress | 6-23 |
| Table 7-1 Delay (msec) for 512 Octet L3_PDU's | 7-3 |
| Table 7-2 Delay (msec) for 1600 Octet L3_PDU's | 7-3 |
| Table 7-3 Delay (msec) for 4096 Octet L3_PDU's | 7-4 |