

---

## Generic Requirements for XA-PVC-CRS

### Contents

1.	Introduction.....	1-1
1.1	Purpose and Scope .....	1-2
1.2	Nationally Consistent LEC XA-PVC-CRS Phases.....	1-2
1.3	Document Organization .....	1-3
1.4	Key Documents.....	1-4
1.5	Requirements Terminology.....	1-5
2.	Background.....	2-1
2.1	Cell Relay Service Overview .....	2-1
2.2	Exchange Access PVC Cell Relay Service .....	2-5
2.3	Benefits of Nationally Consistent XA-PVC-CRS .....	2-7
3.	Service Features.....	3-1
3.1	Connection Type .....	3-1
3.2	Carrier Selection .....	3-2
3.3	Physical Interface at the B-ICI.....	3-2
3.4	Cell Transport .....	3-3
3.5	Communication Configurations.....	3-3
3.5.1	Point-to-Point Connections.....	3-3
3.5.2	Point-to-Multipoint Connections .....	3-4
3.5.3	Multipoint-to-Multipoint Connections .....	3-14
3.6	Cell Transfer Rates .....	3-14
3.7	Quality of Service Classes .....	3-19
3.8	Bi-directional Connections .....	3-19
3.9	Traffic Management.....	3-20
3.9.1	Network Parameter Control .....	3-20
3.9.2	Egress Shaping.....	3-22
3.9.3	Priority Control.....	3-22
3.9.4	Explicit Forward Congestion Indication.....	3-22
3.9.5	Connection Admission Control and Network Traffic Management.....	3-23

---

3.10	Routing to ICs .....	3-24
3.11	Network Management Capabilities .....	3-24
3.11.1	XA-OM Capabilities .....	3-25
3.11.2	Network Management via ATM Layer Management .....	3-26
3.12	Other Features at the User-Network Interface .....	3-28
4.	BISDN Inter Carrier Interface .....	4-1
4.1	Functional Organization of the Protocol at the B-ICI .....	4-1
4.2	ATM Layer at the B-ICI .....	4-2
4.2.1	ATM Cell Structure and Encoding .....	4-3
4.2.2	ATM Layer Procedures .....	4-5
4.3	Physical Layer Specification at the B-ICI .....	4-7
4.4	Additional B-ICI Criteria .....	4-8
5.	Performance and Quality of Service .....	5-1
5.1	Delay Objectives .....	5-1
5.1.1	Cell Transfer Delay .....	5-1
5.1.2	Cell Delay Variation .....	5-2
5.2	Accuracy Objectives .....	5-3
5.2.1	Cell Loss Ratio .....	5-3
5.2.2	Errored Cell Ratio .....	5-3
5.2.3	Mis-inserted Cell Ratio .....	5-3
5.3	Availability Objectives .....	5-4
5.3.1	Scheduled Hours of Service .....	5-4
5.3.2	Service Availability .....	5-4
5.3.3	Mean Time to Service Restoral .....	5-4
5.3.4	Mean Time Between Service Outages .....	5-5
6.	Usage Information to Support Billing .....	6-1
6.1	Motivation .....	6-1
6.2	Overview of the Usage Measurement Functions .....	6-2
6.3	Usage Measurement Strategy for XA-PVC-CRS .....	6-2
6.3.1	Usage Information Generated by the LEC Network .....	6-3
6.3.2	Additional XA-PVC-CRS Parameters .....	6-5
6.4	Data Generation .....	6-5

---

---

6.4.1	Identifying Unidirectional Cell Flows .....	6-6
6.4.2	AMA Cell Counts .....	6-9
6.4.3	AMA Cell Counts for OAM Cells .....	6-9
6.4.4	Usage Information for Pt-Mpt PVCs .....	6-10
6.5	Recording Intervals .....	6-11
6.5.1	Scheduled Closings .....	6-13
6.5.2	Unscheduled Closings .....	6-14
6.6	Data Formatting .....	6-16
6.7	Data Transmitting .....	6-19
6.8	Further Considerations .....	6-20
6.9	Operations and Performance .....	6-20
7.	Issues .....	7-1
7.1	Peak Cell Rates .....	7-1
7.2	Quality of Service Classes .....	7-1
7.3	OAM Cells .....	7-1
7.4	Performance Objectives .....	7-2
7.5	Egress Shaping .....	7-2
7.6	Usage Measurement Strategy .....	7-2
Appendix A.	Provisioning .....	A-1
A.1	Service Activation .....	A-1
A.1.1	Service Negotiation .....	A-1
A.1.2	Physical Connectivity .....	A-1
A.1.3	Service Feature Administration .....	A-2
A.1.4	Acceptance Testing .....	A-2
A.2	Service Assurance .....	A-2
A.2.1	Maintenance and Fault Management .....	A-2
A.2.2	Performance Management .....	A-3
Appendix B.	Rationale for Peak Cell Rate Values .....	B-1
B.1	AAL .....	B-1
B.2	ATM Layer Management and OAM cells .....	B-1
B.3	Rate Calculation .....	B-3
B.3.1	CBR Connections .....	B-3

---

---

B.3.2	VBR Connections .....	B-5
Appendix C.	CRS Traffic Contract and the GCRA .....	C-1
C.1	Carrier-to-Carrier Traffic Contract .....	C-1
C.2	Conforming Cell .....	C-1
C.3	Compliant Connection .....	C-2
Appendix D.	Proposed BAF Requirements for TR-NWT-001100 .....	D-1
D.1	BAF Table Changes Proposed for Division 2 of TR-NWT-001100 .....	D-1
D.2	BAF Structure Change Proposed for Division 3 of TR-NWT-001100 .....	D-5
D.3	BAF Call Type Code Changes Proposed for Division 4 of TR-NWT-001100 .....	D-6
D.4	BAF Module Changes Proposed for Division 5 of TR-NWT-001100 .....	D-7
Appendix E.	Requirements Summary .....	E-1
References	.....	References-1
Acronyms	.....	Acronyms-1

---

## List of Figures

Figure 2-1. Virtual Channel Connections.....	2-2
Figure 2-2. Virtual Path Connections.....	2-3
Figure 2-3. End User Networking Using PVC CRS .....	2-4
Figure 2-4. Scope of XA-PVC-CRS .....	2-5
Figure 2-5. XA-PVC-CRS Access Concentration.....	2-8
Figure 3-1. Example of a Point-to-Point Bi-directional Connection Topology .....	3-4
Figure 3-2. Example of a Point-to-Multipoint Connection .....	3-5
Figure 3-3. Source LEC Performs the Pt-Mpt Resolution Function .....	3-9
Figure 3-4. Distant LEC Performs the Pt-Mpt Resolution Function.....	3-11
Figure 3-5. Source and Distant LECs Perform the Pt-Mpt Resolution Function.....	3-12
Figure 3-6. Exchange Access Operations Management Service.....	3-25
Figure 4-1. Functional Organization of the Protocol at the B-ICI .....	4-2
Figure 4-2. ATM Cell Header Format at the B-ICI .....	4-3
Figure 6-1. Usage Information Generation Location .....	6-4
Figure 6-2. Identifying Unidirectional Cell Flows.....	6-8
Figure 6-3. Usage Information for Pt-Mpt PVCs.....	6-11
Figure C-1. GCRA Flowchart.....	C-3

---

## List of Tables

Table 3-1.	Supported PCR Values for XA-PVC-CRS on a VCC without an associated VPC .....	3-17
Table 3-2.	Supported PCR Values for XA-PVC-CRS on a VPC .....	3-18
Table 4-1.	PTI Code Points .....	4-4
Table 4-2.	Preassigned Header Field Values .....	4-5
Table 5-1.	Performance Objectives by QOS Class .....	5-1
Table 5-2.	CDV Distribution .....	5-2
Table 5-3.	CLR Values .....	5-3
Table 6-1.	Identifying Unidirectional Cell Flows .....	6-8
Table B-1.	Number of OAM PM Operations per Second .....	B-2