

Contents

Technical Advisory Notice Of Disclaimer	iii
1 Introduction	
1.1 Purpose and Scope of Document	1-1
1.2 Organization	1-1
2 General Information	
2.1 Functional Characteristics	2-1
2.1.1 Rate Conversion	2-1
2.1.2 Duty Cycle Conversion	2-1
2.1.3 Shaped Gain Control	2-2
2.1.4 Sealing Current and Its Reversal	2-2
2.1.5 Code Recognition	2-2
2.1.6 Timing	2-2
2.1.7 Control Bit Insertion	2-3
2.1.8 Multiplexing	2-3
3 Network Compatibility	
3.1 Local Loop Signal Format	3-1
3.1.1 Cross-Connect Signal Format	3-2
3.1.2 Rate Matching	3-3
3.1.3 Code Mapping	3-3
3.1.4 Electrical Characteristics	3-3
4 Secondary Channel	
4.1 Secondary Channel Capability	4-1
4.1.1 Local Loop Bit Rate	4-1
4.2 Secondary Channel Signal Formats	4-1
4.2.1 Intra-Office Signals	4-1
4.2.2 Loop Signals	4-2
4.3 Electrical Characteristics	4-3
5 Other Requirements and Objectives	
5.1 Maintenance Access	5-1
5.1.1 Digital Receiver	5-1
5.1.2 Digital Transmitter	5-1
5.2 Physical Design Requirements	5-1
5.2.1 Basic Physical Requirements	5-1
5.2.2 Location	5-2
5.2.3 Office Cabling	5-2
5.2.4 DSX-0	5-2

Appendix A: References

Appendix B: Glossary

List of Figures

Figure 1	OCU Application	1-2
Figure 2	Binary-to-Bipolar Conversion	2-2
Figure 3	Composite Timing Signal	2-3
Figure 4	Modified Bipolar Signals	3-1
Figure 5	Cross-Connect Byte Format	3-3
Figure 6	Circuit Model	3-4
Figure 7	Unfiltered DS-CS Signal at Rate R	3-5
Figure 8	General Frequency Domain Template	3-7
Figure 9	2.4 kb/s Frequency Domain Template	3-8
Figure 10	4.8 kb/s Frequency Domain Template	3-9
Figure 11	9.6 kb/s Frequency Domain Template	3-10
Figure 12	56 kb/s Frequency Domain Template	3-11
Figure 13	Byte Formats	4-3

List of Tables

Table A	Byte Repetitions	3-3
Table B	Pulse Amplitude	3-4
Table C	Minimum Additional Attenuation	3-4
Table D	Attenuation Factors	3-5
Table E	Channel Bit Rates (kb/s)	4-2
Table F	Cable Length Restrictions	5-2