

---

Voice Grade Special Access Services -  
Transmission Parameter Limits and Interface Combinations

**CONTENTS**

1. Introduction . . . . .	1-1
1.1 Document Overview . . . . .	1-1
1.2 Purpose . . . . .	1-1
1.3 Scope . . . . .	1-1
1.3.1 Voice Grade Special Access Services . . . . .	1-2
1.3.2 IntraLATA Private Line Services . . . . .	1-2
1.4 Applicability of Technical Specifications . . . . .	1-2
1.5 Alternative Arrangements . . . . .	1-2
1.6 Document Organization . . . . .	1-3
1.7 Requirements Terminology . . . . .	1-3
1.8 Reason for Reissue . . . . .	1-3
2. Service Descriptions and Technical Considerations . . . . .	2-1
2.1 General . . . . .	2-1
2.2 Voice Grade (VG) Special Access . . . . .	2-1
2.3 IntraLATA Private Line Service (IPLS) . . . . .	2-2
2.4 Channel Configurations . . . . .	2-3
2.4.1 2-Wire and Effective 2-Wire Channels . . . . .	2-3
2.4.2 Effective 4-Wire Channel . . . . .	2-4
2.5 4-Wire Channel . . . . .	2-4
2.6 Transfer Arrangements . . . . .	2-5
2.7 Signal-Level Considerations . . . . .	2-6
2.7.1 Maximum Signal Power on Multipoint Channels . . . . .	2-7
2.8 Echo Return Loss and Stability . . . . .	2-8
2.8.1 Equal Level Echo Path Loss vs. Return Loss Measurements . . . . .	2-11
2.9 Multipoint Service . . . . .	2-12
2.9.1 Bridging Arrangements . . . . .	2-12
2.9.2 Multipoint Design Considerations . . . . .	2-15
2.9.3 Maximum Number of Links . . . . .	2-15
2.9.4 Multipoint Design . . . . .	2-16
2.9.5 Signaling Arrangements . . . . .	2-19
3. Interface Descriptions . . . . .	3-1
3.1 General . . . . .	3-1
3.2 Interface Codes . . . . .	3-1
3.2.1 NCI Code Structure and Components . . . . .	3-1
3.3 Conventions . . . . .	3-12
3.3.1 Transmit and Receive Transmission Directions . . . . .	3-12
3.3.2 Simplex Signaling Sense (Polarity) 4-Wire POT . . . . .	3-12

---

3.3.3	Compatible Transmission Level Points (TLPs) at Interfaces	3-13
3.4	Tabulation of VG Interface Code Combinations	3-14
3.4.1	Availability Categories	3-14
3.4.2	Digital High-Capacity Interfaces	3-15
3.5	Standard Interface Illustrations	3-16
3.5.1	Interface Code 04AB2	3-16
3.5.2	Interface Code 02AC2	3-17
3.5.3	Interface Code 04AC2	3-18
3.5.4	Interface Code 02CC8	3-19
3.5.5	Interface Code 02CT3	3-20
3.5.6	Interface Code 04CT2	3-21
3.5.7	Interface Code 02DA2	3-22
3.5.8	Interface Code 04DA2	3-23
3.5.9	Interface Code 06DA2	3-24
3.5.10	Interface Code 02DB2	3-25
3.5.11	Interface Code 04DB2	3-26
3.5.12	Interface Code 02DC8	3-27
3.5.13	Interface Code 04DD2	3-28
3.5.14	Interface Code 02DE2	3-29
3.5.15	Interface Code 04DE2	3-30
3.5.16	Interface Codes 04DS	3-31
3.5.17	Interface Code 04DX2	3-32
3.5.18	Interface Codes 04EA2-E, 04EA2-M	3-33
3.5.19	Interface Codes 06EA2-E, 06EA2-M	3-34
3.5.20	Interface Codes 06EB2-E, 06EB2-M	3-35
3.5.21	Interface Codes 08EB2-E, 08EB2-M	3-36
3.5.22	Interface Code 08EC2	3-37
3.5.23	Interface Code 06EX2-A	3-38
3.5.24	Interface Code 06EX2-B	3-39
3.5.25	Interface Codes 02GO2, 02GO3	3-40
3.5.26	Interface Code 04GO2	3-41
3.5.27	Interface Codes 02GS2, 02GS3	3-42
3.5.28	Interface Code 04GS2	3-43
3.5.29	Interface Codes 02LA2, 02LB2, 02LC2	3-44
3.5.30	Interface Codes 02LO2, 02LO3	3-45
3.5.31	Interface Code 04LO2	3-46
3.5.32	Interface Code 02LR2	3-47
3.5.33	Interface Code 04LR2	3-48
3.5.34	Interface Codes 02LS2, 02LS3	3-49
3.5.35	Interface Code 04LS2	3-50
3.5.36	Interface Code 02N02	3-51
3.5.37	Interface Code 04NO2	3-52
3.5.38	Interface Code 02PR2	3-53
3.5.39	Interface Code 04PR2	3-54

---

---

3.5.40	Interface Code 02RV2-O . . . . .	3-55
3.5.41	Interface Code 02RV2-T . . . . .	3-56
3.5.42	Interface Code 04RV2-O . . . . .	3-57
3.5.43	Interface Codes 04RV2-T . . . . .	3-58
3.5.44	Interface Code 04SF2 . . . . .	3-59
3.5.45	Interface Code 02TF2 . . . . .	3-60
3.5.46	Interface Code 04TF2 . . . . .	3-61
3.5.47	CO-NCI Code Overview . . . . .	3-62
3.6	Transitional Interface Illustrations . . . . .	3-66
3.6.1	Interface Codes 02AB2, 02AB3 . . . . .	3-66
3.6.2	Interface Code 04AB3 . . . . .	3-67
3.6.3	Interface Code 04DX3 . . . . .	3-68
3.6.4	Interface Code 06DX2 . . . . .	3-69
3.6.5	Interface Code 02DY2 . . . . .	3-70
3.6.6	Interface Code 04DY2 . . . . .	3-71
3.6.7	Interface Codes 06DY2, 06DY3 . . . . .	3-72
3.6.8	Interface Codes 09DY2, 09DY3 . . . . .	3-73
3.6.9	Interface Codes 04EA3-E, 04EA3-M . . . . .	3-74
3.6.10	Interface Codes 09EA2, 09EA3 . . . . .	3-75
3.6.11	Interface Codes 06EB3-E, 06EB3-M . . . . .	3-76
3.6.12	Interface Code 04GO3 . . . . .	3-77
3.6.13	Interface Code 06GO2 . . . . .	3-78
3.6.14	Interface Codes 04GS3 . . . . .	3-79
3.6.15	Interface Code 06GS2 . . . . .	3-80
3.6.16	Interface Code 04LO3 . . . . .	3-81
3.6.17	Interface Code 06LO2 . . . . .	3-82
3.6.18	Interface Code 02LR3 . . . . .	3-83
3.6.19	Interface Code 04LR3 . . . . .	3-84
3.6.20	Interface Code 04LS3 . . . . .	3-85
3.6.21	Interface Code 06LS2 . . . . .	3-86
3.6.22	Interface Codes 04RV3-T . . . . .	3-87
3.6.23	Interface Code 04SF3 . . . . .	3-88
3.6.24	Interface Code 02TF3 . . . . .	3-89
4.	Signaling Arrangements . . . . .	4-1
4.1	General . . . . .	4-1
4.2	Loop-Start . . . . .	4-1
4.2.1	Loop-Start Operation Closed-End (LS) . . . . .	4-1
4.2.2	Loop-Start Operation Open-End (LO) . . . . .	4-1
4.2.3	Loop-Start Signaling - Reference Information . . . . .	4-2
4.3	Ground-Start Signaling . . . . .	4-3
4.3.1	Ground-Start Operation Closed-End (GS) . . . . .	4-3
4.3.2	Ground-Start Operation Open-End (GO) . . . . .	4-3
4.3.3	Ground-Start Signaling - Reference Information . . . . .	4-3
4.4	E&M Lead Signaling . . . . .	4-4
4.4.1	Type I E&M Interface (EA-E, EA-M) . . . . .	4-5

---

---

4.4.2	Type II E&M Interface (EB-E, EB-M)	4-6
4.4.3	Type III E&M Interface (EC)	4-7
4.5	Reverse-Battery Signaling (RV-O, RV-T)	4-7
4.5.1	Reverse-Battery Operation	4-8
4.5.2	Reverse-Battery Signaling - Reference Information	4-8
4.6	Duplex (DX) Signaling	4-9
4.6.1	DX Operation	4-9
4.7	Single-Frequency (SF) Signaling	4-10
4.8	Digital Multiplexed (DS) Signaling	4-10
4.8.1	SF Signaling for Digital Multiplexed Interface	4-11
4.9	Tandem Signaling (EX)	4-11
5.	Special Access Channel Specifications	5-1
5.1	General	5-1
5.2	Transmission Performance	5-1
5.3	Special Access Voice Grade 1 (VG1)	5-3
5.3.1	Available Signaling — 2-Wire EU-NI Only	5-3
5.3.2	Available Options	5-4
5.3.3	Loss Deviation	5-4
5.3.4	Three-Tone Slope	5-4
5.3.5	Attenuation Distortion	5-4
5.3.6	C-Message Noise	5-4
5.3.7	Echo Control	5-5
5.3.8	VG1 Compatible EU-NI, IC-POT and CO-NCI Code Combinations	5-6
5.3.9	VG1 Compatible TLP Ranges at the EU-NI	5-7
5.3.10	VG1 Compatible TLP Ranges at the IC-POT	5-8
5.4	Special Access Voice Grade 2 (VG2)	5-9
5.4.1	Special Access 2-Point Voice Grade 2 (VG2)	5-9
5.4.2	Available Signaling for 2-Point VG2	5-9
5.4.3	Special Access Multipoint Voice Grade 2 (VG2)	5-10
5.4.4	Available Signaling For Multipoint VG2	5-11
5.4.5	Available Options	5-11
5.4.6	Loss Deviation	5-11
5.4.7	Three-Tone Slope	5-11
5.4.8	Attenuation Distortion	5-12
5.4.9	C-Message Noise	5-12
5.4.10	Echo Control	5-12
5.4.11	VG2 Compatible EU-NI, IC-POT and CO-NCI Code Combinations	5-13
5.4.12	Registered Equipment/Facility Identification Code (RE/FIC) Cross- Reference	5-14
5.4.13	VG2 Compatible TLP Ranges at the EU-NI	5-15
5.4.14	VG2 Compatible TLP Ranges at the IC-POT	5-16
5.5	Special Access Voice Grade 3 (VG3)	5-17
5.5.1	Available Signaling	5-17

---

---

5.5.2	Available Options . . . . .	5-18
5.5.3	Loss Deviation . . . . .	5-18
5.5.4	Three-Tone Slope . . . . .	5-18
5.5.5	Attenuation Distortion . . . . .	5-18
5.5.6	C-Message Noise . . . . .	5-19
5.5.7	Echo Control . . . . .	5-19
5.5.8	VG3 Compatible EU-NI, IC-POT and CO-NCI Code Combinations . . . . .	5-20
5.5.8	VG3 Compatible EU-NI, IC-POT and CO-NCI Code Combinations (continued) . . . . .	5-21
5.5.9	VG3 Compatible TLP Ranges at the EU-NI . . . . .	5-22
5.5.9	VG3 Compatible TLP Ranges at the EU-NI (continued) . . . . .	5-23
5.5.10	VG3 Compatible TLP Ranges at the IC-POT . . . . .	5-24
5.6	Special Access Voice Grade 4 (VG4) . . . . .	5-25
5.6.1	Available Options . . . . .	5-25
5.6.2	Loss Deviation . . . . .	5-25
5.6.3	Three-Tone Slope . . . . .	5-26
5.6.4	Attenuation Distortion . . . . .	5-26
5.6.5	C-Message Noise . . . . .	5-26
5.6.6	Signal-to-C Message Noise Ratio . . . . .	5-26
5.6.7	VG4 Compatible EU-NI, IC-POT and CO-NCI Code Combinations . . . . .	5-27
5.6.8	VG4 Compatible TLP Ranges at the EU-NI . . . . .	5-27
5.6.9	VG4 Compatible TLP Ranges at the IC-POT . . . . .	5-28
5.7	Special Access Voice Grade 5 (VG5) . . . . .	5-29
5.7.1	Special Access 2-Point Voice Grade 5 (VG5) . . . . .	5-29
5.7.2	Special Access Multipoint (VG5) . . . . .	5-30
5.7.3	Available Signaling . . . . .	5-31
5.7.4	Available Options . . . . .	5-31
5.7.5	Loss Deviation . . . . .	5-31
5.7.6	Three-Tone Slope . . . . .	5-31
5.7.7	Attenuation Distortion . . . . .	5-32
5.7.8	C-Message Noise . . . . .	5-32
5.7.9	C-Notched Noise . . . . .	5-32
5.7.10	Impulse Noise . . . . .	5-32
5.7.11	Phase Hit, Gain Hit, and Dropout Performance . . . . .	5-32
5.7.12	Echo Control . . . . .	5-33
5.7.13	VG5 Compatible EU-NI, IC-POT and CO-NCI Code Combinations . . . . .	5-34
5.7.14	VG5 Compatible TLP Ranges at the EU-NI . . . . .	5-35
5.7.15	VG5 Compatible TLP Ranges at the IC-POT . . . . .	5-36
5.7.15	VG5 Compatible TLP Ranges at the IC-POT (continued) . . . . .	5-37
5.8	Special Access Voice Grade 6 (VG6) . . . . .	5-38
5.8.1	Special Access 2-Point Voice Grade 6 (VG6) . . . . .	5-38
5.8.2	Special Access Multipoint (VG6) . . . . .	5-39

---

---

5.8.3	Available Signaling . . . . .	5-39
5.8.4	Available Options . . . . .	5-39
5.8.5	Loss Deviation . . . . .	5-40
5.8.6	Three-Tone Slope . . . . .	5-40
5.8.7	Attenuation Distortion . . . . .	5-40
5.8.8	Envelope Delay Distortion . . . . .	5-40
5.8.9	C-Message Noise . . . . .	5-41
5.8.10	C-Notched Noise . . . . .	5-41
5.8.11	Impulse Noise . . . . .	5-41
5.8.12	Signal to Intermodulation Distortion Ratio . . . . .	5-41
5.8.13	Phase Jitter . . . . .	5-41
5.8.14	Frequency Shift . . . . .	5-42
5.8.15	Phase Hit, Gain Hit, and Dropout Performance . . . . .	5-42
5.8.16	VG6 Compatible EU-NI, IC-POT and CO-NCI Code Combinations . . . . .	5-42
5.8.17	VG6 Compatible TLP Ranges at the EU-NI . . . . .	5-43
5.8.18	VG6 Compatible TLP Ranges at the IC-POT . . . . .	5-43
5.9	Special Access Voice Grade 7 (VG7) . . . . .	5-44
5.9.1	Available Signaling . . . . .	5-44
5.9.2	Available Options . . . . .	5-45
5.9.3	Loss Deviation . . . . .	5-45
5.9.4	Three-Tone Slope . . . . .	5-45
5.9.5	Attenuation Distortion . . . . .	5-46
5.9.6	Envelope Delay Distortion . . . . .	5-46
5.9.7	C-Message Noise . . . . .	5-46
5.9.8	C-Notched Noise . . . . .	5-46
5.9.9	Impulse Noise . . . . .	5-47
5.9.10	Signal to Intermodulation Distortion Ratio . . . . .	5-47
5.9.11	Phase Jitter . . . . .	5-47
5.9.12	Frequency Shift . . . . .	5-47
5.9.13	Phase Hit, Gain Hit, and Dropout Performance . . . . .	5-47
5.9.14	Echo Control . . . . .	5-48
5.9.15	VG7 Compatible EU-NI, IC-POT and CO-NCI Code Combinations . . . . .	5-49
5.9.15	VG7 Compatible EU-NI, IC-POT and CO-NCI Code Combinations (continued) . . . . .	5-50
5.9.16	VG7 Compatible TLP Ranges at the EU-NI . . . . .	5-51
5.9.16	VG7 Compatible TLP Ranges at the EU-NI (continued) . . . . .	5-52
5.9.17	VG7 Compatible TLP Ranges at the IC-POT . . . . .	5-53
5.10	Special Access Voice Grade 8 (VG8) . . . . .	5-54
5.10.1	Available Signaling . . . . .	5-54
5.10.2	Available Options . . . . .	5-54
5.10.3	Loss Deviation . . . . .	5-55
5.10.4	Three-Tone Slope . . . . .	5-55
5.10.5	Attenuation Distortion . . . . .	5-55

---

---

5.10.6	Envelope Delay Distortion . . . . .	5-55
5.10.7	C-Message Noise . . . . .	5-55
5.10.8	C-Notched Noise . . . . .	5-56
5.10.9	Impulse Noise . . . . .	5-56
5.10.10	Signal to Intermodulation Distortion Ratio . . . . .	5-56
5.10.11	Phase Jitter . . . . .	5-56
5.10.12	Frequency Shift . . . . .	5-57
5.10.13	Phase Hit, Gain Hit, and Dropout Performance . . . . .	5-57
5.10.14	Echo Control . . . . .	5-57
5.10.15	VG8 Compatible EU-NI, IC-POT and CO-NCI Code Combinations . . . . .	5-58
5.10.16	VG8 Compatible TLP Ranges at the EU-NI . . . . .	5-59
5.10.17	VG8 Compatible TLP Ranges at the IC-POT . . . . .	5-60
5.11	Special Access Voice Grade 9 (VG9) . . . . .	5-61
5.11.1	Available Signaling . . . . .	5-61
5.11.2	Available Options . . . . .	5-61
5.11.3	Loss Deviation . . . . .	5-62
5.11.4	Three-Tone Slope . . . . .	5-62
5.11.5	Attenuation Distortion . . . . .	5-62
5.11.6	Envelope Delay Distortion . . . . .	5-62
5.11.7	C-Message Noise . . . . .	5-62
5.11.8	C-Notched Noise . . . . .	5-63
5.11.9	Impulse Noise . . . . .	5-63
5.11.10	Signal to Intermodulation Distortion Ratio . . . . .	5-63
5.11.11	Phase Jitter . . . . .	5-63
5.11.12	Frequency Shift . . . . .	5-64
5.11.13	Phase Hit, Gain Hit, and Dropout Performance . . . . .	5-64
5.11.14	VG9 Compatible IC-POT to IC-POT and CO-NCI Code Combinations . . . . .	5-64
5.11.15	VG9 Compatible TLP Ranges at the IC-POT . . . . .	5-65
5.12	Special Access Voice Grade 10 (VG10) . . . . .	5-66
5.12.1	Special Access 2-Point Voice Grade 10 (VG10) . . . . .	5-66
5.12.2	Special Access Multipoint Voice Grade 10 (VG10) . . . . .	5-67
5.12.3	Available Signaling . . . . .	5-67
5.12.4	Available Options . . . . .	5-67
5.12.5	Loss Deviation . . . . .	5-68
5.12.6	Three-Tone Slope . . . . .	5-68
5.12.7	Attenuation Distortion . . . . .	5-68
5.12.8	Envelope Delay Distortion . . . . .	5-68
5.12.9	C-Message Noise . . . . .	5-68
5.12.10	C-Notched Noise . . . . .	5-69
5.12.11	Impulse Noise . . . . .	5-69
5.12.12	Signal to Intermodulation Distortion Ratio . . . . .	5-69
5.12.13	Phase Jitter . . . . .	5-69
5.12.14	Frequency Shift . . . . .	5-69

---

---

5.12.15	Phase Hit, Gain Hit, and Dropout Performance . . . . .	5-70
5.12.16	VG10 Compatible EU-NI, IC-POT and CO-NCI Code Combinations . . . . .	5-70
5.12.17	VG10 Compatible TLP Ranges at the EU-NI . . . . .	5-70
5.12.18	VG10 Compatible TLP Ranges at the IC-POT . . . . .	5-71
5.13	Special Access Voice Grade 11 (VG11) . . . . .	5-72
5.13.1	Special Access 2-Point Voice Grade 11 (VG11) . . . . .	5-72
5.13.2	Special Access Multipoint (VG11) . . . . .	5-73
5.13.3	Available Signaling . . . . .	5-73
5.13.4	Available Options . . . . .	5-73
5.13.5	Loss Deviation . . . . .	5-74
5.13.6	Three-Tone Slope . . . . .	5-74
5.13.7	Attenuation Distortion . . . . .	5-74
5.13.8	Envelope Delay Distortion . . . . .	5-74
5.13.9	C-Message Noise . . . . .	5-74
5.13.10	C-Notched Noise . . . . .	5-75
5.13.11	Impulse Noise . . . . .	5-75
5.13.12	Signal to Intermodulation Distortion Ratio . . . . .	5-75
5.13.13	Phase Jitter . . . . .	5-75
5.13.14	Frequency Shift . . . . .	5-76
5.13.15	Phase Hit, Gain Hit, and Dropout Performance . . . . .	5-76
5.13.16	VG11 Compatible EU-NI, IC-POT and CO-NCI Code Combinations . . . . .	5-76
5.13.17	VG11 Compatible TLPs at the EU-NI . . . . .	5-76
5.13.18	VG11 Compatible TLP Ranges at the IC-POT . . . . .	5-77
5.14	Special Access Voice Grade 12 (VG12) . . . . .	5-78
5.14.1	Special Access 2-Point Voice Grade 12 (VG12) . . . . .	5-78
5.14.2	Special Access Multipoint (VG12) . . . . .	5-79
5.14.3	Available Options . . . . .	5-79
5.14.4	Loss Deviation . . . . .	5-80
5.14.5	Three-Tone Slope . . . . .	5-80
5.14.6	Attenuation Distortion . . . . .	5-80
5.14.7	Envelope Delay Distortion . . . . .	5-80
5.14.8	C-Message Noise . . . . .	5-80
5.14.9	C-Notched Noise . . . . .	5-81
5.14.10	Impulse Noise . . . . .	5-81
5.14.11	Frequency Shift . . . . .	5-81
5.14.12	Phase Hit, Gain Hit and Dropout Performance . . . . .	5-81
5.14.13	VG12 Compatible EU-NI, IC-POT and CO-NCI Code Combinations . . . . .	5-82
5.14.14	VG12 Compatible TLP Ranges at the EU-NI . . . . .	5-82
5.14.15	VG12 Compatible TLP Ranges at the IC-POT . . . . .	5-83
5.15	Special Access Voice Grade - Customized (VGC) . . . . .	5-84
5.15.1	Attenuation Distortion Options . . . . .	5-85
5.15.2	1004-Hz Loss Deviation Options . . . . .	5-86

---



---

5.15.3	Three-Tone Slope . . . . .	5-86
5.15.4	Signal-to-Intermodulation Distortion Ratio Options . . . . .	5-87
5.15.5	Impulse Noise Options . . . . .	5-87
5.15.6	Envelope Delay Distortion Options . . . . .	5-88
5.15.7	C-Notched Noise & Signal-to-Noise Ratio . . . . .	5-89
5.15.8	Frequency Shift Options . . . . .	5-89
5.15.9	Phase Jitter Options . . . . .	5-89
5.15.10	Phase Hit, Gain Hit, and Dropout Performance . . . . .	5-90
5.15.11	Echo Control . . . . .	5-90
5.15.12	Compatible Interface Options . . . . .	5-90
5.15.13	Interim Alternative Standards . . . . .	5-91
5.16	Other Options . . . . .	5-93
5.16.1	C-Conditioning Option . . . . .	5-93
5.16.2	Improved Attenuation Distortion Option . . . . .	5-94
5.16.3	Improved Envelope Delay Distortion Option . . . . .	5-94
5.16.4	Data Capability Option . . . . .	5-95
5.16.5	T-Conditioning Option . . . . .	5-96
5.16.6	Simplex Reversal Option . . . . .	5-96
5.17	C-Message Noise Limits (dBmC0) . . . . .	5-97
6.	IPLS Channel Specifications . . . . .	6-1
6.1	IntraLATA Private Line Service Voice Grade 2 (IPLS VG2) . . . . .	6-1
6.1.1	Available Signaling . . . . .	6-2
6.1.2	Available Options . . . . .	6-2
6.1.3	Loss Deviation . . . . .	6-2
6.1.4	Three-Tone Slope . . . . .	6-2
6.1.5	Attenuation Distortion . . . . .	6-3
6.1.6	C-Message Noise . . . . .	6-3
6.1.7	Echo Control . . . . .	6-3
6.1.8	IPLS VG2 Compatible EU-NI to EU-NI Interface Combinations . . . . .	6-3
6.1.9	IPLS VG2 Compatible TLP Ranges at the EU-NI . . . . .	6-4
6.1.10	Registered Equipment/Facility Identification Codes . . . . .	6-4
6.2	IntraLATA Private Line Service Voice Grade 3 (IPLS VG3) . . . . .	6-5
6.2.1	Available Signaling . . . . .	6-6
6.2.2	Available Options . . . . .	6-6
6.2.3	Loss Deviation . . . . .	6-6
6.2.4	Three-Tone Slope . . . . .	6-6
6.2.5	Attenuation Distortion . . . . .	6-6
6.2.6	C-Message Noise . . . . .	6-7
6.2.7	Echo Control . . . . .	6-7
6.2.8	IPLS VG3 Compatible EU-NI to EU-NI Interface Combinations . . . . .	6-7
6.2.9	IPLS VG3 Compatible TLP Ranges at the EU-NI . . . . .	6-8
6.2.10	Tie-Trunk Cross-Reference Table . . . . .	6-9
6.3	IntraLATA Private Line Service Voice Grade 7 (IPLS VG7) . . . . .	6-10

---

6.3.1	Available Signaling . . . . .	6-11
6.3.2	Available Options . . . . .	6-11
6.3.3	Loss Deviation . . . . .	6-11
6.3.4	Three-Tone Slope . . . . .	6-11
6.3.5	Attenuation Distortion . . . . .	6-12
6.3.6	C-Message Noise . . . . .	6-12
6.3.7	Echo Control . . . . .	6-12
6.3.8	C-Notched Noise . . . . .	6-12
6.3.9	Envelope Delay Distortion . . . . .	6-12
6.3.10	Impulse Noise . . . . .	6-13
6.3.11	Signal-to-Intermodulation Distortion Ratio . . . . .	6-13
6.3.12	Phase Jitter . . . . .	6-13
6.3.13	Frequency Shift . . . . .	6-13
6.3.14	Phase Hit, Gain Hit, and Dropout Objective . . . . .	6-13
6.3.15	IPLS VG7 Compatible EU-NI to EU-NI Interface Combinations . . . . .	6-14
6.3.16	IPLS VG7 Compatible TLP Ranges at the EU-NI . . . . .	6-15
6.3.16	IPLS VG7 Compatible TLP Ranges at the EU-NI (continued) . . . . .	6-16
6.3.17	Tie-Trunk Cross-Reference Table . . . . .	6-17
6.4	IntraLATA Private Line Service Voice Grade 10 (IPLS VG10) . . . . .	6-18
6.4.1	Available Options . . . . .	6-18
6.4.2	Loss Deviation . . . . .	6-18
6.4.3	Three-Tone Slope . . . . .	6-19
6.4.4	Attenuation Distortion . . . . .	6-19
6.4.5	C-Message Noise . . . . .	6-19
6.4.6	Echo Control . . . . .	6-19
6.4.7	C-Notched Noise . . . . .	6-19
6.4.8	Envelope Delay Distortion . . . . .	6-20
6.4.9	Impulse Noise . . . . .	6-20
6.4.10	Signal-to-Intermodulation Distortion Ratio . . . . .	6-20
6.4.11	Phase Jitter . . . . .	6-20
6.4.12	Frequency Shift . . . . .	6-20
6.4.13	Phase Hit, Gain Hit, and Dropout Objective . . . . .	6-20
6.4.14	IPLS VG10 Compatible EU-NI to EU-NI Interface Combinations . . . . .	6-21
6.4.15	IPLS VG10 Compatible TLP Ranges at the EU-NI . . . . .	6-21
6.5	Echo Control Performance . . . . .	6-22
6.6	IPLS Conditioning Options . . . . .	6-23
6.6.1	C-Conditioning . . . . .	6-23
6.6.2	Data Capability . . . . .	6-24
7.	Glossary . . . . .	7-1
7.1	Terms — Defined . . . . .	7-1
7.2	Acronyms — Defined . . . . .	7-10

---

References . . . . .	R-1
----------------------	-----

**LIST OF FIGURES**

Figure 2-1. Typical 2-Wire and Effective 2-Wire Channel Configurations . . . . . 2-4	-
Figure 2-2. Typical Effective 4-Wire Channel Configuration . . . . .	2-4
Figure 2-3. Typical 4-Wire Channel Configuration . . . . .	2-4
Figure 2-4. Configuration of a Through Connection . . . . .	2-5
Figure 2-5. Station Terminal Transfer or Exclusion Configuration . . . . .	2-6
Figure 2-6. Transmission Level Point Concept . . . . .	2-7
Figure 2-7. Relationship of EPL, TLPs, and ELEPL . . . . .	2-10
Figure 2-8. ELEPL to RLMS-Reading Conversion Chart . . . . .	2-11
Figure 2-9. End-Link and Mid-Link Definitions . . . . .	2-13
Figure 2-10. Two Multipoint Access Services Connected by Interexchange Carrier . . . . .	2-14
Figure 2-11. A Multipoint Access Service Connected to Seven 2-Point Access Lines . . . . .	2-14
Figure 2-12. Multipoint Access Services with a 2-Point Access Line . . . . .	2-15
Figure 3-1. Transmit and Receive Transmission Directions . . . . .	3-12
Figure 3-2. Standard Simplex Sense for 04LO, 04LS, 04GO, 04GS, and 04DX Interfaces . . . . .	3-13
Figure 3-3. Standard Simplex Sense for 04RV2-0 Interface . . . . .	3-13
Figure 3-4. CO-NCI Code (BF) Split-Frequency Bridge . . . . .	3-62
Figure 3-5. CO-NCI Code (BR) Bridging . . . . .	3-63
Figure 3-6. CO-NCI Code (TA) Transfer Arrangement . . . . .	3-64
Figure 3-7. CO-NCI Code (CS) Digital Cross-Connect System . . . . .	3-65
Figure 3-8. CO-NCI Code (DM) Data Stream in VF Band at CO Location . . . . . 3-65	-
Figure 4-1. Loop-Start Signaling Circuit . . . . .	4-2
Figure 4-2. Ground-Start Signaling . . . . .	4-4
Figure 4-3. Type I E&M Interface — M-Lead Originate . . . . .	4-5

---

Figure 4-4. Type II E&M Interface — M-Lead Originate . . . . .	4-6
Figure 4-5. Type III E&M Lead Interface . . . . .	4-7
Figure 4-6. Reverse-Battery Signaling . . . . .	4-8
Figure 4-7. DX Signaling Circuit . . . . .	4-9
Figure 5-1. VG1 Configurations . . . . .	5-3
Figure 5-2. 2-Point VG2 Configurations . . . . .	5-9
Figure 5-3. Multipoint VG2 Configurations . . . . .	5-10
Figure 5-4. VG3 Configurations . . . . .	5-17
Figure 5-5. VG4 Configuration . . . . .	5-25
Figure 5-6. 2-Point VG5 Configurations . . . . .	5-29
Figure 5-7. Multipoint VG5 Configurations . . . . .	5-30
Figure 5-8. 2-Point VG6 Configuration . . . . .	5-38
Figure 5-9. Multipoint VG6 Configurations . . . . .	5-39
Figure 5-10. VG7 Configurations . . . . .	5-44
Figure 5-11. VG8 Configurations . . . . .	5-54
Figure 5-12. VG9 Configuration . . . . .	5-61
Figure 5-13. 2-Point VG10 Configurations . . . . .	5-66
Figure 5-14. Multipoint VG10 Configurations . . . . .	5-67
Figure 5-15. 2-Point VG11 Configurations . . . . .	5-72
Figure 5-16. Multipoint VG11 Configurations . . . . .	5-73
Figure 5-17. 2-Point VG12 Configurations . . . . .	5-78
Figure 5-18. Multipoint VG12 Configurations . . . . .	5-79
Figure 6-1. IPLS VG2 Configurations . . . . .	6-1
Figure 6-2. IPLS VG3 Configurations . . . . .	6-5
Figure 6-3. IPLS VG7 Configurations . . . . .	6-10
Figure 6-4. IPLS VG10 Configurations . . . . .	6-18

**LIST OF TABLES**

Table 2-1. VG Special Access Services . . . . .	2-1
Table 2-1. VG Special Access Services (continued) . . . . .	2-2

---

---

Table 2-2. IPLS Services . . . . .	2-3
Table 2-3. Guidelines for Maximum Transmitted Power of Simultaneous Signals . . . . .	2-8
Table 2-4. Multipoint Applications of VG Special Access Services . . . . .	2-12
Table 2-5. Attenuation Distortion — Multipoint Channels . . . . .	2-17
Table 2-6. Envelope Delay Distortion - Multipoint Channels . . . . .	2-18
Table 3-1. NCI Protocol Codes and Options (Page 1 of 5) . . . . .	3-4
Table 3-1. NCI Protocol Codes and Options (Page 2 of 5) . . . . .	3-5
Table 3-1. NCI Protocol Codes and Options (Page 3 of 5) . . . . .	3-6
Table 3-1. NCI Protocol Codes and Options (Page 4 of 5) . . . . .	3-7
Table 3-2. Protocol Codes and Options - CO Terminations (Page 1 of 4) . . . . .	3-8
Table 3-2. Protocol Codes and Options - CO Terminations (Page 2 of 4) . . . . .	3-9
Table 3-2. Protocol Codes and Options - CO Terminations (Page 3 of 4) . . . . .	3-10
Table 3-2. Protocol Codes and Options - CO Terminations (Page 4 of 4) . . . . .	3-11
Table 3-3. Digital High-Capacity Interfaces . . . . .	3-15
Table 4-1. E&M Lead Signal States . . . . .	4-5