
Generic Requirements for ISDN Basic Access Digital Subscriber Lines

Contents

| | | |
|---------|-------------------------------------------------------------------------|-----|
| 1. | Introduction..... | 1-1 |
| 1.1 | Purpose..... | 1-1 |
| 1.2 | Changes from Issue 1 of TR-TSY-000393 | 1-1 |
| 1.3 | Document Organization | 1-2 |
| 1.4 | Requirements Definition and Conventions | 1-2 |
| 2. | DSL Overview and Related Technical References..... | 2-1 |
| 2.1 | Description of DSL Technology | 2-1 |
| 2.2 | DSL Transmission and System Interfaces | 2-1 |
| 2.3 | Transport Systems Embedding DSLs | 2-2 |
| 3. | Loop Plant Environment | 3-1 |
| 4. | Spectrum Management | 4-1 |
| 4.1 | Crosstalk..... | 4-1 |
| 4.2 | Electromagnetic Emission and Immunity Requirements and Objectives | 4-2 |
| 5. | Transmission Characteristics | 5-1 |
| 5.1 | Transmission Method..... | 5-1 |
| 5.2 | Line Code | 5-1 |
| 5.2.1 | Characteristics of Pulses | 5-2 |
| 5.2.1.1 | Transmitted Pulses..... | 5-2 |
| 5.2.1.2 | Received Pulses | 5-2 |
| 5.2.2 | Power Spectrum of the Transmitted Signal | 5-3 |
| 5.2.2.1 | Power Spectral Density..... | 5-3 |
| 5.2.2.2 | Total Power..... | 5-3 |
| 5.3 | Baud Rate | 5-3 |
| 5.4 | Timing..... | 5-3 |
| 5.5 | Jitter..... | 5-3 |
| 5.5.1 | NT Input Signal Jitter Tolerance..... | 5-4 |
| 5.5.2 | NT Output Jitter Limitation | 5-4 |
| 5.5.3 | LT Input Signal Jitter Tolerance | 5-4 |
| 5.5.4 | LT Output Jitter Limitation..... | 5-5 |
| 5.6 | Message Propagation Delay | 5-5 |
| 5.7 | Frame Structure..... | 5-5 |
| 5.7.1 | Synchronization Word | 5-5 |
| 5.7.2 | User Data (2B+D) | 5-5 |
| 5.7.3 | M Channel..... | 5-6 |
| 5.7.4 | Super frames | 5-6 |

| | | |
|----------|----------------------------------------------------------------|------|
| 5.7.4.1 | Embedded Operations Channel (eoc) | 5-7 |
| 5.7.4.2 | Cyclic Redundancy Check (crc) | 5-7 |
| | 5.7.4.2.1crc Algorithms: | 5-7 |
| | 5.7.4.2.2Bits covered by the crc | 5-8 |
| 5.7.4.3 | The act Bit..... | 5-8 |
| 5.7.4.4 | Far End Block Error (febe)..... | 5-8 |
| 5.7.4.5 | The dea Bit..... | 5-8 |
| 5.7.4.6 | NT Power Status Bits (ps ₁ , ps ₂)..... | 5-9 |
| 5.7.4.7 | NT Test Mode Indicator Bit (ntm)..... | 5-9 |
| 5.7.4.8 | Cold-Start-Only Bit (cso) | 5-10 |
| 5.7.4.9 | U-Interface-Only-Activation (uoa)..... | 5-10 |
| 5.7.4.10 | S/T-Interface-Activity-Indicator (sai)..... | 5-10 |
| 5.7.4.11 | Alarm Indication Bit (aib) | 5-10 |
| 5.7.4.12 | Network Indicator Bit for Network Use (1*) | 5-10 |
| 5.7.4.13 | Reserved Bits | 5-11 |
| 5.7.5 | Frame Offset | 5-11 |
| 5.8 | Scrambling Method | 5-11 |
| 5.9 | Transmitter Linearity | 5-11 |
| 5.10 | Start-Up Procedure..... | 5-12 |
| 5.10.1 | Definition | 5-13 |
| 5.10.1.1 | Start-Up..... | 5-13 |
| 5.10.1.2 | Total Activation | 5-13 |
| 5.10.1.3 | Cold-Start-Only | 5-13 |
| 5.10.1.4 | Warm Start..... | 5-13 |
| 5.10.1.5 | Cold Start | 5-13 |
| 5.10.1.6 | Full Operational Status | 5-14 |
| 5.10.1.7 | Total Deactivation | 5-14 |
| 5.10.1.8 | Turn-off..... | 5-14 |
| 5.10.1.9 | Transparency..... | 5-14 |
| 5.10.2 | Continuous Operation | 5-15 |
| 5.10.3 | RESET | 5-15 |
| 5.10.3.1 | FULL RESET | 5-15 |
| 5.10.3.2 | RECEIVE RESET | 5-16 |
| 5.10.4 | Timers | 5-16 |
| 5.10.5 | Signals During Start-Up..... | 5-17 |
| 5.10.6 | Line Rate During Start-Up | 5-17 |
| 5.10.7 | Start-Up Sequence..... | 5-17 |
| 5.10.7.1 | Wake-Up..... | 5-17 |
| 5.10.7.2 | Start-up from Customer Equipment..... | 5-17 |
| 5.10.7.3 | Start-up from the L T..... | 5-18 |
| 5.10.7.4 | Progress Indicators..... | 5-18 |
| 5.10.7.5 | Turn-off Procedure | 5-18 |
| 5.10.7.6 | Transparency..... | 5-19 |
| 5.10.7.7 | Start- Up Time Requirements | 5-20 |

| | | |
|-------------|-----------------------------------------------------------------------------|------|
| 5.11 | NT Maintenance Modes | 5-21 |
| 5.11.1 | NT Quiet Mode | 5-21 |
| 5.11.2 | Insertion Loss Measurement Test | 5-22 |
| 5.11.3 | NT Quiet Mode and Insertion Loss Measurement Test Trigger Signal... 5-23 | |
| 5.11.4 | dc Signaling Format | 5-23 |
| 5.11.5 | Low Frequency ac Signaling Format | 5-24 |
| 6. | Generic DSL Power and Interface Requirements | 6-1 |
| 6.1 | Power Requirements | 6-1 |
| 6.2 | Line Interface | 6-1 |
| 6.2.1 | Impedance and Return Loss | 6-1 |
| 6.2.2 | Sealing Current | 6-1 |
| 6.2.3 | Metallic Termination..... | 6-1 |
| 6.2.3.1 | ON State..... | 6-2 |
| 6.2.3.2 | OFF State..... | 6-2 |
| 6.2.3.3 | NT Capacitance | 6-2 |
| 6.2.4 | Behavior of the NT during Metallic Testing..... | 6-3 |
| 6.2.5 | NT Network Side Resistance to Ground..... | 6-3 |
| 6.2.6 | Longitudinal Output Voltage | 6-3 |
| 6.2.7 | NT Longitudinal Balance..... | 6-4 |
| 6.2.8 | LT Longitudinal Balance | 6-4 |
| 6.2.9 | Electrical Protection..... | 6-4 |
| 6.2.10 | Electrostatic Discharge | 6-4 |
| 6.2.11 | Electrical Safety | 6-5 |
| Appendix A: | | |
| | GLOSSARY..... | A-1 |
| Appendix B: | | |
| | CHARACTERISTICS OF TELEPHONE LOOP PLANT..... | B-1 |
| B.1 | Introduction | B-1 |
| B.2 | Physical Characteristics | B-1 |
| B.3 | Transmission Characteristics | B-2 |
| B.4 | Discussion | B-2 |
| Appendix C: | | |
| | LABORATORY MEASUREMENT OF BER..... | C-1 |
| C.1 | Test Procedure..... | C-1 |
| C.1.1 | Simulated Crosstalk | C-1 |
| C.1.1.1 | Calibration of Crosstalk Simulation Filter..... | C-2 |
| C.1.1.2 | Measurement of Simulated NEXT Power and PSD | C-3 |
| C.1.2 | Longitudinal Noise..... | C-3 |
| C.1.3 | Power-Related Metallic Noise | C-4 |
| C.1.4 | Procedure | C-4 |
| C.2 | Margin..... | C-5 |

C.3 Notes on Test Procedure for Measuring BER..... C-5

Appendix D:
SUBSCRIBER LOOPS FOR TESTING BER D-1

REFERENCES References-1

List of Figures

| | | |
|--------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|
| Figure 2-1. | Access Reference Configuration | 2-3 |
| Figure 2-2. | Architectures for ISDN Basic Access | 2-4 |
| Figure 4-1. | Models of 1% NEXT for 18 kFt of 22GA PIC, Terminated With The Characteristic Impedance Z_0 of Cable at Each Frequency. Next Disturbers In Same Cable Binder Unit of 50 pairs | 4-3 |
| Figure 5-1. | 2B1Q Encoding of 2B+D Bit Fields..... | 5-24 |
| Figure 5-2. | Normalized Pulse from NT or LT Transmitter..... | 5-25 |
| Figure 5-3. | Upper Bound of Power Spectral Density of Signal from NT or LT Transmitter..... | 5-26 |
| Figure 5-4. | Range of Permissible Sinusoidal Jitter, Signal Originating from LT..... | 5-27 |
| Figure 5-5. | ISDN Basic Access 2B1Q DSL 1.5 Millisecond Basic Frame | 5-28 |
| Figure 5-6. | 2B1Q Superframe Technique and Overhead Bit Assignments | 5-29 |
| Figure 5-7. | CRC-12 Generator..... | 5-30 |
| Figure 5-8. | DSL Framing and Overhead Function Temporal Relationships | 5-31 |
| Figure 5-9. | Scrambler and Descrambler..... | 5-32 |
| Figure 5-10. | Measurement of DSL Transmitter Linearity | 5-33 |
| Figure 5-11. | Definitions of Signals During Start-Up..... | 5-34 |
| Figure 5-12. | State Sequence for DSL Transceiver Start-up..... | 5-35 |
| Figure 5-13. | NT Loop Testing States..... | 5-36 |
| Figure 6-1. | Minimum Return Loss..... | 6-6 |
| Figure 6-2. | Illustration of dc Characteristics of the NT (bilateral switch and holding current)..... | 6-7 |
| Figure 6-3. | Measurement Method for Longitudinal Output Voltage..... | 6-8 |
| Figure 6-4. | NT-Longitudinal Balance | 6-9 |
| Figure 6-5. | Measurement Method for Longitudinal Balance..... | 6-10 |
| Figure 6-6. | LT-Longitudinal Balance | 6-11 |
| Figure B-1. | 1983 Loop Survey - All Loops | B-3 |
| Figure B-2. | 1983 Loop Survey - Non-Loaded Loops | B-4 |
| Figure B-3. | 1983 Loop Survey | B-5 |
| Figure C-1. | Laboratory Test Set-Up for Measuring BER..... | C-8 |
| Figure C-2. | PSD for Simulated Near End Crosstalk (NEXT) for Testing 2B1Q System . C-9 | |
| Figure C-3. | Crosstalk Calibration Impedance, Z_C | C-10 |
| Figure C-4. | Waveform for Longitudinal Noise | C-11 |
| Figure C-5. | Power Spectral Density (PSD) of Assumed Interferers..... | C-12 |
| Figure D-1a | Loops for Testing Received Signal Performance: #1 - #5..... | D-2 |
| Figure D-1b | Loops for Testing Received Signal Performance: #6 - #10..... | D-3 |
| Figure D-1c | Loops for Testing Received Signal Performance: #11 - #15..... | D-4 |
